DATA SHEET FOR 120KW CCS2 CHARGER

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC±10%
Frequency	50Hz±10%
Efficiency	≥94%
Power Factor	≥0.99
Total Harmonic Factor	THD <5%
POWER OUTPUT	
Output Voltage	150V-1000V DC
Rated Power	120kW Maximum (can charge two cars at 60 kW simultaneously)
Rated Output Current	200A Maximum
No. of Output	2 nos of Charging guns.
Plug	CCS-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault, Over Temperature
USER INTERFACE	
Display	9” TFT Color Touch Screen
Status Indicator	LED Lamps for ON, Charging and Fault
User Authorization	App/ RFID card
COMMUNICATION	
Network Connectivity	SIM/ Ethernet/ Wifi
Communication Protocol	OCPP V1.6
ENVIRONMENT	
Operating Temperature	-20°C to 60 °C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East), Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

Ingress Protection	IP- 55
Cooling mode	Forced Cooling
Noise	≤55dB
Length of charging gun Cable	5m
Dimensions (W x D x H)	750mm X 550mm X 1600mm
Installation	Floor Mounted
REGULATION	
Charging Mode Standard	IEC61851-1 Charging mode – 4