22 kW AC Wall Box Charger:



Product Overview:

22kW wall box AC Charger is composed of main control unit, charging interface, metering and charging unit. It's resistant to vibration and it covers a small area which can be installed in indoor and outdoor environments and provides AC power for electric vehicles with on board charger.

Product Features:

- Protection against lightning protection, leakage, short circuit,
- over current.
- Wall or Pole mounted installation.
- Smart interface and easy usability.
- Monitor and control through Bijlify mobile app & 3rd party systems.
- Supports IEC 61851 standard charging sequence.

Applications:

- EV Charging stations in buildings,

Evigo Charge Pvt. Ltd.
D-1, Udyog Sadan No.3, MIDC Industrial Area,
Andheri (East) Mumbai - 400093, Maharashtra.
Ph: +91 89768 03536 Email: info@bijlifynow.com
GST No.: 27AAFCE2840Q1Z8

- Charge point operators, commercial buildings.
- EV Charging stations for large, medium and small operators.
- EV dealers and service providers

Specifications:

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ± 10%
Frequency	50Hz ± 10%
POWER OUTPUT	
Rated Power	22kW
Rated Output Current	32A
No. of Output	1
Plug	AC Type-2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over Voltage, Under Voltage, Surge Protection, Short Circuit Protection, Ground Fault
USER INTERFACE	
Display	20x4 Character LCD display with blue backlight
Status Indicator	Multi colored LED indicator
User Authorization	App
COMMUNICATION	
Network Connectivity	GSM/ GPRo 3G/4G Connectivity
Communication Protocol	OCPP 1.6
ENVIRONMENT	
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet
Ingress Protection	IP 55
Cooling	Natural Cooling
Length of charging gun	5m
Dimensions (WxDxH)	310 mm X 140mm X 450mm
Installation	Wall or Pole Mounted
REGULATION	
Charging Mode Standard	IEC 61851-1 Charging