Annexures – I

PRODUCT OVERVIEW, FEATURES AND SPECIFICATIONS

3.3kW AC Wall box Charger



Product Overview:

3.3kW AC Wall box Charger Lite is composed of main control unit, protection and metering. It is an intelligent AC Charger with a modular design. It has smallest footprint which can be installed in indoor and outdoor environments and provides AC power for electric vehicles with on board charger. It is generally installed at buildings, commercial complexes, operators, EV dealers and service providers. It supports IEC60309 Industrial Power Socket.

Product Features:

- Charging protection such as short circuit, over current, connection abnormality and emergency stop.
- Smart connectivity: SIM Based.
- Energy measurement: External.
- Stand-alone charger, easy to install.
- Supports QR code and app connectivity.

Applications:

- Supports Electric Car, Electric Bike and Electric Scooters.

Specifications:

POWER INPUT	
Power Connection	P + N + PE
Input Voltage	230VAC±10%
Frequency	50Hz±10%
POWER OUTPUT	
Rated Power	3.3kW
Rated Output Current	15A
Energy Measurement Accuracy	Class 1
No. of Output	1
Plug	IEC 60309
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Short Circuit, Isolation
USER INTERFACE	
Status Indicator	LED Lamps for ON, Charging and Fault
User Authorization	App
COMMUNICATION	
Network Connectivity	SIM based
Communication Protocol	MQTT
ENVIRONMENT	
Operating Temperature	-5°C to 60 °C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Polycarbonate
Ingress Protection	All weather functionality-IP55
Cooling	Natural Cooling
Dimensions (WxDxH)	300mmX163mmX400mm
Installation	Wall Mounted

***Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.**