Bijlify™

DataSheet

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : customer.support@evigocharge.com

PRO - I *(AC Type II Smart Charger)*



Product Overview

7.4kW wallbox AC Charger is composed of main control unit, charging interface, metering and charging unit. It's resistant to vibration and it covers a small area which can be installed in indoor and outdoor environments and provides AC power for electric vehicles with on board charger.

Product Features

- Charging protection such as input over/under voltage, connection abnormality, emergency stop.
- Protection against lightning protection, leakage, short circuit, over current.
- Wall or Pole mounted installation.
- Smart interface and easy usability.
- Monitor and control through EViGO mobile app & 3rd party systems.
- Supports IEC 61851 standard charging sequence.

Applications

Residential & Commercial buildings

Commercial Buildings, CPO*

Charging Stations (L,M,S)

EV Dealers & Service Providers

Specifications

POWER INPUT	
Power Connection	P + N + PE
Input Voltage	230 VAC±10%
Frequency	50Hz±10%
POWER OUTPUT	
Rated Power	7.4 kW
Rated Output Current	32Amp
No. of Output	1
Plug	AC Type 2
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	Over Current, Over/Under Voltage, Surge Protection,
	Short Circuit Protection,Earth-Leakage, Ground Fault
USER INTERFACE	
Display	20x4 Character LCD display with blue backlight
User Authorization	Multicolored LED indicator
User Authorization	QR Code
COMMUNICATION	
Network Connectivity	GSM/ GPRS
Communication Protocal	OCPP v1.6j

#Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : customer.support@evigocharge.com

ENVIRONMENT	
Operating Temperature	-20°C to 60°C
Storage Temperature	-40°C to 70°C
Humidity	5% to 95% without condensation
Altitude	≤2000m
Place of Installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	Hot-dip galvanized steel sheet
Ingress Protection	IP-55
Cooling	Natural Cooling
Length of charging gun	5m
Installation	Wall / Pole Mounted
Dimensions (WXDXH)	310mmx140mmx450mm
REGULATION	
Charging Mode Standard	IEC 61851-1 Charging Mode-3