Bijlify™

DataSheet

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : info@bijlifynow.com

X'TREME-I

(240kW [120kWx2] Dual Gun CCS2 Charger)



Product Overview

Bijlify X'TREME 240kW(120kW Dual Gun) CCS2 DC Fast Charging station is able to charge all current and next generation vehicles with CCS protocols.
The 60kW~240kW charging station is a configurable dual outlet (default) fast charging station, supporting the charging needs of each customer.

Product Features

- Charging protection such as short circuit, over current, connection abnormality, E/F and emergency stop
- Smart Connectivity: GSM/GPRS
- Easy to install, stand alone charger.
- Supports QR code and app connectivity.
- OCPP Compliant
- IE61 851, IEC62196, ISO15118/DIN70121

Applications

EV Fleet Operators

EV Dealers

Charging Operators/ Stations (L,M,S)

EV Service Providers

Specifications

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ±10%
Frequency	50Hz±10%
POWER OUTPUT	
Rated Power	240kW (Dual - 120kW per connector)
Rated Output Voltage/Current	150-1000VDC, 200 Amps per connector
Energy Measurement Accuracy	Class 1
No. of Output	CCS 2
Plug	CCS 2 5 mtr cable length (Mode-4)
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	O/C, S/C, SPD, Isolation, EF
USER INTERFACE	
Status Indicator	Power ON, Charging ON and Fault
User Authorization	QR Code
COMMUNICATION	
Network Connectivity	GSM/ GPRS, WiFi, LAN
Communication Protocal	OCPP v1.6 J

#Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : info@bijlifynow.com

ENVIRONMENT	
Operating Temperature	-5ºC to 60ºC
Storage Temperature	-5ºC to 70ºC
Humidity	5% to 95% without condensation
Altitude	≤ 2000m
Place of Installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	MS Powder Coated
Ingress Protection	IP-54 / IK-10
Cooling	Force Cooled
Dimensions (WXDXH)	(850mmx750mmx1700mm)
Installation	Pedestal