Bijlify™

DataSheet

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : info@bijlifynow.com

X'TREME-I

(60kW [30kW x2] Dual Gun CCS2 Charger)



Product Overview

Bijlify X'TREME 60kW CCS2 DC Fast Charging station is able to charge all current and next generation vehicles with CCS protocols.
The 60kW~240kW charging station is a configurable dual outlet (default) fast charging station, supporting the charging needs of each customer.

Product Features

- Charging protection such as short circuit, over current, connection abnormality, E/F and emergency stop
- Smart Connectivity: GSM/GPRS
- Easy to install, stand alone charger.
- Supports QR code and app connectivity.
- OCPP Compliant
- IE61 851, IEC62196, ISO15118/DIN70121

Applications

EV Fleet Operators

EV Dealers

Charging Operators/ Stations (L,M,S)

EV Service Providers

Specifications

POWER INPUT	
Power Connection	3P + N + PE
Input Voltage	415VAC ±10%
Frequency	50Hz±10%
POWER OUTPUT	
Rated Power	60kW (30kW+30kW per connector)
Rated Output Voltage/Current	150-1000VDC, 150 Amps per connector
Energy Measurement Accuracy	Class 1
No. of Output	CCS 2
Plug	CCS 2 5 mtr cable length (Mode-4)
PROTECTION	
Push Button	Emergency Stop Button
Electrical Protection	O/C, S/C, SPD, Isolation, EF
USER INTERFACE	
Status Indicator	Power ON, Charging ON and Fault
User Authorization	QR Code
COMMUNICATION	
Network Connectivity	GSM/ GPRS, WiFi, LAN
Communication Protocal	OCPP v1.6 J

#Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

for more information -
www.Bijlifynow.com
Call: +91 8976803536
Email : info@bijlifynow.com

ENVIRONMENT	
Operating Temperature	-5ºC to 60ºC
Storage Temperature	-5ºC to 70ºC
Humidity	5% to 95% without condensation
Altitude	≤ 2000m
Place of Installation	Indoor and Outdoor
MECHANICAL DESIGN	
Shell Material	MS Powder Coated
Ingress Protection	IP-54 / IK-10
Cooling	Force Cooled
Dimensions (WXDXH)	(650mmx450mmx1600mm)
Installation	Floor Mounting