


Medical Image Processing for Interventional Applications

Random Walker – Algorithm

Online Course – Unit 41

Andreas Maier, Stefan Steidl, Frank Schebesch

Pattern Recognition Lab (CS 5)



Topics

Random Walks for Image Segmentation

Algorithm

Dirichlet Integral

Decomposition

Solution

Summary

Take Home Messages

Further Readings

Problem Statement

K -way image segmentation

- User-defined **seeds**
- Indicating regions of the image belonging to K objects

Random walk

- Labeling an **unseeded** pixel by resolving the question:
What is the probability of a random walker starting at this pixel that it first reaches seed point k ?
- Selecting the label of the most probable seed destination for each pixel
- Biasing the random walker to avoid crossing sharp intensity gradients

Problem Statement

Image as discrete object

- **Graph** with a fixed number of vertices and edges
- Each node represents one pixel in the image.
- Edges connect neighboring pixels: e. g., 4-connectivity (2-D), 6-connectivity (3-D), 8-connectivity (2-D).
- A real-valued **weight** is assigned to each edge representing the likelihood that a random walker will cross this edge.
 - Weight of zero: the random walker may not move along that edge.
- Purely combinatorial operators:
 - No discretization
 - No discretization errors or ambiguities

Problem Statement

Edge weights for adjacent pixels i and j

Gaussian weighting function:

$$w_{ij} = \exp(-\beta(g_i - g_j)^2)$$

where

- g_i : image intensity at pixel i
- β : only free parameter!

- Useful operation: prior normalization of the square gradients:

$$\forall e_{ij} \in E : (g_i - g_j)^2 \in [0, 1]$$

- Modification to handle color or general vector-valued data: $(g_i - g_j)^2 \longrightarrow ||\mathbf{g}_i - \mathbf{g}_j||^2$

Problem Statement

Four mathematically equivalent ways (Grady, 2006)

1. *“If a random walker leaving the pixel is most likely to first reach a seed bearing label s , assign the pixel to label s .”*

Problem Statement

Four mathematically equivalent ways (Grady, 2006)

1. *“If a random walker leaving the pixel is most likely to first reach a seed bearing label s , assign the pixel to label s .”*
2. *“If the seeds are alternately replaced by grounds/unit voltage sources, assign the pixel to the label for which its seeds being ‘on’ produces the greatest electrical potential.”*

Problem Statement

Four mathematically equivalent ways (Grady, 2006)

1. *“If a random walker leaving the pixel is most likely to first reach a seed bearing label s , assign the pixel to label s .”*
2. *“If the seeds are alternately replaced by grounds/unit voltage sources, assign the pixel to the label for which its seeds being ‘on’ produces the greatest electrical potential.”*
3. *“Assign the pixel to the label for which its seeds have the largest effective conductance (i. e., smallest effective resistance) with the pixel.”*

Problem Statement

Four mathematically equivalent ways (Grady, 2006)

1. *“If a random walker leaving the pixel is most likely to first reach a seed bearing label s , assign the pixel to label s .”*
2. *“If the seeds are alternately replaced by grounds/unit voltage sources, assign the pixel to the label for which its seeds being ‘on’ produces the greatest electrical potential.”*
3. *“Assign the pixel to the label for which its seeds have the largest effective conductance (i. e., smallest effective resistance) with the pixel.”*
4. *“If a 2-tree is drawn randomly from the graph (with probability given by the product of weights in the 2-tree), assign the pixel to the label for which the pixel is most likely to remain connected to.”*

Topics

Random Walks for Image Segmentation

Algorithm

Dirichlet Integral

Decomposition

Solution

Summary

Take Home Messages

Further Readings

Algorithm

Combinatorial Laplacian matrix L

$$L_{ij} = \begin{cases} d_i & \text{if } i = j, \\ -w_{ij} & \text{if } v_i \text{ and } v_j \text{ are adjacent nodes,} \\ 0 & \text{otherwise,} \end{cases}$$

where

- L_{ij} is indexed by vertices v_i and v_j ,
- $d_i = \sum w(e_{ij})$ for all edges e_{ij} incident on node v_i .

Algorithm

Example: Pixels of a 4×4 *image*

	1	2	3	4
1	V_1	V_2	V_3	V_4
2	V_5	V_6	V_7	V_8
3	V_9	V_{10}	V_{11}	V_{12}
4	V_{13}	V_{14}	V_{15}	V_{16}

Algorithm

Example: Pixels of a 4×4 image and the according *combinatorial Laplacian matrix* L

	1	2	3	4
1	V_1	V_2	V_3	V_4
2	V_5	V_6	V_7	V_8
3	V_9	V_{10}	V_{11}	V_{12}
4	V_{13}	V_{14}	V_{15}	V_{16}

$$L = \begin{bmatrix} d_1 & -w_{1,2} & 0 & 0 & -w_{1,5} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ -w_{1,2} & d_2 & -w_{2,3} & 0 & 0 & -w_{2,6} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & -w_{2,3} & d_3 & -w_{3,4} & 0 & 0 & -w_{3,7} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & -w_{3,4} & d_4 & 0 & 0 & 0 & -w_{4,8} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ -w_{1,5} & 0 & 0 & 0 & d_5 & -w_{5,6} & 0 & 0 & -w_{5,9} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & -w_{2,6} & 0 & 0 & -w_{5,6} & d_6 & -w_{6,7} & 0 & 0 & -w_{6,10} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & -w_{3,7} & 0 & 0 & -w_{6,7} & d_7 & -w_{7,8} & 0 & 0 & -w_{7,11} & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -w_{4,8} & 0 & 0 & -w_{7,8} & d_8 & 0 & 0 & 0 & -w_{8,12} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -w_{5,9} & 0 & 0 & 0 & d_9 & -w_{9,10} & 0 & 0 & -w_{9,13} & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & -w_{6,10} & 0 & 0 & -w_{9,10} & d_{10} & -w_{10,11} & 0 & 0 & -w_{10,14} & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & -w_{7,11} & 0 & 0 & -w_{10,11} & d_{11} & -w_{11,12} & 0 & 0 & -w_{11,15} & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{8,12} & 0 & 0 & -w_{11,12} & d_{12} & 0 & 0 & 0 & -w_{12,16} \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{9,13} & 0 & 0 & 0 & d_{13} & -w_{13,14} & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{10,14} & 0 & 0 & -w_{13,14} & d_{14} & -w_{14,15} & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{11,15} & 0 & 0 & -w_{14,15} & d_{15} & -w_{15,16} \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{12,16} & 0 & 0 & -w_{15,16} & d_{16} \end{bmatrix}$$

Algorithm

Combinatorial formulation of the Dirichlet integral

$$D(\mathbf{x}) = \frac{1}{2} \mathbf{x}^T \mathbf{L} \mathbf{x} = \frac{1}{2} \sum_{e_{ij} \in E} w_{ij} (x_i - x_j)^2$$

Partitioning the vertices into two sets:

- marked/seed nodes V_M ,
- unseeded nodes V_U ,

such that $V_M \cup V_U = V$ and $V_M \cap V_U = \emptyset$.

Without loss of generality: The nodes in \mathbf{L} and \mathbf{x} are **ordered**, i. e., seed nodes are first, unseeded nodes are second.

Algorithm

Decomposition

$$D[\mathbf{x}_U] = \frac{1}{2} (\mathbf{x}_M^T \ \mathbf{x}_U^T) \begin{bmatrix} \mathbf{L}_M & \mathbf{B} \\ \mathbf{B}^T & \mathbf{L}_U \end{bmatrix} \begin{pmatrix} \mathbf{x}_M \\ \mathbf{x}_U \end{pmatrix} = \frac{1}{2} (\mathbf{x}_M^T \mathbf{L}_M \mathbf{x}_M + 2\mathbf{x}_U^T \mathbf{B}^T \mathbf{x}_M + \mathbf{x}_U^T \mathbf{L}_U \mathbf{x}_U)$$

\mathbf{L} is positive semi-definite, i. e., the only critical points of $D[\mathbf{x}]$ will be minima.

Algorithm

Differentiating w. r. t. \mathbf{x}_U and finding the critical points:

$$\mathbf{L}_U \mathbf{x}_U = -\mathbf{B}^T \mathbf{x}_M$$

- System of linear equations with $|V_U|$ unknowns
- Equation will be non-singular
 - if the graph is connected, or
 - if every connected component contains a seed.

Algorithm

Solution to the combinatorial Dirichlet problem for label s

- x_i^s : probability (potential) assumed at node v_i for label s
- Set of labels: $\forall v_j \in V_M : Q(v_j) = s, s \in \mathbb{Z}, 0 < s \leq K$
- $V_M \times 1$ vector \mathbf{m}^s :

$$m_j^s = \begin{cases} 1 & \text{if } Q(v_j) = s, \\ 0 & \text{if } Q(v_j) \neq s \end{cases}$$

Algorithm

Solution to the combinatorial Dirichlet problem for label s

- x_i^s : probability (potential) assumed at node v_i for label s
- Set of labels: $\forall v_j \in V_M : Q(v_j) = s, s \in \mathbb{Z}, 0 < s \leq K$
- $V_M \times 1$ vector \mathbf{m}^s :

$$m_j^s = \begin{cases} 1 & \text{if } Q(v_j) = s, \\ 0 & \text{if } Q(v_j) \neq s \end{cases}$$

Solution for one label:

$$\mathbf{L}_U \mathbf{x}^s = -\mathbf{B}^T \mathbf{m}^s$$

Algorithm

Solution to the combinatorial Dirichlet problem for label s

- x_i^s : probability (potential) assumed at node v_i for label s
- Set of labels: $\forall v_j \in V_M : Q(v_j) = s, s \in \mathbb{Z}, 0 < s \leq K$
- $V_M \times 1$ vector \mathbf{m}^s :

$$m_j^s = \begin{cases} 1 & \text{if } Q(v_j) = s, \\ 0 & \text{if } Q(v_j) \neq s \end{cases}$$

Solution for one label:

$$\mathbf{L}_U \mathbf{x}^s = -\mathbf{B}^T \mathbf{m}^s$$

Solution for all labels:

$$\mathbf{L}_U \mathbf{X} = -\mathbf{B}^T \mathbf{M}$$

where \mathbf{X}, \mathbf{M} are matrices with K columns taken by each \mathbf{x}^s and \mathbf{m}^s , respectively.

Algorithm

Note:

- At any node the probabilities x_i^s will sum to unity:

$$\forall v_i \in V : \sum_s x_i^s = 1.$$

- Hence, only $K - 1$ sparse linear systems must be solved.

Topics

Random Walks for Image Segmentation

Algorithm

Dirichlet Integral

Decomposition

Solution

Summary

Take Home Messages

Further Readings

Take Home Messages

- For the segmentation using a random walker, we describe pixel transitions from one pixel to a neighboring pixel in form of graph edges.
- In the algorithm the combinatorial Dirichlet problem has to be solved to find a segmentation result.

Further Readings

These slides are based on the following publication:

L. Grady. “Random Walks for Image Segmentation”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 28.11 (Nov. 2006), pp. 1768–1783. DOI: 10.1109/TPAMI.2006.233

His implementations in Matlab can be downloaded here:

- Graph Analysis Toolbox
- Random Walker