


Medical Image Processing for Interventional Applications

Super-Resolution: Regularization

Online Course – Unit 23

Andreas Maier, Thomas Köhler, Frank Schebesch

Pattern Recognition Lab (CS 5)



Topics

Maximum A Posteriori Estimation

Image Priors

Summary

Take Home Messages

Further Readings

Super-Resolution and Ill-posed Problems

ML estimation on a synthetic example:

- Super-resolution is an **ill-posed** problem
→ ML reconstruction might lead to unstable solutions with amplified noise.



Figure 1: Example for insufficient result from ML estimation

Super-Resolution and Ill-posed Problems

ML estimation on a synthetic example:

- Super-resolution is an **ill-posed** problem
→ ML reconstruction might lead to unstable solutions with amplified noise.
- **Way out:** Incorporate prior knowledge into super-resolution algorithm.



Figure 1: Example for insufficient result from ML estimation

Maximum A Posteriori Estimation

Extension of the ML estimation to MAP estimation:

- For maximum a posteriori (MAP) estimation, a suitable prior $p(\mathbf{x})$ is used.

Maximum A Posteriori Estimation

Extension of the ML estimation to MAP estimation:

- For maximum a posteriori (MAP) estimation, a suitable prior $p(\mathbf{x})$ is used.
- According to Bayes formula, we have:

$$\hat{\mathbf{x}}_{MAP} = \arg \max_{\mathbf{x}} p(\mathbf{x})p(\mathbf{y} | \mathbf{x}) = \arg \min_{\mathbf{x}} \{ -\log p(\mathbf{x}) - \log p(\mathbf{y} | \mathbf{x}) \} .$$

Maximum A Posteriori Estimation

Extension of the ML estimation to MAP estimation:

- For maximum a posteriori (MAP) estimation, a suitable prior $p(\mathbf{x})$ is used.
- According to Bayes formula, we have:

$$\hat{\mathbf{x}}_{MAP} = \arg \max_{\mathbf{x}} p(\mathbf{x})p(\mathbf{y} | \mathbf{x}) = \arg \min_{\mathbf{x}} \{ -\log p(\mathbf{x}) - \log p(\mathbf{y} | \mathbf{x}) \}.$$

- For additive Gaussian noise, MAP estimation is equivalent to:

$$\hat{\mathbf{x}}_{MAP} = \arg \min_{\mathbf{x}} \sum_{k=1}^K \left\| \mathbf{y}^{(k)} - \mathbf{W}^{(k)} \mathbf{x} \right\|_2^2 - \log p(\mathbf{x}) = \arg \min_{\mathbf{x}} \left\| \mathbf{y} - \mathbf{W} \mathbf{x} \right\|_2^2 - \log p(\mathbf{x}).$$

Topics

Maximum A Posteriori Estimation

Image Priors

Summary

Take Home Messages

Further Readings

Image Prior and Regularization Term

Mathematical framework for image priors in super-resolution:

- We define the prior distribution according to the exponential form:

$$p(\mathbf{x}) = \frac{1}{Z} \exp(-\lambda R(\mathbf{x})),$$

where Z is a normalization constant, and $R(\mathbf{x})$ denotes a regularization term with regularization weight $\lambda \geq 0$.

Image Prior and Regularization Term

Mathematical framework for image priors in super-resolution:

- We define the prior distribution according to the exponential form:

$$p(\mathbf{x}) = \frac{1}{Z} \exp(-\lambda R(\mathbf{x})),$$

where Z is a normalization constant, and $R(\mathbf{x})$ denotes a regularization term with regularization weight $\lambda \geq 0$.

- The regularizer $R(\mathbf{x})$ can be defined such that it penalizes large variations in \mathbf{x} .

Image Prior and Regularization Term

Mathematical framework for image priors in super-resolution:

- We define the prior distribution according to the exponential form:

$$p(\mathbf{x}) = \frac{1}{Z} \exp(-\lambda R(\mathbf{x})),$$

where Z is a normalization constant, and $R(\mathbf{x})$ denotes a regularization term with regularization weight $\lambda \geq 0$.

- The regularizer $R(\mathbf{x})$ can be defined such that it penalizes large variations in \mathbf{x} .
- The regularization weight λ measures the impact of the prior:
 - $\lambda = 0$: simple ML estimation,
 - $\lambda \rightarrow \infty$: estimation dominated by the prior distribution.

Selected Priors for Super-Resolution

Gaussian prior (Tikhonov regularization):

- $p(\mathbf{x})$ is a normal distribution, i. e., $\mathbf{x} \sim N(0, \mathbf{\Sigma})$ and accordingly:

$$p(\mathbf{x}) = \frac{1}{(2\pi)^{N/2} |\mathbf{\Sigma}|^{1/2}} \exp \left(-\frac{1}{2} \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} \right).$$

Selected Priors for Super-Resolution

Gaussian prior (Tikhonov regularization):

- $p(\mathbf{x})$ is a normal distribution, i. e., $\mathbf{x} \sim N(0, \mathbf{\Sigma})$ and accordingly:

$$p(\mathbf{x}) = \frac{1}{(2\pi)^{N/2} |\mathbf{\Sigma}|^{1/2}} \exp \left(-\frac{1}{2} \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} \right).$$

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda ||\mathbf{Q}\mathbf{x}||_2^2.$$

$\mathbf{Q}\mathbf{x}$ computes variations in \mathbf{x} , e. g., gradient (first-order) or curvature (second-order).

Selected Priors for Super-Resolution

Gaussian prior (Tikhonov regularization):

- $p(\mathbf{x})$ is a normal distribution, i. e., $\mathbf{x} \sim N(0, \mathbf{\Sigma})$ and accordingly:

$$p(\mathbf{x}) = \frac{1}{(2\pi)^{N/2} |\mathbf{\Sigma}|^{1/2}} \exp \left(-\frac{1}{2} \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} \right).$$

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda ||\mathbf{Q}\mathbf{x}||_2^2.$$

$\mathbf{Q}\mathbf{x}$ computes variations in \mathbf{x} , e. g., gradient (first-order) or curvature (second-order).

- This regularization favors smooth solutions for \mathbf{x} .

Selected Priors for Super-Resolution

Gaussian prior (Tikhonov regularization):

- $p(\mathbf{x})$ is a normal distribution, i. e., $\mathbf{x} \sim N(0, \mathbf{\Sigma})$ and accordingly:

$$p(\mathbf{x}) = \frac{1}{(2\pi)^{N/2} |\mathbf{\Sigma}|^{1/2}} \exp \left(-\frac{1}{2} \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} \right).$$

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda \mathbf{x}^T \mathbf{\Sigma}^{-1} \mathbf{x} = \arg \min_{\mathbf{x}} ||\mathbf{y} - \mathbf{W}\mathbf{x}||_2^2 + \lambda ||\mathbf{Q}\mathbf{x}||_2^2.$$

$\mathbf{Q}\mathbf{x}$ computes variations in \mathbf{x} , e. g., gradient (first-order) or curvature (second-order).

- This regularization favors smooth solutions for \mathbf{x} .
- It facilitates a closed-form solution, but does not preserve discontinuities.

Selected Priors for Super-Resolution

Total variation (TV):

- $p(\mathbf{x})$ is modeled by a Laplacian distribution:

$$p(\mathbf{x}) \propto \exp(-\lambda \|\mathbf{Qx}\|_1).$$

Selected Priors for Super-Resolution

Total variation (TV):

- $p(\mathbf{x})$ is modeled by a Laplacian distribution:

$$p(\mathbf{x}) \propto \exp(-\lambda \|\mathbf{Q}\mathbf{x}\|_1).$$

- We define an isotropic version of the TV prior:

$$p(\mathbf{x}) \propto \exp(-\lambda R(\mathbf{x})), \quad \text{where } R(\mathbf{x}) = \sqrt{\|\mathbf{Q}_u\mathbf{x}\|_2^2 + \|\mathbf{Q}_v\mathbf{x}\|_2^2}.$$

\mathbf{Q}_u and \mathbf{Q}_v are gradient operators for horizontal and vertical direction, respectively.

Selected Priors for Super-Resolution

Total variation (TV):

- $p(\mathbf{x})$ is modeled by a Laplacian distribution:

$$p(\mathbf{x}) \propto \exp(-\lambda \|\mathbf{Q}\mathbf{x}\|_1).$$

- We define an isotropic version of the TV prior:

$$p(\mathbf{x}) \propto \exp(-\lambda R(\mathbf{x})), \quad \text{where } R(\mathbf{x}) = \sqrt{\|\mathbf{Q}_u\mathbf{x}\|_2^2 + \|\mathbf{Q}_v\mathbf{x}\|_2^2}.$$

\mathbf{Q}_u and \mathbf{Q}_v are gradient operators for horizontal and vertical direction, respectively.

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \sqrt{\|\mathbf{Q}_u\mathbf{x}\|_2^2 + \|\mathbf{Q}_v\mathbf{x}\|_2^2}.$$

Selected Priors for Super-Resolution

Total variation (TV):

- $p(\mathbf{x})$ is modeled by a Laplacian distribution:

$$p(\mathbf{x}) \propto \exp(-\lambda \|\mathbf{Q}\mathbf{x}\|_1).$$

- We define an isotropic version of the TV prior:

$$p(\mathbf{x}) \propto \exp(-\lambda R(\mathbf{x})), \quad \text{where } R(\mathbf{x}) = \sqrt{\|\mathbf{Q}_u\mathbf{x}\|_2^2 + \|\mathbf{Q}_v\mathbf{x}\|_2^2}.$$

\mathbf{Q}_u and \mathbf{Q}_v are gradient operators for horizontal and vertical direction, respectively.

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \sqrt{\|\mathbf{Q}_u\mathbf{x}\|_2^2 + \|\mathbf{Q}_v\mathbf{x}\|_2^2}.$$

- It favors piecewise constant solutions for \mathbf{x} (edge preserving regularization).

Selected Priors for Super-Resolution

Bilateral total variation (BTV):

- BTV is a generalization of the TV prior

Selected Priors for Super-Resolution

Bilateral total variation (BTV):

- BTV is a generalization of the TV prior
- Compare \mathbf{x} to multiple shifted versions as generalization of the gradient in a $(2P + 1) \times (2P + 1)$ window:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{u=-P}^P \sum_{v=-P}^P \alpha^{|u|+|v|} \left\| \mathbf{x} - \mathbf{S}_i^u \mathbf{S}_j^v \mathbf{x} \right\|_1 \right).$$

\mathbf{S}_i^u and \mathbf{S}_j^v are shifts of u and v pixels in horizontal and vertical direction, respectively.

Selected Priors for Super-Resolution

Bilateral total variation (BTV):

- BTV is a generalization of the TV prior
- Compare \mathbf{x} to multiple shifted versions as generalization of the gradient in a $(2P+1) \times (2P+1)$ window:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{u=-P}^P \sum_{v=-P}^P \alpha^{|u|+|v|} \|\mathbf{x} - \mathbf{S}_i^u \mathbf{S}_j^v \mathbf{x}\|_1 \right).$$

\mathbf{S}_i^u and \mathbf{S}_j^v are shifts of u and v pixels in horizontal and vertical direction, respectively.

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \left(\sum_{u,v=-n}^n \alpha^{|u|+|v|} \|\mathbf{x} - \mathbf{S}_i^u \mathbf{S}_j^v \mathbf{x}\|_1 \right).$$

Selected Priors for Super-Resolution

Bilateral total variation (BTV):

- BTV is a generalization of the TV prior
- Compare \mathbf{x} to multiple shifted versions as generalization of the gradient in a $(2P + 1) \times (2P + 1)$ window:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{u=-P}^P \sum_{v=-P}^P \alpha^{|u|+|v|} \|\mathbf{x} - \mathbf{S}_i^u \mathbf{S}_j^v \mathbf{x}\|_1 \right).$$

\mathbf{S}_i^u and \mathbf{S}_j^v are shifts of u and v pixels in horizontal and vertical direction, respectively.

- Then, MAP estimation can be expressed as:

$$\hat{\mathbf{x}}_{\text{MAP}} = \arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \left(\sum_{u,v=-n}^n \alpha^{|u|+|v|} \|\mathbf{x} - \mathbf{S}_i^u \mathbf{S}_j^v \mathbf{x}\|_1 \right).$$

- It reduces "staircasing" artifacts which occur using the common TV prior.

Selected Priors for Super-Resolution

Huber prior:

- $p(\mathbf{x})$ is modeled by the Huber loss function:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{i=1}^N h_{\tau}([Q\mathbf{x}]_i) \right),$$
$$h_{\tau}(z) = \begin{cases} \frac{1}{2}z^2, & \text{if } |z| \leq \tau, \\ \tau \left(|z| - \frac{\tau}{2} \right), & \text{otherwise.} \end{cases}$$




Figure 2: Comparison of quadratic loss and Huber loss

Selected Priors for Super-Resolution

Huber prior:

- $p(\mathbf{x})$ is modeled by the Huber loss function:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{i=1}^N h_{\tau}([\mathbf{Q}\mathbf{x}]_i) \right),$$

$$h_{\tau}(z) = \begin{cases} \frac{1}{2}z^2, & \text{if } |z| \leq \tau, \\ \tau \left(|z| - \frac{\tau}{2} \right), & \text{otherwise.} \end{cases}$$

- Then, MAP estimation can be expressed as:

$$\arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \sum_{i=1}^N h_{\tau}([\mathbf{Q}\mathbf{x}]_i).$$




Figure 2: Comparison of quadratic loss and Huber loss

Selected Priors for Super-Resolution

Huber prior:

- $p(\mathbf{x})$ is modeled by the Huber loss function:

$$p(\mathbf{x}) \propto \exp \left(-\lambda \sum_{i=1}^N h_{\tau}([\mathbf{Q}\mathbf{x}]_i) \right),$$

$$h_{\tau}(z) = \begin{cases} \frac{1}{2}z^2, & \text{if } |z| \leq \tau, \\ \tau \left(|z| - \frac{\tau}{2} \right), & \text{otherwise.} \end{cases}$$

- Then, MAP estimation can be expressed as:

$$\arg \min_{\mathbf{x}} \|\mathbf{y} - \mathbf{W}\mathbf{x}\|_2^2 + \lambda \sum_{i=1}^N h_{\tau}([\mathbf{Q}\mathbf{x}]_i).$$

- It yields piecewise smooth solutions (edge preserving regularization).




Figure 2: Comparison of quadratic loss and Huber loss

ML and MAP Estimation: Discussion



Figure 3: Low-resolution frame (left), ML estimation (middle), MAP estimation with TV prior (right)

Topics

Maximum A Posteriori Estimation

Image Priors

Summary

Take Home Messages

Further Readings

Take Home Messages

- Super-resolution is an ill-posed problem, so using regularization by utilizing prior knowledge is a good idea.
- We introduced several regularizers: Tikhonov, TV, BTV, and the edge-preserving approach using the Huber loss function.
- Regularization needs extra thought when implementing, but it is an important method to achieve adequate image quality.

Further Readings

Theory of image super-resolution (books and review articles):

- Hayit Greenspan. “Super-Resolution in Medical Imaging”. In: *The Computer Journal* 52.1 (Feb. 2008), pp. 43–63. DOI: [10.1093/comjnl/bxm075](https://doi.org/10.1093/comjnl/bxm075)
- Peyman Milanfar, ed. *Super-Resolution Imaging*. Digital Imaging and Computer Vision. CRC Press, 2011
- Sina Farsiu et al. “Advances and Challenges in Super-Resolution”. In: *International Journal of Imaging Systems and Technology* 14.2 (Aug. 2004), pp. 47–57. DOI: [10.1002/ima.20007](https://doi.org/10.1002/ima.20007)
- Sung Cheol Park, Min Kyu Park, and Moon Gi Kang. “Super-Resolution Image Reconstruction: A Technical Overview”. In: *IEEE Signal Processing Magazine* 20.3 (May 2003), pp. 21–36. DOI: [10.1109/MSP.2003.1203207](https://doi.org/10.1109/MSP.2003.1203207)

ML/MAP super-resolution:

- Lyndsey C. Pickup. “Machine Learning in Multi-frame Image Super-resolution”. PhD Thesis. Robotics Research Group, University of Oxford, 2007
- Michael Elad and Arie Feuer. “Restoration of a Single Superresolution Image from Several Blurred, Noisy, and Undersampled Measured Images”. In: *IEEE Transactions on Image Processing* 6.12 (Dec. 1997), pp. 1646–1658. DOI: [10.1109/83.650118](https://doi.org/10.1109/83.650118)