

bKash PGW Tokenized Payment

API Documentation

Sheikh Pharma

Version 1.0 | April 2026

1. Overview

This document describes the bKash PGW (Payment Gateway) Tokenized Checkout integration for Sheikh Pharma (sheikhpharma.shop). All APIs are implemented as Supabase Edge Functions.

Base URL: <https://vkfloynvxqkxbqpdIzbd.supabase.co/functions/v1>

Callback URL: <https://sheikhpharma.shop/bkash/callback>

bKash Base URL (Sandbox): <https://tokenized.sandbox.bka.sh/v2>

bKash Base URL (Production): <https://tokenized.pay.bka.sh/v2>

2. API Summary

#	API Name	Endpoint	Method
1	Grant Token	(Internal - auto)	POST
2	Create Payment	/bkash-create-payment	POST
3	Execute Payment	/bkash-execute-payment	POST
4	Query Payment	/bkash-execute-payment (fallback)	POST
5	Search Transaction	/bkash-search-transaction	POST
6	Refund	/bkash-refund	POST
7	Refund Status	/bkash-refund	POST

3. Grant Token API

Automatically called internally before Create, Execute, Query, Search, and Refund operations. Tokens are cached for 50 minutes.

bKash Endpoint

```
POST {bkash_base_url}/tokenized-checkout/auth/grant-token
```

Request Headers

Parameter	Type	Description
Content-Type	string	application/json
Accept	string	application/json
username	string	bKash merchant username
password	string	bKash merchant password

Request Body

```
{ "app_key": "...", "app_secret": "..." }
```

Response

```
{ "id_token": "eyJhbGciOiJIUzI1...", "token_type": "Bearer", "expires_in": 3600 }
```

4. Create Payment API

Initializes a bKash payment and returns a redirect URL for the customer.

Endpoint

POST <https://vkfloynvxqkxbqpdIzbd.supabase.co/functions/v1/bkash-create-payment>

Request Body

Parameter	Type	Description
amount	number	Payment amount in BDT (required)
order_id	string	Order UUID from the system (required)
callback_url	string	URL to redirect after payment (required)

Example Request

```
{ "amount": 500, "order_id": "abc-123-def", "callback_url":  
  "https://sheikhpharma.shop/bkash/callback" }
```

Success Response (200)

```
{ "bkashURL": "https://tokenized.pay.bka.sh/...", "paymentID": "TR001234" }
```

Error Response (400)

```
{ "error": "Create payment failed", "errorCode": "2001" }
```

5. Execute Payment API

Called after the customer completes payment on bKash. Confirms the transaction. If Execute times out (30s), Query Payment API is automatically called as fallback.

Endpoint

POST <https://vkfloynvxqkxbqpdldbd.supabase.co/functions/v1/bkash-execute-payment>

Request Body

Parameter	Type	Description
paymentID	string	Payment ID from bKash callback (required)
order_id	string	Order UUID from the system (required)
payment_type	string	Optional: 'cod_delivery_charge', 'lab_service', or empty for full payment

Example Request

```
{ "paymentID": "TR001234", "order_id": "abc-123-def" }
```

Success Response (200)

```
{ "success": true, "trxID": "9HK3001F5E", "amount": "500" }
```

Error Response (400)

```
{ "success": false, "error": "Payment not completed", "statusCode": "2023" }
```

6. Query Payment API (Fallback)

If Execute Payment does not return a response within 30 seconds, this API is automatically called to check the payment status. It is built into the Execute Payment edge function.

bKash Endpoint (called internally)

POST [{bkash_base_url}/tokenized-checkout/payment/status](#)

Request Body

```
{ "paymentID": "TR001234" }
```

Response

```
{ "paymentID": "TR001234", "trxID": "9HK3001F5E", "transactionStatus": "Completed", "amount": "500" }
```

7. Search Transaction API

Search for any transaction using the bKash Transaction ID (trxID).

Endpoint

POST <https://vkfloynvxqkxbqpdIzbd.supabase.co/functions/v1/bkash-search-transaction>

Request Body

Parameter	Type	Description
trxID	string	bKash Transaction ID (required)

Example Request

```
{ "trxID": "9HK3001F5E" }
```

Response

```
{ "trxID": "9HK3001F5E", "initiationTime": "2026-04-13T10:00:00", "completedTime": "2026-04-13T10:01:00", "transactionStatus": "Completed", "amount": "500", "currency": "BDT", "customerMsisdn": "01XXXXXXXXX" }
```

8. Refund API

Process a refund for a completed bKash transaction. If refund response is unclear, Refund Status is automatically checked as fallback.

Endpoint

POST <https://vkfloynvxqkxbqpdldbd.supabase.co/functions/v1/bkash-refund>

Request Body

Parameter	Type	Description
action	string	"refund" (required)
paymentID	string	Original bKash Payment ID (required)
trxID	string	Original bKash Transaction ID (required)
amount	number	Refund amount in BDT (required)
reason	string	Reason for refund (optional)
sku	string	Product SKU (optional)

Example Request

```
{ "action": "refund", "paymentID": "TR001234", "trxID": "9HK3001F5E", "amount": 500, "reason": "Customer return" }
```

Success Response

```
{ "originalTrxID": "9HK3001F5E", "refundTrxID": "9HK3001F5F", "transactionStatus": "Completed", "amount": "500", "completedTime": "2026-04-13T12:00:00" }
```

9. Refund Status API

Check the status of a refund request. Mandatory if refund response is not received within 30 seconds.

Endpoint

POST <https://vkfloynvxqkxbqpdldbd.supabase.co/functions/v1/bkash-refund>

Request Body

Parameter	Type	Description
action	string	"refund_status" (required)
paymentID	string	Original bKash Payment ID (required)
trxID	string	Original bKash Transaction ID (required)

Example Request

```
{ "action": "refund_status", "paymentID": "TR001234", "trxID": "9HK3001F5E" }
```

Response

```
{ "originalTrxID": "9HK3001F5E", "refundTrxID": "9HK3001F5F", "transactionStatus": "Completed", "amount": "500", "completedTime": "..." }
```

10. Payment Flow

1. Customer selects bKash at checkout
2. System calls Create Payment API to get bKashURL
3. Customer is redirected to bKash for payment (OTP + PIN)
4. bKash redirects to callback URL: <https://sheikhpharma.shop/bkash/callback>
5. Callback page calls Execute Payment API with paymentID
6. If Execute times out, Query Payment API is called automatically
7. Order is updated as paid on success

11. Credentials Storage

All bKash credentials are stored securely as Supabase Edge Function secrets and also configurable via `site_settings` table:

Parameter	Type	Description
BKASH_APP_KEY	string	bKash App Key
BKASH_APP_SECRET	string	bKash App Secret
BKASH_USERNAME	string	bKash Merchant Username
BKASH_PASSWORD	string	bKash Merchant Password
BKASH_BASE_URL	string	bKash API Base URL (sandbox/production)