


FACULTY OF
COMPUTER SCIENCE

Otto-von-Guericke-University Magdeburg

**Faculty of Computer Science**

Department of Databases and Software Engineering

# TBD

## Bachelor thesis

Author:

Lukas Eichel

Examiner:

Prof. Dr. rer. nat. habil. Gunter Saake

2nd Examiner and Supervisor:

Dr.-Ing. David Broneske

Magdeburg, 31.07.2024

## Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguique possit, augeri amplificarique non possit. At etiam Athenis, ut e patre audiebam facete et urbane Stoicos irridente, statua est in quo a nobis philosophia defensa et collaudata est, cum id, quod maxime placeat, facere possimus, omnis voluptas assumenda est, omnis dolor repellendus. Temporibus autem quibusdam et.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguique possit, augeri amplificarique non possit. At etiam Athenis, ut e patre audiebam facete et urbane Stoicos irridente, statua est in quo a nobis philosophia defensa et collaudata est, cum id, quod maxime placeat, facere possimus, omnis voluptas assumenda est, omnis dolor repellendus. Temporibus autem quibusdam et.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguique possit, augeri amplificarique non possit. At etiam Athenis, ut e patre audiebam facete et urbane Stoicos irridente, statua est in quo a nobis philosophia defensa et collaudata est, cum id, quod maxime placeat, facere possimus, omnis voluptas assumenda est, omnis dolor repellendus. Temporibus autem quibusdam et.

# Contents


**1. Introduction** **1**

1.1. Motivation . . . . . 1

1.2. Structure . . . . . 1

**2. Background** **1**

2.1. Emotion . . . . . 2

2.1.1. Emotion Classification . . . . . 3

2.1.2. Emotion in Text . . . . . 4

2.1.3. Emotion in Speech . . . . . 4

2.1.4. Emotion in Facial Expression . . . . . 5

2.2. Classification Approaches . . . . . 6

2.2.1. Classification in Text . . . . . 6

2.2.2. Classification in Audio . . . . . 9

2.2.3. Classification in Images and Videos . . . . . 9

2.3. Datasets . . . . . 9

**Bibliography** **11**


use more s
for
“word”

# Chapter 1.

# Introduction

## 1.1. Motivation

motivation

## 1.2. Structure

structure

# Chapter 2.

# Background

*This chapter will give an introduction and overview on different approaches to classify types of emotions with respect to their advantages and disadvantages. Furthermore it will explain the approaches to recognize emotion in the mediums text, video and audio. Based on this common implementation techniques and architectures for Neural Networks are presented.*

use m
syno
for “v

## 2.1. Emotion

There is no unambigious definition for the term ‘emotion’. There are many different emotion, with different level of intensity. While asking what an emotion is and where it comes from, William James discussed two different theories about the origin of them. Either there are seperate ares in the cerebrum or else they correspond to motory and sensory processes [1]. Many work in psychology add further aspects to the latter. In order to provide a framework, the following chapters will focus just on the outputted emotion and how to recognize it.





Figure 2.1.: Information flows from both high to low to high in a system that can express, recognize and “have” emotions [2].

As shown in the figure, the motory and senory processes are considered as high-level information. This is defined as the semantic of the situation like the emotion state of the person,

or an instruction to the computer to simulate a expression. The left side of the figure shows the latter. However the right side explains that low-level expressive information, like a facial expression or a pitch change in the voice is needed to get the semantic of the emotional state. In addition there can be non-expressive data as a valid input. It describes the passive influence on a persons state like the weather or the setting of the environment. Most datasets won't cover this type of information.

The mid-level patterns the given input and combines different low-level signals to get a better reasioning for an high-level output. For example a slightly faster speech rate and a tense articulation can be clustered together to get classified as an angered expression.

### 2.1.1. Emotion Classification

There are different apporaches to classify the semantic high-level features. The most popular classification is the basic-emotion framework by Paul Ekman [3] describing six different emotions: anger, disgust, fear, surprise, sadness and happiness. This arose from different facial expression, which Ekman categorized to the corresponding emotion.

Over the time different frameworks were built on this foundation to introduce for each basic emotion multiple detailled emotions. A common model is the Plutchik wheel of emotion, which is commonly used to classify emotion in text. It offers eight types of basic emotion: joy, trust, fear, surprise and their opposites sadness, disgust, anger and anticipation [4].





Figure 2.2.: Plutchik Wheel of Emotion [5].

For each emotion there are multiple level of intensity. For example the enhanced level for disgust is loathing, a more moderate level is boredom. In total there are 24 different emotion.

Why can it be better to have more emotion variety?

Although there will be a loss of detail, the content of this thesis will focus on the basic emotion from Paul Ekman. The wheel of emotion from Plutchik is suitable for emotion detection in text but most datasets in facial emotion recognition are focused on Ekmans emotion theory .

Why I wont use the Wheel of Emotion

### 2.1.2. Emotion in Text

The most common approach to classify emotion from natural language text, is to cluster the content from these sentences. In order to make it possible, two assumptions are needed.

1. There is a function that is able to map words and sentences to their corresponding emotion.

This can be approached by training a deep neural network with a suitable dataset or a clustering algorithm that measures the similarity between words and sentences to match their corresponding emotion label. The function must be surjective, so a token won't be able to be labeled with more than one emotion at the time.

For a relieable result in training, the second assumption is important.

2. Words and sentences do not change their meaning over time.

This is also the flaw from emotion detection in text. For example the sentence "I'm glad to be here"

briefly explain irony which can lead to different meanings for the same sentence

### 2.1.3. Emotion in Speech

show different chanings in audio diagrams

| Emotion / Feature | Fear | Anger | Sadness | Hapiness | Disgust |
|---|---|---|---|---|---|
| **Speech Rate** | much faster | slightly faster | slightly slower | faster or slower | very much slower |
| **Pitch Average** | very much higher | very much higher | slightly lower | much higher | very much lower |
| **Pitch Range** | much wider | much wider | slightly narrower | much wider | slightly wider |
| **Intensity** | normal | higher | lower | higher | lower |
| **Voice Quality** | irregular voicing | breathy chest tone | resonant | breathy blaring | grubled chest tone |
| **Pitch Changes** | normal | abrupt on stressed syllables | downward inflections | smooth upward inflections | wide downward terminal inflections |
| **Articulation** | precise | tense | slurring | normal | normal |

Table 2.1.: Features of an audio with correlating emotion [2], [6].

### 2.1.4. Emotion in Facial Expression

talk about the facs system

## 2.2. Classification Approaches

Over time many approaches to detect and classify emotion has been developed. There are severeral supervised architectures and unsupervised techniques which represent the current state of the art for emotion detection in text, audio and video.

### 2.2.1. Classification in Text

## Word Embedding and Tokenization

The most important part of all classification approaches is called word embedding. It represents words as real-valued vectors [7]. It uses syntactic but also the semantic meaning of the words to get a useful vector. This technique is commonly used in natural language processing like information retrieval in text.

To generate such an embedding function $A$, a one-hot vector [8] is needed. It represents every word in a space of words as an different vector. For example the sentence:

$$\textit{The tree is green.}$$

will be first tokenized into a set of words $V$.

$$V = \{\textit{the}, \textit{tree}, \textit{is}, \textit{green}\}$$

The size of the set $|V| = 4$. As a result a mapping $w \in V$ to a $|V|$-dimensional vector is needed.

$$A : V \to \mathbb{R}^{|V|}$$

| $w_i \in V$ | $A(w_i)$ | $w_i \in V$ | $A(w_i)$ |
|---|---|---|---|
| the | $\begin{pmatrix}1\\0\\0\\0\end{pmatrix}$ | tree | $\begin{pmatrix}0\\1\\0\\0\end{pmatrix}$ |
| is | $\begin{pmatrix}0\\0\\1\\0\end{pmatrix}$ | green | $\begin{pmatrix}0\\0\\0\\1\end{pmatrix}$ |

Table 2.2.: Possible one-hot vector mapping for the sentence “The tree is green.”

To measure the similarity the cosine similarity is often used [8], [9]. Similar words or synonyms should have a smaller angle between each other, than unsimilar words.

$$\text{sim}(w_1, w_2) = \cos(\theta) = \frac{w_1 \cdot w_2}{\|w_1\| \, \|w_2\|}$$

While the one-hot vector embeds it syntactically only, there won’t be any similarity or dissimilarity between the words. Therefore a semantic consideration will be useful.

**The Continous Bag-of-Words Model**, shortly CBOW is capable to take context of a word as an input to calculate an embedded vector with emphasis on syntax and semantic. It consists of a neural network which mainly constitutes of three layers: the input layer, a hidden layer and the output layer [10].





Figure 2.3.: Left: Simple CBOW-architecture for a single word; Right: CBOW-architecture for multiple words. Words have length $k$ and are padded to size $V$ to match the dimension [8].

The architecture shown on the right side of Figure 3 takes one one-hot vector $A(w_i)$ as an input expression. To get the context of the inputted term, phrases before and after are needed. Therefore an addition to the architecture is necessary.

With unspuervised learning the model on the right of Figure 3 is able to generate a new vector which represents the context of a word. Now, under consideration of the cosine similarity, words with a similar context have a quite smaller angle then without any connection in semantics. In both architectures, the hidden layer acts like an arithmetic operator which combines the context to the outputted one-hot vector.





Figure 2.4.: Skip-Gram Model. All words have size V (after padding) [11].

**The Skip-Gram Model** calculates an embedding in reverse from the idea of the CBOW-Model. As the architecture shows in Figure 4 it tries to calculate the surrounding words with a given target term. Therefore a training like the CBOW with contextual phrases is needed before it can work like a semantical decoder. Both architectures are commonly used in different pretrained word embedding networks, like Word2Vec from Google [11], [12].

**Fast WordPiece Tokenization** is an approach to tokenize sentences and words in an efficient way by splitting words into smaller subwords. It is used in a language understanding transformer model from Google which is called Bert [13].

The basic problem from other tokenization methods like the normal WordPiece Tokenization starts in the vocabulary tokenization in tries. Trie memory is a paradigma which is able to store strings efficiently where each edge of the data structure stores phonemes. Traversing a path consisting of multiple edges results in a word. As a result the structure does not have to store reduntant parts of words [14].

The tokenization has to search for the longest token at a position. Therefore it starts from the shortest substring and iterates over the input text, while trie matching to match the longest prefix which matches a vocabulary token [15]. If the trie matching fails at the next character, the algorithm has to involve backtracking because the longest vocabulary token may be several characters back. This results into a time complexity of $O(nm)$ where $m$ is the maximum vocabulary token length and $n$ the input length.

Fast WordPiece Tokenization introduces so called failure links and pops. Failure pops are a list of longest-matching prefix tokens of a node in the trie, which can be removed in order until a failure link node is reached. The failure node is able to represent the missing suffix. This whole algorithm called LinMaxMatch has a time complexity of only $O(n)$.

## Supervised Approaches

With a given word embedding and tokenization supervised learning approaches are able to recognize emotion in text. Therefore an annotated dataset is needed, which has a relieable mapping from sentence or word to the corresponding emotion.





Figure 2.5.: Deep Learning Assisted Semantic Text Analysis

Most models are using the architecture paradigma shown in Figure 5. They mostly differ in the step of combining the feature vectors ant the type of classification because it offers the biggest room to maneuver. A preprocessing and feature extraction is always necessary. Sometimes a WordNet [16] is integrated to get a better overview about synonyms or to paraphrase words.

**Convolutional and Recurrent Neural Networks (CNN/RNN)** are an effective approach on sentiment analysis of text [17]. Convulation consists of a kernel-funciton which

downscales the input but keeps the important features. This technique is called Pooling and brings several benefits like less memory usage, less overfitting in training and a faster computation time. An appropriate kernel function for text evaluation can be an CBOW model in between of the calculation layers. It is able to reduce multiple words to a single one-hot vectors

ToDo

#### Suport Vector Machines (SVM)

"Write about an Idea"

#### Transormers

"Write about an Idea"

There are also some approaches with Naive-Bayes Networks like .... These aren't covered in this thesis and relay to future work.

find some nb

## Unsupervised Approaches

## 2.2.2. Classification in Audio

## 2.2.3. Classification in Images and Videos

## 2.3. Datasets

# Bibliography


[1] W. James, "What is an Emotion?," *Mind*, vol. 9, no. 34, pp. 188–205, 1884, Accessed: Mar. 11, 2024. [Online]. Available: http://www.jstor.org/stable/2246769

[2] R. W. Picard, "Affective computing." MIT Press, Cambridge, Mass. [u.a.], 1997.

[3] K. R. Scherer and P. Ekman, Eds., *Approaches To Emotion*, 1st ed. Psychology Press, 1984.

[4] P. Kumar and M. Vardhan, "PWEBSA: Twitter sentiment analysis by combining Plutchik wheel of emotion and word embedding," *International Journal of Information Technology*, vol. 14, no. 1, pp. 69–77, Feb. 2022.

[5] D. Chafale and A. Pimpalkar, "Review on Developing Corpora for Sentiment Analysis Using Plutchik's Wheel of Emotions with Fuzzy Logic," *International Journal of Computer Sciences and Engineering (IJCSE)*, vol. 2, pp. 14–18, 2014.

[6] I. R. Murray and J. L. Arnott, "Applying an analysis of acted vocal emotions to improve the simulation of synthetic speech," *Computer Speech & Language*, vol. 22, no. 2, pp. 107–129, 2008, [Online]. Available: https://www.sciencedirect.com/science/article/pii/S0885230807000393

[7] B. Wang, A. Wang, F. Chen, Y. Wang, and C.-C. J. Kuo, "Evaluating word embedding models: methods and experimental results," *APSIPA Transactions on Signal and Information Processing*, vol. 8, p. e19, 2019, doi: 10.1017/ATSIP.2019.12.

[8] D. Karani, "Introduction to word embedding and Word2Vec," *Towards Data Science*, vol. 1, 2018.

[9] Y. Li and T. Yang, "Word Embedding for Understanding Natural Language: A Survey," in *Guide to Big Data Applications*, S. Srinivasan, Ed., Cham: Springer International Publishing, 2018, pp. 83–104.

[10] K. Choudhary and R. Beniwal, "Xplore Word Embedding Using CBOW Model and Skip-Gram Model," in *2021 7th International Conference on Signal Processing and Communication (ICSC)*, 2021, pp. 267–270. doi: 10.1109/ICSC53193.2021.9673321.

[11] T. Mikolov, K. Chen, G. Corrado, and J. Dean, "Efficient estimation of word representations in vector space," *arXiv preprint arXiv:1301.3781*, 2013.

[12] L. Ma and Y. Zhang, "Using Word2Vec to process big text data," in *2015 IEEE International Conference on Big Data (Big Data)*, 2015, pp. 2895–2897. doi: 10.1109/BigData.2015.7364114.

[13] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding." 2019.

[14] E. Fredkin, "Trie memory," *Commun. ACM*, vol. 3, no. 9, pp. 490–499, Sep. 1960, doi: 10.1145/367390.367400.

[15] X. Song, A. Salcianu, Y. Song, D. Dopson, and D. Zhou, "Fast WordPiece Tokenization," in *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, M.-F. Moens, X. Huang, L. Specia, and S. W.-t. Yih, Eds., Online and Punta Cana, Dominican Republic: Association for Computational Linguistics, Nov. 2021, pp. 2089–2103. doi: 10.18653/v1/2021.emnlp-main.160.

[16] C. Fellbaum and K. Brown, "Encyclopedia of language and linguistics." Elsevier Oxford, 2005.

[17] B. Liu, "Text sentiment analysis based on CBOW model and deep learning in big data environment," *Journal of ambient intelligence and humanized computing*, vol. 11, no. 2, pp. 451–458, 2020.

[18] K. Roberts, M. A. Roach, J. Johnson, J. Guthrie, and S. M. Harabagiu, "EmpaTweet: Annotating and Detecting Emotions on Twitter.," in *Lrec*, 2012, pp. 3806–3813.

,

# Appendix C.

# Appendix

# Statement of Authorship

I herewith assure that I wrote the present thesis independently, that the thesis has not been partially or fully submitted as graded academic work and that I have used no other means than the ones indicated. I have indicated all parts of the work in which sources are used according to their wording or to their meaning.

I am aware of the fact that violations of copyright can lead to injunctive relief and claims for damages of the author as well as a penalty by the law enforcement agency.

Magdeburg, July 31, 2024

_____

Signature