

Apply filters to SQL queries

My organization is focused on strengthening system security. As part of my role, I investigate potential security issues, safeguard the system, and ensure employee computers are properly updated. This project demonstrates how I applied SQL filters to identify and analyze security-related activities.

Retrieve After Hours Failed Login Attempts (Rewritten)

A potential security incident occurred outside normal business hours (after 18:00). To investigate, I created a SQL query that retrieves all failed login attempts that happened after this time.

This query filters the `log_in_attempts` table to show only records where the login time is later than 18:00 and the attempt was unsuccessful.

```
MariaDB [organization]> SELECT *  
  -> FROM log_in_attempts  
  -> WHERE login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0

The first part of the screenshot is my query, and the second part is a portion of the output. This query filters for failed login attempts

that occurred after 18:00. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `AND` operator to filter my results to output only login attempts that occurred after 18:00 and were unsuccessful. The first condition is `login_time > '18:00'`, which filters for the login attempts that occurred after 18:00. The second condition is `success = FALSE`, which filters for the failed login attempts.

Retrieve login attempts on specific dates

A suspicious event occurred on 2022-05-09. Any login activity that happened on 2022-05-09 or on the day before needs to be investigated.

The following code demonstrates how I created a SQL query to filter for login attempts that occurred on specific dates.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all login attempts that occurred on 2022-05-09 or 2022-05-08. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `OR` operator to filter my results to output only login attempts that occurred on either 2022-05-09 or 2022-05-08. The first condition is `login_date = '2022-05-09'`, which filters for logins on 2022-05-09. The

second condition is `login_date = '2022-05-08'`, which filters for logins on 2022-05-08.

Retrieve login attempts outside of Mexico

After investigating the organization's data on login attempts, I believe there is an issue with the login attempts that occurred outside of Mexico. These login attempts should be investigated.

The following code demonstrates how I created a SQL query to filter for login attempts that occurred outside of Mexico.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all login attempts that occurred in countries other than Mexico. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with `NOT` to filter for countries other than Mexico. I used `LIKE` with `MEX%` as the pattern to match because the dataset represents Mexico as `MEX` and `MEXICO`. The percentage sign (%) represents any number of unspecified characters when used with `LIKE`.

Retrieve employees in Marketing

My team wants to update the computers for certain employees in the Marketing department. To do this, I have to get information on which employee machines to update.

The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Marketing department in the East building.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Marketing' AND office LIKE 'East%';  
+-----+-----+-----+-----+-----+  
| employee_id | device_id      | username | department | office      |  
+-----+-----+-----+-----+-----+  
|          1000 | a320b137c219 | elarson  | Marketing  | East-170    |  
|          1052 | a192b174c940 | jdarosa  | Marketing  | East-195    |  
|          1075 | x573y883z772 | fbautist | Marketing  | East-267    |
```

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Marketing department in the East building. First, I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `AND` to filter for employees who work in the Marketing department and in the East building. I used `LIKE` with `East%` as the pattern to match because the data in the `office` column represents the East building with the specific office number. The first condition is the `department = 'Marketing'` portion, which filters for employees in the Marketing department. The second condition is the `office LIKE 'East%'` portion, which filters for employees in the East building.

Retrieve employees in Finance or Sales

The machines for employees in the Finance and Sales departments also need to be updated. Since a different security update is needed, I have to get information on employees only from these two departments.

The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Finance or Sales departments.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Finance and Sales departments. First, I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `OR` to filter for employees who are in the Finance and Sales departments. I used the `OR` operator instead of `AND` because I want all employees who are in either department. The first condition is `department = 'Finance'`, which filters for employees from the Finance department. The second condition is `department = 'Sales'`, which filters for employees from the Sales department.

Retrieve all employees not in IT

My team needs to make one more security update on employees who are not in the Information Technology department. To make the update, I first have to get information on these employees.

The following demonstrates how I created a SQL query to filter for employee machines from employees not in the Information Technology department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434

The first part of the screenshot is my query, and the second part is a portion of the output. The query returns all employees not in the Information Technology department. First, I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `NOT` to filter for employees not in this department.

Summary

I applied SQL filters to extract key information about login attempts and employee machines from the **log_in_attempts** and **employees** tables. To narrow down results, I used the **AND**, **OR**, and **NOT** operators, along with the **LIKE** keyword and the % wildcard for pattern matching. These techniques allowed me to efficiently identify suspicious activities and target specific employee groups for security update