

SolarWinds - AEM Edge Delivery Services Admin Guide

Configuration, access, publishing, and operational
procedures

Date: October 6, 2026

Table of Contents

- SolarWinds - AEM Edge Delivery Services Admin Guide 3
 - Quick Reference 3
 - Operating Model 3
 - Authentication and Roles 4
 - Admin API Command Templates 5
 - Configuration Changes and Recovery 6
 - Logs and Common Troubleshooting 7
 - Operational Checklist 7
 - References 8

SolarWinds - AEM Edge Delivery Services Admin Guide

Administration reference for the SolarWinds site. The organization and site details below were supplied from a verified Config Service session. The command examples are templates only: they have not been executed by this guide. Before using one, confirm the target, use an approved token, and ensure your account has the required role.

Quick Reference

Purpose	Destination
Admin login	https://admin.hlx.page/login/adobedrago/solarwinds-eds
Config Service	https://admin.hlx.page/config/adobedrago/
Config UI	https://tools.aem.live/
Preview	https://main-solarwinds-eds-adobedrago.aem.page/
Live	https://main-solarwinds-eds-adobedrago.aem.live/
Document Authoring	https://da.live/#/adobedrago/solarwinds-eds/

Setting	Verified value
Organization	adobedrago
Site	solarwinds-eds
Setup	Single standard site
Code repository	adobedrago/solarwinds-eds
Content source	https://content.da.live/adobedrago/solarwinds-eds (markup)
Production code branch	main

Operating Model

The Config Service is the authoritative place for site configuration. Use the Config UI for routine interactive changes, and use the Admin API when automation or a repeatable command is appropriate. A successful API response means the request was accepted or completed; for asynchronous bulk operations, check the returned job before reporting completion.

Code and content have separate release paths. Merging approved code changes to `main` ships code through AEM Code Sync. Content authors work in Document Authoring, preview changes, review the preview URL, and publish approved content separately. Publishing content does not deploy repository code, and merging code does not publish content edits.

Authentication and Roles

Open the Admin login URL above and sign in through the configured identity provider. For API work, send an Admin API token in the `x-auth-token` request header. Never put a real token in a command saved to shell history, a script, a repository, a ticket, or this guide. Initialize `AUTH_TOKEN` using your organization-approved credential handling method in the current terminal session; do not print it. An API key, when explicitly provisioned for automation, uses the documented authorization: `token <API_KEY>` header and should be narrowly scoped and rotated under organizational policy.

The Admin API checks both the authenticated identity and the role required by the operation. Use the least-privileged role that covers the task.

Role	Typical responsibility
<code>basic_author</code>	Basic author operations, including preview work
<code>author</code>	Author workflows and related preview/job operations
<code>publish</code>	Author capabilities plus publishing and live-resource operations
<code>develop</code>	Author capabilities plus code updates
<code>config</code>	Read redacted configuration only
<code>config_admin</code>	Read and change configuration; includes publish capabilities
<code>admin</code>	All Admin API permissions; reserve for trusted administrators

Review and Change Site Role Mappings

Read the current access configuration before editing it. Role mappings live under `access/admin`; do not confuse them with the organization user directory. Preserve existing mappings when changing one person so you do not unintentionally remove other users' access. This request is a template for granting an author and a configuration administrator:

```
curl -X POST "https://admin.hlx.page/config/${ORG}/sites/${SITE}/access/admin.json" \
-H "content-type: application/json" \
-H "x-auth-token: ${AUTH_TOKEN}" \
--data '{
  "role": {
    "author": ["author@example.com"],
    "config_admin": ["config-admin@example.com"]
  }
}'
```

Replace the example addresses with approved identities and merge this example with the existing access settings before sending. To remove a person from a role, update that role's configured identity list and retain all other entries. Review the effective config after the change. Do not delete the site or overwrite the whole site configuration to change an access mapping.

For the separate organization user directory, list entries with `GET /config/{org}/users.json`, create or update an entry with `POST /config/{org}/users.json` and a JSON body containing `email` and `roles`, and remove a directory entry with `DELETE /config/{org}/users/{id}.json`. These directory operations do not replace the site's `access/admin` role mapping; confirm which access layer needs to change before modifying either.

Admin API Command Templates

The following examples target this repository's known production identifiers. Set these non-secret values in the terminal and initialize AUTH_TOKEN securely before running an example:

```
export ORG=adobedrago
export SITE=solarwinds-eds
export OWNER=adobedrago
export REPO=solarwinds-eds
export REF=main
```

Commands below are operational templates, not records of actions performed. Confirm the target path and approval first. Replace /path/to/page with the site-relative path, usually without the domain name. Shell quoting and URL-encode path characters as needed.

Check Site or Resource Status

```
curl -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/config/${ORG}/sites/${SITE}.json"

curl -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/status/${ORG}/${SITE}/${REF}/path/to/page"
```

The first request reads site configuration. The second reports status for a resource, including preview and live state where available. The Config UI is also suitable for reviewing configuration interactively.

Preview and Publish Content

For an individual page, update preview from the configured content source, inspect the preview URL and content, then publish only after approval:

```
curl -X POST -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/preview/${ORG}/${SITE}/${REF}/path/to/page"

curl -X POST -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/live/${ORG}/${SITE}/${REF}/path/to/page"
```

Publishing copies the previewed resource to live and purges the live CDN. To unpublish a page, use the destructive operation below only after confirming the URL and approval:

```
curl -X DELETE -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/live/${ORG}/${SITE}/${REF}/path/to/page"
```

Bulk preview and publish use a wildcard endpoint with a JSON paths list. Bulk jobs can run asynchronously and return a job link or name; inspect that job and its details before declaring the work complete. Never use a broad wildcard until its impact is understood.

```
curl -X POST "https://admin.hlx.page/preview/${ORG}/${SITE}/${REF}/*" \
  -H "content-type: application/json" \
  -H "x-auth-token: ${AUTH_TOKEN}" \
  --data '{"paths":["/section/*"]}'

curl -X POST "https://admin.hlx.page/live/${ORG}/${SITE}/${REF}/*" \
```

```
-H "content-type: application/json" \  
-H "x-auth-token: ${AUTH_TOKEN}" \  
--data '{"paths":["/section/*"]}'
```

Check an Asynchronous Job

Use the job URL returned by the API whenever possible. The general job status route is:

```
curl -H "x-auth-token: ${AUTH_TOKEN}" \  
"https://admin.hlx.page/job/${ORG}/${SITE}/${REF}/preview/${JOB_NAME}"
```

Replace `preview` with the operation topic, such as `publish`, and set `JOB_NAME` to the name returned by the API. Check progress and failed-item details. Starting a bulk request is not the same as confirming every item succeeded.

Purge a Live Cache Entry

Publishing normally purges the live CDN for that resource. Use cache purge only when a stale delivery cache remains or the operation is otherwise approved. This endpoint purges a single path:

```
curl -X POST -H "x-auth-token: ${AUTH_TOKEN}" \  
"https://admin.hlx.page/cache/${ORG}/${SITE}/${REF}/path/to/page"
```

The wildcard form can affect the whole site. Avoid it as a routine troubleshooting step.

Refresh Code Bus Content

Code is normally synchronized when approved changes land on `main`. If an administrator must explicitly refresh the code bus, the recursive code update template is:

```
curl -X POST -H "x-auth-token: ${AUTH_TOKEN}" \  
"https://admin.hlx.page/code/${OWNER}/${REPO}/${REF}/*"
```

Coordinate a manual refresh with the code owner. This updates code-bus content from the repository branch; it is not a substitute for code review or merging a change.

Configuration Changes and Recovery

Inspect the current site configuration before changing it. Headers are managed under the site's `headers` config; CDN settings under `cdn`; access roles under `access/admin`. There were no custom header or CDN values supplied for this handover, so review the live configuration in the Config UI or Admin API rather than assuming those settings are empty.

Do not casually change the production code owner/repository or the content source. A content source change creates a new Content Bus ID; previously previewed and published content must be previewed and published again, and index/sitemap configuration may need to be recreated. For risky production changes, validate on a separate site/configuration first and follow the organization's change approval process.

Configuration versions can be reviewed and restored using the Admin API. Record the current state and the intended version before a restore; a restore changes active configuration:

```
curl -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/config/${ORG}/sites/${SITE}/versions.json"

curl -X POST -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/config/${ORG}/sites/${SITE}.json?restoreVersion=${VERSION_ID}"
```

Logs and Common Troubleshooting

```
curl -H "x-auth-token: ${AUTH_TOKEN}" \
  "https://admin.hlx.page/log/${ORG}/${SITE}/${REF}?since=15m"
```

Symptom	Checks and next step
401 Unauthorized	Sign in again or renew the approved token; verify the header format and expiry without printing the token.
403 Forbidden	Confirm the caller's identity, site role mapping, and permission required by the specific operation. <code>config</code> is read-redacted; use <code>config_admin</code> for configuration changes.
404 Not Found	Check organization, site, branch, path spelling, and whether the resource exists in the expected content source.
429 Too Many Requests	Respect the service rate limit and retry after a suitable delay; avoid repeated broad bulk requests.
Bulk operation appears unfinished	Follow the returned job link and inspect progress and failed-item details.
Preview is stale	Update preview from the content source, then inspect the preview URL and Admin API status.
Live is stale	Confirm the approved content is in preview, publish that resource, then check live status and delivery. Purge a cache entry only if required.
Code is stale	Confirm the change is on the intended repository branch and that code sync has run; use the manual refresh template only with the code owner's approval.

Operational Checklist

1. Confirm the exact site, branch, and resource path before any API request.
2. Verify the account or API key has only the permissions needed for the task.
3. Preview and review content before publishing; treat delete, wildcard, and configuration restore operations as high impact.
4. For bulk operations, retain the returned job reference and verify the final job state and failures.
5. Record the change through the team's normal approval/audit process, without recording credentials.

References

Resource	URL
AEM Admin API reference	https://www.aem.live/docs/admin.html
Config Service setup	https://www.aem.live/docs/config-service-setup
Author authentication and role permissions	https://www.aem.live/docs/authentication-setup-authoring
AEM Edge Delivery Services operational UI	https://tools.aem.live/