

A Condition-Indexed Operating Envelope and Representation-Repair Study for Automatic Modulation Classification under Structured Interference

Anonymous Author(s)

Abstract—Uniform model rankings hide a central design question in automatic modulation classification (AMC): under structured interference, the ranking of a compact spectral representation and a much larger I/Q-domain classifier can itself depend on physical conditions. We study this rank exchange in source-disjoint 3GPP TR 38.901 TDL-profile simulations, comparing VIMD-Net, a 39500-parameter spectral network, with strong I/Q-domain comparators across the complete SNR–SIR plane. The original sealed confirmatory family resolves a positive whole-configuration contrast of 4.57 percentage points ([3.65, 5.49] percentage points) for the complete configuration over its shared spectral backbone, while the two component-level interventions (teacher form and route count) are bounded rather than individually resolved. Marginally over the hard-interference split the compact model trails both I/Q comparators (macro-F1 0.4406 versus 0.4599 and 0.4872); the ranking reverses only in the severe, high-overlap corner. In a post-hoc severe-interference analysis at SIR = −15 dB, the compact model gains 9.74 percentage points over MCLDNN and 10.46 percentage points over IQFormer-inspired, with a positive paired effect in all ten seeds. A two-variable overlap–SIR envelope, where overlap is the fraction of jammer energy inside the target’s dominant time–frequency support, is fitted on in-distribution and hard-interference cells only. It predicts the gain against IQFormer-inspired on held-out regime cells with RMSE 6.23 percentage points versus 8.37 percentage points for a constant predictor estimated from the fitting cells ($R_{\text{skill}}^2 = 0.45$); the validated skill is cross-regime transport of gain magnitude rather than sign classification. A failed clean-retention gate is then localized and repaired prospectively: a received-I/Q sidecar raises the total model size from 39500 to 46794 parameters while improving clean macro-F1 by 11.77 percentage points and hard-interference macro-F1 by 4.37 percentage points; these Tier-2 results are exploratory and outside the sealed family. The paper reports a simulation-only operating envelope and a repair path, not uniform superiority.

Index Terms—Automatic modulation classification, structured interference, interference overlap, vehicular Doppler, operating envelope, condition-dependent model comparison, representation repair, compact neural networks.

Evidence status. The original sealed family resolves one positive whole-configuration contrast (A5 vs A0), while two component contrasts and the clean-retention gate do not pass. Severe-interference, operating-envelope, and Tier-2 repair results are exploratory or post-hoc. All conclusions are restricted to source-disjoint simulation.

I. INTRODUCTION

AUTOMATIC modulation classification supports spectrum monitoring and blind receiver configuration by inferring a waveform’s modulation from received samples. Deep AMC has progressed from convolutional I/Q classifiers [1], [2] to complex-valued, multi-stream, recurrent, and Transformer-like representations [3]–[7]. Compact architectures remain

attractive when inference cost matters [8], [9], but average accuracy alone does not say where a compact representation is preferable.

This omission is consequential in mobile and vehicular receivers. A high-mobility terminal facing structured interference must decide on a limited compute budget whether to run a compact spectral front end or a high-capacity I/Q path; the same model can trail the high-capacity I/Q classifier in weak or narrowband interference yet lead it in a severe corner where the interference overlaps the target’s own time–frequency support. Averaging these regimes produces a ranking but erases the design rule.

This paper asks a narrower question: *can the sign and size of the compact-model advantage be indexed by physical condition variables, and can the boundary revealed by that index be repaired?* We answer using a frozen source-disjoint simulation campaign, artifact-only post-hoc analysis, and prospective Tier-2 experiments. The base model, VIMD-Net, maps a complex STFT to target-dominant, jammer-dominant, and unexplained-or-ambiguous routes; its supervision is physics-informed in the sense that a simulation-component teacher, available only during training, is derived from independently tracked target, jammer, and residual components. We do not claim that a specific routing or teacher component is individually confirmed (Section V-A); the contribution is the boundary and its repair, not the architecture itself.

The contributions are:

- a condition-indexed rank exchange, exposed over the complete structured-interference SNR–SIR plane, between a compact spectral model and stronger I/Q-domain classifiers, instead of a single marginal ranking;
- a low-dimensional target-support-overlap–SIR empirical envelope whose cross-regime gain-transport skill is evaluated on regime cells excluded from fitting, against an explicit fit-domain constant baseline and with a bounded, non-causal interpretation;
- a separation of the original sealed whole-configuration contrast from post-hoc severe-interference evidence, using paired statistics, multiplicity control, and full-region visualization so a favorable corner is not read as uniform superiority; and
- a prospective diagnosis-and-repair chain that turns a failed clean-retention gate into a representation-information finding: a received-I/Q sidecar increases the total model size only modestly while repairing clean and hard-interference performance, and a spectral capacity

ladder shows that width alone does not remove the boundary.

The claim is deliberately not that VIMD-Net is uniformly best. It is that the compact and high-capacity representations exchange rank in a reproducible, condition-dependent way, that this boundary can be described by physical covariates, and that, for its principal clean boundary, the evidence is more consistent with a repairable representation-information gap than with insufficient clean exposure alone.

II. RELATED WORK AND CLAIM BOUNDARY

A. Strong and Efficient AMC Representations

CNN and recurrent AMC systems learn directly from I/Q sequences [1], [2], [5]; later work preserves complex structure, fuses temporal and spatial streams, or applies attention [3], [4], [6], [7]. Vehicular and mobile receivers have motivated a distinct line of work on reparameterized causal convolutions, cross-scale kernel selection with IQ-imbalance and carrier-offset compensation, and channel-robust cumulant features [10]–[12]. Compact and efficient AMC has received sustained attention for cost-sensitive deployment [8], [9]. These lines of work motivate strong I/Q-domain comparators and prevent us from presenting a lightweight architecture or a fusion scheme as the primary novelty.

B. Robust, Cross-Domain, and Interference-Aware AMC

Channel adaptation, masked or contrastive learning, and interference-tolerant features address different nuisance sources [13]–[16], while overlapped-signal classification, denoising masked autoencoding, and cross-domain prototypical adaptation populate the 2024–2026 frontier [17]–[19]. Interference-tolerant recognition [16] and tensor-based malicious-interference recognition for MIMO [20] address structured interference directly, including low-SIR conditions. Our setting differs: we neither reconstruct sources nor aim to be a universally interference-robust classifier; we study how the *ranking* of compact spectral versus high-capacity I/Q models changes with the interference condition itself.

C. Distinction: Condition-Indexed Ranking and Repair

Interference-tolerant recognition, domain adaptation, lightweight architectures, and multi-representation fusion are all active, including recent knowledge-guided and multimodal preprints [21]–[24]. Our contribution is not another claim that one representation dominates on average. We model the condition dependence of the ranking itself, fit a low-dimensional empirical boundary to that rank exchange, expose the negative regions instead of reporting only favorable averages, and prospectively intervene on the revealed boundary. We state this positioning as a claim about emphasis, not as an exhaustive systematic-review result.

III. SYSTEM MODEL AND VIMD CONFIGURATION

A. Mobile Received Signal and Paired Views

We model a receiver-side AMC front end under terrestrial high-mobility conditions. For source sequence $s[n]$ and jammer $u[n]$, one received window is

$$x[n] = \mathcal{R}(\mathcal{H}_s(s)[n] + \kappa \mathcal{H}_u(u)[n] + w[n]), \quad (1)$$

where $\mathcal{H}_s$ and $\mathcal{H}_u$ are independently drawn fading and mobility operators (parameterized by carrier frequency, terminal speed, and 3GPP TR 38.901 [25] TDL-A/C/D profiles during training, with TDL-B/E held out for channel evaluation), κ scales the jammer contribution so that the realized SIR, defined as $10 \log_{10}(E[|\mathcal{H}_s(s)|^2]/E[|\kappa \mathcal{H}_u(u)|^2])$ on the simulator's tracked powers, matches the target value, w is receiver noise, and $\mathcal{R}$ applies the frozen receiver chain. The carrier frequency is $f_c = 5.9$ GHz, representative of intelligent-transport-system (ITS) and vehicle-to-everything (V2X) operation [26], and the complex baseband sampling rate is 1 MHz. Terminal speeds seen during training are 0, 60, 120, and 150 km/h, giving a maximum nominal Doppler shift of about 820 Hz; the held-speed split uses 180 and 250 km/h, i.e. up to about 1367 Hz, so speed and TDL profile are held out along separate axes. The held-speed split probes deeper intra-window non-stationarity and Doppler spread: $T_c \approx 0.423/f_D$ falls from about 1.29 ms at 60 km/h to 0.31 ms at 250 km/h, below the 1024 μ s decision window.

Training pairs two independently impaired observations of the same immutable source; inference uses one view. Pairing is therefore a training and statistical-alignment device, not additional test-time information. This model is a controlled simulation of a mobile receiver, not a complete V2X geometry; no MAC- or network-layer V2X performance is claimed.

Unanchored in-taxonomy cochannel collisions are excluded: without a physical target anchor, exchanging two admissible emitters can preserve the mixture while changing the requested single label, which requires a different label definition.

B. Three-Route Spectral Allocation

Let $Z = \text{STFT}(x) \in \mathbb{C}^{F \times T}$. The front end receives real, imaginary, and log-magnitude planes and produces logits A_s, A_j, A_o on the same lattice. The allocation masks are

$$\begin{aligned} [M_s, M_j, M_o] &= \text{softmax}([A_s, A_j, A_o]), \\ M_s + M_j + M_o &= 1. \end{aligned} \quad (2)$$

An environment encoder produces a scalar ambiguous-route gate λ and a bounded bypass ρ . The modulation and jammer routes are

$$\begin{aligned} Z_m &= (M_s + \lambda M_o + \rho) \odot Z, \\ Z_j &= (M_j + (1 - \lambda) M_o) \odot Z. \end{aligned} \quad (3)$$

Because these weights are real and nonnegative, every retained coefficient keeps the mixture STFT phase. The bounded bypass ρ is a per-window scalar in the frozen range [0.05, 0.35]; because it is added to both route weights, the allocation stays nonnegative but is no longer an exact partition of the mixture power, i.e. $Z_m + Z_j \neq Z$ in general. This is the ratio-masking

construction familiar from supervised source separation [27], [28], where the limits of magnitude-only masks and the value of phase-aware or complex targets are well documented [29], [30]; the elementary phase-preservation property does not imply source identifiability.

C. Simulation-Component Teacher

During training only, independently tracked post-channel target, jammer, and residual components define powers P_s, P_j, P_u on the student's lattice. With $q_k = P_k / (P_s + P_j + P_u)$, the fixed teacher is

$$M_s^* = [q_s - q_j]_+, \quad M_j^* = [q_j - q_s]_+, \quad (5)$$

$$M_o^* = q_u + 2 \min(q_s, q_j). \quad (6)$$

The routes are nonnegative and sum to one; negligible-energy cells are assigned to the uncertainty route by the finite-precision implementation. We call this construction *physics-informed* because the supervision uses simulator-tracked components; it does not imply that the margin teacher or the three-route allocation is individually confirmed (Section V-A). The teacher is not needed at inference.

D. Training Objective

The total loss is

$$\mathcal{L} = \mathcal{L}_{\text{mod}} + \alpha \mathcal{L}_{\text{teacher}} + \beta \mathcal{L}_{\text{jammer}} + \gamma \mathcal{L}_{\text{link}} + \eta \mathcal{L}_{\text{contrast}} + \theta \mathcal{L}_{\text{orth}}, \quad (7)$$

where $\mathcal{L}_{\text{mod}}$ is the modulation classification loss, $\mathcal{L}_{\text{teacher}}$ is a Jensen–Shannon [31] alignment between student and teacher masks, $\mathcal{L}_{\text{jammer}}$ and $\mathcal{L}_{\text{link}}$ constrain the jammer-family and link-quality auxiliary objectives, $\mathcal{L}_{\text{contrast}}$ is a supervised-contrastive loss [32] over exact-source positives that encourages condition invariance, $\mathcal{L}_{\text{orth}}$ is a route-orthogonality regularizer, and $\alpha, \beta, \gamma, \eta, \theta$ are nonnegative weights. The exact-source contrastive loss is an auxiliary training objective, not a headline contribution.

E. Information Contract and Complexity

At inference every model receives only the mixture; simulator-tracked target, jammer, and SIR quantities are training-only or post-hoc audit variables. VIMD-Net uses 39500 parameters and 41.8 million reported MACs.

F. Implementation Details

Unless otherwise stated, all models are trained on the same source-disjoint cache with the same data budget, optimization budget, stopping rule, and validation-only model-selection criterion. Model-specific architectural and objective components follow the predefined configuration of each variant.

Input and front end. One example is a complex baseband window of 1024 samples (1024 μs at 1 MHz, 4 samples per symbol, root-raised-cosine roll-off 0.35), power-normalized by the frozen receiver automatic gain control so that every window carries the same average power. The spectral front end applies a two-sided STFT with $N_{\text{FFT}} = 64$, hop 16, a

periodic Hann window of length 64, and no centering or zero padding, giving a 64×61 time–frequency lattice at 15.6 kHz per bin. The student and the fixed teacher share this lattice exactly.

Architecture width. The sealed configuration uses 24 spectral channels, embedding dimension 48, environment dimension 32, and dropout 0.05, for 39500 parameters. The prospective capacity ladder widens only these three numbers: the M tier uses (40, 80, 48) and the L tier (64, 128, 64).

Optimization and model selection. All fits use AdamW with an initial learning rate of 3×10^{-4} , weight decay 10^{-2} , batch size 16, mixed precision, gradient-norm clipping at 5.0, and a shared 30-epoch budget. Auxiliary losses follow a fixed staged schedule, and the learning rate is held until the complete objective has been active for several epochs and then decays on a cosine to a floor of 0.05 times its initial value. The reported checkpoint is chosen solely by validation modulation cross-entropy under a common eligibility window and 8-epoch early-stopping rule. Optimizer settings, schedule, and selection rule are identical for every model; no architecture-specific hyperparameter sweep was performed for any comparator, and validation data are never used for evaluation.

Loss weights. In (7), $\alpha = 0.50$, $\beta = 0.25$, $\gamma = 0.05$, $\eta = 0.10$, and $\theta = 0.01$, with label smoothing 0.05 and contrastive temperature 0.12. The route-orthogonality regularizer is part of the A5 whole-configuration bundle but is not isolated in a dedicated component contrast.

Seeds. The sealed campaign uses 10 algorithm seeds shared across all models, with the model-initialization seed shared by reported seed so that paired comparisons are seed-aligned; the matched-subset displays use the first five. Exact schedules, seed identifiers, teacher construction, and cache provenance are recorded in the reproduction package. Fig. 1 is a method illustration, not performance evidence.

IV. EVIDENCE PROTOCOL

A. Frozen Source-Disjoint Campaign

The artifact-locked campaign contains 12 model variants, 10 algorithm seeds, 120 fits, 11 evaluation splits, and 100000 training source sequences. Target classes are BPSK, PI/2-BPSK, QPSK, 8PSK, 16QAM, 64QAM, 256QAM, GMSK, CPFSK, and 4FSK, covering PSK, QAM, continuous-phase, and FSK families. Structured jammer families span tone, multitone, chirp, sweep, partial-band, pulse, comb, and out-of-taxonomy (cochannel and OFDM-like) modulated sources. TDL-A/C/D profiles are seen during training, while TDL-B/E profiles support held-channel evaluation. The evaluation grid spans eight SNR levels from -10 to 18 dB. The in-distribution split uses SIR levels -10 to 10 dB in 5 dB steps, whereas the hard-interference split spans $\text{SIR} \in \{-15, -10, -5, 0\}$ dB, so $\text{SIR} = -15$ dB occurs only in the hard-interference split and $\text{SIR} = +5$ and $+10$ dB only in the in-distribution split. Each hard-interference SNR–SIR evaluation cell of Fig. 2 contains 131–181 source-disjoint test windows (mean 156; all ten classes, 5–26 per class), read from the frozen prediction cache. The envelope aggregates of Section V-C use a coarser partition of the same predictions and are correspondingly denser: each




Fig. 1. A deterministic cache record and the fixed simulation-component teacher of Eqs. (5)–(6). Top row: received mixture, tracked target, tracked jammer, and noise-plus-artifact spectrograms; bottom row: the target-dominant, jammer-dominant, and uncertainty route masks. The teacher is a training-only construction from simulator-tracked components; it is unavailable at inference and is not performance evidence.

held-regime envelope cell contains 216–279 source-disjoint windows (mean 250). The fit-domain division (in-distribution plus hard-interference cells) is fixed in the exploratory analysis protocol before any envelope is fitted. Jammer family, speed, channel, combined OOD, receiver stress, and clean-retention splits share source identities across model comparisons. The receiver-stress split (ADC quantization and per-emitter synchronization) is retained in the artifact package and evaluated for the Tier-2 sidecar, but it does not enter the sealed or envelope claims of this paper and is not used in any reported model-selection claim; its per-split aggregates are included in the reproduction package rather than in the manuscript.

B. Comparator Fairness

Table I summarizes the comparators. All models are retrained under the same source-disjoint protocol; “IQFormer-inspired” and “MCLDNN” denote architecture-faithful unified-retraining references, not exact reproductions of every original training recipe. Comparator fairness is enforced at the budget rather than at the tuning level: every model sees the same training source count, the same epoch budget, the same early-stopping patience and checkpoint criterion, and the same validation protocol. CSSL is retained as an adaptation-oriented reference rather than a tuned upper bound; its 8.63 million parameters but only 155.3 million MACs reflect an aggressive encoder downsampling and a large projection head inherited from the official 1024-sample RadioML topology, so parameter count alone is a poor cost proxy for this comparator. Figures label this comparator “IQFormer-insp.” so that no figure has to be read against the text; “A5” and “VIMD-Net” denote the same sealed configuration, and “CSSL” abbreviates the contrastive self-supervised learning

TABLE I
COMPARATOR AND COMPLEXITY SUMMARY (HARD-INTERFERENCE SETTING).

Model	Domain	Params	MACs	Seeds
A0	spectral	8458	6.3 M	10
A5 / VIMD-Net	spectral allocation	39500	41.8 M	10
sidecar	spectral + received I/Q	46794	43.1 M	10
MCLDNN	I/Q	406070	398.2 M	10
IQFormer-inspired	multimodal I/Q	354984	355.6 M	10
CSSL	I/Q (adaptation)	8631948	155.3 M	10

reference of [15], whose released code snapshot [33] we retrain under our protocol.

As a post-review comparator-fidelity check, the MCLDNN and IQFormer implementations were additionally evaluated on the public RML2016.10a benchmark [1] under the protocol of the official benchmark result table of the IQFormer release [34]: the 11-class set, the full -20 to 18 dB SNR grid, per-stratum 600/200/200 splits seeded at 233, no augmentation or input-length change. Over three algorithm seeds, all-SNR test accuracy is 58.5% for MCLDNN (seed minimum and maximum 58.1 and 59.4%) and 65.2% for IQFormer-inspired (64.8 and 65.8%); these brackets are the seed range, not confidence intervals. The corresponding reference-release values, obtained by averaging its per-SNR accuracies over the same twenty SNR bins, are 62.1% and 64.2%. IQFormer-inspired therefore closely matches its reference-release value (+1.0 pp), whereas MCLDNN sits 3.5 pp lower while remaining in the same broad all-SNR range. Per-SNR deviations of up to about 8 pp remain in individual bins, so we read E1 as range-level comparator-implementation fidelity rather than pointwise reproduction, and not as evidence for the simulator-domain envelope.

C. Original Sealed Confirmatory Family

The sealed family contains three hard-interference contrasts: the complete configuration versus A0, the margin teacher versus a proportional-power teacher, and the tri-route model versus a dual-route control. A5 differs from A0 in allocation, teacher, auxiliary objectives, residual bypass, and capacity (about $4.7\times$ parameters), so A5–A0 is a whole-configuration effect.

D. Exploratory and Tier-2 Evidence Classes

All SIR-cell, overlap, fusion, condition-transfer, probe, re-pair, and capacity analyses are exploratory. In particular, the severe SIR stratification is post hoc. Tier-2 experiments were designed after inspecting the frozen evidence and are outside the frozen confirmatory family; they cannot retroactively change a sealed conclusion. The clean-retention gate was preregistered separately and did not pass; clean behavior is therefore treated as a boundary to explain and repair, not as a preserved property of the sealed model.

E. Statistical Procedures

The sealed family uses a joint non-studentized max-absolute-deviation hierarchical paired bootstrap with 10000 draws, resampling class-stratified source clusters while keeping algorithm seeds as fixed blocks, so pairing is preserved at the source level. The design resolution of 1.31 percentage points is the simultaneous minimum detectable effect at 80% power under this joint interval, an exploratory calibration rather than a sealed significance threshold. Because seeds are fixed blocks, the reported intervals are conditional on the realized seed set; a seed-randomization variant resampling the ten realized seeds with replacement keeps the A5–A0 contrast positive (95% percentile interval $[4.02, 5.19]$ percentage points) while the teacher-form and route-count contrasts span zero ($[-0.15, 0.42]$ and $[-0.15, 1.04]$ percentage points). In the severe corner, all 10 seeds share the same sign; the sign-flip permutation probability 0.0018 is a permutation test over the source-paired samples (an exact two-sided seed-level sign test would give $2/1024 \approx 0.0020$). The SIR = −15 dB aggregate is computed from source-paired predictions pooled across the eight SNR conditions before macro-F1 aggregation; it is therefore not the arithmetic mean of the eight displayed cell-level differences in Fig. 2.

V. RESULTS

A. Positive Sealed Whole-Configuration Contrast and Bounded Component Effects

Table II reports the complete sealed family. The complete configuration improves over its shared A0 backbone by 4.57 percentage points, with a simultaneous interval of $[3.65, 5.49]$ percentage points, about 3.5 times the design resolution of 1.31 percentage points. The teacher-form and route-count interventions do not clear zero individually; under the same joint interval their contributions are bounded within 1.36 percentage points. Thus the configuration-level effect is resolved but cannot be assigned to either isolated component at this

TABLE II
SEALED CONFIRMATORY HARD-INTERFERENCE FAMILY. DIFFERENCES ARE CANDIDATE MINUS REFERENCE IN MACRO-F1 PERCENTAGE POINTS.

Contrast	Diff.	Sim. low	Sim. high
Full configuration vs A0	4.57	3.65	5.49
Margin vs proportional teacher	0.16	−0.76	1.08
Tri-route vs dual-route	0.44	−0.47	1.36

resolution, and because the family rule required all three contrasts, the family gate did not pass. At the same parameter tier, the residual-free A7 variant is nominally above A5 by 0.21 percentage points in the marginal hard-interference aggregate (Fig. 4); treating the ten realized seeds as a random effect gives a 95% percentile interval of $[-0.19, 0.62]$ percentage points, so the difference is not resolved at this design’s power; we therefore attribute the compact frontier position to the VIMD family at this budget, not uniquely to any single component.

B. Rank Exchange across the SNR–SIR Plane

Marginal hard-interference macro-F1 is 0.4406 for A5, 0.4599 for MCLDNN, and 0.4872 for IQFormer-inspired. Those averages favor the larger models, but Fig. 2 shows why no single ranking is adequate: rank changes with SNR and SIR, with A5 leading only in the severe, high-overlap corner.

At SIR = −15 dB, in a post-hoc analysis, A5 gains 9.74 percentage points over MCLDNN ($[7.52, 12.14]$) and 10.46 percentage points over IQFormer-inspired ($[6.78, 14.29]$); these two headline intervals are marginal stratified-bootstrap intervals and are not multiplicity-adjusted. All 10 seeds have the same sign, and the sign-flip permutation probability is 0.0018. Of 64 inspected cells, 12 survive Holm correction; all are on the severe SIR row. These checks reinforce the corner result without converting the post-hoc analysis into confirmation, and the severe corner is an in-sample stratification of the hard-interference cells, not a held-out validation.

C. Empirical Overlap–SIR Operating Envelope

The rank exchange motivates an empirical envelope fit rather than another marginal average. For reference b , we fit

$$\Delta_b = \beta_{0,b} + \beta_{1,b}o + \beta_{2,b} \text{SIR}, \quad (8)$$

where Δ_b is A5 minus the reference macro-F1 and o is the *target-support jammer overlap*. We avoid the more common “spectral occupancy” because o is not an occupied-bin or occupied-bandwidth fraction. The covariate is defined from the simulator-tracked target and jammer components rather than from the mixture. For each window we compute the STFT power of the tracked target and of the tracked jammer separately, order the time–frequency cells by descending target power, and take the target’s 99%-energy support $\mathcal{S}$ as the smallest set of cells whose cumulative target power reaches 99% of the total. The overlap is then the fraction of the jammer’s total STFT power that falls inside $\mathcal{S}$:

$$o = \frac{\sum_{(f,t) \in \mathcal{S}} P_j(f,t)}{\sum_{(f,t)} P_j(f,t)}. \quad (9)$$




Fig. 2. Post-hoc operating map over all hard-interference SNR-SIR cells; each entry is A5 minus the named strong baseline in macro-F1 percentage points. A star marks a positive unadjusted paired lower interval; Holm- surviving cells are reported in the text. Displaying the full map prevents the severe corner from being read as a uniform ranking.

Thus $o = 0.8$ means that 80% of the jammer’s energy lies within the target’s dominant support, not that the jammer fills 80% of the plane. The cell-level covariate is the mean of o over the windows of that cell.

Equation (9) is evaluated on a fixed analysis lattice, a Hann-windowed 128-point STFT with hop 32, deliberately independent of the 64-point VIMD front-end lattice of Section III-F: the front-end lattice is what the model sees, whereas the analysis lattice is a measurement instrument for the physical audit. The overlap is computed once per window when the cache is built, before any model is trained; it is stored in the sealed cache, checksummed in the cache manifest, and read unchanged by every model, split, and comparison in this paper. It is never an input feature of VIMD-Net or of any comparator, and it is not tuned against any model’s predictions.

The fit uses 32 aggregates, and the count is reconstructible from the protocol rather than asserted. A cell is one (split, SIR stratum, overlap quartile) triple that retains at least 150 windows and all ten classes. The `hard_interference` split contributes 4 SIR strata ($-15, -10, -5, 0$ dB) $\times$ 4 overlap quartiles = 16 cells. The `id_test` split contributes 16 further cells over its five SIR strata, with 3, 3, 4, 3, and 3 cells at $-10, -5, 0, +5$, and $+10$ dB. The asymmetry has a single cause: the lowest overlap quartile of this split is populated almost entirely by the jammer-free in-distribution windows, which carry $o = 0$ and the SIR = 0 dB cache sentinel, so that bin clears the window floor only in the 0 dB stratum and is dropped in the other four. Hence $16 + 16 = 32$, and the SIR = $+5$ and $+10$ dB in-distribution cells do enter the fit even though they lie outside the hard-interference split. The primary held set is the 80 finite-SIR interfered cells formed the same way from unseen jammer, unseen speed, held-out channel, and combined OOD (4×5 SIR strata $\times$ 4 quartiles = 80). Clean retention is deliberately outside this primary envelope because a jammer-free window has no physical finite SIR. Overlap and SIR are nearly orthogonal across the fitting cells (Pearson $r = -0.003$; -0.03 over all 113 cells), so strong

linear collinearity between the two fitted covariates is not evident. We nevertheless interpret Eq. (8) as descriptive rather than causal, because the overlap is simulator-derived and the study is observational with respect to this covariate; low pooled correlation bounds collinearity, not confounding.

Against IQFormer-inspired, the fitted overlap coefficient is 14.38 percentage points per unit overlap and the SIR coefficient is -1.036 percentage points per dB. Magnitude skill is scored against an explicitly defined trivial baseline: the constant predictor outputs the mean gain over the 32 fitting cells (-8.27 percentage points for IQFormer-inspired, -4.63 percentage points for MCLDNN) and is evaluated unchanged on the 80 held-regime cells, with $R_{\text{skill}}^2 = 1 - \text{MSE}_{\text{envelope}}/\text{MSE}_{\text{const}}$. On that basis the envelope attains RMSE 6.23 percentage points against 8.37 percentage points for the constant predictor, for $R_{\text{skill}}^2 = 0.45$ (Fig. 3); the MCLDNN envelope gives 8.10 percentage points against 9.63 percentage points ($R_{\text{skill}}^2 = 0.29$). Adding the cell-level mean SNR as a third covariate lowers the held-regime RMSE only modestly (to 6.15 and 8.05 percentage points, $R_{\text{skill}}^2 = 0.46$ and 0.30), so the two-variable model remains primary. Two limits of this score are stated explicitly. An oracle constant equal to the mean of the held-regime cells themselves would attain 6.04 and 6.81 percentage points ($R_{\text{skill}}^2 = -0.06$ and -0.42), so the envelope is worse than a hindsight-optimal constant inside the held-regime domain and its advantage lies in transporting the gain level across regimes rather than resolving variation within them. Sign agreement is 0.975 (0.950 for MCLDNN) while 0.963 (0.900) of held-regime gains are negative, so a majority-sign predictor is nearly as accurate and sign agreement is a secondary diagnostic only.

The skill is therefore not uniform: it is strongest in the unseen-speed and held-out-channel regimes and weak or negative in the unseen-jammer and combined-OOD regimes, so the pooled R_{skill}^2 is a regime-weighted average rather than a uniformly strong transport property.

Solving Eq. (8) for zero gain gives break-even overlaps




Fig. 3. Exploratory overlap-SIR operating envelope. The abscissa of panel (a) is the target-support jammer overlap of Eq. (9), not an occupied-bandwidth fraction. Filled blue markers are the cells that fit Eq. (8); open markers are held-regime cells, coloured by which side of the campaign is held out, orange for the channel-side splits (unseen speed, held-out channel) and green for the interference-side splits (unseen jammer, combined OOD). Panel (b) compares predicted and observed held-regime gains. RMSE is 6.23 percentage points versus 8.37 percentage points for a constant predictor estimated from the fitting cells ($R^2_{\text{skill}} = 0.45$); an oracle constant equal to the held-regime mean would attain 6.04 percentage points. Sign agreement is a secondary diagnostic only, because the held-regime sign distribution is strongly imbalanced.

TABLE III

HELD-REGIME ENVELOPE SKILL BY REGIME. GAINS AND RMSE IN PERCENTAGE POINTS; THE CONSTANT BASELINE IS THE MEAN GAIN OVER THE 32 FITTING CELLS. ONLY FINITE-SIR INTERFERED HELD CELLS ENTER THIS TABLE.

Reference	Held regime	Cells	Obs. gain	Env. RMSE	Const. RMSE	R^2_{skill}
IQFormer-insp.	unseen speed	20	-12.4	3.94	7.87	0.75
IQFormer-insp.	held channel	20	-11.3	4.86	7.59	0.59
IQFormer-insp.	combined OOD	20	-16.5	7.50	9.23	0.34
IQFormer-insp.	unseen jammer	20	-16.1	7.74	8.67	0.20
IQFormer-insp.	pooled	80	-14.1	6.23	8.37	0.45
MCLDNN	unseen speed	20	-8.9	4.66	8.88	0.73
MCLDNN	held channel	20	-8.0	5.41	9.06	0.64
MCLDNN	combined OOD	20	-14.6	10.23	10.28	0.01
MCLDNN	unseen jammer	20	-14.4	10.34	10.24	-0.02
MCLDNN	pooled	80	-11.5	8.10	9.63	0.29




Fig. 4. Hard-interference macro-F1 versus parameter count on the matched five-seed subset; bars are ± 1 standard deviation over those seeds. Filled circles are sealed models (blue: the A0-A7 spectral family, of which only A0 and A5 are labelled; gray: the I/Q comparators); the open orange square is the prospective Tier-2 received-I/Q sidecar, which is exploratory and outside the sealed family. The Pareto reading is descriptive and regime-specific.

of 0.58 (vs. IQFormer-inspired) and 0.48 (vs. MCLDNN) at SIR = -15 dB, rising to 0.87 and 0.66 at SIR = -10 dB; the = -10 dB value against IQFormer-inspired exceeds the largest per-cell overlap observed in this campaign (0.84), so it marks a break-even point the campaign does not actually reach. The required overlap rises as interference becomes less severe, and these values are simulator-domain reference thresholds conditional on an overlap estimate, not deployment-ready control thresholds.

The preregistered mechanism expectation was non-increasing gain with overlap. The sealed directional test rejected that sign. Exploratory quintiles instead show monotonically increasing A5-CSSL gain, from a negative low-overlap region to a strongly positive high-overlap region. We return to the interpretation of this reversal in Section VI-C.

D. Complexity and Complementarity

A5 remains useful outside its winning region because its errors differ from those of the I/Q models: probability fusion with IQFormer-inspired improves over the stronger constituent by 4.71 percentage points (seed-ensemble control: 1.49 percentage points), and the MCLDNN fusion and control gains are 5.70 and 1.69 percentage points. This is supporting evidence of complementary decisions, not marginal superiority.

Table I gives the corresponding parameter and MAC budgets; compactness is stated as a parameter and MACs property rather than an end-to-end inference-cost claim.




Fig. 5. A5 clean condition-transfer taxonomy. A star marks a class whose jammer-free condition was not seen during training; the four covered classes are unstarred. The plot localizes the clean boundary rather than aggregating it.

E. Clean-Boundary Diagnosis

The clean-retention split contains all ten modulations, but the two training views expose jammer-free windows for only 4 classes (PI/2-BPSK, 8PSK, 256QAM, and CPFSK); the remaining 6 classes (BPSK, QPSK, 16QAM, 64QAM, GMSK, and 4FSK) are a condition-transfer test. The four covered classes are marked without a star in Fig. 5, where a star denotes a class whose jammer-free condition was not seen during training. Among uncovered constellation-order cells, transfer failure occurs in 100% of compact-spectral cells versus 11% of I/Q high-capacity cells. The clean-retention gate did not pass. Figure 5 localizes the failure rather than hiding it in an aggregate.

We then followed a prospective decision chain. Frozen-checkpoint linear and MLP probes used a correctly reconstructed jammer-free counterfactual and source-disjoint clean cross-validation; probe performance is the unweighted mean F1 over three constellation-order-sensitive classes (QPSK, 16QAM, 64QAM), close to 0.1 for chance on this ten-class problem. The preregistered decision rule declares a representation *information-present*, *head-limited* when this mean exceeds 0.25 and *representation-limited* otherwise, requiring *all* design-seed cells to exceed the threshold. For A5, 5 of the six design-seed cells (three algorithm seeds $\times$ the reconstructed jammer-free counterfactual and clean cross-validation probes, with one cell borderline at 0.256) lie below it, so we record the representation-limited side; the determination is robust to raising the threshold to 0.30 but flips at 0.20, a sensitivity we state explicitly. The strong I/Q baselines exceed the threshold in 18 of 18 cells. The evidence therefore leans toward missing constellation information in the compact spectral representation rather than a classification head that fails to use available information.

Adding clean windows for every class tests the simpler coverage explanation. It changes clean macro-F1 by only 0.15 percentage points ($[-0.31, 0.63]$) and hard macro-F1 by -0.30 percentage points ($[-0.91, 0.27]$). Coverage alone is therefore insufficient. A preregistered negative control gates the modulation route using predicted interference presence. Relative to A5, it changes clean macro-F1 by -0.30 percentage points ($[-0.66, 0.08]$) and hard macro-F1 by -0.18 percentage points ($[-0.72, 0.35]$). The learned gate averages 99.994% on clean windows and 99.991% under hard interference, so it saturates

near the modulated route in both conditions rather than implementing the intended clean identity fallback. This arm is a negative control, not stand-alone evidence that a functional mask fallback was learned.

F. Prospective I/Q Repair and Capacity Controls

The next intervention adds a received-I/Q sidecar while retaining the spectral routes and the same source mixture. It increases the *total* model size from 39500 to 46794 parameters (+18%) and the MAC count to 43.1 million (about +3%); the sidecar is a small addition to the model, not a 46794-parameter module bolted onto a 39500-parameter one. It raises clean macro-F1 by 11.77 percentage points ($[11.06, 12.49]$) and hard macro-F1 by 4.37 percentage points ($[3.44, 5.31]$), i.e. clean macro-F1 rises from 0.5005 to 0.6182 and hard-interference macro-F1 from 0.4406 to 0.4843. Its overall hard score is statistically near IQFormer-inspired ($\Delta = -0.29$ percentage points, $[-1.95, 1.46]$), while at severe SIR (-15 dB) it remains ahead of IQFormer-inspired by 12.09 percentage points ($[8.32, 15.88]$). The sidecar was designed prospectively after the clean-boundary diagnosis; it is interpreted as an intervention on the hypothesized information bottleneck, not as retroactive evidence for the original A5 architecture and not as a new multimodal fusion architecture. This repairs the clean boundary without erasing the structured-interference region.

The sidecar is a two-channel depthwise-separable 1-D I/Q branch ($2 \rightarrow 12 \rightarrow 12$ depthwise $\rightarrow 24 \rightarrow 24$ depthwise channels) with group normalization and SiLU activations, whose per-window temporal mean/std/max pooling is projected to a 24-dimensional embedding and fused residually with the spectral embedding. It stays cheap because it is a single low-temporal-resolution depthwise pass with aggressive time pooling, so its parameter growth is dominated by the projection and fusion layers. It consumes only the received mixture and requires no component bookkeeping at inference.

Widening the spectral model without changing its representation domain separates capacity from representation. On the matched five-seed subset, hard-interference macro-F1 rises monotonically across the ladder, from 0.436 at the sealed S width to 0.455 at M (+1.94 percentage points, $[1.07, 2.80]$) and 0.468 at L (+3.18 percentage points, $[2.44, 3.96]$ over S). The widest tier nonetheless stays below IQFormer-inspired on the marginal hard split (0.468 versus 0.496; -2.84 percentage points, $[-4.30, -1.31]$), while at SIR = -15 dB it retains the compact-model advantage (+14.07 percentage points, $[9.55, 18.51]$) and on clean retention it is still 18.1 percentage points behind that comparator. Width therefore raises the average and leaves the condition-dependent boundary in place; it does not substitute for the representation change made by the sidecar.

VI. DISCUSSION

A. What the Operating Envelope Establishes

The evidence supports a practical model-selection statement within the simulator domain. Within the present simulator campaign, the compact spectral configuration becomes relatively most competitive when interference is severe and

jammer energy strongly overlaps the target-dominant time–frequency support. This empirical pattern should not be interpreted as confirmation of a specific routing or allocation mechanism; no sealed contrast isolates the teacher or route component (Section V-A). A larger I/Q model is preferable in weak, clean, or low-overlap conditions unless the compact system includes an I/Q side channel. The two models are also complementary enough that late probability fusion can outperform either alone. The weak overlap–SIR correlation in the fitted cells indicates that the envelope is not reproducing one covariate through the other, but does not establish causal independence.

B. What It Does Not Establish

Eq. (8) is empirical and descriptive, not a causal structural equation. The target-support overlap is simulator-derived because it requires separately tracked target and jammer components, and it is not directly observable at an uncooperative receiver; the break-even overlaps are therefore simulator-domain reference values conditional on an overlap estimate. The severe SIR corner is an in-sample stratification, and the held-out evaluation covers regimes within the same frozen simulator campaign, not real-world out-of-distribution conditions. A future prospective campaign should randomize overlap and SIR more independently and estimate a receiver-observable overlap proxy (e.g., occupied-bandwidth or learned estimators), then test whether the envelope retains cross-regime skill without simulator component bookkeeping; validation with receiver-observable overlap estimates and over-the-air or public recordings [35] is a separate external-validity step, and public benchmarks cannot validate the envelope itself because they do not expose the separately tracked target and jammer components required for the overlap covariate.

C. Meaning of the Failed Directional Hypothesis

The preregistered directional mechanism hypothesis was not supported. The data reject the expectation that the compact model’s relative gain should decrease with increasing overlap. The surviving result is therefore empirical rather than mechanistic: the target-support jammer overlap organizes the observed rank exchange, but the observed direction should not be interpreted as confirmation of the originally hypothesized masking mechanism. In this paper, “physics-informed” refers to the construction of the training supervision, not to a confirmed monotonic physical law.

D. Representation Repair and Practical Model Selection

The sequence of interventions matters: the frozen probe narrows the cause, the coverage arm rejects a cheap explanation, the I/Q sidecar repairs the predicted missing information, and the capacity ladder separates width from representation. The Tier-2 evidence is more consistent with a representation-information gap than with insufficient clean exposure alone. The sidecar is a prospective intervention on that hypothesis, not the new main classifier and not a multimodal-fusion novelty.

E. Vehicular Relevance of the Operating Boundary

At $f_c = 5.9$ GHz and the held-speed conditions (Section III-A), the envelope can be read as a receiver-side model-selection reference for compute-constrained ITS/V2X receivers: large target-support overlap represents structured interference concentrated on the target-dominant support, where the compact spectral front end is relatively most competitive, while a high-capacity I/Q path is preferable at low overlap unless an I/Q side channel is present. The practical reading is conditional on an observable overlap estimator (Section VI-B), and the boundary is a simulation-domain design rule rather than a deployment-ready controller; no specific road geometry or traffic process is claimed.

VII. LIMITATIONS AND REPRODUCIBILITY

The evidence has the following explicit limits. First, all results are from source-disjoint TR 38.901 TDL-profile simulations, not a complete vehicular geometry or a MAC-/network-layer V2X evaluation. Second, the teacher uses simulation-component bookkeeping and cannot supervise unreferenced recordings. Third, the target-support overlap covariate is simulator-derived because it requires separately tracked target and jammer components, and is not directly available at a receiver. Fourth, the original confirmatory family gate did not pass: only the complete A5–A0 contrast is a positive sealed result, and the clean-retention gate likewise did not pass. Fifth, the severe-interference, operating-envelope, fusion, condition-transfer, probe, sidecar, and capacity analyses are exploratory or post-hoc, with post-hoc status stated where applicable. Sixth, the public-benchmark check validates comparator implementation only; external validation of the envelope is not yet established, and both I/Q comparators are unified-retraining references rather than exact recipe reproductions.

Reproducibility is enforced at the artifact boundary. Each manuscript macro stores the source path, row selector, evidence class, precision, and source SHA-256, and every figure is rendered from a CSV file with its own provenance manifest. The resolved macros, figure-source CSVs, per-seed aggregates, run configurations, and the full provenance manifest are released as a reproduction package upon acceptance. The frozen run stores cache identity, configurations, checkpoints, source-aligned predictions, seed aggregates, paired statistics, environment metadata, and execution records, preventing a favorable Tier-2 result from overwriting an unfavorable sealed gate.

VIII. CONCLUSION

Compact spectral and high-capacity I/Q representations exchange rank across the structured-interference plane. A low-dimensional overlap–SIR envelope transports the gain level across regime cells excluded from fitting with measurable skill relative to a fit-domain constant baseline, while a post-hoc severe-interference analysis identifies a reproducible compact-model advantage in one corner of the plane. The original sealed family resolves a positive whole-configuration A5–A0 contrast but not the isolated teacher or route-count effects. A prospective probe–coverage–sidecar chain further indicates

that the clean-condition failure is repairable by restoring a small amount of received-I/Q information, while spectral capacity alone does not remove the boundary; the intervention chain localizes a repairable representation bottleneck within the tested architecture family rather than establishing a causal diagnosis. The result is therefore a simulation-domain operating envelope and representation-repair study, not a claim of uniform superiority or a deployment-ready selector.

REFERENCES

- [1] T. J. O'Shea, J. Corgan, and T. C. Clancy, "Convolutional radio modulation recognition networks," in *Engineering Applications of Neural Networks*, 2016, pp. 213–226.
- [2] F. Meng, P. Chen, L. Wu, and X. Wang, "Automatic modulation classification: A deep learning enabled approach," *IEEE Trans. Veh. Technol.*, vol. 67, no. 11, pp. 10760–10772, 2018.
- [3] Y. Tu, Y. Lin, C. Hou, and S. Mao, "Complex-valued networks for automatic modulation classification," *IEEE Trans. Veh. Technol.*, vol. 69, no. 9, pp. 10085–10089, 2020.
- [4] Z. Zhang, H. Luo, C. Wang, C. Gan, and Y. Xiang, "Automatic modulation classification using CNN-LSTM based dual-stream structure," *IEEE Trans. Veh. Technol.*, vol. 69, no. 11, pp. 13521–13531, 2020.
- [5] J. Xu, C. Luo, G. Parr, and Y. Luo, "A spatiotemporal multi-channel learning framework for automatic modulation recognition," *IEEE Wireless Commun. Lett.*, vol. 9, no. 10, pp. 1629–1632, 2020.
- [6] J. Cai, F. Gan, X. Cao, and W. Liu, "Signal modulation classification based on the transformer network," *IEEE Trans. Cogn. Commun. Netw.*, vol. 8, no. 3, pp. 1348–1357, 2022.
- [7] M. Shao, D. Li, S. Hong, J. Qi, and H. Sun, "IQFormer: A novel transformer-based model with multi-modality fusion for automatic modulation recognition," *IEEE Trans. Cogn. Commun. Netw.*, vol. 11, no. 3, pp. 1623–1634, 2025.
- [8] Y. Wang, J. Yang, M. Liu, and G. Gui, "LightAMC: Lightweight automatic modulation classification via deep learning and compressive sensing," *IEEE Trans. Veh. Technol.*, vol. 69, no. 3, pp. 3491–3495, 2020.
- [9] T. A. To, A. Argyriou, A. A. Puspitasari, S. L. Cotton, and B. M. Lee, "Efficient automatic modulation classification for next-generation wireless networks," *IEEE Trans. Green Commun. Netw.*, vol. 10, no. 1, pp. 249–259, 2026.
- [10] N. Tang, X. Wang, F. Zhou, S. Tang, and Y. Lyu, "Reparameterization causal convolutional network for automatic modulation classification," *IEEE Trans. Veh. Technol.*, vol. 73, no. 6, pp. 8576–8583, 2024.
- [11] B. Ren, K. C. Teh, H. An, and E. Gunawan, "OFDM modulation classification using Cross-SKNet with blind IQ imbalance and carrier frequency offset compensation," *IEEE Trans. Veh. Technol.*, vol. 73, no. 6, pp. 8389–8403, 2024.
- [12] S. Huang, Y. Chen, J. He, S. Chang, and Z. Feng, "Channel-robust automatic modulation classification using companding spectral quotient cumulants," *IEEE Trans. Veh. Technol.*, vol. 73, no. 11, pp. 17749–17753, 2024.
- [13] S. Wang, H. Xing, C. Wang, H. Zhou, B. Hou, and L. Jiao, "SigDA: A superimposed domain adaptation framework for automatic modulation classification," *IEEE Trans. Wireless Commun.*, vol. 23, no. 10, pp. 13159–13172, 2024.
- [14] C. Xiao, S. Yang, Z. Feng, and L. Jiao, "MCLHN: Toward automatic modulation classification via masked contrastive learning with hard negatives," *IEEE Trans. Wireless Commun.*, vol. 23, no. 10, pp. 14304–14319, 2024.
- [15] M. Du, J. Pan, and D. Bi, "A contrastive learner for automatic modulation classification," *IEEE Trans. Wireless Commun.*, vol. 24, no. 4, pp. 3575–3589, 2025.
- [16] X. Sun, C. Wu, Y. Li, Y. Li, T. Huang, J. Yu, and H. Zhang, "Toward interference-tolerant automatic modulation recognition via multi-stage feature extraction network," *IEEE Trans. Veh. Technol.*, vol. 74, no. 8, pp. 12629–12640, 2025.
- [17] G. Jajoo and P. Singh, "Modulation classification for overlapped signals using deep learning," *IEEE Open J. Commun. Soc.*, vol. 5, pp. 3839–3851, 2024.
- [18] A. Faysal, M. Rostami, T. Boushine, R. G. Roshan, N. Muralidhar, Y.-D. Yao, and H. Wang, "DenoMAE2.0: Improving denoising masked autoencoders by classifying local patches for automatic modulation classification," *IEEE Trans. Commun.*, vol. 74, pp. 929–943, 2026.
- [19] W. Li, Z. Chen, T. Liu, H. Chen, and G. Xu, "Confidence-guided prototypical contrastive domain adaptation for cross-domain automatic modulation classification," *IEEE Trans. Cogn. Commun. Netw.*, vol. 12, pp. 6929–6941, 2026.
- [20] J. Zhang, X. Zhang, W. X. Zheng, Y. Chen, N. Zhao, J. Li, and M. Liu, "Modulation recognition via tensor analysis for MIMO systems with malicious interference," *IEEE Trans. Veh. Technol.*, vol. 75, no. 8, pp. 18609–18613, 2026.
- [21] S. Wang, C. Wang, H. Xing, H. Mo, L. Han, and L. Jiao, "DKDNet: Dual knowledge and data-driven network for cross-domain automatic modulation classification," arXiv preprint arXiv:2607.08031, 2026.
- [22] J. Wang, W. Xie, Y. Mu, X. Liu, Z. Zhao, and J. Zhang, "Mixture-of-experts transformer for automatic modulation recognition," arXiv preprint arXiv:2606.09085, 2026.
- [23] Z. Yang, Y. Luomei, Z. Liu, Z. Liu, and F. Xu, "ZoomSpec: A physics-guided coarse-to-fine framework for wideband spectrum sensing," arXiv preprint arXiv:2604.13568, 2026.
- [24] Y. Liu, M. Liu, W. Xie, X. Liu, W. Liu, Y. Sun, X. Qiu, C. Yuan, and J. Li, "RIS-MAE: A self-supervised modulation classification method based on raw IQ signals and masked autoencoder," arXiv preprint arXiv:2508.00274, 2025.
- [25] 3GPP, "Study on channel model for frequencies from 0.5 to 100 GHz," 3rd Generation Partnership Project, Tech. Rep. TR 38.901, V18.0.0, 2024.
- [26] —, "Study on evaluation methodology of new vehicle-to-everything (V2X) use cases for LTE and NR," 3rd Generation Partnership Project, Tech. Rep. TR 37.885, V15.3.0, 2019.
- [27] A. Narayanan and D. Wang, "Ideal ratio mask estimation using deep neural networks for robust speech recognition," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, 2013, pp. 7092–7096.
- [28] Y. Wang, A. Narayanan, and D. Wang, "On training targets for supervised speech separation," *IEEE/ACM Trans. Audio, Speech, Lang. Process.*, vol. 22, no. 12, pp. 1849–1858, 2014.
- [29] H. Erdogan, J. R. Hershey, S. Watanabe, and J. Le Roux, "Phase-sensitive and recognition-boosted speech separation using deep recurrent neural networks," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, 2015, pp. 708–712.
- [30] D. S. Williamson, Y. Wang, and D. Wang, "Complex ratio masking for monaural speech separation," *IEEE/ACM Trans. Audio, Speech, Lang. Process.*, vol. 24, no. 3, pp. 483–492, 2016.
- [31] J. Lin, "Divergence measures based on the Shannon entropy," *IEEE Trans. Inf. Theory*, vol. 37, no. 1, pp. 145–151, 1991.
- [32] P. Khosla, P. Teterwak, C. Wang, A. Sarna, Y. Tian, P. Isola, A. Maschinot, C. Liu, and D. Krishnan, "Supervised contrastive learning," in *Advances in Neural Information Processing Systems*, vol. 33, 2020, pp. 18661–18673.
- [33] M. Du, J. Pan, and D. Bi, "CSSL-AMC-Pytorch," [Online]. Available: <https://github.com/duminyang20/CSSL-AMC-Pytorch>, 2025, commit 2fbc5b3, accessed Jul. 28, 2026.
- [34] M. Shao, D. Li, S. Hong, J. Qi, and H. Sun, "IQFormer," [Online]. Available: <https://github.com/WestdoorSad/IQFormer>, 2025, commit 7ee6ac9, accessed Jul. 28, 2026.
- [35] T. J. O'Shea, T. Roy, and T. C. Clancy, "Over-the-air deep learning based radio signal classification," *IEEE J. Sel. Topics Signal Process.*, vol. 12, no. 1, pp. 168–179, 2018.