CLARITY. CONTINUITY. CONTROL.

# SentinelOps operating manual

Practical procedures for confident daily operation. Choose the task, check the prerequisites, follow the steps and verify the result.

**This edition**

32 modules / 71 procedures / Reviewed 2026-10-30

Your assigned section determines which modules you can open. Your role, record state and operation-specific gates determine what you can do.

Read the environment, record identity, scope and last successful update before acting. A stale snapshot or missing signal is not a healthy/empty system.

Guidance links only navigate. They never approve, execute, requeue, delete or change configuration.

After a write, verify the saved result and custody/history. If completion is uncertain, inspect the existing outcome before retrying.

Downloads are dated reference copies. Protect operational/customer information and use the current in-app guide after a deployment.

# Find your workspace

Checklist operations 4

Template authoring 6

Task workspace and analytics 7

Database growth and capacity 8

Performance and achievements 9

Team scheduling and patterns 10

Personal schedule 12

Service monitoring and investigation 13

Outage ledger and event history 14

Service configuration and controls 15

Daily extraction pipeline 16

Extraction run history 17

Manual extraction and overwrite 18

Extraction source configuration 19

RTGS recovery and automation 20

Fabric overview 22

Incident investigation 23

Service catalog and controls 25

Agent monitoring 27

Database fabric 28

Service clusters 29

Business flows 30

Dependency topology 31

Agent and service onboarding 32

Environment rollover 33

Procedure library 35

CRB reporting 36

Hovering queue 37

Hovering robot settings 39

Funds custody and clearing 40

Personal loans - 48 months 44

SMS queue monitoring 46

CHECKLISTS

# Checklist operations

Find the correct shift, record truthful outcomes, and leave a usable handover.

Where to go: /checklists

**Access and authority**

Checklist operations access; available actions also depend on your role, participation and the run state.

## 01 / Find a shift or historical run

Before you begin: Know the operating date and shift.

### 1. Set the time window

Open Checklists. Choose All Time, Week, Specific Day or Date Range, then use search, lifecycle and shift filters.

### 2. Open the matching run

Check its date, shift hours and lifecycle before opening. Today coverage describes initialization, not completed work.

### How to confirm success

The workspace header matches the intended shift and date.

### Stop and check

Do not work in a historical or completed run simply because its title matches today.

## 02 / Work an item and its substeps

Before you begin: Open the intended run and join if participating.

### 1. Read before acting

Read the item instructions, type, timing and existing activity. Start Working where offered; this claims progress, not completion.

### 2. Record the actual outcome

Open substeps for multi-step work. Mark Complete only after checking the real system. Skip or Report Issue requires the reason/evidence requested by the dialog. Use Previous, Next and Next Open to navigate; navigation does not record an outcome.

### 3. Verify the saved state

Wait for the response. Check the item/subitem state and progress. Expand activity to inspect who recorded the result and when.

### How to confirm success

Each action is reflected in the saved status and activity.

### Stop and check

If a save fails, refresh and inspect the recorded state before repeating it. Do not mark unfinished work complete to reach 100%.

## 03 / Coordinate members and handover

Before you begin: Join the shift when doing work; know what the next operator needs.

### 1. Review incoming notes

Open Handover notes, filter Incoming and read priority, context and required follow-up. Acknowledge only after reading; acknowledgement is not resolution.

### 2. Leave a useful note

Choose Add Handover Note. Describe what happened, what is pending, the affected service/reference and the next action. Select the available priority/destination fields and save.

### 3. Confirm team context

Check Team members and participation. Presence is connection/activity context, not proof that someone completed an item. Filter Outgoing to confirm your saved note.

### How to confirm success
The next shift can see the note and its acknowledgement state.

### Stop and check
Do not put passwords or unnecessary customer details in notes.

## 04 / Close, inspect, share or export a run
Before you begin: Review incomplete items, exceptions and handover first.

### 1. Resolve outstanding work
Use the open-item view to find gaps. Normal completion and exception completion are different outcomes; supply the required justification for exceptions.

### 2. Finalize once
Use the completion control available to your role and state, review the confirmation, then verify the saved lifecycle. Inspect opens the record for review.

### 3. Share the evidence
Use Share for the run link or PDF for a snapshot. Recipients still need access to open the live record; a PDF will not update after download.

### How to confirm success
The final lifecycle and exported snapshot tell the same story.

### Stop and check
A closed shift can still have exceptions. A completed counter alone is not evidence of a clean close.

## Something is blocking you?
### No runs match
Clear filters and check the date and shift. If coverage was not initialized, contact the planner; do not invent a replacement record.

### Action unavailable
Check participation, lifecycle and role. Ask the owner/admin about missing authority.

## Terms in plain language
### Lifecycle
The state of the whole checklist run.

### Subitem
A smaller executable step within an item.

Procedure reference: checklists.execution / 2026-10-30

CHECKLISTS

# Template authoring

Build reusable shift instructions and review them before operators use them.

Where to go: /templates

**Access and authority**

Template authoring access and the role required by the create/edit/delete controls.

## 01 / Create or revise a template

Before you begin: Know the section, shift and operating procedure.

### 1. Choose the template

Open Templates from Checklists or the command menu. Inspect an existing template before creating a duplicate. Choose Create or Edit as appropriate.

### 2. Build the work in order

Set the required template fields. Add ordered items and subitems with clear instructions, types and timing. For conditional/scheduled work, fill the fields the builder exposes and check the condition or schedule rather than assuming it applies every day.

### 3. Save and inspect

Resolve validation errors, save, then open View to verify the resulting briefing and item order. Template edits define future work; review a live run separately.

### How to confirm success

The saved template has the correct shift, instructions and sequence.

### Stop and check

Do not use template edits as a way to alter the history of an already executed run.

## 02 / Review or retire a template

Before you begin: Confirm the template identity and operational owner.

### 1. Inspect the briefing

Use View to check every item, subitem, timing and required action. Compare it with the approved operational procedure.

### 2. Edit or delete deliberately

Edit to correct instructions. If Delete is available, review the confirmation and impact before accepting; do not remove a template still required for shift coverage.

### How to confirm success

The library shows the intended current template.

### Stop and check

If unsure whether a template is still used, stop and confirm with the shift owner.

## Something is blocking you?

### Validation fails

Correct the named field or item in the builder, then save again.

### Missing control

Template entitlement does not override role restrictions.

## Terms in plain language

### Template

The reusable blueprint; an instance is a dated run created from it.

Procedure reference: checklists.templates / 2026-10-30

TASK MANAGER

# Task workspace and analytics

Keep persistent work owned, dated and traceable beyond a shift.

Where to go: /tasks

**Access and authority**

Task workspace access; editing and assignment depend on your role and relationship to the task.

## 01 / Find and investigate work

Before you begin: Know whether you own, assigned or supervise the work.

**1. Choose a lane**

Open Task Center. Choose Assigned To Me, Tasks I Assigned, Team Tasks, Overdue or Completed as appropriate.

**2. Narrow and inspect**

Search and filter status/priority. Open the task details; read description, assignee, due date, comments and history before changing anything.

**How to confirm success**

You can identify the owner, next action and latest recorded change.

**Stop and check**

A completed task may have been completed late; retain that distinction.

## 02 / Create, assign and update a task

Before you begin: Have a clear outcome, owner and realistic due date.

**1. Create the work**

Use the create task action. Fill the required title, description, scope/type, priority, assignee and due date fields offered by the form.

**2. Progress the task**

Open details or Edit. Update the permitted fields/status and record useful context in comments. Save and wait for confirmation.

**3. Verify and close**

Complete only after verifying the outcome. Reopen/edit only where permitted, and check history after changes. Read analytics in the context of the selected scope.

**How to confirm success**

The task card and history reflect the saved owner, dates and outcome.

**Stop and check**

Do not delete or mark work completed to conceal a missed deadline.

## Something is blocking you?

**Task missing**

Check lane, filters and permissions before recreating it.

**Save failed**

Reopen the task and check history before retrying.

## Terms in plain language

**Overdue**

The due time has passed without the required completion.

Procedure reference: task_manager.tasks / 2026-10-30

DATABASE

# Database growth and capacity

Read capacity, growth and estimated runway without changing the database.

Where to go: /database-stats

**Access and authority**

Database growth and capacity access; this screen is telemetry and forecasting.

## 01 / Assess current capacity

Before you begin: Know which database the configured telemetry describes.

### 1. Check freshness

Open Database Statistics. Read the timestamp and connection/cached-fallback state before using the figures. Refresh if needed.

### 2. Compare capacity and growth

Read used space, provisioned total and remaining buffer. Inspect Growth contour and Daily ledger for actual changes rather than relying on one value.

### 3. Interpret runway

Read the estimated full date, risk state and confidence/control notes. Compare current daily growth with the seven-day average; escalate sustained pressure with the timestamp and evidence.

### How to confirm success

You have a dated capacity assessment, with uncertainty explained.

### Stop and check

A forecast is an estimate, not a guarantee or a command to expand/shrink storage.

## Something is blocking you?

### No or stale telemetry

Refresh once; if still stale, escalate the source connection and include the last successful timestamp.

## Terms in plain language

### Runway

Estimated time until available capacity is consumed at the observed growth rate.

### Cached fallback

Previously fetched evidence used when fresh telemetry is unavailable.

Procedure reference: database.statistics / 2026-10-30

PERFORMANCE

# Performance and achievements

Understand recorded contribution, evidence-based reliability and achievement levels.

Where to go: /performance

**Access and authority**

Performance access; the screen uses the visible person/team scope.

## 01 / Understand a score fairly

Before you begin: Choose the period you want to review.

**1. Read Overview**

Check contribution points separately from reliability rates. A dash means no eligible evidence; a limited sample needs more observations.

**2. Inspect Evidence & scoring**

Read the breakdown, eligible samples, weights and recent contributions. Tasks without deadlines can earn completion credit without a timeliness bonus. Passive membership and days off are not contribution evidence.

**3. Interpret team context**

Compare recorded contribution volume with workload and shift opportunities. Shared ranks can occur for ties; the table is not a staff appraisal.

**How to confirm success**

You can explain the score using underlying records and sample sizes.

**Stop and check**

Do not infer poor performance from missing evidence or compare different workloads as equivalent.

## 02 / Earn and collect achievement levels

Before you begin: Open Achievements and choose an award.

**1. Read the requirements**

Inspect Amateur, Skilled and Expert requirements and remaining progress. Every requirement for a level must be met.

**2. Collect in order**

Collect the available level when enabled. Verify it becomes collected before trying the next level. Current progress uses the calendar year; previously unlocked/collected levels remain recorded.

**How to confirm success**

The achievement shows the earned level and the next requirements.

**Stop and check**

Do not create duplicate work or work unnecessary hours solely for points.

## Something is blocking you?

**Unexpected score**

Check the selected period and underlying completion/attendance records. Raise a specific record discrepancy with the administrator.

## Terms in plain language

**Contribution**

Credit for recorded eligible work.

**Reliability**

A rate calculated from eligible evidence, not raw volume.

Procedure reference: performance.dashboard / 2026-10-30

TEAM

# Team scheduling and patterns

Plan coverage using section-specific patterns, date ranges and individual assignments.

Where to go: /team

**Access and authority**

Team scheduling access; the current Team page requires Admin or Manager.

## 01 / Inspect coverage for a date or person

Before you begin: Select the correct section.

### 1. Set the view window

Use the shortcuts or custom date/range controls. Apply the member/user filter to inspect a specific person; clear it to review the section.

### 2. Read the schedule

Check shift dates, hours, coverage and assignments. Open an assignment for details before editing it.

### How to confirm success

The visible schedule matches your section, dates and people.

### Stop and check

A filtered empty schedule does not prove the whole team has no assignments.

## 02 / Create or maintain a shift pattern

Before you begin: Know the rotation, shift definitions and timezone.

### 1. Open Patterns

Create a pattern or edit the intended existing one in the selected section. Set name, rotation/cycle, shift sequence and any rest/off days shown by the form.

### 2. Review and save

Check ordering, hours and timezone. Save and verify the pattern appears in this section. Delete only an obsolete pattern after checking its use.

### How to confirm success

The pattern is available to Smart Assignment for the same section.

### Stop and check

Do not invent shift times to work around a missing pattern; obtain the planner-approved definition.

## 03 / Use Smart Assignment

Before you begin: Have a saved pattern or a known single shift and selected members.

### 1. Choose the assignment mode

Open Smart Assignment. Bulk Pattern needs a pattern and start/end dates. Single Shift needs a date and shift.

### 2. Set the scope

Choose the correct section pattern, dates and members. Check that the end is not before the start and that the selected people are intended.

### 3. Assign and verify

Submit once. Inspect the resulting schedule across the full requested range, not only the first day. Correct individual assignments using the provided edit/remove controls.

### How to confirm success

Members have the intended dates and shifts in the schedule.

### Stop and check

If patterns fail to load, use Retry patterns. If none exist, create one in the current section first.

## Something is blocking you?

### Wrong/missing pattern

Verify section selection, retry loading, then inspect Patterns.

### Assignment conflict or rejected save

Read the server response and inspect existing assignments before resubmitting.

## Terms in plain language

### Pattern

A reusable rotation, applied over a date range.

Procedure reference: team.scheduling / 2026-10-30

TEAM

# Personal schedule

See your upcoming shifts and open the correct work for the day.

Where to go: /schedule

**Access and authority**

Personal schedule access; this is your assigned schedule, not the planner.

## 01 / Prepare for a shift

Before you begin: Check your signed-in identity.

### 1. Choose the time view

Open Schedule from the operator menu. Use its calendar/time controls to find the intended date.

### 2. Inspect the assignment

Read shift hours, section and relevant details. Open the linked checklist when offered and confirm its date before joining.

### 3. Resolve a mismatch

If an expected shift is absent or incorrect, contact the Team planner with the date and shift. Check again after correction.

### How to confirm success

You know when to work and which checklist belongs to that shift.

### Stop and check

Do not assume a calendar entry alone proves attendance or completion.

## Something is blocking you?

### No assignments

Check the date range and your account; ask the planner to verify section/member assignment.

## Terms in plain language

### Assignment

The shift allocated to you by the planner.

Procedure reference: team.schedule / 2026-10-30

NETWORK SENTINEL

# Service monitoring and investigation

Identify degraded services and inspect current signals before escalating.

Where to go: /network-sentinel

**Access and authority**

Service monitoring access; manual checks and controls additionally require configuration authority.

## 01 / Investigate a live service

Before you begin: Know the service, environment or affected group.

**1. Scope the service list**

Filter environment, service group, search and health. Read connection/freshness indicators before interpreting the counts.

**2. Inspect the signal**

Select the service. Read Signal for sampled availability and latency, and Evidence for the latest probe/reason. Compare ICMP and TCP evidence; a failed network probe is not proof that every business function has failed.

**3. Preserve evidence**

Use Evidence TXT to download a dated investigation snapshot. Include service/environment and timestamps when escalating.

**How to confirm success**

The selected service has a clear, dated evidence trail.

**Stop and check**

Unknown or stale signal is not healthy. Do not infer recovery from an interrupted live connection.

## 02 / Request a current check

Before you begin: The service must be selected; Check now must be available to your role.

**1. Check once**

Choose Check now and wait for the response. Read the separate manual-probe result and its timestamp.

**2. Compare observations**

Compare the manual result with scheduled monitoring and incident evidence. Refresh/reopen the service if needed before escalation.

**How to confirm success**

The manual result identifies what was checked and when.

**Stop and check**

Repeated clicks do not make monitoring more reliable; investigate persistent failure instead.

## Something is blocking you?

**Live updates interrupted**

Keep the last snapshot marked stale, refresh and check the monitoring source connection.

## Terms in plain language

**ICMP**

A network reachability probe, often called ping.

**TCP**

A connection check to a configured service port.

**Sampled availability**

Availability inferred from recorded probes, not continuous proof of business success.

Procedure reference: network_sentinel.monitoring / 2026-10-30

NETWORK SENTINEL

# Outage ledger and event history

Trace outages and major events for a selected service.

Where to go: /network-sentinel

**Access and authority**

Outage ledger access; service monitoring permission is separately required for Signal/Evidence.

## 01 / Trace an outage

Before you begin: Identify the service and approximate incident date.

### 1. Open Timeline

Select the service, then Timeline. Review current outages, today's events and the Major Events Archive.

### 2. Read the chronology

Compare start/end times, duration, severity and summaries. A restored service and an unresolved investigation are different facts.

### 3. Escalate with references

Record service name, environment and event timestamps. Use the live investigation to confirm present health rather than treating historical recovery as current evidence.

### How to confirm success

You can describe the outage sequence and distinguish it from current health.

### Stop and check

Only retained events are visible; no older rows does not prove there were no earlier outages.

## Something is blocking you?

### Archive empty

Check the service and today's events; older retained events appear separately.

## Terms in plain language

### Outage

A recorded period of detected service failure.

Procedure reference: network_sentinel.outage_history / 2026-10-30

NETWORK SENTINEL

# Service configuration and controls

Maintain monitoring targets and control whether checks run.

Where to go: /network-sentinel

**Access and authority**

Configuration access plus Manager/Admin for add/edit/check/enable; Delete requires Admin.

## 01 / Add or edit a monitored service

Before you begin: Obtain the approved target host, ports, environment and monitoring requirements.

### 1. Open the editor

Choose Add Service or select a service and Edit. Verify the service identity and environment before changing the target.

### 2. Set the checks

Fill the displayed address/port, probe and timing fields. Use appropriate target values; save and read any validation response.

### 3. Verify monitoring

Select the saved service, run Check now if allowed and inspect fresh evidence. Saving configuration is not proof of reachability.

### How to confirm success

The saved target and new probe evidence match the intended service.

### Stop and check

Do not point production checks at a test host or use a successful ping as proof of application availability.

## 02 / Enable, disable or remove monitoring

Before you begin: Know the maintenance/change reference and affected service.

### 1. Choose the scope

Select the exact service and read its identity. Disable pauses its monitoring; Enable resumes it.

### 2. Confirm the result

Wait for the saved state. For deletion, read the confirmation and use it only for a genuinely retired entry. Recheck the list and related evidence.

### How to confirm success

The service shows the intended monitoring state.

### Stop and check

Disabling monitoring does not fix the service; it changes visibility.

## Something is blocking you?

### Control unavailable

Check both module entitlement and role; do not bypass the restriction.

Procedure reference: network_sentinel.configuration / 2026-10-30

TRUSTLINK

# Daily extraction pipeline

Follow the daily IDC/DigiPay extraction through validation and file readiness.

Where to go: /trustlink?tab=pipeline

**Access and authority**

Daily extraction access; triggering runs and changing sources have separate permissions.

## 01 / Check today's extraction

Before you begin: Know the required business date and enabled sources.

### 1. Read the run identity

Open Trustlink and Pipeline. Check date, status, selected run and source route. Confirm whether today's export already exists.

### 2. Follow each stage

Read IDC Ingest, DigiPay Ingest, Transformation, Validation, File Save and Download. Inspect failed/skipped stages and row counts; an intentionally disabled source is not a successful ingestion.

### 3. Download the ready file

Use Download Export only when the file is present. Confirm the filename/date and record counts before onward delivery through your approved process.

### How to confirm success

You can show which inputs ran and which export is ready.

### Stop and check

A completed extraction or local download is not proof that an external recipient received the file.

## Something is blocking you?

### Run failed or file absent

Inspect the failing stage and history. Ask an authorized operator to recover the run rather than repeatedly triggering new runs.

## Terms in plain language

### Pipeline

The ordered stages that turn source data into an export.

Procedure reference: trustlink.daily_extraction / 2026-10-30

TRUSTLINK

# Extraction run history

Inspect past runs and retrieve the correct retained export.

Where to go: /trustlink?tab=history

**Access and authority**

Run history access; file deletion remains restricted by role and run eligibility.

## 01 / Inspect or download a historical run

Before you begin: Know the date/run you need.

### 1. Select the run

Open History and narrow the period/search using the available controls. Open the run inspector to read stage outcomes, timestamps, row counts and errors.

### 2. Retrieve the artifact

Use Download only if the run has a file. Match filename and business date to your request. Missing files are different from missing run history.

### How to confirm success

The downloaded file belongs to the selected recorded run.

### Stop and check

Do not substitute today's file for a missing historical export.

## 02 / Remove an eligible saved export

Before you begin: Have authorization to remove that artifact.

### 1. Review the eligible file

Use the delete-file control only where offered. Read the confirmation for the selected run; file removal is not a rerun.

### 2. Confirm the outcome

After confirmation, verify the file is unavailable and inspect the retained run record.

### How to confirm success

The artifact availability and run history reflect the deletion.

### Stop and check

Do not delete a file still needed for delivery, reconciliation or retention.

## Something is blocking you?

### Download unavailable

Check file presence in the inspector; request the approved recovery path if it was removed.

Procedure reference: trustlink.run_history / 2026-10-30

TRUSTLINK

# Manual extraction and overwrite

Start a controlled extraction or replace today's export when justified.

Where to go: /trustlink?tab=pipeline

**Access and authority**

Manual extraction access plus the operation's role restrictions.

## 01 / Run an extraction

Before you begin: Verify today's state and that source configuration is correct.

### 1. Inspect before triggering

Check whether a run is active or today's export already exists. If ready, download it instead of creating a duplicate.

### 2. Run and follow

Choose Run Extraction (or Trigger First Run). Wait for scheduling, then follow Pipeline through completion and file readiness.

### How to confirm success

The new run has a terminal status and a verified artifact.

### Stop and check

A scheduling response means accepted, not completed.

## 02 / Overwrite today's export

Before you begin: Have a valid reason and approval to replace the existing output.

### 1. Review what will change

Inspect today's existing export and affected delivery process. Choose the overwrite action and read its warning.

### 2. Confirm deliberately

Accept only if replacement is intended. Follow the resulting run and verify the new file/date/counts before distributing it.

### How to confirm success

The replacement export is checked and the run history explains the operation.

### Stop and check

Do not overwrite simply to troubleshoot a download or while another operator is distributing the previous artifact.

## Something is blocking you?

### Already exists

Download the current export, or use the explicit overwrite workflow if a replacement is authorized.

Procedure reference: trustlink.manual_run / 2026-10-30

TRUSTLINK

# Extraction source configuration

Choose the data sources used by the next extraction.

Where to go: /trustlink?tab=pipeline

**Access and authority**

Source configuration access and Admin role.

## 01 / Change IDC/DigiPay ingestion

Before you begin: Know the approved extraction route.

### 1. Inspect the current route

Read the IDC and DigiPay ingest controls and the current run's evidence.

### 2. Change the next route

Toggle the intended source. At least one source must stay enabled. Wait for the saved "Next extraction route" message.

### 3. Verify the next run

Inspect its stage outcomes and counts. The toggle does not retroactively rewrite an earlier run or artifact.

### How to confirm success

The next extraction uses the intended enabled inputs.

### Stop and check

Do not disable a source to hide a failed ingestion without business approval.

## Something is blocking you?

### Both sources cannot be disabled

Keep the required source enabled; the form deliberately rejects an empty route.

Procedure reference: trustlink.configuration / 2026-10-30

TRUSTLINK

# RTGS recovery and automation

Assess RTGS cases and request governed regeneration with a reason and evidence.

Where to go: /trustlink?tab=rtgs

**Access and authority**

RTGS access; recovery uses configured operator authority, policy changes require Admin.

## 01 / Investigate RTGS cases

Before you begin: Know the transaction reference or age lane.

### 1. Run/read the assessment

Open RTGS. Refresh the database assessment and inspect cases by age/status. Read the case evidence and eligibility before selecting it.

### 2. Inspect custody

Read the relevant run/action result and source state. Distinguish a regeneration request from final payment processing.

### How to confirm success

You have fresh evidence for each intended recovery.

### Stop and check

A case's age alone is not sufficient authority to regenerate it.

## 02 / Regenerate selected cases

Before you begin: Resolve the underlying issue and obtain the operational reference.

### 1. Select eligible cases

Select the exact transaction IDs. Review older-than-96-hour cases carefully; the request carries that acknowledgement for selected aged cases.

### 2. Provide a reason and submit

Enter a meaningful reason/change reference of at least eight characters. Submit the regeneration action once. Read per-case outcomes, including partial failure.

### 3. Reassess

Run the database assessment again to see updated queue state and inspect action history.

### How to confirm success

Each request has a recorded outcome and refreshed source evidence.

### Stop and check

Do not repeat a request blindly after a timeout or assume regeneration proves payment settlement.

# 03 / Maintain automated recovery and cadence

Before you begin: Have Admin authority for policy and approved schedule intent.

### 1. Review current controls

Inspect automatic five-day regeneration and the returned active schedule. Read the current cadence and enabled state.

### 2. Change and verify

Toggle the authorized policy or select the offered 30/60-minute cadence. Wait for saved confirmation and re-read the active schedule/action history.

### How to confirm success

The policy and active schedule reflect the approved change.

### Stop and check

If the runtime has not returned a schedule, the displayed selection alone does not configure automation.

## Something is blocking you?

### Some cases failed

Review each outcome and fresh assessment before deciding on another request.

## Terms in plain language

### Regeneration

Recreates/requeues the eligible processing request; it is not evidence of settlement.

Procedure reference: trustlink.rtgs / 2026-10-30

NEXUS

# Fabric overview

Read the fabric's current posture and move into the correct investigation.

Where to go: /nexus

**Access and authority**

Fabric overview access. Each Nexus workspace also has its own entitlement.

## 01 / Orient yourself in Nexus

Before you begin: Know the environment or affected business journey.

### 1. Check freshness and scope

Open Nexus. Read the overview and refresh state. Use search to locate incidents, services, clusters, flows or dependencies.

### 2. Choose the right workspace

Use Incidents for current/unresolved cases, Services for runtime evidence and controls, and Clusters/Flows/Dependencies for relationships. Linked Stats and Network Sentinel consoles require their own access.

### 3. Separate facts from inference

Read source timestamps and evidence before acting on a root-cause suggestion. An unavailable source is not healthy and a likely cause is not a confirmed verdict.

### How to confirm success

You know which workspace holds the evidence and which service/incident to inspect.

### Stop and check

Do not execute controls from a summary alone. Open the detailed evidence and relevant procedure.

## Something is blocking you?

### Workspace missing

Ask the section administrator to check that specific module; the overview does not grant all Nexus operations.

## Terms in plain language

### Fabric

The catalog of services, their relationships and operational evidence.

### Correlation

Combining signals to propose a shared incident or cause.

Procedure reference: nexus.dashboard / 2026-10-30

NEXUS

# Incident investigation

Investigate impact, gather evidence, coordinate response and record a verified outcome.

Where to go: /nexus?workspace=incidents

**Access and authority**

Incident investigation access; diagnostics, tasks, verdicts and notification settings remain role-gated.

## 01 / Investigate an incident

Before you begin: Identify the affected journey/service and incident time.

### 1. Choose a case

In Incidents, use All unresolved, Active now, Shift pulse, Last 24h or Older. Open Incident Command View. Restored cases can still await an operator verdict.

### 2. Read the evidence

Review Overview, Topology and Evidence. Compare suspected root, confidence, affected services, timeline and business-flow scope. Inspect original evidence when a mapped link is available.

### 3. Request assistance

Use Request Diagnostics if allowed, then inspect the resulting Actions/evidence. Create Response Task for owned follow-up. SOP Copilot can explain/cite procedures; verify the cited version and prerequisites.

### How to confirm success

The response is based on dated evidence, with assigned follow-up where needed.

### Stop and check

Confidence is a hypothesis score, not certainty. Missing deep-link mapping should be corrected in the catalog, not guessed.

## 02 / Record an operator verdict

Before you begin: Have verified the cause and whether the action worked.

### 1. Review the restored state

Compare current signal and the incident end time. Confirm whether impact ended and identify remaining work.

### 2. Record the outcome

Open Outcome. Supply the supported verdict, actual root/cause, action result and explanation required by the form. Submit once and confirm the recorded learning/closure state.

### How to confirm success

The incident carries an attributable human outcome, not just automatic recovery.

### Stop and check

Do not confirm a root cause merely because it was Nexus's top candidate.

# 03 / Configure incident notification delivery

Before you begin: Have Admin authority and an approved recipient/channel scope.

### 1. Open Notification Mesh

Choose Configure. Review active-shift recipient scope, channels, extra email recipients and last delivery/queue state.

### 2. Save and inspect delivery

Set the approved controls, save, then inspect subsequent delivery status and failures. Extra recipients must be intentional.

### How to confirm success

The mesh shows the saved scope and evidence of delivery attempts.

### Stop and check

In-app or email delivery status does not prove a person read the message. Desktop browser alerts require supported HTTPS permission.

## Something is blocking you?

### Diagnostics/action fails

Read the returned error and Actions record; do not repeat disruptive commands.

### No evidence link

Open the correct service contract and have its Network Sentinel mapping verified.

## Terms in plain language

### Awaiting verdict

Impact may have ended, but human investigation closure is still pending.

### Blast radius

The services or journeys inferred to be affected.

Procedure reference: nexus.incidents / 2026-10-30

NEXUS

# Service catalog and controls

Inspect a service's live evidence and manage its governed contract and controls.

Where to go: /nexus?workspace=services

**Access and authority**

Service catalog access; catalog changes require Admin, runtime actions require configured authority and successful gates.

## 01 / Investigate a service

Before you begin: Select the correct service and environment.

### 1. Open Live Operations

Read active impact, runtime agent, Network Sentinel, host posture and heartbeat. Check timestamps; no signal/unknown is not healthy.

### 2. Inspect signals and logs

Open the signal explorer and log-tail/evidence controls offered by the contract. Set the relevant scope and refresh. Compare runtime observations with external probes and incident history.

### How to confirm success

You can identify the source and age of each observation.

### Stop and check

Log excerpts can contain sensitive operational data; share only the necessary evidence.

## 02 / Create or update a service contract

Before you begin: Have the stable identity, owner, environment, bindings and approved endpoints.

### 1. Open Contract Configuration

Create a service or edit the selected contract. Set its identity/type, ownership, agent/network bindings, observation settings and certification stage.

### 2. Set valid control routes

Supply only approved extraction, formatting, shipping, diagnostics and control endpoints exposed by the editor. Review timeout/safety settings and associated cluster routing.

### 3. Save and validate

Save and inspect fresh evidence from the service. Delete only retired contracts after reviewing the impact and confirmation. A saved endpoint is not a proven working endpoint.

### How to confirm success

The persisted contract and live evidence describe the intended service.

### Stop and check

Do not promote certification or enable control merely to make a button available.

# 03 / Start, stop or restart a service

Before you begin: Have change authority, verified service identity, current evidence and a justified action.

### 1. Open the Service Control Gate

From the service or incident choose Service Control. Read eligibility, readiness, allowlisted action and current runtime state. Request diagnostics first when required.

### 2. Request and verify the challenge

Choose the intended action and provide the required reason. Request the OTP challenge. Check the action/service again before entering the issued one-time code.

### 3. Follow the result

Submit once and inspect command outcome and fresh service state. If blocked, expired or uncertain, read the reason and reconcile before a new request.

### How to confirm success

A command has an attributable result, supported by refreshed runtime evidence.

### Stop and check

Never treat STOP/RESTART as a harmless probe or reuse an expired challenge.

## Something is blocking you?

### Control blocked

Read the gate: readiness, certification, allowlist, cooldown or missing evidence must be resolved legitimately.

### Stale heartbeat

Check the agent and telemetry route before treating the runtime state as current.

## Terms in plain language

### Contract

The saved identity, bindings and allowed operations for one service.

### OTP

A one-time code that confirms the requested controlled action.

Procedure reference: nexus.services / 2026-10-30

NEXUS

# Agent monitoring

Inspect the runtime agents that report service evidence and carry allowed commands.

Where to go: /nexus?workspace=agents

**Access and authority**

Agent monitoring access; onboarding credentials and catalog edits have separate controls.

## 01 / Investigate an agent

Before you begin: Know the host/agent expected to report the service.

### 1. Open the agent

Select it in Agents. Read identity, environment, heartbeat age and reported capabilities/linked services.

### 2. Correlate the gap

Compare agent freshness with the service's external Network Sentinel checks. If heartbeat is stale, inspect deployment/connectivity through the responsible owner.

### 3. Verify recovery

Refresh after the owner restores reporting and confirm a new heartbeat and service evidence.

### How to confirm success

The agent's presence and capabilities are backed by recent observations.

### Stop and check

An installed agent is not necessarily connected, and its existence does not authorize arbitrary shell commands.

## Something is blocking you?

### Agent missing

Verify deployment, identity and token configuration with the host owner using Onboarding. Do not publish tokens in incident notes.

## Terms in plain language

### Heartbeat

A periodic signal that the agent is still reporting.

### Allowlist

The explicit set of permitted commands.

Procedure reference: nexus.agents / 2026-10-30

NEXUS

# Database fabric

Represent databases and inspect their connectivity, usage and dependent services.

Where to go: /nexus?workspace=databases

**Access and authority**

Database fabric access; contract/connection changes require Admin.

## 01 / Inspect or configure database fabric

Before you begin: Know the database identity, environment, owner and approved connection profile.

**1. Open the database**

Select its fabric entry and review engine, schemas, connectivity and observed symptoms such as sessions, locks, lag or pool pressure where available.

**2. Maintain the contract**

Use configuration to set the intended database profile and access bindings. Enter required connection fields securely; preserve correct schema/environment mappings.

**3. Test and verify**

Use the connection test where offered. Read its result and refresh evidence. A successful connection test is not proof of application transaction success.

**How to confirm success**

The saved database contract and test result refer to the intended environment.

**Stop and check**

Do not infer that a database is down from one application's pool pressure or missing telemetry.

## 02 / Trace a database impact

Before you begin: Identify the affected application/service.

**1. Follow its relationships**

Review connected services and the dependency topology. Distinguish a dependency declared in the catalog from evidence of a current failure.

**2. Escalate with scope**

Capture database, schema, dependent service, timestamps and observed error. Use the incident workflow for response ownership.

**How to confirm success**

The escalation identifies the affected path and supporting signal.

**Stop and check**

Catalog visibility is not permission to change database data.

## Something is blocking you?

**Connection test fails**

Read the error, confirm environment/endpoint and ask the database owner to verify approved credentials/network access.

## Terms in plain language

**Pool pressure**

An application's demand for available database connections.

Procedure reference: nexus.databases / 2026-10-30

NEXUS

# Service clusters

Group services and inspect the shared routing paths used by a cluster.

Where to go: /nexus?workspace=clusters

**Access and authority**

Cluster access; create/edit/delete require Admin.

## 01 / Explore a cluster

Before you begin: Know the affected service group.

### 1. Open Fabric Preview

Select the cluster and inspect entry points, service mesh, membership, routing readiness and ownership.

### 2. Follow the route

Trace the service path and inspect missing diagnostics or other route indicators. Open the relevant service to verify runtime evidence.

### How to confirm success

You understand which services and routes form the cluster.

### Stop and check

A drawn connection describes configuration; it is not proof that traffic is currently flowing.

## 02 / Maintain cluster membership and routes

Before you begin: Have the approved service grouping and endpoint contracts.

### 1. Open Configuration

Create or edit the cluster identity, owner, environment and service/entry membership.

### 2. Set routing and save

Review extraction, formatting, shipping, diagnostics and restart routing fields offered by the editor. Save and revisit Fabric Preview for missing routes. Delete only retired clusters after confirmation.

### How to confirm success

The preview matches the saved membership and intended routes.

### Stop and check

Do not change a shared route without checking all member services that depend on it.

## Something is blocking you?

### Missing route

Have the owner supply the approved endpoint; do not substitute an unrelated working URL.

## Terms in plain language

### Entry point

A service at the beginning of the cluster's path.

Procedure reference: nexus.clusters / 2026-10-30

NEXUS

# Business flows

Describe a business journey so incident impact follows the user's actual service path.

Where to go: /nexus?workspace=flows

**Access and authority**

Business flows access; create/edit/delete require Admin.

## 01 / Follow a business journey

Before you begin: Know the business outcome and participating services.

**1. Open the flow**

Select the journey and inspect ordered service steps, entry/outcome and current evidence correlation.

**2. Read impact in context**

Check required versus optional steps and the affected path. Open linked incidents/services for evidence rather than interpreting all catalog dependencies as impacted.

**How to confirm success**

You can explain which step prevents the business outcome.

**Stop and check**

An optional service failure may not stop the whole journey; verify the flow's declared rules.

## 02 / Create or maintain a flow

Before you begin: Have the process owner's approved step sequence.

**1. Configure the journey**

Create/edit name, ownership and ordered service steps. Set required/optional behavior and the fields the editor requires.

**2. Save and inspect**

Review the rendered journey after saving. Remove obsolete flows only after confirming that incident correlation no longer needs them.

**How to confirm success**

The visual journey reflects the approved sequence and scope.

**Stop and check**

Incorrect flow membership can mislead business-impact calculations.

## Something is blocking you?

**Unexpected impact**

Inspect the flow's service order and required flags before accepting the inferred impact.

## Terms in plain language

**Required step**

A step necessary for the declared business outcome.

Procedure reference: nexus.flows / 2026-10-30

NEXUS

# Dependency topology

Define and inspect directed relationships between services.

Where to go: /nexus?workspace=dependencies

**Access and authority**

Dependency topology access; changes require Admin.

## 01 / Read a dependency path

Before you begin: Identify the affected service and business flow.

### 1. Inspect direction

Open Dependencies and select the relationship. Read from/to services, purpose/type, scope and any evidence hints.

### 2. Compare live evidence

Trace upstream/downstream effects and check the related incident/service. Distinguish a catalog edge from an observed failure.

### How to confirm success

The investigation describes who depends on whom and why.

### Stop and check

Reversing the direction can invert the suspected cause and impact.

## 02 / Maintain a dependency

Before you begin: Know both service identities and the actual interaction.

### 1. Configure the edge

Create/edit source and target, purpose, scope and available timeout/failure hints. Use flow-scoped relationships when appropriate.

### 2. Save and validate

Inspect topology and affected flow after saving. Delete only obsolete relationships after reviewing the confirmation.

### How to confirm success

The saved edge describes the real dependency and intended scope.

### Stop and check

Do not add speculative relationships merely to force correlation.

## Something is blocking you?

### Graph looks wrong

Check source/target, flow scope and service identities before adjusting incident conclusions.

## Terms in plain language

### Directed edge

A relationship from one service to the service it uses.

Procedure reference: nexus.dependencies / 2026-10-30

NEXUS

# Agent and service onboarding

Connect an agent/service through governed credentials and evidence-based readiness.

Where to go: /nexus?workspace=onboarding

**Access and authority**

Onboarding access; token and catalog operations require the relevant Admin authority.

## 01 / Onboard an agent and service

Before you begin: Have the target host, owner, environment and approved deployment plan.

**1. Review readiness**

Open Onboarding and inspect missing contracts, bindings, agent credentials and readiness requirements. Identify the specific service/host.

**2. Provision securely**

Use the offered agent-token controls only with authority. Copy a newly issued token into the approved agent configuration through the deployment owner; never place it in tickets or screenshots.

**3. Register and observe**

Create/bind the service contract, deploy the configured agent and verify fresh heartbeat/telemetry. Progress certification only when the required observation/diagnostic/control evidence is proven.

**How to confirm success**

The service is mapped to an agent and reports fresh evidence at the justified readiness stage.

**Stop and check**

Token generation alone is not onboarding completion. Rotation can invalidate deployed credentials; coordinate the rollout.

## 02 / Review or rotate an agent token

Before you begin: Know the active agents using the credential and the replacement plan.

**1. Inspect current status**

Read the current token status without exposing its secret. Identify the authorized rotation/generation control.

**2. Coordinate the change**

Issue the replacement only under the approved plan, update agent configurations and verify reporting resumes. Treat a one-time display as sensitive.

**How to confirm success**

Expected agents report successfully using the approved credential.

**Stop and check**

Do not rotate during an incident without considering the effect on current telemetry.

## Something is blocking you?

**Agent still absent**

Check endpoint, token and host connectivity with the deployment owner; do not repeatedly issue new credentials.

## Terms in plain language

**Certification**

The recorded readiness stage justified by observed capabilities and tests.

Procedure reference: nexus.onboarding / 2026-10-30

NEXUS

# Environment rollover

Prepare, test and execute a governed environment change with explicit scope and proof.

Where to go: /nexus?workspace=rollover

**Access and authority**

Environment rollover access; configuration and execution are role- and challenge-gated.

## 01 / Configure and test a rollover

Before you begin: Have an approved source/target environment and change plan.

### 1. Review the environment contract

Create/edit the intended environment, connection profiles, schemas and replacement rules. Check each source value and target value; empty or wrong targets can affect the wrong environment.

### 2. Test connections

Run the available environment and schema connection tests. Inspect results for every required connection. Saving a profile is not a successful test.

### 3. Review the execution scope

Read the current assessment/test evidence and intended changes before requesting authorization. Save changes, then repeat affected tests.

### How to confirm success

The saved contract and fresh tests support the exact planned change.

### Stop and check

Do not proceed with missing targets, ambiguous replacements or failed tests.

## 02 / Authorize and follow a rollover

Before you begin: Have the approved change window, fresh tests, reason and rollback/recovery owner.

### 1. Request the challenge

Select the intended action and review source/target and scope. Request the one-time-code challenge only when the gates permit it.

### 2. Confirm once

Enter the issued code for that challenge and execute once. Follow execution history and detailed outcomes rather than assuming the request succeeded.

### 3. Verify and follow up

Check target connectivity and application behavior through the approved change procedure. Review/set available reminders for follow-up and acknowledge them appropriately.

### How to confirm success

Execution history and post-change checks show what actually changed.

### Stop and check

If completion is uncertain, stop and verify actual state before retrying. A test does not perform the rollover.

# 03 / Manage obsolete contracts and reminders

Before you begin: Confirm the environment is no longer in operational use.

### 1. Review dependencies and history

Inspect the selected environment and existing execution/reminder records.

### 2. Use the provided control

Edit reminders or delete an obsolete contract only where allowed and after reading the confirmation. Verify the resulting list.

### How to confirm success

The active configuration reflects the approved inventory.

### Stop and check

Do not delete a contract to hide failed execution evidence.

## Something is blocking you?

### OTP expired or gate blocked

Correct the failed prerequisite and request a fresh challenge for the same verified scope.

### Test failure

Review the exact schema/connection result with the owner; do not weaken controls to continue.

## Terms in plain language

### Rollover

A controlled change from one environment/configuration to another.

Procedure reference: nexus.rollover / 2026-10-30

NEXUS

# Procedure library

Find, maintain and govern operational procedures used by operators and Copilot.

Where to go: /nexus?workspace=sops

**Access and authority**

Procedure library access; registry changes and approval require the relevant Admin authority.

## 01 / Find the applicable procedure

Before you begin: Know the service, incident or operational task.

**1. Search the library**

Inspect the procedure title, scope, version/status and content. Distinguish indexed material from a managed registry record.

**2. Use with current evidence**

Read prerequisites, steps and stop rules. In SOP Copilot, verify the cited source and version before acting. A recommendation does not authorize a control action.

**How to confirm success**

You have the correct procedure for the service and current task.

**Stop and check**

Do not execute an outdated or unapproved instruction because it was retrieved by search.

## 02 / Adopt, edit or approve a procedure

Before you begin: Have the owner-approved procedure and governance authority.

**1. Adopt when necessary**

For indexed-only material, use Adopt to create the managed record before editing/approving it. Inspect imported metadata and content.

**2. Revise the contract**

Update the applicable service/scope, version, steps, prerequisites and other required fields in Governed SOP Contract. Save and inspect the managed record.

**3. Govern the status**

Apply the available approval/status controls only after review. Delete only obsolete managed records after checking the impact and confirmation.

**How to confirm success**

The managed procedure has an attributable current version and governance state.

**Stop and check**

Indexed availability is not the same as approval. Editing a registry record is not proof that all external source documents changed.

## Something is blocking you?

**Cannot edit indexed SOP**

Adopt it into the managed registry using the allowed action, then review it.

## Terms in plain language

**Indexed**

Available for retrieval/search.

**Managed**

Tracked in the editable, governed procedure registry.

Procedure reference: nexus.sops / 2026-10-30

REPORTING

# CRB reporting

Extract the supported LMS regulatory reports and verify artifacts before delivery.

Where to go: /reports?workspace=crb

**Access and authority**

CRB reporting access. Extraction requires Admin, Manager or Supervisor; other actions follow their displayed restrictions.

## 01 / Generate CRB reports

Before you begin: Know the required report contract and approved reporting date/scope.

### 1. Review the workspace

Open Reporting > CRB extracts. Inspect the supported Contract data and Individual client details contracts and the latest run.

### 2. Start extraction

Use the extraction action when authorized. Submit once and follow Queued/Running to Completed, Partial or Failed. Inspect per-report results and errors.

### 3. Verify artifacts

Check report name, row count, size and generation time. Download the correct available CSV artifact and verify it before regulatory delivery through the approved channel.

### How to confirm success

The selected run contains the expected verified report artifacts.

### Stop and check

Partial is not a complete delivery. Generating/downloading a file does not submit it to a regulator.

## 02 / Inspect a previous reporting run

Before you begin: Know the date/report requested.

### 1. Select the recorded run

Use the run history in CRB extracts. Read its outcome and per-report artifact status.

### 2. Download or escalate

Retrieve present artifacts; for missing/failed outputs, preserve the run reference/error and ask the authorized operator to recover the extraction.

### How to confirm success

The supplied report is traceable to a specific run and generation timestamp.

### Stop and check

Do not silently replace missing historical evidence with a current extract.

## Something is blocking you?

### Source unavailable

Escalate the configured LMS connection; do not interpret a failed query as zero customers.

## Terms in plain language

### Artifact

The output file belonging to a recorded extraction.

Procedure reference: reports.crb / 2026-10-30

REPORTING

# Hovering queue

Monitor loan-ledger movement, repair eligible stale dates and recover reviewed failures.

Where to go: /reports?workspace=hovering

**Access and authority**

Hovering queue access. Operational actions require their configured role; midnight policy is Admin-only.

## 01 / Investigate queue movement

Before you begin: Know the debit account/reference or affected period.

### 1. Read the operating state

Open Hovering queue > Queue command. Read source connection, bot operating window, backlog, movement and last-read context. A paused window and a source failure are different.

### 2. Scope and inspect

Search debit account/reference; filter status and created-from/before times. Open a row in the right drawer to read amount, reference, installment date, failure description and source identifiers.

### How to confirm success

The investigation names the specific record/state and current source evidence.

### Stop and check

A throughput estimate needs sufficient observations; no measured rate is not proof of a stopped bot.

## 02 / Carry stale installments into today

Before you begin: Confirm the record is Pending with an installment date before the current source date.

### 1. Choose exact or whole eligible scope

For one record, use its date-repair control in the drawer. The sidebar bulk command acts on the eligible overdue scope, not merely the rows on the current page; review its confirmation.

### 2. Repair and verify

Accept only the intended scope. Read the updated count and refresh records/custody. Date repair changes eligible stale installment dates; it does not authorize a debit or guarantee bot processing.

### How to confirm success

The affected records show the current date and a custody entry.

### Stop and check

Already-current dates need no change. Do not use date repair as a substitute for resolving a failure.

## 03 / Requeue failed records

Before you begin: Resolve the reported cause and have authority to retry processing.

### 1. Select failures

Choose Failed, narrow the reason and filters, then Review selected or Review all filtered failures. Read the exact preview; all filtered can span pages.

### 2. Review and confirm

Check identities, amounts and explanations. Reviews expire after ten minutes; changed records require a new review. Confirm requeue once only if the cause was addressed.

### 3. Check the outcome

Read the updated count and Pending state. The bot may process the records again; use custody history to trace the action before any repeat.

### How to confirm success

Only reviewed eligible failures return to Pending with recorded evidence.

### Stop and check

Requeue is not proof of successful financial processing. If the response is uncertain, inspect custody and source state first.

## 04 / Manage midnight repair and custody

Before you begin: Admin authority is required to change the automatic date-repair policy.

### 1. Inspect the policy

Read the current midnight repair state and date boundary. Toggle only under the approved operating decision.

### 2. Confirm the audit

Review Custody marks. Browse full custody history, page through results, and collapse it to return to recent marks. Check actor, timestamp, count and reference.

### How to confirm success

The saved policy and subsequent repairs are attributable.

### Stop and check

Enabling automation permits future eligible repairs; it is not an immediate proof that today's queue was repaired.

## Something is blocking you?

### Failed review expired or record changed

Refresh and create a new preview; never reuse stale scope.

### Unexpected date

Check source timezone and installment date with the owner; browser display time may differ.

## Terms in plain language

### Pending

Waiting for further processing.

### Custody

Attributable evidence of the operator/system change.

Procedure reference: reports.hovering / 2026-10-30

REPORTING

# Hovering robot settings

Maintain robot credentials and approved operational settings through protected controls.

Where to go: /reports?workspace=settings

**Access and authority**

Robot settings access. Password rotation uses configured editor roles; general settings require Admin.

## 01 / Rotate a robot credential

Before you begin: Have the correct new core-system credential through an approved secure channel.

### 1. Identify the robot

Open Hovering queue > Robot controls, or the settings workspace if it is your only available reporting module. Check the ROBHOV identity and Encryption lane readiness.

### 2. Rotate securely

Choose Rotate for the exact identity. Enter and confirm the new password, then choose Encrypt and rotate. Wait for completion.

### 3. Verify custody and operation

Check Setting custody for the key, actor and outcome. Coordinate with the robot owner to verify authentication/processing; the existing secret is never displayed.

### How to confirm success

A completed rotation is recorded without retaining plaintext in custody.

### Stop and check

Do not rotate the wrong identity or paste credentials into notes. If encryption is not configured, stop and contact the administrator.

## 02 / Change a general robot setting

Before you begin: Have Admin authority and an approved operational value.

### 1. Read the current value

In General controls locate the exact setting and its last-updated time. Confirm its purpose and units with the operating owner.

### 2. Save one deliberate change

Enter the authorized value and save that setting. Check the resulting value and Setting custody status.

### How to confirm success

The intended key has a confirmed saved value and audit entry.

### Stop and check

A setting label is not a lending-policy approval. Do not experiment with production processing limits.

## Something is blocking you?

### Rotation failed

Read the error and custody state, verify the target identity with the owner, and avoid repeated blind rotations.

## Terms in plain language

### Encryption lane

The configured mechanism that protects the credential before handoff.

Procedure reference: reports.hovering_settings / 2026-10-30

FUNDS CUSTODY

# Funds custody and clearing

Prepare, verify, authorize and prove exact unauthorized-debit and queue-custody corrections.

Where to go: /funds-custody

**Access and authority**

The current Funds Custody page is Admin-restricted in addition to module access. Backend maker/checker/reversal roles and write gates still govern each operation.

## 01 / Prepare a Finance batch

Before you begin: A Finance reference and CSV/XLSX containing a single Account or RRN column.

### 1. Import and seal scope

In Batch control choose Create controlled batch, select Account or RRN, and use the matching one-column template. Keep identifiers as text to preserve leading zeroes. Review validation, source owner/reference and hash. Correct invalid input in a new source file, not in sealed rows.

### 2. Verify Oracle evidence

Run Verify Oracle evidence. Wait for reconciliation and inspect execution-safe, special-review, blocked and no-action classifications. Open each selected row to inspect mapping, currency, amount and queue identity.

### 3. Arm the intended tranche

Select only proven intended rows. Read the current operating-window limit; the default protection window is 08:00-19:00 with at most 20 pending rows per tranche. Outside it, Arm all pending can select remaining eligible scope. The server's displayed limit is authoritative.

### 4. Submit the sealed selection

Review count, authorized value and reference, then Submit. Unarmed rows are not in the submitted payload. Move to Execution desk for checker review.

### How to confirm success

A submitted payload identifies the exact selected effects and immutable source.

### Stop and check

A created batch is not verified authority. Blocked/no-action rows must not be forced into execution.

## 02 / Investigate an account or RRN

Before you begin: An external account or RRN and supporting authorization if preparing a correction.

### 1. Resolve the identity

Open Account explorer. Search by external account or switch to RRN. Confirm the uniquely resolved internal account and the specific currency balance row. Inspect holds, liens, unauthorized debit, physical queued amount and queue rows.

### 2. Choose the operation deliberately

Full debit clears the complete physical unauthorized debit and includes the proven debit queues for that internal account and currency. Specific queue clearing uses the approved transaction amount/fees and exact queue identity. A true partial debit clearing intentionally retains that queue until its complete authority is released.

### 3. Prepare and verify

Use the offered controlled-batch action for the selected currency/scope. Follow verification, selection and submission in Batch control. Lookup and selection alone do not mutate Oracle.

### How to confirm success

The controlled batch reflects the intended account, currency and operation mode.

### Stop and check

Unknown queue currency, ambiguous mapping, or queued authority exceeding full debit blocks safe clearing. Explicit credit queues and other currencies remain outside full-debit scope.

## 03 / Repair residual queue custody

Before you begin: Evidence that unauthorized debit is already zero, plus a justified queue repair.

### 1. Inspect exact evidence

In Account explorer inspect the selected currency, physical queued amount and outstanding rows. A queue-only cleanup differs from a debit reduction.

### 2. Choose the eligible repair

Use exact queue-row removal when those debit rows still exist. An orphaned physical queue-amount reset is only eligible when no live debit queue rows remain in that currency. Create the controlled batch and reconcile it.

### 3. Submit and authorize

Review the zero-debit-effect payload, exact queue deletions/reset, reference and approval. Verify resulting evidence in Execution desk and Custody trail.

### How to confirm success

The approved queue custody is corrected without reducing unauthorized debit again.

### Stop and check

Do not reset a physical queue amount while live queue rows remain. Preserve this cleanup path for existing residues; it is not a substitute for correct full clearing.

## 04 / Review a submitted payload

Before you begin: A submitted payload, checker authority and supporting reference. Approval executes the mutation.

### 1. Review before approval

In Execution desk inspect maker/checker, source and payload hashes, account/internal account, currency, before/after debit values and every queue deletion/reset. A different authorized checker is normal practice; the explicit Admin exception permits self-approval where configured.

### 2. Approve and execute once

Confirm both application and Oracle write gates in the intended environment. Use Approve and execute only when the exact sealed effects are authorized. There is no later manual execute step. Live row/scope changes require reconciliation and a fresh approval.

### 3. Prove the outcome

Read terminal status, before/after evidence and exact affected queue keys. Full-clear post-validation rejects remaining in-scope debit queues and rolls back that transaction. Specific full-transaction clearing removes its approved exact queue, not unrelated rows.

### How to confirm success

The execution has a proven terminal outcome and immutable evidence.

### Stop and check

COMMIT UNCERTAIN or a timeout is a stop condition: verify actual database state with the owner before retrying, replacing or reversing. Old full-debit payloads that predate queue-inclusive clearing must be reconciled and approved afresh.

## 05 / Trace an outcome or eligible reversal

Before you begin: An account/RRN, batch/execution reference or approximate date.

### 1. Browse the chronology

Open Custody trail. Search the identifier and expand year, month/day and activity as available. Inspect actor, time, references, sealed intent and execution proof.

### 2. Reverse only if eligible

In Execution desk use rollback only when the recorded committed execution is eligible and your role permits it. Provide the exact reason and review the proposed compensating change. Do not assume this is an unconditional undo.

### 3. Verify and archive

Confirm the reversal result and linked custody event. Archive eligible completed/rolled-back Account Explorer batches to clear the active rail; archiving does not erase custody.

### How to confirm success

You can reconstruct the original decision, effect and any compensating reversal.

### Stop and check

Changed live state can make reversal unsafe. Do not edit or remove history to simplify the narrative.

## 06 / Review specific-record policy

Before you begin: Admin authority and an approved scope decision.

### 1. Inspect the policy

Read the specific-record clearing policy in Execution desk. It controls whether non-admin operators can prepare transaction-specific clearing; Admin remains eligible under the backend contract.

### 2. Change and confirm

Toggle only under the approved operating decision and verify its recorded custody event. Page visibility and backend operation authority remain separate.

### How to confirm success

The policy is explicit and attributable.

### Stop and check

Do not change a policy or write gate merely to bypass a blocked operation.

## Something is blocking you?

### Full-debit approval predates queue-inclusive clearing

Reconcile and submit a fresh payload, then obtain approval for the full current queue scope.

### Queue scope changed after approval

Do not force execution. Re-read Oracle, reconcile and review a fresh payload.

### Blocked or special review

Open the interpretation. Resolve mapping/currency/amount ambiguity with Finance and the database owner; special review requires explicit evidence-based justification.

### Commit uncertain means stop

Preserve execution reference and logs. Have the database owner prove actual balance/queue state before any retry or reversal.

### Write gates closed

Verify the intended environment and approved configuration with the owner; do not enable writes just to make the control usable.

## Terms in plain language

### Unauthorized debit

The physical pending debit amount being governed; unauthorized credit is outside this workspace.

### Sealed payload

An immutable description of approved effects; changing scope needs new approval.

### Compensating reversal

A separately governed action restoring eligible recorded effects, subject to current-state checks.

Procedure reference: funds_custody.workspace / 2026-10-30

REPORTING

# Personal loans - 48 months

Monitor the approved 48-month personal-loan queues, analyze scoped evidence and recover failures.

Where to go: /reports?workspace=personal-loans

**Access and authority**

Personal-loan access; recovery follows the operation's role restrictions, full custody history is Admin-only.

## 01 / Find and inspect an application

Before you begin: Know the currency or application/customer/account/loan reference.

### 1. Select currency and filters

Choose USD, ZWL or Both currencies. Search and filter Pending/Success/Failed, created-from/before dates and failure reason where applicable. Five-second checks refresh the visible source; read the last-verified/stale indicator.

### 2. Open the right drawer

Select the record and inspect identity, tenure, amount, account, failure description and dates. Only USD PERSONAL LOAN 48 MONTHS and ZWL PERSONAL LOAN 48 MONTHS belong to this workspace.

### How to confirm success

The application is identified with a dated, scoped source state.

### Stop and check

Approved amount is not proof of funds disbursed. Do not combine currency totals as if they were one monetary unit.

## 02 / Analyze or download a credit report

Before you begin: Decide the currency, state, period and reporting boundaries.

### 1. Set boundaries explicitly

Open Reporting boundaries. Choose Application created or Bot processed date basis; optionally set exact branch, maturity and next-pay dates. Apply boundaries before analyzing/downloading. Maturity after is exclusive; maturity through and pay-through are inclusive. Missing dates do not match date boundaries.

### 2. Inspect the scoped report

Choose Analyze scope. Read totals by currency/state, missing amounts, observed min/max and daily activity. Daily activity uses current states and is not a reconstruction of historical status transitions.

### 3. Download the scope

Choose Download CSV for all matching pages, up to 10,000 rows. Narrow scope if the export is too large. The legacy preset must be explicitly applied and is a reporting filter, not a lending limit.

### How to confirm success

The report and CSV reflect the applied scope and snapshot time.

### Stop and check

Observed minimum/maximum amounts are not approved lending-policy limits. Protect exported customer data.

# 03 / Review and requeue failures

Before you begin: Resolve the failure cause first; only status_id=18 and is_processed=2 are eligible.

### 1. Prepare the exact scope

Choose Failed and Review selected or Review all filtered failures. Alternatively paste/import up to 500 numeric application IDs in plain text/CSV under 50 KB. Read the preview: missing, changed or out-of-scope IDs are excluded.

### 2. Confirm the reviewed records

Check every identity and failure cause. The review expires after ten minutes and changed records need a new preview. Confirm once to return eligible rows to Pending (status_id=31, is_processed=0).

### 3. Verify the result

Check updated count and refreshed queue. Administrators can Browse custody history for action state, actor, time and reviewed evidence.

### How to confirm success

Only the eligible reviewed applications return to processing with an attributable record.

### Stop and check

Do not requeue successful or unreviewed applications; the bot may process them again.

## Something is blocking you?

### Export exceeds limit

Narrow period/branch/currency and download separate clearly identified scopes.

### Recovery outcome uncertain

Inspect source and custody before creating another recovery; preserve the action reference.

## Terms in plain language

### Observed min/max

The smallest/largest amounts in the filtered evidence, not policy thresholds.

Procedure reference: reports.personal_loans / 2026-10-30

REPORTING

# SMS queue monitoring

Monitor retained SMS queue health and inspect message evidence without changing delivery.

Where to go: /reports?workspace=sms

**Access and authority**

SMS monitoring access. The source also contains EMAIL records; this workspace deliberately includes only non-deleted SMS.

## 01 / Read queue health and freshness

Before you begin: Confirm the source connection is configured.

### 1. Read live mode

Open SMS queue monitoring. Live / source events means database notifications trigger refresh. Polling fallback / 1s means source hooks are not installed. A disconnected/paused view is a snapshot; use Resume or Refresh when needed.

### 2. Interpret status counts

Queued waits for sending; Retryable failed but can retry; Error exhausted/failed processing; SEND means the source reports sent. Read oldest waiting, aging and retained history alongside these counts.

### 3. Investigate the backlog

Use aged waiting and source/status/time filters to isolate pressure. Counts are for retained rows, not all-time delivery; archival can lower them.

### How to confirm success

You can explain the backlog and the freshness of the evidence.

### Stop and check

SEND is not a handset-delivery receipt. SEND rows updated in 15 minutes are not measured gateway throughput.

## 02 / Inspect a message and escalate

Before you begin: Have a queue ID, exact recipient or known source.

### 1. Locate the record

Use exact ID/recipient lookup or source/status/time filters. Browse older pages if needed; list recipients are masked.

### 2. Open evidence

Select the record to open the right drawer. Read status, retry count, message, response, source and timestamps. An open drawer refreshes with source changes.

### 3. Escalate the cause

For an aged queue, ask the gateway/source owner to check processing. For retry/error, provide the reference and relevant response through an approved channel. The workspace has no send, retry, delete or edit controls.

### How to confirm success

The escalation contains an exact record reference and actionable response.

### Stop and check

Do not copy full customer messages/recipients unnecessarily. If a record disappears, it may have been archived or removed.

## Something is blocking you?

### No data loaded

Check the displayed connection error with the administrator; an unavailable source is not an empty queue.

### Snapshot stale

Resume if paused, check connectivity and refresh. Automatic reconnect resynchronizes; never present old counts as live.

## Terms in plain language

### Retryable

A failed attempt still eligible for retry by the delivery service.

### Retained queue

Only rows still present in the active source.

Procedure reference: reports.sms / 2026-10-30