NEXUS

Service catalog and controls

Inspect a service's live evidence and manage its governed contract and controls.

Where to go: /nexus?workspace=services

Access and authority

Service catalog access; catalog changes require Admin, runtime actions require configured authority and successful gates.

01 / Investigate a service

Before you begin: Select the correct service and environment.

1. Open Live Operations

Read active impact, runtime agent, Network Sentinel, host posture and heartbeat. Check timestamps; no signal/unknown is not healthy.

2. Inspect signals and logs

Open the signal explorer and log-tail/evidence controls offered by the contract. Set the relevant scope and refresh. Compare runtime observations with external probes and incident history.

How to confirm success

You can identify the source and age of each observation.

Stop and check

Log excerpts can contain sensitive operational data; share only the necessary evidence.

02 / Create or update a service contract

Before you begin: Have the stable identity, owner, environment, bindings and approved endpoints.

1. Open Contract Configuration

Create a service or edit the selected contract. Set its identity/type, ownership, agent/network bindings, observation settings and certification stage.

2. Set valid control routes

Supply only approved extraction, formatting, shipping, diagnostics and control endpoints exposed by the editor. Review timeout/safety settings and associated cluster routing.

3. Save and validate

Save and inspect fresh evidence from the service. Delete only retired contracts after reviewing the impact and confirmation. A saved endpoint is not a proven working endpoint.

How to confirm success

The persisted contract and live evidence describe the intended service.

Stop and check

Do not promote certification or enable control merely to make a button available.

03 / Start, stop or restart a service

Before you begin: Have change authority, verified service identity, current evidence and a justified action.

1. Open the Service Control Gate

From the service or incident choose Service Control. Read eligibility, readiness, allowlisted action and current runtime state. Request diagnostics first when required.

2. Request and verify the challenge

Choose the intended action and provide the required reason. Request the OTP challenge. Check the action/service again before entering the issued one-time code.

3. Follow the result

Submit once and inspect command outcome and fresh service state. If blocked, expired or uncertain, read the reason and reconcile before a new request.

How to confirm success

A command has an attributable result, supported by refreshed runtime evidence.

Stop and check

Never treat STOP/RESTART as a harmless probe or reuse an expired challenge.

Something is blocking you?

Control blocked

Read the gate: readiness, certification, allowlist, cooldown or missing evidence must be resolved legitimately.

Stale heartbeat

Check the agent and telemetry route before treating the runtime state as current.

Terms in plain language

Contract

The saved identity, bindings and allowed operations for one service.

OTP

A one-time code that confirms the requested controlled action.

Procedure reference: nexus.services / 2026-10-30