REPORTING

Hovering robot settings

Maintain robot credentials and approved operational settings through protected controls.

Where to go: /reports?workspace=settings

Access and authority

Robot settings access. Password rotation uses configured editor roles; general settings require Admin.

01 / Rotate a robot credential

Before you begin: Have the correct new core-system credential through an approved secure channel.

1. Identify the robot

Open Hovering queue > Robot controls, or the settings workspace if it is your only available reporting module. Check the ROBHOV identity and Encryption lane readiness.

2. Rotate securely

Choose Rotate for the exact identity. Enter and confirm the new password, then choose Encrypt and rotate. Wait for completion.

3. Verify custody and operation

Check Setting custody for the key, actor and outcome. Coordinate with the robot owner to verify authentication/processing; the existing secret is never displayed.

How to confirm success

A completed rotation is recorded without retaining plaintext in custody.

Stop and check

Do not rotate the wrong identity or paste credentials into notes. If encryption is not configured, stop and contact the administrator.

02 / Change a general robot setting

Before you begin: Have Admin authority and an approved operational value.

1. Read the current value

In General controls locate the exact setting and its last-updated time. Confirm its purpose and units with the operating owner.

2. Save one deliberate change

Enter the authorized value and save that setting. Check the resulting value and Setting custody status.

How to confirm success

The intended key has a confirmed saved value and audit entry.

Stop and check

A setting label is not a lending-policy approval. Do not experiment with production processing limits.

Something is blocking you?

Rotation failed

Read the error and custody state, verify the target identity with the owner, and avoid repeated blind rotations.

Terms in plain language

Encryption lane

The configured mechanism that protects the credential before handoff.

Procedure reference: reports.hovering_settings / 2026-10-30