

Contents

1 Data structures	3	7 Polygon	14
1.1 DSU rollback	3	7.1 Area polygon	14
1.2 Monotone queue $\mathcal{O}(n)$	3	7.2 Perimeter	14
1.3 Stack queue $\mathcal{O}(n)$	3	7.3 Cut polygon line	14
1.4 In-Out trick	3	7.4 Common area circle polygon $\mathcal{O}(n)$	14
1.5 Parallel binary search $\mathcal{O}((n+q) \cdot \log n)$	4	7.5 Point in polygon	14
1.6 Mos $\mathcal{O}((n+q) \cdot \sqrt{n})$	4	7.6 Convex hull $\mathcal{O}(n \log n)$	14
1.7 Hilbert order	4	7.7 Is convex	15
1.8 Sqrt decomposition	4	7.8 Point in convex polygon $\mathcal{O}(\log n)$	15
1.9 Sparse table	4	8 Graphs	15
1.10 Fenwick	5	8.1 Cycle	15
1.11 Disjoint intervals	5	8.2 Cutpoints and bridges	15
1.12 Fenwick 2D offline	5	8.3 Tarjan	15
1.13 Fenwick ND	5	8.4 Isomorphism	15
1.14 Lazy segtree	6	8.5 Two sat $\mathcal{O}(2 \cdot n)$	15
1.15 Dynamic segtree	6	8.6 LCA	16
1.16 Persistent segtree	6	8.7 Virtual tree $\mathcal{O}(n \cdot \log n)$ "lca tree"	16
1.17 Li Chao	7	8.8 Dynamic connectivity	16
1.18 Wavelet	7	8.9 Euler-tour + HLD + LCA $\mathcal{O}(n \cdot \log n)$	17
1.19 Segtree 2D	7	8.10 Centroid $\mathcal{O}(n \cdot \log n)$	17
1.20 Static to dynamic	8	8.11 Guni Paths	17
1.21 Ordered tree	8	8.12 Guni $\mathcal{O}(n \cdot \log n)$	18
1.22 Treap	8	8.13 Link-Cut tree $\mathcal{O}(n \cdot \log n)$	18
2 Dynamic programming	9	9 Flows	19
2.1 All submasks of a mask	9	9.1 Blossom $\mathcal{O}(n^3)$	19
2.2 Broken profile $\mathcal{O}(n \cdot m \cdot 2^n)$ with $n \leq m$	9	9.2 Hopcroft Karp $\mathcal{O}(e\sqrt{v})$	20
2.3 Convex hull trick $\mathcal{O}(n^2) \Rightarrow \mathcal{O}(n)$	9	9.3 Hungarian $\mathcal{O}(n^2 \cdot m)$	21
2.4 Digit dp	9	9.4 Dinic $\mathcal{O}(\min(e \cdot \text{flow}, v^2 \cdot e))$	21
2.5 Divide and conquer $\mathcal{O}(k \cdot n^2) \Rightarrow \mathcal{O}(k \cdot n \log n)$	10	9.5 Min-Cost flow $\mathcal{O}(\min(e \cdot \text{flow}, v^2 \cdot e))$	22
2.6 Knapsack 01 $\mathcal{O}(n \cdot \text{Max}W)$	10	10 Game theory	22
2.7 Knuth $\mathcal{O}(n^3) \Rightarrow \mathcal{O}(n^2)$	10	10.1 Grundy numbers	22
2.8 Matrix exponentiation $\mathcal{O}(n^3 \cdot \log n)$	10	11 Math	22
2.9 SOS dp	10	11.1 Bits	22
2.10 Inverse SOS dp	10	11.2 Bitset	23
2.11 Steiner	10	11.3 Fpow	23
3 Geometry	11	11.4 Fraction	23
3.1 Geometry	11	11.5 Modular	23
3.2 Radial order	11	11.6 Probability	24
3.3 Sort along line	11	11.7 Simplex	24
4 Point	11	11.8 Gauss jordan $\mathcal{O}(n^2 \cdot m)$	25
4.1 Point	11	11.9 Xor basis	25
4.2 Angle between vectors	12	12 Combinatorics	25
4.3 Closest pair of points $\mathcal{O}(n \cdot \log n)$	12	12.1 Factorial	25
4.4 KD Tree	12	12.2 Factorial mod small prime	25
5 Lines and segments	12	12.3 Choose	26
5.1 Line	12	12.4 Pascal	26
5.2 Segment	13	12.5 Stars and bars	26
5.3 Projection	13	12.6 Lucas	26
5.4 Distance point line	13	12.7 Burnside lemma	26
5.5 Distance point segment	13	12.8 Catalan	26
5.6 Distance segment segment	13	12.9 Bell numbers	26
6 Circle	13	12.10 Stirling numbers	26
6.1 Circle	13	12.11 Stirling numbers 2	26
6.2 Distance point circle	14		
6.3 Common area circle circle	14		
6.4 Minimum enclosing circle $\mathcal{O}(n)$ wow!!	14		

13 Number theory	27
13.1 Amount of divisors $\mathcal{O}(n^{1/3})$	27
13.2 Chinese remainder theorem	27
13.3 Euclid $\mathcal{O}(\log(a \cdot b))$	27
13.4 Factorial factors	27
13.5 Inverse	27
13.6 Factorize sieve	27
13.7 Sieve	27
13.8 Phi $\mathcal{O}(\sqrt{n})$	27
13.9 Phi sieve	27
13.10 Miller rabin $\mathcal{O}(\text{Witnesses} \cdot (\log n)^3)$	27
13.11 Pollard Rho $\mathcal{O}(n^{1/4})$	28
14 Polynomials	28
14.1 Berlekamp Massey	28
14.2 Lagrange $\mathcal{O}(n)$	28
14.3 FFT	29
14.4 Fast Walsh Hadamard Transform	29
14.5 Primitive root	29
14.6 NTT	30
15 Strings	30
15.1 KMP $\mathcal{O}(n)$	30
15.2 KMP automaton $\mathcal{O}(\text{Alphabet} * n)$	30
15.3 Z $\mathcal{O}(n)$	30
15.4 Manacher $\mathcal{O}(n)$	31
15.5 Hash	31
15.6 Min rotation $\mathcal{O}(n)$	31
15.7 Suffix array $\mathcal{O}(n \log n)$	31
15.8 Trie	32
15.9 Aho Corasick $\mathcal{O}(\sum s_i)$	32
15.10 Eertree $\mathcal{O}(\sum s_i)$	33
15.11 Suffix automaton $\mathcal{O}(\sum s_i)$	33

Think twice, code once

Template.cpp

```
#include <bits/stdc++.h>
using namespace std;

#define fore(i, l, r) for (auto i = (l); i < (r); i++)
#define sz(x) int(x.size())
#define all(x) begin(x), end(x)
#define f first
#define s second
#define pb push_back

#ifdef LOCAL
#include "debug.h"
#else
#define debug(...)
#endif

using ld = long double;
using lli = long long;
using ii = pair<int, int>;

int main() {
    cin.tie(0) -> sync_with_stdio(0), cout.tie(0);
    return 0;
}

/* Please, check the following:
 * int overflow, array bounds
```

Debug.h

```
#include <bits/stdc++.h>
using namespace std;

template <class A, class B>
ostream& operator<<(ostream& os, const pair<A, B>& p) {
    return os << "(" << p.first << ", " << p.second << ")";
}

template <class A, class B, class C>
basic_ostream<A, B>& operator<<(basic_ostream<A, B>& os,
    const C& c) {
    os << "[";
    for (const auto& x : c)
        os << ", " + 2 * (&x == &begin(c)) << x;
    return os << "]";
}

void print(string s) {
    cout << endl;
}

template <class H, class... T>
void print(string s, const H& h, const T&... t) {
    const static string reset = "\033[0m", blue = "\033[1;34m",
        purple = "\033[3;95m";
    bool ok = 1;
    do {
        if (s[0] == '\n')
            ok = 0;
        else
            cout << blue << s[0] << reset;
        s = s.substr(1);
    } while (s.size() && s[0] != ',');
    if (ok)
        cout << ": " << purple << h << reset;
    print(s, t...);
}

#define debug(...) print(__VA_ARGS__, __VA_ARGS__)
```

Randoms

```
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count());
```

Compilation (gedit ~/.zshenv)

```
touch in{1..9} // make files in1, in2, ..., in9
tee {a..z}.cpp < tem.cpp // make files with tem.cpp
rm -r a.cpp // deletes file a.cpp :(

red = '\x1B[0;31m'
green = '\x1B[0;32m'
removeColor = '\x1B[0m'

compile() {
    alias flags='-Wall -Wextra -Wfatal-errors -Wshadow -w -
        mcmmodel=medium'
    g++-11 --std=c++17 $2 ${flags} $1.cpp -o $1
}

go() {
    file=$1
    name="${file%.*}"
    input=$2
    moreFlags=$3
    compile ${name} ${moreFlags}
    ./${name} < ${input}
}

run() { go $1 $2 "" }
debug() { go $1 $2 -DLOCAL }
```

```

random() { # Make small test cases!!!
    file=$1
    name="{file%.*}"
    compile ${name} ""
    compile gen ""
    compile brute ""

    for ((i = 1; i <= 300; i++)); do
        printf "Test case #${i}"
        ./gen > tmp
        diff -ywi <(. /name < tmp) <(. /brute < tmp) > $nameDiff
        if [[ $? -eq 0 ]]; then
            printf "${green} Accepted ${removeColor}\n"
        else
            printf "${red} Wrong answer ${removeColor}\n"
            break
        fi
    done
}

```

Data structures

1.1 DSU rollback

```

struct Dsu {
    vector<int> par, tot;
    stack<ii> mem;

    Dsu(int n = 1) : par(n + 1), tot(n + 1, 1) {
        iota(all(par), 0);
    }

    int find(int u) {
        return par[u] == u ? u : find(par[u]);
    }

    void unite(int u, int v) {
        u = find(u), v = find(v);
        if (u != v) {
            if (tot[u] < tot[v])
                swap(u, v);
            mem.emplace(u, v);
            tot[u] += tot[v];
            par[v] = u;
        } else {
            mem.emplace(-1, -1);
        }
    }

    void rollback() {
        auto [u, v] = mem.top();
        mem.pop();
        if (u != -1) {
            tot[u] -= tot[v];
            par[v] = v;
        }
    }
};

```

1.2 Monotone queue $\mathcal{O}(n)$

// MonotoneQueue<int, greater<int>> = Max-MonotoneQueue

```

template <class T, class F = less<T>>
struct MonotoneQueue {
    deque<pair<T, int>> q;
    F f;

    void add(int pos, T val) {
        while (q.size() && !f(q.back().f, val))
            q.pop_back();
        q.emplace_back(val, pos);
    }
}

```

```

void trim(int pos) { // >= pos
    while (q.size() && q.front().s < pos)
        q.pop_front();
}

T query() {
    return q.empty() ? T() : q.front().f;
}
};

```

1.3 Stack queue $\mathcal{O}(n)$

```

template <class T, class F = function<T(const T&, const T&)>
>>
struct Stack : vector<T> {
    vector<T> s;
    F f;

    Stack(const F& f) : f(f) {}

    void push(T x) {
        this->pb(x);
        s.pb(s.empty() ? x : f(s.back(), x));
    }

    T pop() {
        T x = this->back();
        this->pop_back();
        s.pop_back();
        return x;
    }

    T query() {
        return s.back();
    }
};

template <class T, class F = function<T(const T&, const T&)>
>>
struct Queue {
    Stack<T> a, b;
    F f;

    Queue(const F& f) : a(f), b(f), f(f) {}

    void push(T x) {
        b.push(x);
    }

    T pop() {
        if (a.empty())
            while (!b.empty())
                a.push(b.pop());
        return a.pop();
    }

    T query() {
        if (a.empty())
            return b.query();
        if (b.empty())
            return a.query();
        return f(a.query(), b.query());
    }
};

```

1.4 In-Out trick

```

vector<int> in[N], out[N];
vector<Query> queries;

for (x, 0, N) {
    for (int i : in[x])

```

```

    add(queries[i]);
    // solve
    for (int i : out[x])
        rem(queries[i]);
}

```

1.5 Parallel binary search $\mathcal{O}((n + q) \cdot \log n)$

There are q queries, n updates, you are asked to find when a certain condition is met with a prefix of updates.

```

int lo[QUERIES], hi[QUERIES];
queue<int> solve[UPDATES];
vector<Update> updates;
vector<Query> queries;

fore (it, 0, 1 + __lg(UPDATES)) {
    fore (i, 0, sz(queries))
        if (lo[i] != hi[i]) {
            int mid = (lo[i] + hi[i]) / 2;
            solve[mid].emplace(i);
        }
    fore (i, 0, sz(updates)) {
        // add the i-th update, we have a prefix of updates
        while (!solve[i].empty()) {
            int qi = solve[i].front();
            solve[i].pop();
            if (can(queries[qi]))
                hi[qi] = i;
            else
                lo[qi] = i + 1;
        }
    }
}

```

1.6 Mos $\mathcal{O}((n + q) \cdot \sqrt{n})$

Mo's in a tree, extended euler tour $\text{tin}[u] = ++\text{timer}$, $\text{tout}[u] = ++\text{timer}$

- $u = \text{lca}(u, v)$, $\text{query}(\text{tin}[u], \text{tin}[v])$
- $u \neq \text{lca}(u, v)$, $\text{query}(\text{tout}[u], \text{tin}[v]) + \text{query}(\text{tin}[\text{lca}], \text{tin}[\text{lca}])$

```

struct Query {
    int l, r, i;
};

vector<Query> queries;

const int BLOCK = sqrt(N);
sort(all(queries), [&](Query& a, Query& b) {
    const int ga = a.l / BLOCK, gb = b.l / BLOCK;
    if (ga == gb)
        return a.r < b.r;
    return ga < gb;
});

```

```

int l = queries[0].l, r = l - 1;
for (auto& q : queries) {
    while (r < q.r)
        add(++r);
    while (r > q.r)
        rem(r--);
    while (l < q.l)
        rem(l++);
    while (l > q.l)
        add(--l);
    ans[q.i] = solve();
}

```

1.7 Hilbert order

```

struct Query {
    int l, r, i;
    lli order = hilbert(l, r);
}

lli hilbert(int x, int y, int pw = 21, int rot = 0) {
    if (pw == 0)
        return 0;
    int hpw = 1 << (pw - 1);
    int k = ((x < hpw ? y < hpw ? 0 : 3 : y < hpw ? 1 : 2) +
        rot) & 3;
    const int d[4] = {3, 0, 0, 1};
    lli a = 1LL << ((pw < 1) - 2);
    lli b = hilbert(x & (x ^ hpw), y & (y ^ hpw), pw - 1, (
        rot + d[k]) & 3);
    return k * a + (d[k] ? a - b - 1 : b);
}

```

1.8 Sqrt decomposition

```

const int BLOCK = sqrt(N);

void update(int i) {}

int query(int l, int r) {
    while (l <= r)
        if (l % BLOCK == 0 && l + BLOCK - 1 <= r) {
            // solve for block
            l += BLOCK;
        } else {
            // solve for individual element
            l++;
        }
}

```

1.9 Sparse table

```

template <class T, class F = function<T(const T&, const T&)
>>
struct Sparse {
    vector<T> sp[21]; // n <= 2^21
    F f;
    int n;

    Sparse(T* begin, T* end, const F& f) : Sparse(vector<T>(
        begin, end), f) {}

    Sparse(const vector<T>& a, const F& f) : f(f), n(sz(a)) {
        sp[0] = a;
        for (int k = 1; (1 << k) <= n; k++) {
            sp[k].resize(n - (1 << k) + 1);
            fore (l, 0, sz(sp[k])) {
                int r = l + (1 << (k - 1));
                sp[k][l] = f(sp[k - 1][l], sp[k - 1][r]);
            }
        }
    }

    T query(int l, int r) {
        #warning Can give TLE D:, change it to a log table
        int k = __lg(r - l + 1);
        return f(sp[k][l], sp[k][r - (1 << k) + 1]);
    }

    T queryBits(int l, int r) {
        optional<T> ans;
        for (int len = r - l + 1; len; len -= len & -len) {
            int k = __builtin_ctz(len);
            ans = ans ? f(ans.value(), sp[k][l]) : sp[k][l];
            l += (1 << k);
        }
    }
}

```

```

    }
    return ans.value();
}
};

```

1.10 Fenwick

```

template <class T>
struct Fenwick {
    vector<T> fenw;

    Fenwick(int n) : fenw(n, T()) {} // 0-indexed

    void update(int i, T v) {
        for (; i < sz(fenw); i |= i + 1)
            fenw[i] += v;
    }

    T query(int i) {
        T v = T();
        for (; i >= 0; i &= i + 1, --i)
            v += fenw[i];
        return v;
    }

    // First position such that fenwick's sum >= v
    int lower_bound(T v) {
        int pos = 0;
        for (int k = __lg(sz(fenw)); k >= 0; k--)
            if (pos + (1 << k) <= sz(fenw) && fenw[pos + (1 << k)
                - 1] < v) {
                pos += (1 << k);
                v -= fenw[pos - 1];
            }
        return pos + (v == 0);
    }
};

```

1.11 Disjoint intervals

```

template <class T>
struct DisjointIntervals {
    set<pair<T, T>> st;

    void insert(T l, T r) {
        auto it = st.lower_bound({l, -1});
        if (it != st.begin() && l <= prev(it)->s)
            l = (--it)->f;
        for (; it != st.end() && it->f <= r; st.erase(it++))
            r = max(r, it->s);
        st.insert({l, r});
    }

    void erase(T l, T r) {
        auto it = st.lower_bound({l, -1});
        if (it != st.begin() && l <= prev(it)->s)
            --it;
        T mn = l, mx = r;
        for (; it != st.end() && it->f <= r; st.erase(it++))
            mn = min(mn, it->f), mx = max(mx, it->s);
        if (mn < l)
            st.insert({mn, l - 1});
        if (r < mx)
            st.insert({r + 1, mx});
    }
};

```

1.12 Fenwick 2D offline

```

template <class T>
struct Fenwick2D { // add, build then update, query
    vector<vector<T>> fenw;
    vector<vector<int>> ys;
    vector<int> xs;

```

```

    vector<ii> pts;

    void add(int x, int y) {
        pts.pb({x, y});
    }

    void build() {
        sort(all(pts));
        for (auto&& [x, y] : pts) {
            if (xs.empty() || x != xs.back())
                xs.pb(x);
            swap(x, y);
        }
        fenw.resize(sz(xs)), ys.resize(sz(xs));
        sort(all(pts));
        for (auto&& [x, y] : pts) {
            swap(x, y);
            int i = lower_bound(all(xs), x) - xs.begin();
            for (; i < sz(fenw); i |= i + 1)
                if (ys[i].empty() || y != ys[i].back())
                    ys[i].pb(y);
        }
        fore (i, 0, sz(fenw))
            fenw[i].resize(sz(ys[i]), T());
    }

    void update(int x, int y, T v) {
        int i = lower_bound(all(xs), x) - xs.begin();
        for (; i < sz(fenw); i |= i + 1) {
            int j = lower_bound(all(ys[i]), y) - ys[i].begin();
            for (; j < sz(fenw[i]); j |= j + 1)
                fenw[i][j] += v;
        }
    }

    T query(int x, int y) {
        T v = T();
        int i = upper_bound(all(xs), x) - xs.begin() - 1;
        for (; i >= 0; i &= i + 1, --i) {
            int j = upper_bound(all(ys[i]), y) - ys[i].begin() - 1;
            for (; j >= 0; j &= j + 1, --j)
                v += fenw[i][j];
        }
        return v;
    }
};

```

1.13 Fenwick ND

```

template <class T, int... N>
struct Fenwick {
    T v = T();

    void update(T v) {
        this->v += v;
    }

    T query() {
        return v;
    }
};

template <class T, int N, int... M>
struct Fenwick<T, N, M...> {
    Fenwick<T, M...> fenw[N];

    template <typename... Args>
    void update(int i, Args... args) {
        for (; i < N; i |= i + 1)
            fenw[i].update(args...);
    }

```

```

}

template <typename... Args>
T query(int l, int r, Args... args) {
    T v = 0;
    for (; r >= 0; r &= r + 1, --r)
        v += fenw[r].query(args...);
    for (--l; l >= 0; l &= l + 1, --l)
        v -= fenw[l].query(args...);
    return v;
}
};

// Fenwick<lli, 10, 20, 30> is a 3D Fenwick<lli> of 10 * 2
// 0 * 30

```

1.14 Lazy segtree

```

struct Lazy {
    int l, r;
    Lazy *left, *right;
    lli sum = 0, lazy = 0;

    Lazy(int l, int r) : l(l), r(r), left(0), right(0) {
        if (l == r) {
            sum = a[l];
            return;
        }
        int m = (l + r) >> 1;
        left = new Lazy(l, m);
        right = new Lazy(m + 1, r);
        pull();
    }

    void push() {
        if (!lazy)
            return;
        sum += (r - l + 1) * lazy;
        if (l != r) {
            left->lazy += lazy;
            right->lazy += lazy;
        }
        lazy = 0;
    }

    void pull() {
        sum = left->sum + right->sum;
    }

    void update(int ll, int rr, lli v) {
        push();
        if (rr < l || r < ll)
            return;
        if (ll <= l && r <= rr) {
            lazy += v;
            push();
            return;
        }
        left->update(ll, rr, v);
        right->update(ll, rr, v);
        pull();
    }

    lli query(int ll, int rr) {
        push();
        if (rr < l || r < ll)
            return 0;
        if (ll <= l && r <= rr)
            return sum;
        return left->query(ll, rr) + right->query(ll, rr);
    }
}

```

```

};

```

1.15 Dynamic segtree

```

template <class T>
struct Dyn {
    int l, r;
    Dyn *left, *right;
    T val;

    Dyn(int l, int r) : l(l), r(r), left(0), right(0) {}

    void pull() {
        val = (left ? left->val : T()) + (right ? right->val :
            T());
    }

    template <class... Args>
    void update(int p, const Args&... args) {
        if (l == r) {
            val = T(args...);
            return;
        }
        int m = (l + r) >> 1;
        if (p <= m) {
            if (!left)
                left = new Dyn(l, m);
            left->update(p, args...);
        } else {
            if (!right)
                right = new Dyn(m + 1, r);
            right->update(p, args...);
        }
        pull();
    }

    T query(int ll, int rr) {
        if (rr < l || r < ll || r < l)
            return T();
        if (ll <= l && r <= rr)
            return val;
        int m = (l + r) >> 1;
        return (left ? left->query(ll, rr) : T()) + (right ?
            right->query(ll, rr) : T());
    }
};

```

1.16 Persistent segtree

```

template <class T>
struct Per {
    int l, r;
    Per *left, *right;
    T val;

    Per(int l, int r) : l(l), r(r), left(0), right(0) {}

    Per* pull() {
        val = left->val + right->val;
        return this;
    }

    void build() {
        if (l == r)
            return;
        int m = (l + r) >> 1;
        (left = new Per(l, m))->build();
        (right = new Per(m + 1, r))->build();
        pull();
    }

    template <class... Args>
    Per* update(int p, const Args&... args) {

```

```

if (p < l || r < p)
    return this;
Per* tmp = new Per(l, r);
if (l == r) {
    tmp->val = T(args...);
    return tmp;
}
tmp->left = left->update(p, args...);
tmp->right = right->update(p, args...);
return tmp->pull();
}

T query(int ll, int rr) {
    if (r < ll || rr < l)
        return T();
    if (ll <= l && r <= rr)
        return val;
    return left->query(ll, rr) + right->query(ll, rr);
}
};

```

1.17 Li Chao

```

struct LiChao {
    struct Fun {
        lli m = 0, c = -INF;
        lli operator()(lli x) const {
            return m * x + c;
        }
    } f;

    lli l, r;
    LiChao *left, *right;
    LiChao(lli l, lli r, Fun f) : l(l), r(r), f(f), left(0),
        right(0) {}

    void add(Fun& g) {
        lli m = (l + r) >> 1;
        bool bl = g(l) > f(l), bm = g(m) > f(m);
        if (bm)
            swap(f, g);
        if (l == r)
            return;
        if (bl != bm)
            left ? left->add(g) : void(left = new LiChao(l, m, g));
        else
            right ? right->add(g) : void(right = new LiChao(m + 1,
                r, g));
    }

    lli query(lli x) {
        if (l == r)
            return f(x);
        lli m = (l + r) >> 1;
        if (x <= m)
            return max(f(x), left ? left->query(x) : -INF);
        return max(f(x), right ? right->query(x) : -INF);
    }
};

```

1.18 Wavelet

```

struct Wav {
    int lo, hi;
    Wav *left, *right;
    vector<int> amt;

    template <class Iter>
    Wav(int lo, int hi, Iter b, Iter e) : lo(lo), hi(hi) { //
        array 1-indexed
        if (lo == hi || b == e)
            return;

```

```

amt.reserve(e - b + 1);
amt.pb(0);
int mid = (lo + hi) >> 1;
auto leq = [mid](auto x) {
    return x <= mid;
};
for (auto it = b; it != e; it++)
    amt.pb(amt.back() + leq(*it));
auto p = stable_partition(b, e, leq);
left = new Wav(lo, mid, b, p);
right = new Wav(mid + 1, hi, p, e);
}

// kth value in [l, r]
int kth(int l, int r, int k) {
    if (r < l)
        return 0;
    if (lo == hi)
        return lo;
    if (k <= amt[r] - amt[l - 1])
        return left->kth(amt[l - 1] + 1, amt[r], k);
    return right->kth(l - amt[l - 1], r - amt[r], k - amt[r]
        + amt[l - 1]);
}

// Count all values in [l, r] that are in range [x, y]
int count(int l, int r, int x, int y) {
    if (r < l || y < x || y < lo || hi < x)
        return 0;
    if (x <= lo && hi <= y)
        return r - l + 1;
    return left->count(amt[l - 1] + 1, amt[r], x, y) +
        right->count(l - amt[l - 1], r - amt[r], x, y);
}
};

```

1.19 Segtree 2D

```

struct Dyn {
    int l, r;
    lli mx = -INF;
    Dyn *left, *right;

    Dyn(int l, int r) : l(l), r(r), left(0), right(0) {}

    void pull() {
        mx = max(mx, (left ? left->mx : -INF));
        mx = max(mx, (right ? right->mx : -INF));
    }

    void update(int p, lli v) {
        if (l == r) {
            mx = v;
            return;
        }
        int m = (l + r) >> 1;
        if (p <= m) {
            if (!left)
                left = new Dyn(l, m);
            left->update(p, v);
        } else {
            if (!right)
                right = new Dyn(m + 1, r);
            right->update(p, v);
        }
        pull();
    }

    lli qmax(int ll, int rr) {
        if (rr < l || r < ll || r < l)
            return -INF;

```

```

    if (ll <= l && r <= rr)
        return mx;
    int m = (l + r) >> 1;
    return max((left ? left->qmax(ll, rr) : 0), (right ?
        right->qmax(ll, rr) : 0));
}
};

struct Seg2D {
    int x1, x2;
    Seg2D *left, *right;
    Dyn* tree;

    Seg2D(int x1, int x2, int y1, int y2) : x1(x1), x2(x2),
        tree(0), left(0), right(0) {
        tree = new Dyn(y1, y2);
        if (x1 == x2)
            return;
        int m = (x1 + x2) >> 1;
        left = new Seg2D(x1, m, y1, y2);
        right = new Seg2D(m + 1, x2, y1, y2);
    }

    void pull(int y, lli v) {
        tree->update(y, max(v, tree->qmax(y, y)));
    }

    void update(int x, int y, lli v) {
        if (x1 == x2) {
            tree->update(y, v);
            return;
        }
        int m = (x1 + x2) >> 1;
        if (x <= m)
            left->update(x, y, v);
        else
            right->update(x, y, v);
        pull(y, v);
    }

    lli qmax(int xx1, int xx2, int yy1, int yy2) {
        if (xx2 < x1 || x2 < xx1)
            return -INF;
        if (xx1 <= x1 && x2 <= xx2)
            return tree->qmax(yy1, yy2);
        return max(left->qmax(xx1, xx2, yy1, yy2), right->qmax(
            xx1, xx2, yy1, yy2));
    }
};

```

1.20 Static to dynamic

```

template <class Black, class T>
struct StaticDynamic {
    Black box[25];
    vector<T> st[25];

    void insert(T& x) {
        int p = 0;
        while (p < 25 && !st[p].empty())
            p++;
        st[p].pb(x);
        for (i, 0, p) {
            st[p].insert(st[p].end(), all(st[i]));
            box[i].clear(), st[i].clear();
        }
        for (auto y : st[p])
            box[p].insert(y);
        box[p].init();
    }
};

```

1.21 Ordered tree

It's a set/map, for a multiset/multimap (? add them as pairs (a[i], i))

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

template <class K, class V = null_type>
using OrderedTree = tree<K, V, less<K>, rb_tree_tag,
    tree_order_statistics_node_update>;
#define rank order_of_key
#define kth find_by_order

```

1.22 Treap

```

struct Treap {
    static Treap* null;
    Treap *left, *right;
    unsigned pri = rng(), sz = 0;
    int val = 0;

    void push() {
        // propagate like segtree, key-values aren't modified!!
    }

    Treap* pull() {
        sz = left->sz + right->sz + (this != null);
        // merge(left, this), merge(this, right)
        return this;
    }

    Treap() {
        left = right = null;
    }

    Treap(int val) : val(val) {
        left = right = null;
        pull();
    }

    template <class F>
    pair<Treap*, Treap*> split(const F& leq) { // {<= val, >
        val}
        if (this == null)
            return {null, null};
        push();
        if (leq(this)) {
            auto p = right->split(leq);
            right = p.f;
            return {pull(), p.s};
        } else {
            auto p = left->split(leq);
            left = p.s;
            return {p.f, pull()};
        }
    }

    Treap* merge(Treap* other) {
        if (this == null)
            return other;
        if (other == null)
            return this;
        push(), other->push();
        if (pri > other->pri) {
            return right = right->merge(other), pull();
        } else {
            return other->left = merge(other->left), other->pull
                ();
        }
    }
}

```



```

}

pair<Treap*, Treap*> leftmost(int k) { // 1-indexed
    return split([&](Treap* n) {
        int sz = n->left->sz + 1;
        if (k >= sz) {
            k -= sz;
            return true;
        }
        return false;
    });
}

auto split(int x) {
    return split([&](Treap* n) {
        return n->val <= x;
    });
}

Treap* insert(int x) {
    auto&& [leq, ge] = split(x);
    // auto&& [le, eq] = split(x); // uncomment for set
    return leq->merge(new Treap(x))->merge(ge); // change
    leq for le for set
}

Treap* erase(int x) {
    auto&& [leq, ge] = split(x);
    auto&& [le, eq] = leq->split(x - 1);
    auto&& [kill, keep] = eq->leftmost(1); // comment for
    set
    return le->merge(keep)->merge(ge); // le->merge(ge) for
    set
}
}* Treap::null = new Treap;

```

2 Dynamic programming

2.1 All submasks of a mask

```
for (int B = A; B > 0; B = (B - 1) & A)
```

2.2 Broken profile $\mathcal{O}(n \cdot m \cdot 2^n)$ with $n \leq m$

Cuenta todas las maneras en las que puedes acomodar fichas de 1x2 y 2x1 en un tablero $n \cdot m$

```
// Answer in dp[m][0][0]
```

```
lli dp[2][N][1 << N];
```

```
dp[0][0][0] = 1;
```

```

fore (c, 0, m) {
    fore (r, 0, n + 1)
        fore (mask, 0, 1 << n) {
            if (r == n) {
                dp[~c & 1][0][mask] += dp[c & 1][r][mask];
                continue;
            }

            if (~(mask >> r) & 1) {
                dp[c & 1][r + 1][mask | (1 << r)] += dp[c & 1][r][
                    mask];

                if (~(mask >> (r + 1)) & 1)
                    dp[c & 1][r + 2][mask] += dp[c & 1][r][mask];
            } else {
                dp[c & 1][r + 1][mask & ~(1 << r)] += dp[c & 1][r][
                    mask];
            }
        }
}

```

```

fore (r, 0, n + 1)
    fore (mask, 0, 1 << n)
        dp[c & 1][r][mask] = 0;
}

```

2.3 Convex hull trick $\mathcal{O}(n^2) \Rightarrow \mathcal{O}(n)$

$dp[i] = \min_{j < i} (dp[j] + b[j] * a[i])$
 $dp[i][j] = \min_{k < j} (dp[i - 1][k] + b[k] * a[j])$
 $b[j] \geq b[j + 1]$ optionally $a[i] \leq a[i + 1]$

// for doubles, use INF = 1/.0, div(a,b) = a / b

```

struct Line {
    mutable lli m, c, p;
    bool operator<(const Line& l) const {
        return m < l.m;
    }
    bool operator<(lli x) const {
        return p < x;
    }
    lli operator()(lli x) const {
        return m * x + c;
    }
};

```

```

template <bool MAX>
struct DynamicHull : multiset<Line, less<>> {
    lli div(lli a, lli b) {
        return a / b - ((a ^ b) < 0 && a % b);
    }
}

```

```

bool isect(iterator i, iterator j) {
    if (j == end())
        return i->p = INF, 0;
    if (i->m == j->m)
        i->p = i->c > j->c ? INF : -INF;
    else
        i->p = div(i->c - j->c, j->m - i->m);
    return i->p >= j->p;
}

```

```

void add(lli m, lli c) {
    if (!MAX)
        m = -m, c = -c;
    auto k = insert({m, c, 0}), j = k++, i = j;
    while (isect(j, k))
        k = erase(k);
    if (i != begin() && isect(--i, j))
        isect(i, j = erase(j));
    while ((j = i) != begin() && (--i)->p >= j->p)
        isect(i, erase(j));
}

```

```

lli query(lli x) {
    if (empty())
        return 0LL;
    auto f = *lower_bound(x);
    return MAX ? f(x) : -f(x);
}

```

2.4 Digit dp

Counts the amount of numbers in $[l, r]$ such are divisible by k . (flag *nonzero* is for different lengths)
 It can be reduced to $dp(i, x, small)$, and has to be solved like $f(r) - f(l - 1)$

```

#define state [i][x][small][big][nonzero]
int dp(int i, int x, bool small, bool big, bool nonzero) {
    if (i == sz(r))
        return x % k == 0 && nonzero;
    int& ans = mem state;
    if (done state != timer) {
        done state = timer;
        ans = 0;
        int lo = small ? 0 : l[i] - '0';
        int hi = big ? 9 : r[i] - '0';
        for (y, lo, max(lo, hi) + 1) {
            bool small2 = small | (y > lo);
            bool big2 = big | (y < hi);
            bool nonzero2 = nonzero | (y > 0);
            ans += dp(i + 1, (x * 10 + y) % k, small2, big2, nonzero2);
        }
    }
    return ans;
}

```

2.5 Divide and conquer $\mathcal{O}(k \cdot n^2) \Rightarrow \mathcal{O}(k \cdot n \log n)$

Split the array of size n into k continuous groups. $k \leq n$
 $cost(a, c) + cost(b, d) \leq cost(a, d) + cost(b, c)$ with $a \leq b \leq c \leq d$

```

lli dp[2][N];

void solve(int cut, int l, int r, int optl, int optr) {
    if (r < l)
        return;
    int mid = (l + r) / 2;
    pair<lli, int> best = {INF, -1};
    for (p, optl, min(mid, optr) + 1)
        best = min(best, {dp[~cut & 1][p - 1] + cost(p, mid), p});
    dp[cut & 1][mid] = best.f;
    solve(cut, l, mid - 1, optl, best.s);
    solve(cut, mid + 1, r, best.s, optr);
}

for (i, 1, n + 1)
    dp[1][i] = cost(1, i);
for (cut, 2, k + 1)
    solve(cut, cut, n, cut, n);

```

2.6 Knapsack 01 $\mathcal{O}(n \cdot MaxW)$

```

for (i, 0, n)
    for (int x = MaxW; x >= w[i]; x--)
        umax(dp[x], dp[x - w[i]] + cost[i]);

```

2.7 Knuth $\mathcal{O}(n^3) \Rightarrow \mathcal{O}(n^2)$

$dp[l][r] = \min_{l \leq k \leq r} \{dp[l][k] + dp[k][r]\} + cost(l, r)$

```

lli dp[N][N];
int opt[N][N];

for (len, 1, n + 1)
    for (l, 0, n) {
        int r = l + len - 1;
        if (r > n - 1)
            break;
        if (len <= 2) {
            dp[l][r] = 0;
            opt[l][r] = l;
            continue;
        }
        dp[l][r] = INF;

```

```

        for (k, opt[l][r - 1], opt[l + 1][r] + 1) {
            lli cur = dp[l][k] + dp[k][r] + cost(l, r);
            if (cur < dp[l][r]) {
                dp[l][r] = cur;
                opt[l][r] = k;
            }
        }
    }
}

```

2.8 Matrix exponentiation $\mathcal{O}(n^3 \cdot \log n)$

If TLE change **Mat** to **array<array<T, N>, N>**

```

template <class T>
struct Mat : vector<vector<T>> {
    int n, m;

    Mat(int n, int m) : vector<vector<T>>(n, vector<T>(m)), n
        (n), m(m) {}

    Mat<T> operator*(const Mat<T>& other) {
        assert(m == other.n);
        Mat<T> ans(n, other.m);
        for (k, 0, m)
            for (i, 0, n)
                for (j, 0, other.m)
                    ans[i][j] += (*this)[i][k] * other[k][j];
        return ans;
    }

    Mat<T> pow(lli k) {
        assert(n == m);
        Mat<T> ans(n, n);
        for (i, 0, n)
            ans[i][i] = 1;
        for (; k > 0; k >>= 1) {
            if (k & 1)
                ans = ans * *this;
            *this = *this * *this;
        }
        return ans;
    }
};

```

2.9 SOS dp

```

// N = amount of bits
// dp[mask] = Sum of all dp[x] such that 'x' is a submask
// of 'mask'
for (i, 0, N)
    for (mask, 0, 1 << N)
        if (mask >> i & 1) {
            dp[mask] += dp[mask ^ (1 << i)];
        }

```

2.10 Inverse SOS dp

```

// N = amount of bits
// dp[mask] = Sum of all dp[x] such that 'mask' is a
// submask of 'x'
for (i, 0, N) {
    for (int mask = (1 << N) - 1; mask >= 0; mask--)
        if (mask >> i & 1) {
            dp[mask ^ (1 << i)] += dp[mask];
        }
}

```

2.11 Steiner

```


// Connect special nodes by a minimum spanning tree
// special nodes [0, k)
for (u, k, n)
    for (a, 0, k)
        umin(dp[u][1 << a], dist[u][a]);

```

```

fore (A, 0, (1 << k))
    fore (u, k, n) {
        for (int B = A; B > 0; B = (B - 1) & A)
            umin(dp[u][A], dp[u][B] + dp[u][A ^ B]);
        fore (v, k, n)
            umin(dp[v][A], dp[u][A] + dist[u][v]);
    }

```



3 Geometry

3.1 Geometry

```

const ld EPS = 1e-20;
const ld INF = 1e18;
const ld PI = acos(-1.0);
enum { ON = -1, OUT, IN, OVERLAP };

#define eq(a, b) (abs((a) - (b)) <= +EPS)
#define neq(a, b) (!eq(a, b))
#define geq(a, b) ((a) - (b) >= -EPS)
#define leq(a, b) ((a) - (b) <= +EPS)
#define ge(a, b) ((a) - (b) > +EPS)
#define le(a, b) ((a) - (b) < -EPS)

int sgn(ld a) {
    return (a > EPS) - (a < -EPS);
}

```

3.2 Radial order

```

struct Radial {
    Pt c;
    Radial(Pt c) : c(c) {}

    int cuad(Pt p) const {
        if (p.x > 0 && p.y >= 0)
            return 0;
        if (p.x <= 0 && p.y > 0)
            return 1;
        if (p.x < 0 && p.y <= 0)
            return 2;
        if (p.x >= 0 && p.y < 0)
            return 3;
        return -1;
    }

    bool operator()(Pt a, Pt b) const {
        Pt p = a - c, q = b - c;
        if (cuad(p) == cuad(q))
            return p.y * q.x < p.x * q.y;
        return cuad(p) < cuad(q);
    }
};

```

3.3 Sort along line

```

void sortAlongLine(vector<Pt>& pts, Line l) {
    sort(all(pts), [&](Pt a, Pt b) {
        return a.dot(l.v) < b.dot(l.v);
    });
}

```

4 Point

4.1 Point

```

struct Pt {
    ld x, y;
    explicit Pt(ld x = 0, ld y = 0) : x(x), y(y) {}

    Pt operator+(Pt p) const {
        return Pt(x + p.x, y + p.y);
    }

    Pt operator-(Pt p) const {
        return Pt(x - p.x, y - p.y);
    }

    Pt operator*(ld k) const {
        return Pt(x * k, y * k);
    }

    Pt operator/(ld k) const {
        return Pt(x / k, y / k);
    }

    ld dot(Pt p) const {
        // 0 if vectors are orthogonal
        // - if vectors are pointing in opposite directions
        // + if vectors are pointing in the same direction
        return x * p.x + y * p.y;
    }

    ld cross(Pt p) const {
        // 0 if collinear
        // - if p is to the right of a
        // + if p is to the left of a
        // gives you 2 * area
        return x * p.y - y * p.x;
    }

    ld norm() const {
        return x * x + y * y;
    }

    ld length() const {
        return sqrtl(norm());
    }

    Pt unit() const {
        return (*this) / length();
    }

    ld angle() const {
        ld ang = atan2(y, x);
        return ang + (ang < 0 ? 2 * acos(-1) : 0);
    }

    Pt perp() const {
        return Pt(-y, x);
    }

    Pt rotate(ld angle) const {
        // counter-clockwise rotation in radians
        // degree = radian * 180 / pi
        return Pt(x * cos(angle) - y * sin(angle), x * sin(
            angle) + y * cos(angle));
    }

    int dir(Pt a, Pt b) const {
        // where am I on the directed line ab
        return sgn((a - *this).cross(b - *this));
    }
}

```

```

bool operator<(Pt p) const {
    return eq(x, p.x) ? le(y, p.y) : le(x, p.x);
}

bool operator==(Pt p) const {
    return eq(x, p.x) && eq(y, p.y);
}

bool operator!=(Pt p) const {
    return !(*this == p);
}

friend ostream& operator<<(ostream& os, const Pt& p) {
    return os << "(" << p.x << ", " << p.y << ")";
}

friend istream& operator>>(istream& is, Pt& p) {
    return is >> p.x >> p.y;
}
};

```

4.2 Angle between vectors

```

ld angleBetween(Pt a, Pt b) {
    ld x = a.dot(b) / a.length() / b.length();
    return acosl(max(-1.0, min(1.0, x)));
}

```

4.3 Closest pair of points $\mathcal{O}(n \cdot \log n)$

```

pair<Pt, Pt> closestPairOfPoints(vector<Pt>& pts) {
    sort(all(pts), [&](Pt a, Pt b) {
        return le(a.y, b.y);
    });
    set<Pt> st;
    ld ans = INF;
    Pt p, q;
    int pos = 0;
    for (i, 0, sz(pts)) {
        while (pos < i && geq(pts[i].y - pts[pos].y, ans))
            st.erase(pts[pos++]);
        auto lo = st.lower_bound(Pt(pts[i].x - ans - EPS, -INF));
        auto hi = st.upper_bound(Pt(pts[i].x + ans + EPS, -INF));
        for (auto it = lo; it != hi; ++it) {
            ld d = (pts[i] - *it).length();
            if (le(d, ans))
                ans = d, p = pts[i], q = *it;
        }
        st.insert(pts[i]);
    }
    return {p, q};
}

```

4.4 KD Tree

Returns nearest point, to avoid self-nearest add an id to the point

```

struct Pt {
    // Geometry point mostly
    ld operator[](int i) const {
        return i == 0 ? x : y;
    }
};

struct KDTree {
    Pt p;
    int k;
    KDTree *left, *right;

    template <class Iter>

```

```

KDTree(Iter l, Iter r, int k = 0) : k(k), left(0), right(
    0) {
    int n = r - l;
    if (n == 1) {
        p = *l;
        return;
    }
    nth_element(l, l + n / 2, r, [&](Pt a, Pt b) {
        return a[k] < b[k];
    });
    p = *(l + n / 2);
    left = new KDTree(l, l + n / 2, k ^ 1);
    right = new KDTree(l + n / 2, r, k ^ 1);
}


```

```

pair<ld, Pt> nearest(Pt x) {
    if (!left && !right)
        return {(p - x).norm(), p};
    vector<KDTree*> go = {left, right};
    auto delta = x[k] - p[k];
    if (delta > 0)
        swap(go[0], go[1]);
    auto best = go[0]->nearest(x);
    if (best.f > delta * delta)
        best = min(best, go[1]->nearest(x));
    return best;
}
};

```

5 Lines and segments



5.1 Line

```

struct Line {
    Pt a, b, v;

    Line() {}
    Line(Pt a, Pt b) : a(a), b(b), v((b - a).unit()) {}

    bool contains(Pt p) {
        return eq((p - a).cross(b - a), 0);
    }

    int intersects(Line l) {
        if (eq(v.cross(l.v), 0))
            return eq((l.a - a).cross(v), 0) ? 1e9 : 0;
        return 1;
    }

    int intersects(Seg s) {
        if (eq(v.cross(s.v), 0))
            return eq((s.a - a).cross(v), 0) ? 1e9 : 0;
        return a.dir(b, s.a) != a.dir(b, s.b);
    }

    template <class Line>
    Pt intersection(Line l) { // can be a segment too
        return a + v * ((l.a - a).cross(l.v) / v.cross(l.v));
    }
}

```

```

Pt projection(Pt p) {
    return a + v * proj(p - a, v);
}

Pt reflection(Pt p) {
    return a * 2 - p + v * 2 * proj(p - a, v);
}
};

```

5.2 Segment

```

struct Seg {
    Pt a, b, v;

    Seg() {}
    Seg(Pt a, Pt b) : a(a), b(b), v(b - a) {}

    bool contains(Pt p) {
        return eq(v.cross(p - a), 0) && leq((a - p).dot(b - p),
            0);
    }

    int intersects(Seg s) {
        int d1 = a.dir(b, s.a), d2 = a.dir(b, s.b);
        if (d1 != d2)
            return s.a.dir(s.b, a) != s.a.dir(s.b, b);
        return d1 == 0 && (contains(s.a) || contains(s.b) || s.
            contains(a) || s.contains(b)) ? 1e9 : 0;
    }

    template <class Seg>
    Pt intersection(Seg s) { // can be a line too
        return a + v * ((s.a - a).cross(s.v) / v.cross(s.v));
    }
};

```

5.3 Projection

```

ld proj(Pt a, Pt b) {
    return a.dot(b) / b.length();
}

```

5.4 Distance point line

```

ld distance(Pt p, Line l) {
    Pt q = l.projection(p);
    return (p - q).length();
}

```

5.5 Distance point segment

```

ld distance(Pt p, Seg s) {
    if (le((p - s.a).dot(s.b - s.a), 0))
        return (p - s.a).length();
    if (le((p - s.b).dot(s.a - s.b), 0))
        return (p - s.b).length();
    return abs((s.a - p).cross(s.b - p) / (s.b - s.a).length
        ());
}

```


5.6 Distance segment segment

```

ld distance(Seg a, Seg b) {
    if (a.intersects(b))
        return 0.L;
    return min({distance(a.a, b), distance(a.b, b), distance(
        b.a, a), distance(b.b, a)});
}

```

6 Circle



6.1 Circle

```

struct Cir : Pt {
    ld r;
    Cir() {}
    Cir(ld x, ld y, ld r) : Pt(x, y), r(r) {}
    Cir(Pt p, ld r) : Pt(p), r(r) {}

    int inside(Cir c) {
        ld l = c.r - r - (*this - c).length();
        return ge(l, 0) ? IN : eq(l, 0) ? ON : OVERLAP;
    }

    int outside(Cir c) {
        ld l = (*this - c).length() - r - c.r;
        return ge(l, 0) ? OUT : eq(l, 0) ? ON : OVERLAP;
    }

    int contains(Pt p) {
        ld l = (p - *this).length() - r;
        return le(l, 0) ? IN : eq(l, 0) ? ON : OUT;
    }

    Pt projection(Pt p) {
        return *this + (p - *this).unit() * r;
    }

    vector<Pt> tangency(Pt p) {
        // point outside the circle
        Pt v = (p - *this).unit() * r;
        ld d2 = (p - *this).norm(), d = sqrt(d2);
        if (leq(d, 0))
            return {}; // on circle, no tangent
        Pt v1 = v * (r / d), v2 = v.perp() * (sqrt(d2 - r * r)
            / d);
        return {*this + v1 - v2, *this + v1 + v2};
    }

    vector<Pt> intersection(Cir c) {
        ld d = (c - *this).length();
        if (eq(d, 0) || ge(d, r + c.r) || le(d, abs(r - c.r)))
            return {}; // circles don't intersect
        Pt v = (c - *this).unit();
        ld a = (r * r + d * d - c.r * c.r) / (2 * d);
        Pt p = *this + v * a;
        if (eq(d, r + c.r) || eq(d, abs(r - c.r)))
            return {p}; // circles touch at one point
        ld h = sqrt(r * r - a * a);
        Pt q = v.perp() * h;
        return {p - q, p + q}; // circles intersects twice
    }

    template <class Line>
    vector<Pt> intersection(Line l) {
        // for a segment you need to check that the point lies
        // on the segment
        ld h2 = r * r - l.v.cross(*this - l.a) * l.v.cross(*
            this - l.a) / l.v.norm();
    }
}

```

```

Pt p = l.a + l.v * l.v.dot(*this - l.a) / l.v.norm();
if (eq(h2, 0))
    return {p}; // line tangent to circle
if (le(h2, 0))
    return {}; // no intersection
Pt q = l.v.unit() * sqrt(h2);
return {p - q, p + q}; // two points of intersection (chord)
}

Cir(Pt a, Pt b, Pt c) {
    // find circle that passes through points a, b, c
    Pt mab = (a + b) / 2, mcb = (b + c) / 2;
    Seg ab(mab, mab + (b - a).perp());
    Seg cb(mcb, mcb + (b - c).perp());
    Pt o = ab.intersection(cb);
    *this = Cir(o, (o - a).length());
}
};

```

6.2 Distance point circle

```

ld distance(Pt p, Cir c) {
    return max(0.L, (p - c).length() - c.r);
}

```

6.3 Common area circle circle

```

ld commonArea(Cir a, Cir b) {
    if (le(a.r, b.r))
        swap(a, b);
    ld d = (a - b).length();
    if (leq(d + b.r, a.r))
        return b.r * b.r * PI;
    if (geq(d, a.r + b.r))
        return 0.0;
    auto angle = [&](ld x, ld y, ld z) {
        return acos((x * x + y * y - z * z) / (2 * x * y));
    };
    auto cut = [&](ld x, ld r) {
        return (x - sin(x)) * r * r / 2;
    };
    ld a1 = angle(d, a.r, b.r), a2 = angle(d, b.r, a.r);
    return cut(a1 * 2, a.r) + cut(a2 * 2, b.r);
}

```

6.4 Minimum enclosing circle $\mathcal{O}(n)$ wow!!

```

Cir minEnclosing(vector<Pt>& pts) { // a bunch of points
    shuffle(all(pts), rng);
    Cir c(0, 0, 0);
    for (i, 0, sz(pts))
        if (!c.contains(pts[i])) {
            c = Cir(pts[i], 0);
            for (j, 0, i)
                if (!c.contains(pts[j])) {
                    c = Cir((pts[i] + pts[j]) / 2, (pts[i] - pts[j]).length() / 2);
                    for (k, 0, j)
                        if (!c.contains(pts[k]))
                            c = Cir(pts[i], pts[j], pts[k]);
                }
        }
    return c;
}

```

7 Polygon

7.1 Area polygon

```

ld area(const vector<Pt>& pts) {
    ld sum = 0;
    for (i, 0, sz(pts))
        sum += pts[i].cross(pts[(i + 1) % sz(pts)]);
    return abs(sum / 2);
}

```

7.2 Perimeter

```

ld perimeter(const vector<Pt>& pts) {
    ld sum = 0;
    for (i, 0, sz(pts))
        sum += (pts[(i + 1) % sz(pts)] - pts[i]).length();
    return sum;
}

```

7.3 Cut polygon line

```

vector<Pt> cut(const vector<Pt>& pts, Line l) {
    vector<Pt> ans;
    int n = sz(pts);
    for (i, 0, n) {
        int j = (i + 1) % n;
        if (geq(l.v.cross(pts[i] - l.a), 0)) // left
            ans.pb(pts[i]);
        Seg s(pts[i], pts[j]);
        if (l.intersects(s) == 1) {
            Pt p = l.intersection(s);
            if (p != pts[i] && p != pts[j])
                ans.pb(p);
        }
    }
    return ans;
}

```

7.4 Common area circle polygon $\mathcal{O}(n)$

```

ld commonArea(Cir c, const vector<Pt>& poly) {
    auto arg = [&](Pt p, Pt q) {
        return atan2(p.cross(q), p.dot(q));
    };
    auto tri = [&](Pt p, Pt q) {
        Pt d = q - p;
        ld a = d.dot(p) / d.norm(), b = (p.norm() - c.r * c.r) / d.norm();
        ld det = a * a - b;
        if (leq(det, 0))
            return arg(p, q) * c.r * c.r;
        ld s = max(0.L, -a - sqrt(det)), t = min(1.L, -a + sqrt(det));
        if (t < 0 || 1 <= s)
            return arg(p, q) * c.r * c.r;
        Pt u = p + d * s, v = p + d * t;
        return u.cross(v) + (arg(p, u) + arg(v, q)) * c.r * c.r;
    };
    ld sum = 0;
    for (i, 0, sz(poly))
        sum += tri(poly[i] - c, poly[(i + 1) % sz(poly)] - c);
    return abs(sum / 2);
}

```

7.5 Point in polygon

```

int contains(const vector<Pt>& pts, Pt p) {
    int rays = 0, n = sz(pts);
    for (i, 0, n) {
        Pt a = pts[i], b = pts[(i + 1) % n];
        if (ge(a.y, b.y))
            swap(a, b);
        if (Seg(a, b).contains(p))
            return ON;
        rays ^= (leq(a.y, p.y) && le(p.y, b.y) && p.dir(a, b) > 0);
    }
    return rays & 1 ? IN : OUT;
}

```

7.6 Convex hull $\mathcal{O}(n \log n)$

```

vector<Pt> convexHull(vector<Pt> pts) {
    vector<Pt> hull;
    sort(all(pts), [&](Pt a, Pt b) {
        return a.x == b.x ? a.y < b.y : a.x < b.x;
    });
}

```

```

});
pts.erase(unique(all(pts)), pts.end());
for (i, 0, sz(pts)) {
    while (sz(hull) >= 2 && hull.back().dir(pts[i], hull[sz(hull) - 2]) < 0)
        hull.pop_back();
    hull.pb(pts[i]);
}
hull.pop_back();
int k = sz(hull);
for (i, sz(pts), 0) {
    while (sz(hull) >= k + 2 && hull.back().dir(pts[i], hull[sz(hull) - 2]) < 0)
        hull.pop_back();
    hull.pb(pts[i]);
}
hull.pop_back();
return hull;
}

```

7.7 Is convex

```

bool isConvex(const vector<Pt>& pts) {
    int n = sz(pts);
    bool pos = 0, neg = 0;
    for (i, 0, n) {
        Pt a = pts[(i + 1) % n] - pts[i];
        Pt b = pts[(i + 2) % n] - pts[(i + 1) % n];
        int dir = sgn(a.cross(b));
        if (dir > 0)
            pos = 1;
        if (dir < 0)
            neg = 1;
    }
    return !(pos && neg);
}

```

7.8 Point in convex polygon $\mathcal{O}(\log n)$

```

bool contains(const vector<Pt>& a, Pt p) {
    int lo = 1, hi = sz(a) - 1;
    if (a[0].dir(a[lo], a[hi]) > 0)
        swap(lo, hi);
    if (p.dir(a[0], a[lo]) >= 0 || p.dir(a[0], a[hi]) <= 0)
        return false;
    while (abs(lo - hi) > 1) {
        int mid = (lo + hi) >> 1;
        (p.dir(a[0], a[mid]) > 0 ? hi : lo) = mid;
    }
    return p.dir(a[lo], a[hi]) < 0;
}

```

8 Graphs

8.1 Cycle

```

bool cycle(int u) {
    vis[u] = 1;
    for (int v : graph[u]) {
        if (vis[v] == 1)
            return true;
        if (!vis[v] && cycle(v))
            return true;
    }
    vis[u] = 2;
    return false;
}

```

8.2 Cutpoints and bridges

```

int tin[N], fup[N], timer = 0;

void weakness(int u, int p = -1) {
    tin[u] = fup[u] = ++timer;
    int children = 0;
    for (int v : graph[u])

```

```

if (v != p) {
    if (!tin[v]) {
        ++children;
        weakness(v, u);
        fup[u] = min(fup[u], fup[v]);
        if (fup[v] >= tin[u] && !(p == -1 && children < 2))
            // u is a cutpoint
            if (fup[v] > tin[u]) // bridge u -> v
    }
    fup[u] = min(fup[u], tin[v]);
}
}

```

8.3 Tarjan

```

int tin[N], fup[N];
bitset<N> still;
stack<int> stk;
int timer = 0;

void tarjan(int u) {
    tin[u] = fup[u] = ++timer;
    still[u] = true;
    stk.push(u);
    for (auto& v : graph[u]) {
        if (!tin[v])
            tarjan(v);
        if (still[v])
            fup[u] = min(fup[u], fup[v]);
    }
    if (fup[u] == tin[u]) {
        int v;
        do {
            v = stk.top();
            stk.pop();
            still[v] = false;
            // u and v are in the same scc
        } while (v != u);
    }
}

```

8.4 Isomorphism

```

lli dp[N], h[N];

lli f(lli x) {
    // K * n <= 9e18
    static uniform_int_distribution<lli> uid(1, K);
    if (!mp.count(x))
        mp[x] = uid(rng);
    return mp[x];
}

```

```

lli hsh(int u, int p = -1) {
    dp[u] = h[u] = 0;
    for (auto& v : graph[u]) {
        if (v == p)
            continue;
        dp[u] += hsh(v, u);
    }
    return h[u] = f(dp[u]);
}

```

8.5 Two sat $\mathcal{O}(2 \cdot n)$

v: true, ~v: false

implies(a, b): if a then b

a	b	a => b
F	F	T
T	T	T
F	T	T
T	F	F


```

    setVal(a): set a = true
    setVal(~a): set a = false

    struct TwoSat {
        int n;
        vector<vector<int>> imp;

        TwoSat(int k) : n(k + 1), imp(2 * n) {} // 1-indexed

        void either(int a, int b) { // a || b
            a = max(2 * a, -1 - 2 * a);
            b = max(2 * b, -1 - 2 * b);
            imp[a ^ 1].pb(b);
            imp[b ^ 1].pb(a);
        }

        void implies(int a, int b) {
            either(~a, b);
        }

        void setVal(int a) {
            either(a, a);
        }

        optional<vector<int>> solve() {
            int k = sz(imp);
            vector<int> s, b, id(sz(imp));
            function<void(int)> dfs = [&](int u) {
                b.pb(id[u] = sz(s)), s.pb(u);
                for (int v : imp[u]) {
                    if (!id[v])
                        dfs(v);
                    else
                        while (id[v] < b.back())
                            b.pop_back();
                }
                if (id[u] == b.back())
                    for (b.pop_back(), ++k; id[u] < sz(s); s.pop_back())
                        id[s.back()] = k;
            };
            vector<int> val(n);
            for (u, 0, sz(imp))
                if (!id[u])
                    dfs(u);
            for (u, 0, n) {
                int x = 2 * u;
                if (id[x] == id[x ^ 1])
                    return nullopt;
                val[u] = id[x] < id[x ^ 1];
            }
            return optional(val);
        }
    };

```

8.6 LCA

```

const int LogN = 1 + __lg(N);
int par[LogN][N], depth[N];

void dfs(int u, int par[]) {
    for (auto& v : graph[u])
        if (v != par[u]) {
            par[v] = u;
            depth[v] = depth[u] + 1;
            dfs(v, par);
        }
}

```

```

int lca(int u, int v) {
    if (depth[u] > depth[v])
        swap(u, v);
    for (k, LogN, 0)
        if (depth[v] - depth[u] >= (1 << k))
            v = par[k][v];
    if (u == v)
        return u;
    for (k, LogN, 0)
        if (par[k][v] != par[k][u])
            u = par[k][u], v = par[k][v];
    return par[0][u];
}

int dist(int u, int v) {
    return depth[u] + depth[v] - 2 * depth[lca(u, v)];
}

void init(int r) {
    dfs(r, par[0]);
    for (k, 1, LogN)
        for (u, 1, n + 1)
            par[k][u] = par[k - 1][par[k - 1][u]];
}

```

8.7 Virtual tree $\mathcal{O}(n \cdot \log n)$ "lca tree"

```

vector<int> virt[N];

int virtualTree(vector<int>& ver) {
    auto byDfs = [&](int u, int v) {
        return tin[u] < tin[v];
    };
    sort(all(ver), byDfs);
    for (i, sz(ver), 1)
        ver.pb(lca(ver[i - 1], ver[i]));
    sort(all(ver), byDfs);
    ver.erase(unique(all(ver)), ver.end());
    for (int u : ver)
        virt[u].clear();
    for (i, 1, sz(ver))
        virt[lca(ver[i - 1], ver[i])].pb(ver[i]);
    return ver[0];
}

```

8.8 Dynamic connectivity

```

struct DynamicConnectivity {
    struct Query {
        int op, u, v, at;
    };

    Dsu dsu; // with rollback
    vector<Query> queries;
    map<ii, int> mp;
    int timer = -1;

    DynamicConnectivity(int n = 0) : dsu(n) {}

    void add(int u, int v) {
        mp[minmax(u, v)] = ++timer;
        queries.pb({'+', u, v, INT_MAX});
    }

    void rem(int u, int v) {
        int in = mp[minmax(u, v)];
        queries.pb({'-', u, v, in});
        queries[in].at = ++timer;
        mp.erase(minmax(u, v));
    }

    void query() {
        queries.push_back({'?', -1, -1, ++timer});
    }
}

```



```

}

void solve(int l, int r) {
    if (l == r) {
        if (queries[l].op == '?') // solve the query here
            return;
    }
    int m = (l + r) >> 1;
    int before = sz(dsu.mem);
    for (int i = m + 1; i <= r; i++) {
        Query& q = queries[i];
        if (q.op == '-' && q.at < l)
            dsu.unite(q.u, q.v);
    }
    solve(l, m);
    while (sz(dsu.mem) > before)
        dsu.rollback();
    for (int i = l; i <= m; i++) {
        Query& q = queries[i];
        if (q.op == '+' && q.at > r)
            dsu.unite(q.u, q.v);
    }
    solve(m + 1, r);
    while (sz(dsu.mem) > before)
        dsu.rollback();
}
};

```

8.9 Euler-tour + HLD + LCA $\mathcal{O}(n \cdot \log n)$

Solves subtrees and paths problems

```

int par[N], nxt[N], depth[N], sz[N];
int tin[N], tout[N], who[N], timer = 0;

int dfs(int u) {
    sz[u] = 1;
    for (auto& v : graph[u])
        if (v != par[u]) {
            par[v] = u;
            depth[v] = depth[u] + 1;
            sz[u] += dfs(v);
            if (graph[u][0] == par[u] || sz[v] > sz[graph[u][0]])
                swap(v, graph[u][0]);
        }
    return sz[u];
}

void hld(int u) {
    tin[u] = ++timer, who[timer] = u;
    for (auto& v : graph[u])
        if (v != par[u]) {
            nxt[v] = (v == graph[u][0] ? nxt[u] : v);
            hld(v);
        }
    tout[u] = timer;
}

template <bool OverEdges = 0, class F>
void processPath(int u, int v, F f) {
    for (; nxt[u] != nxt[v]; u = par[nxt[u]]) {
        if (depth[nxt[u]] < depth[nxt[v]])
            swap(u, v);
        f(tin[nxt[u]], tin[u]);
    }
    if (depth[u] < depth[v])
        swap(u, v);
    f(tin[v] + OverEdges, tin[u]);
}

void updatePath(int u, int v, lli z) {

```

```

    processPath(u, v, [&](int l, int r) {
        tree->update(l, r, z);
    });
}

void updateSubtree(int u, lli z) {
    tree->update(tin[u], tout[u], z);
}

lli queryPath(int u, int v) {
    lli sum = 0;
    processPath(u, v, [&](int l, int r) {
        sum += tree->query(l, r);
    });
    return sum;
}

lli querySubtree(int u) {
    return tree->query(tin[u], tout[u]);
}

int lca(int u, int v) {
    int last = -1;
    processPath(u, v, [&](int l, int r) {
        last = who[l];
    });
    return last;
}

```

8.10 Centroid $\mathcal{O}(n \cdot \log n)$

Solves "all pairs of nodes" problems

```

int cdp[N], sz[N];
bitset<N> rem;

int dfsz(int u, int p = -1) {
    sz[u] = 1;
    for (int v : graph[u])
        if (v != p && !rem[v])
            sz[u] += dfsz(v, u);
    return sz[u];
}

int centroid(int u, int size, int p = -1) {
    for (int v : graph[u])
        if (v != p && !rem[v] && 2 * sz[v] > size)
            return centroid(v, size, u);
    return u;
}

void solve(int u, int p = -1) {
    cdp[u = centroid(u, dfsz(u))] = p;
    rem[u] = true;
    for (int v : graph[u])
        if (!rem[v])
            solve(v, u);
}

```

8.11 Guni Paths

// How many simple paths of distance K exists.

```

vector<int> graph[N];
int cnt[C]; // cnt[x] store the amount of paths with length
            x
int sz[N];
int depth[N]; // depth[u] <- distance from root to u
int cur = -1; // <- Current subtree node
int K;
lli paths = 0;

```

```

int guni(int u, int p = 0, int len = 0) {
    sz[u] = 1;
    depth[u] = len;
    for (auto& v : graph[u])
        if (v != p) {
            sz[u] += guni(v, u, len + 1);
            if (sz[v] > sz[graph[u][0]] || p == graph[u][0])
                swap(v, graph[u][0]);
        }
    return sz[u];
}

void f(int u) {
    // depth[u] + need == K + 2 * depth[cur]
    // need = K + 2 * depth[cur] - depth[u]
    int need = K + 2 * depth[cur] - depth[u];
    if (need >= 0) {
        paths += cnt[need];
    }
}

void compute(int u, int p, int x, bool op) {
    if (op) {
        f(u);
    } else {
        cnt[depth[u]] += x;
    }
    for (auto& v : graph[u])
        if (v != p)
            compute(v, u, x, op);
}

void solve(int u, int p, bool keep = 0) {
    for (i, sz(graph[u]), 0)
        if (graph[u][i] != p)
            solve(graph[u][i], u, !i);

    cur = u;
    for (int i = 1; i < sz(graph[u]); i++) { // <- don't
        change it with a fore
        int v = graph[u][i];
        if (v != p) {
            // Check paths from a node in the subtree of v to any
            // other in the data structure.
            compute(v, u, +1, 1);

            // Update the data structure with subtree of v.
            compute(v, u, +1, 0);
        }
    }

    { // paths from node u to any other node.
        f(u);
        cnt[depth[u]]++;
    }

    if (!keep)
        compute(u, p, -1, 0); // remove
}

```

8.12 Guni $\mathcal{O}(n \cdot \log n)$

Solve subtrees problems

```

int cnt[C], color[N];
int sz[N];

int guni(int u, int p = -1) {
    sz[u] = 1;
    for (auto& v : graph[u])

```

```

        if (v != p) {
            sz[u] += guni(v, u);
            if (sz[v] > sz[graph[u][0]] || p == graph[u][0])
                swap(v, graph[u][0]);
        }
    }
    return sz[u];
}

void update(int u, int p, int add, bool skip) {
    cnt[color[u]] += add;
    for (i, skip, sz(graph[u]))
        if (graph[u][i] != p)
            update(graph[u][i], u, add, 0);
}

void solve(int u, int p = -1, bool keep = 0) {
    for (i, sz(graph[u]), 0)
        if (graph[u][i] != p)
            solve(graph[u][i], u, !i);
    update(u, p, +1, 1); // add
    // now cnt[i] has how many times the color i appears in
    // the subtree of u
    if (!keep)
        update(u, p, -1, 0); // remove
}

```

8.13 Link-Cut tree $\mathcal{O}(n \cdot \log n)$

Solves dynamic trees problems, can handle subtrees and paths maybe with a high constant

```

struct LinkCut {
    struct Node {
        Node *left{0}, *right{0}, *par{0};
        bool rev = 0;
        int sz = 1;
        int sub = 0, vsub = 0; // subtree
        lli path = 0; // path
        lli self = 0; // node info
    };

    void push() {
        if (rev) {
            swap(left, right);
            if (left)
                left->rev ^= 1;
            if (right)
                right->rev ^= 1;
            rev = 0;
        }
    }

    void pull() {
        sz = 1;
        sub = vsub + self;
        path = self;
        if (left) {
            sz += left->sz;
            sub += left->sub;
            path += left->path;
        }
        if (right) {
            sz += right->sz;
            sub += right->sub;
            path += right->path;
        }
    }

    void addVsub(Node* v, lli add) {
        if (v)
            vsub += 1LL * add * v->sub;
    }
}

```

```

    }
};

vector<Node> a;

LinkCut(int n = 1) : a(n) {}

void splay(Node* u) {
    auto assign = [&](Node* u, Node* v, int d) {
        if (v)
            v->par = u;
        if (d >= 0)
            (d == 0 ? u->left : u->right) = v;
    };
    auto dir = [&](Node* u) {
        if (!u->par)
            return -1;
        return u->par->left == u ? 0 : (u->par->right == u ?
            1 : -1);
    };
    auto rotate = [&](Node* u) {
        Node *p = u->par, *g = p->par;
        int d = dir(u);
        assign(p, d ? u->left : u->right, d);
        assign(g, u, dir(p));
        assign(u, p, !d);
        p->pull(), u->pull();
    };
    while (~dir(u)) {
        Node *p = u->par, *g = p->par;
        if (~dir(p))
            g->push();
        p->push(), u->push();
        if (~dir(p))
            rotate(dir(p) == dir(u) ? p : u);
        rotate(u);
    }
    u->push(), u->pull();
}

void access(int u) {
    Node* last = NULL;
    for (Node* x = &a[u]; x; last = x, x = x->par) {
        splay(x);
        x->addVsub(x->right, +1);
        x->right = last;
        x->addVsub(x->right, -1);
        x->pull();
    }
    splay(&a[u]);
}

void reroot(int u) {
    access(u);
    a[u].rev ^= 1;
}

void link(int u, int v) {
    reroot(v), access(u);
    a[u].addVsub(v, +1);
    a[v].par = &a[u];
    a[u].pull();
}

void cut(int u, int v) {
    reroot(v), access(u);
    a[u].left = a[v].par = NULL;
    a[u].pull();
}

```

```

int lca(int u, int v) {
    if (u == v)
        return u;
    access(u), access(v);
    if (!a[u].par)
        return -1;
    return splay(&a[u]), a[u].par ? -1 : u;
}

int depth(int u) {
    access(u);
    return a[u].left ? a[u].left->sz : 0;
}

// get k-th parent on path to root
int ancestor(int u, int k) {
    k = depth(u) - k;
    assert(k >= 0);
    for (;;) {
        a[u].push();
        int sz = a[u].left->sz;
        if (sz == k)
            return access(u), u;
        if (sz < k)
            k -= sz + 1, u = u->ch[1];
        else
            u = u->ch[0];
    }
    assert(0);
}

lli queryPath(int u, int v) {
    reroot(u), access(v);
    return a[v].path;
}

lli querySubtree(int u, int x) {
    // query subtree of u, x is outside
    reroot(x), access(u);
    return a[u].vsub + a[u].self;
}

void update(int u, lli val) {
    access(u);
    a[u].self = val;
    a[u].pull();
}

Node& operator[](int u) {
    return a[u];
}
};

```

9 Flows

9.1 Blossom $\mathcal{O}(n^3)$

Maximum matching on non-bipartite non-weighted graphs

```

struct Blossom {
    int n, m;
    vector<int> mate, p, d, bl;
    vector<vector<int>> b, g;

    Blossom(int n) : n(n), m(n + n / 2), mate(n, -1), b(m), p
        (m), d(m), bl(m), g(m, vector<int>(m, -1)) {}

    void add(int u, int v) { // 0-indexed!!!!
        g[u][v] = u;
        g[v][u] = v;
    }
}

```

```

void match(int u, int v) {
    g[u][v] = g[v][u] = -1;
    mate[u] = v;
    mate[v] = u;
}

vector<int> trace(int x) {
    vector<int> vx;
    while (true) {
        while (bl[x] != x)
            x = bl[x];
        if (!vx.empty() && vx.back() == x)
            break;
        vx.pb(x);
        x = p[x];
    }
    return vx;
}

void contract(int c, int x, int y, vector<int>& vx,
              vector<int>& vy) {
    b[c].clear();
    int r = vx.back();
    while (!vx.empty() && !vy.empty() && vx.back() == vy.
           back()) {
        r = vx.back();
        vx.pop_back();
        vy.pop_back();
    }
    b[c].pb(r);
    b[c].insert(b[c].end(), vx.rbegin(), vx.rend());
    b[c].insert(b[c].end(), vy.begin(), vy.end());
    for (i, 0, c + 1)
        g[c][i] = g[i][c] = -1;
    for (int z : b[c]) {
        bl[z] = c;
        for (i, 0, c) {
            if (g[z][i] != -1) {
                g[c][i] = z;
                g[i][c] = g[i][z];
            }
        }
    }
}

vector<int> lift(vector<int>& vx) {
    vector<int> A;
    while (sz(vx) >= 2) {
        int z = vx.back();
        vx.pop_back();
        if (z < n) {
            A.pb(z);
            continue;
        }
        int w = vx.back();
        int i = (sz(A) % 2 == 0 ? find(all(b[z]), g[z][w]) -
                b[z].begin() : 0);
        int j = (sz(A) % 2 == 1 ? find(all(b[z]), g[z][A.back()]) -
                b[z].begin() : 0);
        int k = sz(b[z]);
        int dif = (sz(A) % 2 == 0 ? i % 2 == 1 : j % 2 == 0)
                  ? 1 : k - 1;
        while (i != j) {
            vx.pb(b[z][i]);
            i = (i + dif) % k;
        }
        vx.pb(b[z][i]);
    }
    return A;
}

```

```

}

int solve() {
    for (int ans = 0;; ans++) {
        fill(d.begin(), d.end(), 0);
        queue<int> Q;
        for (i, 0, m)
            bl[i] = i;
        for (i, 0, n) {
            if (mate[i] == -1) {
                Q.push(i);
                p[i] = i;
                d[i] = 1;
            }
        }
        int c = n;
        bool aug = false;
        while (!Q.empty() && !aug) {
            int x = Q.front();
            Q.pop();
            if (bl[x] != x)
                continue;
            for (y, 0, c) {
                if (bl[y] == y && g[x][y] != -1) {
                    if (d[y] == 0) {
                        p[y] = x;
                        d[y] = 2;
                        p[mate[y]] = y;
                        d[mate[y]] = 1;
                        Q.push(mate[y]);
                    } else if (d[y] == 1) {
                        vector<int> vx = trace(x);
                        vector<int> vy = trace(y);
                        if (vx.back() == vy.back()) {
                            contract(c, x, y, vx, vy);
                            Q.push(c);
                            p[c] = p[b[c][0]];
                            d[c] = 1;
                            c++;
                        } else {
                            aug = true;
                            vx.insert(vx.begin(), y);
                            vy.insert(vy.begin(), x);
                            vector<int> A = lift(vx);
                            vector<int> B = lift(vy);
                            A.insert(A.end(), B.rbegin(), B.rend());
                            for (int i = 0; i < sz(A); i += 2) {
                                match(A[i], A[i + 1]);
                                if (i + 2 < sz(A))
                                    add(A[i + 1], A[i + 2]);
                            }
                        }
                    }
                }
            }
            break;
        }
        if (!aug)
            return ans;
    }
}

```

9.2 Hopcroft Karp $\mathcal{O}(e\sqrt{v})$

```

struct HopcroftKarp {
    int n, m;
    vector<vector<int>> graph;
    vector<int> dist, match;
}

```

```

HopcroftKarp(int k) : n(k + 1), graph(n), dist(n), match(
    n, 0) {} // 1-indexed!!

void add(int u, int v) {
    graph[u].pb(v), graph[v].pb(u);
}

bool bfs() {
    queue<int> qu;
    fill(all(dist), -1);
    for (u, 1, n)
        if (!match[u])
            dist[u] = 0, qu.push(u);
    while (!qu.empty()) {
        int u = qu.front();
        qu.pop();
        for (int v : graph[u])
            if (dist[match[v]] == -1) {
                dist[match[v]] = dist[u] + 1;
                if (match[v])
                    qu.push(match[v]);
            }
    }
    return dist[0] != -1;
}

bool dfs(int u) {
    for (int v : graph[u])
        if (!match[v] || (dist[u] + 1 == dist[match[v]] &&
            dfs(match[v]))) {
            match[u] = v, match[v] = u;
            return 1;
        }
    dist[u] = 1 << 30;
    return 0;
}

int maxMatching() {
    int tot = 0;
    while (bfs())
        for (u, 1, n)
            tot += match[u] ? 0 : dfs(u);
    return tot;
}
};

```

9.3 Hungarian $\mathcal{O}(n^2 \cdot m)$

n jobs, m people for max assignment

```

template <class C>
pair<C, vector<int>> Hungarian(vector<vector<C>>& a) { //
    max assignment
    int n = sz(a), m = sz(a[0]), p, q, j, k; // n <= m
    vector<C> fx(n, numeric_limits<C>::min()), fy(m, 0);
    vector<int> x(n, -1), y(m, -1);
    for (i, 0, n)
        for (j, 0, m)
            fx[i] = max(fx[i], a[i][j]);
    for (i, 0, n) {
        vector<int> t(m, -1), s(n + 1, i);
        for (p = q = 0; p <= q && x[i] < 0; p++)
            for (k = s[p], j = 0; j < m && x[i] < 0; j++)
                if (abs(fx[k] + fy[j] - a[k][j]) < EPS && t[j] < 0)
                    {
                        s[++q] = y[j], t[j] = k;
                        if (s[q] < 0)
                            for (p = j; p >= 0; j = p)
                                y[j] = k = t[j], p = x[k], x[k] = j;
                    }
        if (x[i] < 0) {

```

```

            C d = numeric_limits<C>::max();
            for (k, 0, q + 1)
                for (j, 0, m)
                    if (t[j] < 0)
                        d = min(d, fx[s[k]] + fy[j] - a[s[k]][j]);
            for (j, 0, m)
                fy[j] += (t[j] < 0 ? 0 : d);
            for (k, 0, q + 1)
                fx[s[k]] -= d;
            i--;
        }
    }
    C cost = 0;
    for (i, 0, n)
        cost += a[i][x[i]];
    return make_pair(cost, x);
}

```

9.4 Dinic $\mathcal{O}(\min(e \cdot flow, v^2 \cdot e))$

```

template <class F>
struct Dinic {
    struct Edge {
        int v, inv;
        F cap, flow;
        Edge(int v, F cap, int inv) : v(v), cap(cap), flow(0),
            inv(inv) {}
    };

    F EPS = (F)1e-9;
    int s, t, n;
    vector<vector<Edge>> graph;
    vector<int> dist, ptr;

    Dinic(int n) : n(n), graph(n), dist(n), ptr(n), s(n - 2),
        t(n - 1) {}

    void add(int u, int v, F cap) {
        graph[u].pb(Edge(v, cap, sz(graph[v])));
        graph[v].pb(Edge(u, 0, sz(graph[u]) - 1));
    }

    bool bfs() {
        fill(all(dist), -1);
        queue<int> qu({s});
        dist[s] = 0;
        while (sz(qu) && dist[t] == -1) {
            int u = qu.front();
            qu.pop();
            for (Edge& e : graph[u])
                if (dist[e.v] == -1)
                    if (e.cap - e.flow > EPS) {
                        dist[e.v] = dist[u] + 1;
                        qu.push(e.v);
                    }
        }
        return dist[t] != -1;
    }

    F dfs(int u, F flow = numeric_limits<F>::max()) {
        if (flow <= EPS || u == t)
            return max<F>(0, flow);
        for (int& i = ptr[u]; i < sz(graph[u]); i++) {
            Edge& e = graph[u][i];
            if (e.cap - e.flow > EPS && dist[u] + 1 == dist[e.v])
                {
                    F pushed = dfs(e.v, min<F>(flow, e.cap - e.flow));
                    if (pushed > EPS) {
                        e.flow += pushed;
                        graph[e.v][e.inv].flow -= pushed;

```

```

        return pushed;
    }
}
return 0;
}

F maxFlow() {
    F flow = 0;
    while (bfs()) {
        fill(all(ptr), 0);
        while (F pushed = dfs(s))
            flow += pushed;
    }
    return flow;
}

bool leftSide(int u) {
    // left side comes from sink
    return dist[u] != -1;
}
};

```

9.5 Min-Cost flow $\mathcal{O}(\min(e \cdot flow, v^2 \cdot e))$

```

template <class C, class F>
struct Mcmf {
    struct Edge {
        int u, v, inv;
        F cap, flow;
        C cost;
        Edge(int u, int v, C cost, F cap, int inv) : u(u), v(v),
            cost(cost), cap(cap), flow(0), inv(inv) {}
    };

    F EPS = (F)1e-9;
    int s, t, n;
    vector<vector<Edge*>> graph;
    vector<Edge*> prev;
    vector<C> cost;
    vector<int> state;

    Mcmf(int n) : n(n), graph(n), cost(n), state(n), prev(n),
        s(n - 2), t(n - 1) {}

    void add(int u, int v, C cost, F cap) {
        graph[u].pb(Edge(u, v, cost, cap, sz(graph[v])));
        graph[v].pb(Edge(v, u, -cost, 0, sz(graph[u]) - 1));
    }

    bool bfs() {
        fill(all(state), 0);
        fill(all(cost), numeric_limits<C>::max());
        deque<int> qu;
        qu.push_back(s);
        state[s] = 1, cost[s] = 0;
        while (sz(qu)) {
            int u = qu.front();
            qu.pop_front();
            state[u] = 2;
            for (Edge& e : graph[u])
                if (e.cap - e.flow > EPS)
                    if (cost[u] + e.cost < cost[e.v]) {
                        cost[e.v] = cost[u] + e.cost;
                        prev[e.v] = &e;
                        if (state[e.v] == 2 || (sz(qu) && cost[qu.front()] > cost[e.v]))
                            qu.push_front(e.v);
                        else if (state[e.v] == 0)
                            qu.push_back(e.v);
                        state[e.v] = 1;
                    }
        }
    }
};

```

```

    }
    return cost[t] != numeric_limits<C>::max();
}

pair<C, F> minCostFlow() {
    C cost = 0;
    F flow = 0;
    while (bfs()) {
        F pushed = numeric_limits<F>::max();
        for (Edge* e = prev[t]; e != nullptr; e = prev[e->u])
            pushed = min(pushed, e->cap - e->flow);
        for (Edge* e = prev[t]; e != nullptr; e = prev[e->u])
            {
                e->flow += pushed;
                graph[e->v][e->inv].flow -= pushed;
                cost += e->cost * pushed;
            }
        flow += pushed;
    }
    return make_pair(cost, flow);
}
};

```

10 Game theory

10.1 Grundy numbers

If the moves are consecutive $S = \{1, 2, 3, \dots, x\}$ the game can be solved like $stackSize \pmod{x+1} \neq 0$

```

int mem[N];

int mex(set<int>& st) {
    int x = 0;
    while (st.count(x))
        x++;
    return x;
}

int grundy(int n) {
    if (n < 0)
        return INF;
    if (n == 0)
        return 0;
    int& g = mem[n];
    if (g == -1) {
        set<int> st;
        for (int x : {a, b})
            st.insert(grundy(n - x));
        g = mex(st);
    }
    return g;
}

```

11 Math

11.1 Bits

Bits++	
Operations on <i>int</i>	Function
<code>x & -x</code>	Least significant bit in <i>x</i>
<code>__lg(x)</code>	Most significant bit in <i>x</i>
<code>c = x&-x, r = x+c; (((r^x) >> 2)/c) r</code>	Next number after <i>x</i> with same number of bits set
<code>__builtin_</code>	Function
<code>popcount(x)</code>	Amount of 1's in <i>x</i>
<code>clz(x)</code>	0's to the left of biggest bit
<code>ctz(x)</code>	0's to the right of smallest bit

11.2 Bitset

Bitset<Size>	
Operation	Function
<code>_Find_first()</code>	Least significant bit
<code>_Find_next(idx)</code>	First set bit after index <i>idx</i>
<code>any()</code> , <code>none()</code> , <code>all()</code>	Just what the expression says
<code>set()</code> , <code>reset()</code> , <code>flip()</code>	Just what the expression says x2
<code>to_string('.', 'A')</code>	Print 011010 like .AA.A.

11.3 Fpow

```
template <class T>
T fpow(T x, lli n) {
    T r(1);
    for (; n > 0; n >>= 1) {
        if (n & 1)
            r = r * x;
        x = x * x;
    }
    return r;
}
```

11.4 Fraction

```
struct Frac {
    lli num, den;

    Frac(lli a = 0, lli b = 1) {
        lli g = gcd(a, b);
        num = a / g, den = b / g;
        if (den < 0)
            num *= -1, den *= -1;
    }

    bool operator<(const Frac& f) const {
        return num * f.den < f.num * den;
    }

    bool operator==(const Frac& f) const {
        return num == f.num && den == f.den;
    }

    bool operator!=(const Frac& f) const {
        return !(*this == f);
    }

    friend Frac abs(const Frac& f) {
        return Frac(abs(f.num), f.den);
    }

    friend ostream& operator<<(ostream& os, const Frac& f) {
        return os << f.num << "/" << f.den;
    }

    Frac operator-() const {
        return Frac(-num, den);
    }

    double operator()() const {
        return double(num) / double(den);
    }

    Frac operator*(const Frac& f) {
        return Frac(num * f.num, den * f.den);
    }

    Frac operator/(const Frac& f) {
        return Frac(num * f.den, den * f.num);
    }

    Frac operator+(const Frac& f) {
```

```
        lli k = lcm(den, f.den);
        return Frac(num * (k / den) + f.num * (k / f.den), k);
    }

    Frac operator-(const Frac& f) {
        lli k = lcm(den, f.den);
        return Frac(num * (k / den) - f.num * (k / f.den), k);
    }
};
```

11.5 Modular

```
template <const int M>
struct Modular {
    int v;
    Modular(int a = 0) : v(a) {}
    Modular(lli a) : v(a % M) {
        if (v < 0)
            v += M;
    }

    Modular operator+(Modular m) {
        return Modular((v + m.v) % M);
    }

    Modular operator-(Modular m) {
        return Modular((v - m.v + M) % M);
    }

    Modular operator*(Modular m) {
        return Modular(((1LL * v * m.v) % M));
    }

    Modular inv() {
        return this->pow(M - 2);
    }

    Modular operator/(Modular m) {
        return *this * m.inv();
    }

    Modular& operator+=(Modular m) {
        return *this = *this + m;
    }

    Modular& operator-=(Modular m) {
        return *this = *this - m;
    }

    Modular& operator*=(Modular m) {
        return *this = *this * m;
    }

    Modular& operator/=(Modular m) {
        return *this = *this / m;
    }

    friend ostream& operator<<(ostream& os, Modular m) {
        return os << m.v;
    }

    Modular pow(lli n) {
        Modular r(1), x = *this;
        for (; n > 0; n >>= 1) {
            if (n & 1)
                r = r * x;
            x = x * x;
        }
        return r;
    }
};
```

11.6 Probability

Conditional

The event A happens and the event B has already happened

$$P(A|B) = \frac{P(A \cap B)}{P(B)}$$

If **independent** events

$$P(A|B) = P(A), P(B|A) = P(B)$$

Bayes theorem

$$P(A|B) = \frac{P(B|A) \cdot P(A)}{P(B)}$$

Binomial

$$B = \binom{n}{x} \cdot p^x \cdot (1-p)^{n-x}$$

n = number of trials

x = number of **success** from n trials

p = probability of **success** on a single trial

Geometric

Probability of success at the n th-event after failing the others

$$G = (1-p)^{n-1} \cdot p$$

n = number of trials

p = probability of *success* on a single trial

Poisson

$$Po = \frac{\lambda^k \cdot e^{-\lambda}}{k!}$$

λ = number of times an event is expected (occurs / time)

k = number of occurring events in the limited period of time

Example: The event happens 4 times per minute and we want k events to happen in 10 minutes, then $\lambda = 4 \cdot 10 = 40$

Expected value

$$E_x = \sum_{\forall x} x \cdot p(x)$$

11.7 Simplex

Simplex is used for solving system of linear inequalities

Maximize/Minimize $f(x, y) = 3x + 2y$; all variables are ≥ 0

- $2x + y \leq 18$
- $2x + 3y \leq 42$
- $3x + y \leq 24$

$ans = 33, x = 3, y = 12$

$$a = \begin{bmatrix} 2 & 1 \\ 2 & 3 \\ 3 & 1 \end{bmatrix} \quad b = [18, 42, 24] \quad c = [3, 2]$$

```
template <class T>
pair<T, vector<T>> simplex(vector<vector<T>> a, vector<T> b
    , vector<T> c) {
    const T EPS = 1e-9;
    T sum = 0;
    int n = b.size(), m = c.size();
    vector<int> p(m), q(n);
    iota(all(p), 0), iota(all(q), m);

    auto pivot = [&](int x, int y) {
        swap(p[y], q[x]);
        b[x] /= a[x][y];
        for (i, 0, m)
            if (i != y)
                a[x][i] /= a[x][y];
        a[x][y] = 1 / a[x][y];
        for (i, 0, n)
            if (i != x && abs(a[i][y]) > EPS) {
                b[i] -= a[i][y] * b[x];
                for (j, 0, m)
                    if (j != y)
                        a[i][j] -= a[i][y] * a[x][j];
                a[i][y] = -a[i][y] * a[x][y];
            }
        sum += c[y] * b[x];
        for (i, 0, m)
            if (i != y)
                c[i] -= c[y] * a[x][i];
        c[y] = -c[y] * a[x][y];
    };

    while (1) {
        int x = -1, y = -1;
        ld mn = -EPS;
        for (i, 0, n)
            if (b[i] < mn)
                mn = b[i], x = i;
        if (x < 0)
            break;
        for (i, 0, m)
            if (a[x][i] < -EPS) {
                y = i;
                break;
            }
        assert(y >= 0); // no solution to Ax <= b
        pivot(x, y);
    }

    while (1) {
        int x = -1, y = -1;
        ld mx = EPS;
        for (i, 0, m)
            if (c[i] > mx)
                mx = c[i], y = i;
        if (y < 0)
            break;
        ld mn = 1e200;
        for (i, 0, n)
            if (a[i][y] > EPS && b[i] / a[i][y] < mn) {
                mn = b[i] / a[i][y], x = i;
            }
        assert(x >= 0); // c^T x is unbounded
        pivot(x, y);
    }

    vector<T> ans(m);
    for (i, 0, n)
        if (q[i] < m)
            ans[q[i]] = b[i];
    return {sum, ans};
}
```


11.8 Gauss jordan $\mathcal{O}(n^2 \cdot m)$

```
template <class T>
pair<int, vector<T>> gauss(vector<vector<T>> a, vector<T> b
) {
    const double EPS = 1e-6;
    int n = a.size(), m = a[0].size();
    for (int i = 0; i < n; i++)
        a[i].push_back(b[i]);
    vector<int> where(m, -1);
    for (int col = 0, row = 0; col < m and row < n; col++) {
        int sel = row;
        for (int i = row; i < n; ++i)
            if (abs(a[i][col]) > abs(a[sel][col]))
                sel = i;
        if (abs(a[sel][col]) < EPS)
            continue;
        for (int i = col; i <= m; i++)
            swap(a[sel][i], a[row][i]);
        where[col] = row;

        for (int i = 0; i < n; i++)
            if (i != row) {
                T c = a[i][col] / a[row][col];
                for (int j = col; j <= m; j++)
                    a[i][j] -= a[row][j] * c;
            }
        row++;
    }
    vector<T> ans(m, 0);
    for (int i = 0; i < m; i++)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i = 0; i < n; i++) {
        T sum = 0;
        for (int j = 0; j < m; j++)
            sum += ans[j] * a[i][j];
        if (abs(sum - a[i][m]) > EPS)
            return pair(0, vector<T>());
    }
    for (int i = 0; i < m; i++)
        if (where[i] == -1)
            return pair(INF, ans);
    return pair(1, ans);
}
```

11.9 Xor basis

```
template <int D>
struct XorBasis {
    using Num = bitset<D>;
    array<Num, D> basis, keep;
    vector<int> from;
    int n = 0, id = -1;

    XorBasis() : from(D, -1) {
        basis.fill(0);
    }

    bool insert(Num x) {
        ++id;
        Num k;
        for (i, D, 0)
            if (x[i]) {
                if (!basis[i].any()) {
                    k[i] = 1, from[i] = id, keep[i] = k;
                    basis[i] = x, n++;
                    return 1;
                }
                x ^= basis[i], k ^= keep[i];
            }
        return 0;
    }
};
```

```
}

optional<Num> find(Num x) {
    // is x in xor-basis set?
    // v ^ (v ^ x) = x
    Num v;
    for (i, D, 0)
        if (x[i]) {
            if (!basis[i].any())
                return nullopt;
            x ^= basis[i];
            v[i] = 1;
        }
    return optional(v);
}

optional<vector<int>> recover(Num x) {
    auto v = find(x);
    if (!v)
        return nullopt;
    Num tmp;
    for (i, D, 0)
        if (v.value()[i])
            tmp ^= keep[i];
    vector<int> ans;
    for (int i = tmp._Find_first(); i < D; i = tmp._Find_next(i))
        ans.pb(from[i]);
    return ans;
}

optional<Num> operator[](lli k) {
    lli tot = (1LL << n);
    if (k > tot)
        return nullopt;
    Num v = 0;
    for (i, D, 0)
        if (basis[i]) {
            lli low = tot / 2;
            if ((low < k && v[i] == 0) || (low >= k && v[i]))
                v ^= basis[i];
            if (low < k)
                k -= low;
            tot /= 2;
        }
    return optional(v);
}
};
```

12 Combinatorics

12.1 Factorial

```
fac[0] = 1LL;
for (i, 1, N)
    fac[i] = lli(i) * fac[i - 1] % MOD;
ifac[N - 1] = fpow(fac[N - 1], MOD - 2, MOD);
for (int i = N - 2; i >= 0; i--)
    ifac[i] = lli(i + 1) * ifac[i + 1] % MOD;
```

12.2 Factorial mod small prime

```
lli facMod(lli n, int p) {
    lli r = 1LL;
    for (; n > 1; n /= p) {
        r = (r * ((n / p) % 2 ? p - 1 : 1)) % p;
        for (i, 2, n % p + 1)
            r = r * i % p;
    }
    return r % p;
}
```

12.3 Choose

$$\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k}$$

$$\binom{n}{k_1, k_2, \dots, k_m} = \frac{n!}{k_1! * k_2! * \dots * k_m!}$$

```
lli choose(int n, int k) {
    if (n < 0 || k < 0 || n < k)
        return 0LL;
    return fac[n] * ifac[k] % MOD * ifac[n - k] % MOD;
}
```

```
lli choose(int n, int k) {
    lli r = 1;
    int to = min(k, n - k);
    if (to < 0)
        return 0;
    for (i, 0, to)
        r = r * (n - i) / (i + 1);
    return r;
}
```

12.4 Pascal

```
for (i, 0, N) {
    choose[i][0] = choose[i][i] = 1;
    for (int j = 1; j <= i; j++)
        choose[i][j] = choose[i - 1][j - 1] + choose[i - 1][j];
}
```

12.5 Stars and bars

Enclosing n objects in k boxes

$$\binom{n+k-1}{k-1} = \binom{n+k-1}{n}$$

12.6 Lucas

Changes $\binom{n}{k} \bmod p$, with $n \geq 2e6, k \geq 2e6$ and $p \leq 1e7$

$$\binom{n}{k} \equiv \prod_{i=0}^n \binom{n_i}{k_i} \bmod p$$

```
lli lucas(lli n, lli k) {
    if (k == 0)
        return 1LL;
    return lucas(n / MOD, k / MOD) * choose(n % MOD, k % MOD)
        % MOD;
}
```

12.7 Burnside lemma

Burnside's lemma is a result in group theory that can help when counting objects with symmetry taken into account. It gives a formula to count objects, where two objects that are related by a symmetry (rotation or reflection, for example) are not to be counted as distinct.

let G be a finite group. For each g in G let $f(g)$ denote the set of elements that are fixed by g .

$$|classes| = \frac{1}{|G|} \cdot \sum_{g \in G} f(g)$$

12.8 Catalan

Number of ways to insert n pairs of parentheses in a word of $n + 1$ letters.

Consider all the $\binom{2n}{n}$ paths on squared paper that start at $(0, 0)$, end at (n, n) and at each step, either make a $(+1, +1)$ step or a $(+1, -1)$ step. Then the number of such paths that never go below the x-axis.

Number of ordered rooted trees with n nodes, not including the root.

$$C_n = \frac{(2n)!}{(n+1)! \cdot n!}$$

$$C_n = \binom{2n}{n} - \binom{2n}{n+1}$$

i	0/1	2	3	4	5	6	7	8	9	10
C_i	1	2	5	14	42	132	429	1430	4862	16796

```
catalan[0] = 1LL;
for (i, 0, N) {
    catalan[i + 1] = catalan[i] * lli(4 * i + 2) % MOD * fpow
        (i + 2, MOD - 2) % MOD;
}
```

12.9 Bell numbers

The number of ways a set of n elements can be partitioned into **nonempty** subsets

$$B_{n+1} = \sum_{k=0}^n \binom{n}{k} \cdot B_k$$

i	5	6	7	8	9	10	11
B_i	52	203	877	4140	21147	115975	678570

12.10 Stirling numbers

Count the number of permutations of n elements with k disjoint cycles Signed way, $k > 0$

$$s(0, 0) = 1, s(n, 0) = s(0, n) = 0$$

$$s(n, k) = -(n-1) \cdot s(n-1, k) + s(n-1, k-1)$$

The unsigned way doesn't have sign $|-(n-1)|$

The sum of products of the $\binom{n}{k}$ subsets of size k of $\{0, 1, \dots, n-1\}$ is $s(n, n-k)$

12.11 Stirling numbers 2

How many ways are of dividing a set of n **different** objects into k **nonempty** subsets. $\{ \binom{n}{k} \}$

$$s_2(0, 0) = 1, s_2(n, 0) = s_2(0, n) = 0$$

$$s_2(n, k) = s_2(n-1, k-1) + k \cdot s_2(n-1, k)$$

$$s_2(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^i \cdot \binom{k}{i} \cdot (k-i)^n$$

```
Mint stirling2(int n, int k) {
    Mint sum = 0;
    for (i, 0, k + 1)
        sum += fpow<Mint>(-1, i) * choose(k, i) * fpow<Mint>(k
            - i, n);
    return sum * ifac(k);
};
```

13 Number theory

13.1 Amount of divisors $\mathcal{O}(n^{1/3})$

```
ull amountOfDivisors(ull n) {
    ull cnt = 1;
    for (auto p : primes) {
        if (1LL * p * p * p > n)
            break;
        if (n % p == 0) {
            ull k = 0;
            while (n > 1 && n % p == 0)
                n /= p, ++k;
            cnt *= (k + 1);
        }
    }
    ull sq = mysqrt(n); // the last x * x <= n
    if (miller(n))
        cnt *= 2;
    else if (sq * sq == n && miller(sq))
        cnt *= 3;
    else if (n > 1)
        cnt *= 4;
    return cnt;
}
```

13.2 Chinese remainder theorem

- $x \equiv 3 \pmod{4}$
- $x \equiv 5 \pmod{6}$
- $x \equiv 2 \pmod{5}$

$$x \equiv 47 \pmod{60}$$

```
pair<lli, lli> crt(pair<lli, lli> a, pair<lli, lli> b) {
    if (a.s < b.s)
        swap(a, b);
    auto p = euclid(a.s, b.s);
    lli g = a.s * p.f + b.s * p.s, l = a.s / g * b.s;
    if ((b.f - a.f) % g != 0)
        return {-1, -1}; // no solution
    p.f = a.f + (b.f - a.f) % b.s * p.f % b.s / g * a.s;
    return {p.f + (p.f < 0) * l, l};
}
```

13.3 Euclid $\mathcal{O}(\log(a \cdot b))$

```
pair<lli, lli> euclid(lli a, lli b) {
    if (b == 0)
        return {1, 0};
    auto p = euclid(b, a % b);
    return {p.s, p.f - a / b * p.s};
}
```

13.4 Factorial factors

```
vector<ii> factorialFactors(lli n) {
    vector<ii> fac;
    for (auto p : primes) {
        if (n < p)
            break;
        lli mul = 1LL, k = 0;
        while (mul <= n / p) {
            mul *= p;
            k += n / mul;
        }
        fac.emplace_back(p, k);
    }
    return fac;
}
```

13.5 Inverse

```
lli inv(lli a, lli m) {
    a %= m;
```

```
    assert(a);
    return a == 1 ? 1 : m - 1LL * inv(m, a) * m / a;
}
```

13.6 Factorize sieve

```
int factor[N];

void factorizeSieve() {
    iota(factor, factor + N, 0);
    for (int i = 2; i * i < N; i++)
        if (factor[i] == i)
            for (int j = i * i; j < N; j += i)
                factor[j] = i;
}
```

```
map<int, int> factorize(int n) {
    map<int, int> cnt;
    while (n > 1) {
        cnt[factor[n]]++;
        n /= factor[n];
    }
    return cnt;
}
```

13.7 Sieve

```
bitset<N> isPrime;
vector<int> primes;

void sieve() {
    isPrime.set();
    isPrime[0] = isPrime[1] = 0;
    for (int i = 2; i * i < N; ++i)
        if (isPrime[i])
            for (int j = i * i; j < N; j += i)
                isPrime[j] = 0;
    fore (i, 2, N)
        if (isPrime[i])
            primes.pb(i);
}
```

13.8 Phi $\mathcal{O}(\sqrt{n})$

```
lli phi(lli n) {
    if (n == 1)
        return 0;
    lli r = n;
    for (lli i = 2; i * i <= n; i++)
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            r -= r / i;
        }
    if (n > 1)
        r -= r / n;
    return r;
}
```

13.9 Phi sieve

```
bitset<N> isPrime;
int phi[N];

void phiSieve() {
    isPrime.set();
    iota(phi, phi + N, 0);
    fore (i, 2, N)
        if (isPrime[i])
            for (int j = i; j < N; j += i) {
                isPrime[j] = (i == j);
                phi[j] = phi[j] / i * (i - 1);
            }
}
```

13.10 Miller rabin $\mathcal{O}(\text{Witnesses} \cdot (\log n)^3)$

```

ull mul(ull x, ull y, ull MOD) {
    lli ans = x * y - MOD * ull(1.L / MOD * x * y);
    return ans + MOD * (ans < 0) - MOD * (ans >= lli(MOD));
}

// use mul(x, y, mod) inside fpow
bool miller(ull n) {
    if (n < 2 || n % 6 % 4 != 1)
        return (n | 1) == 3;
    ull k = __builtin_ctzll(n - 1), d = n >> k;
    for (ull p : {2, 325, 9375, 28178, 450775, 9780504, 17952
        65022}) {
        ull x = fpow(p % n, d, n), i = k;
        while (x != 1 && x != n - 1 && p % n && i--)
            x = mul(x, x, n);
        if (x != n - 1 && i != k)
            return 0;
    }
    return 1;
}

```

13.11 Pollard Rho $\mathcal{O}(n^{1/4})$

```

ull rho(ull n) {
    auto f = [n](ull x) {
        return mul(x, x, n) + 1;
    };
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y)
            x = ++i, y = f(x);
        if (q = mul(prd, max(x, y) - min(x, y), n))
            prd = q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}

// if used multiple times, try memorization!!
// try factoring small numbers with sieve
void pollard(ull n, map<ull, int>& fac) {
    if (n == 1)
        return;
    if (miller(n)) {
        fac[n]++;
    } else {
        ull x = rho(n);
        pollard(x, fac);
        pollard(n / x, fac);
    }
}

```

14 Polynomials

14.1 Berlekamp Massey

For a linear recurrence of length n you need to feed at least $2n$ terms into Berlekamp-Massey to guarantee getting the same or equivalent recurrence.

```

template <class T>
struct BerlekampMassey {
    int n;
    vector<T> s, t, pw[20];

    vector<T> combine(vector<T> a, vector<T> b) {
        vector<T> ans(sz(t) * 2 + 1);
        for (int i = 0; i <= sz(t); i++)
            for (int j = 0; j <= sz(t); j++)
                ans[i + j] += a[i] * b[j];
        for (int i = 2 * sz(t); i > sz(t); --i)
            for (int j = 0; j < sz(t); j++)

```

```

                ans[i - 1 - j] += ans[i] * t[j];
        ans.resize(sz(t) + 1);
        return ans;
    }
}

```

```

BerlekampMassey(const vector<T>& s) : n(sz(s)), t(n), s(s)
    ) {
    vector<T> x(n), tmp;
    t[0] = x[0] = 1;
    T b = 1;
    int len = 0, m = 0;
    for (i, 0, n) {
        ++m;
        T d = s[i];
        for (int j = 1; j <= len; j++)
            d += t[j] * s[i - j];
        if (d == 0)
            continue;
        tmp = t;
        T coef = d / b;
        for (int j = m; j < n; j++)
            t[j] -= coef * x[j - m];
        if (2 * len > i)
            continue;
        len = i + 1 - len;
        x = tmp;
        b = d;
        m = 0;
    }
    t.resize(len + 1);
    t.erase(t.begin());
    for (auto& x : t)
        x = -x;
    pw[0] = vector<T>(sz(t) + 1), pw[0][1] = 1;
    for (i, 1, 20)
        pw[i] = combine(pw[i - 1], pw[i - 1]);
}

```

```

T operator[](lli k) {
    vector<T> ans(sz(t) + 1);
    ans[0] = 1;
    for (i, 0, 20)
        if (k & (1LL << i))
            ans = combine(ans, pw[i]);
    T val = 0;
    for (i, 0, sz(t))
        val += ans[i + 1] * s[i];
    return val;
}
};

```

14.2 Lagrange $\mathcal{O}(n)$

Calculate the extrapolation of $f(k)$, given all the sequence $f(0), f(1), f(2), \dots, f(n)$

$$\sum_{i=1}^{10} i^5 = 220825$$

```

template <class T>
struct Lagrange {
    int n;
    vector<T> y, suf, fac;

    Lagrange(vector<T>& y) : n(sz(y)), y(y), suf(n + 1, 1),
        fac(n, 1) {
        for (i, 1, n)
            fac[i] = fac[i - 1] * i;
    }

    T operator[](lli k) {
        for (int i = n - 1; i >= 0; i--)

```

```

    suf[i] = suf[i + 1] * (k - i);

    T pref = 1, val = 0;
    for (i, 0, n) {
        T num = pref * suf[i + 1];
        T den = fac[i] * fac[n - 1 - i];
        if ((n - 1 - i) % 2)
            den *= -1;
        val += y[i] * num / den;
        pref *= (k - i);
    }
    return val;
}
};

```

14.3 FFT

```

template <class Complex>
void FFT(vector<Complex>& a, bool inv = false) {
    const static double PI = acos(-1.0);
    static vector<Complex> root = {0, 1};
    int n = sz(a);
    for (int i = 1, j = 0; i < n - 1; i++) {
        for (int k = n >> 1; (j ^ k) < k; k >>= 1)
            ;
        if (i < j)
            swap(a[i], a[j]);
    }
    int k = sz(root);
    if (k < n)
        for (root.resize(n); k < n; k <= 1) {
            Complex z(cos(PI / k), sin(PI / k));
            for (i, k >> 1, k) {
                root[i << 1] = root[i];
                root[i << 1 | 1] = root[i] * z;
            }
        }
    for (int k = 1; k < n; k <= 1)
        for (int i = 0; i < n; i += k << 1)
            for (j, 0, k) {
                Complex t = a[i + j + k] * root[j + k];
                a[i + j + k] = a[i + j] - t;
                a[i + j] = a[i + j] + t;
            }
    if (inv) {
        reverse(1 + all(a));
        for (auto& x : a)
            x /= n;
    }
}

template <class T>
vector<T> convolution(const vector<T>& a, const vector<T>& b) {
    if (a.empty() || b.empty())
        return {};

    int n = sz(a) + sz(b) - 1, m = n;
    while (n != (n & -n))
        ++n;

    vector<complex<double>> fa(all(a)), fb(all(b));
    fa.resize(n), fb.resize(n);
    FFT(fa, false), FFT(fb, false);
    for (i, 0, n)
        fa[i] *= fb[i];
    FFT(fa, true);

    vector<T> ans(m);
    for (i, 0, m)

```

```

        ans[i] = round(real(fa[i]));
    return ans;
}

template <class T>
vector<T> convolutionTrick(const vector<T>& a,
                          const vector<T>& b) { // 2 FFT's
                                              instead of 3!!

    if (a.empty() || b.empty())
        return {};

    int n = sz(a) + sz(b) - 1, m = n;
    while (n != (n & -n))
        ++n;

    vector<complex<double>> in(n), out(n);
    for (i, 0, sz(a))
        in[i].real(a[i]);
    for (i, 0, sz(b))
        in[i].imag(b[i]);

    FFT(in, false);
    for (auto& x : in)
        x *= x;
    for (i, 0, n)
        out[i] = in[-i & (n - 1)] - conj(in[i]);
    FFT(out, false);

    vector<T> ans(m);
    for (i, 0, m)
        ans[i] = round(imag(out[i]) / (4 * n));
    return ans;
}

```

14.4 Fast Walsh Hadamard Transform

```

template <char op, bool inv = false, class T>
vector<T> FWHT(vector<T> f) {
    int n = f.size();
    for (int k = 0; (n - 1) >> k; k++)
        for (int i = 0; i < n; i++)
            if (i >> k & 1) {
                int j = i ^ (1 << k);
                if (op == '^')
                    f[j] += f[i], f[i] = f[j] - 2 * f[i];
                if (op == '|')
                    f[i] += (inv ? -1 : 1) * f[j];
                if (op == '&')
                    f[j] += (inv ? -1 : 1) * f[i];
            }
        if (op == '^' && inv)
            for (auto& i : f)
                i /= n;
    return f;
}

```

14.5 Primitive root

```

int primitive(int p) {
    auto fpow = [&](lli x, int n) {
        lli r = 1;
        for (; n > 0; n >>= 1) {
            if (n & 1)
                r = r * x % p;
            x = x * x % p;
        }
        return r;
    };

    for (int g = 2; g < p; g++) {
        bool can = true;
        for (int i = 2; i * i < p; i++)
            if ((p - 1) % i == 0) {

```

```

    if (fpow(g, i) == 1)
        can = false;
    if (fpow(g, (p - 1) / i) == 1)
        can = false;
}
if (can)
    return g;
}
return -1;
}

```

14.6 NTT

```

template <const int G, const int M>
void NTT(vector<Modular<M>>& a, bool inv = false) {
    static vector<Modular<M>> root = {0, 1};
    static Modular<M> primitive(G);
    int n = sz(a);
    for (int i = 1, j = 0; i < n - 1; i++) {
        for (int k = n >> 1; (j ^ k) < k; k >>= 1)
            ;
        if (i < j)
            swap(a[i], a[j]);
    }
    int k = sz(root);
    if (k < n)
        for (root.resize(n); k < n; k <= 1) {
            auto z = primitive.pow((M - 1) / (k <= 1));
            fore (i, k >> 1, k) {
                root[i <= 1] = root[i];
                root[i <= 1 | 1] = root[i] * z;
            }
        }
    for (int k = 1; k < n; k <= 1)
        for (int i = 0; i < n; i += k <= 1)
            fore (j, 0, k) {
                auto t = a[i + j + k] * root[j + k];
                a[i + j + k] = a[i + j] - t;
                a[i + j] = a[i + j] + t;
            }
    if (inv) {
        reverse(1 + all(a));
        auto invN = Modular<M>(1) / n;
        for (auto& x : a)
            x = x * invN;
    }
}

template <int G = 3, const int M = 998244353>
vector<Modular<M>> convolution(vector<Modular<M>> a, vector<Modular<M>> b) {
    // find G using primitive(M)
    // Common NTT couple (3, 998244353)
    if (a.empty() || b.empty())
        return {};

    int n = sz(a) + sz(b) - 1, m = n;
    while (n != (n & -n))
        ++n;
    a.resize(n, 0), b.resize(n, 0);

    NTT<G, M>(a, NTT<G, M>(b));
    fore (i, 0, n)
        a[i] = a[i] * b[i];
    NTT<G, M>(a, true);

    return a;
}

```

15 Strings

15.1 KMP $\mathcal{O}(n)$

- aaabaab - [0, 1, 2, 0, 1, 2, 0]
- abacaba - [0, 0, 1, 0, 1, 2, 3]

```

template <class T>
vector<int> lps(T s) {
    vector<int> p(sz(s), 0);
    for (int j = 0, i = 1; i < sz(s); i++) {
        while (j && (j == sz(s) || s[i] != s[j]))
            j = p[j - 1];
        if (j < sz(s) && s[i] == s[j])
            j++;
        p[i] = j;
    }
    return p;
}

```

```

// positions where t is on s
template <class T>
vector<int> kmp(T& s, T& t) {
    vector<int> p = lps(t), pos;
    debug(lps(t), sz(s));
    for (int j = 0, i = 0; i < sz(s); i++) {
        while (j && (j == sz(t) || s[i] != t[j]))
            j = p[j - 1];
        if (j < sz(t) && s[i] == t[j])
            j++;
        if (j == sz(t))
            pos.pb(i - sz(t) + 1);
    }
    return pos;
}

```

15.2 KMP automaton $\mathcal{O}(\text{Alphabet} * n)$

```

template <class T, int ALPHA = 26>
struct KmpAutomaton : vector<vector<int>> {
    KmpAutomaton() {}
    KmpAutomaton(T s) : vector<vector<int>>(sz(s) + 1, vector<int>(ALPHA)) {
        s.pb(0);
        vector<int> p = lps(s);
        auto& nxt = *this;
        nxt[0][s[0] - 'a'] = 1;
        fore (i, 1, sz(s))
            fore (c, 0, ALPHA)
                nxt[i][c] = (s[i] - 'a' == c ? i + 1 : nxt[p[i - 1]][c]);
    }
};

```

15.3 Z $\mathcal{O}(n)$

z_i is the length of the longest substring starting from i which is also a prefix of s string will be in range $[i, i + z_i)$

- aaabaab - [0, 2, 1, 0, 2, 1, 0]
- abacaba - [0, 0, 1, 0, 3, 0, 1]

```

template <class T>
vector<int> zalgorithm(T& s) {
    vector<int> z(sz(s), 0);
    for (int i = 1, l = 0, r = 0; i < sz(s); i++) {
        if (i <= r)
            z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < sz(s) && s[i + z[i]] == s[z[i]])
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
}

```

```

    return z;
}

```

15.4 Manacher $\mathcal{O}(n)$

- aaabaab - $[[0, 1, 1, 0, 0, 2, 0], [0, 1, 0, 2, 0, 0, 0]]$
- abacaba - $[[0, 0, 0, 0, 0, 0, 0], [0, 1, 0, 3, 0, 1, 0]]$

```

template <class T>
vector<vector<int>> manacher(T& s) {
    vector<vector<int>> pal(2, vector<int>(sz(s), 0));
    for (k, 0, 2) {
        int l = 0, r = 0;
        for (i, 0, sz(s)) {
            int t = r - i + !k;
            if (i < r)
                pal[k][i] = min(t, pal[k][l + t]);
            int p = i - pal[k][i], q = i + pal[k][i] - !k;
            while (p >= 1 && q + 1 < sz(s) && s[p - 1] == s[q + 1])
                ++pal[k][i], --p, ++q;
            if (q > r)
                l = p, r = q;
        }
    }
    return pal;
}

```

15.5 Hash

bases = [17777771, 10006793, 10101283, 10101823, 10136359, 10157387, 10166249]

mods = [999727999, 1000000123, 1000002193, 1000008223, 1000009999, 1000027163, 1070777777]

```

using Hash = int; // maybe an array<int, 2>
Hash pw[N], ipw[N];

struct Hashing {
    static constexpr int P = 10166249, M = 1070777777;
    vector<Hash> h;

    static void init() {
        const int Q = inv(P, M);
        pw[0] = ipw[0] = 1;
        for (i, 1, N) {
            pw[i] = 1LL * pw[i - 1] * P % M;
            ipw[i] = 1LL * ipw[i - 1] * Q % M;
        }
    }

    Hashing(string& s) : h(sz(s) + 1, 0) {
        for (i, 0, sz(s)) {
            lli x = s[i] - 'a' + 1;
            h[i + 1] = (h[i] + x * pw[i]) % M;
        }
    }

    Hash query(int l, int r) {
        return 1LL * (h[r + 1] - h[l] + M) * ipw[l] % M;
    }

    static pair<Hash, int> merge(vector<pair<Hash, int>>& cuts) {
        pair<Hash, int> ans = {0, 0};
        for (i, sz(cuts), 0) {
            ans.f = (cuts[i].f + 1LL * ans.f * pw[cuts[i].s] % M) % M;
            ans.s += cuts[i].s;
        }
    }
}

```

```

    return ans;
}
};

```

15.6 Min rotation $\mathcal{O}(n)$

- baabaaa - 4
- abacaba - 6

```

template <class T>
int minRotation(T& s) {
    int n = sz(s), i = 0, j = 1;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && s[(i + k) % n] == s[(j + k) % n])
            k++;
        (s[(i + k) % n] <= s[(j + k) % n] ? j : i) += k + 1;
        j += i == j;
    }
    return i < n ? i : j;
}

```

15.7 Suffix array $\mathcal{O}(n \log n)$

- Duplicates $\sum_{i=1}^n lcp[i]$
- Longest Common Substring of various strings
Add *notUsed* characters between strings, i.e. $a + \$ + b + \# + c$
Use two-pointers to find a range $[l, r]$ such that all *notUsed* characters are present, then $query(lcp[l + 1], \dots, lcp[r])$ for that window is the common length.

```

template <class T>
struct SuffixArray {
    int n;
    T s;
    vector<int> sa, pos, sp[25];

    SuffixArray(const T& x) : n(sz(x) + 1), s(x), sa(n), pos(n) {
        n {
            s.pb(0);
            for (i, 0, n)
                sa[i] = i, pos[i] = s[i];
            vector<int> nsa(sa), npos(n), cnt(max(260, n), 0);
            for (int k = 0; k < n; k ? k *= 2 : k++) {
                fill(all(cnt), 0);
                for (i, 0, n)
                    nsa[i] = (sa[i] - k + n) % n, cnt[pos[i]]++;
                partial_sum(all(cnt), cnt.begin());
                for (int i = n - 1; i >= 0; i--)
                    sa[--cnt[pos[nsa[i]]]] = nsa[i];
                for (int i = 1, cur = 0; i < n; i++) {
                    cur += (pos[sa[i]] != pos[sa[i - 1]] || pos[(sa[i] + k) % n] != pos[(sa[i - 1] + k) % n]);
                    npos[sa[i]] = cur;
                }
                pos = npos;
                if (pos[sa[n - 1]] >= n - 1)
                    break;
            }
            sp[0].assign(n, 0);
            for (int i = 0, j = pos[0], k = 0; i < n - 1; ++i, ++k)
                while (k >= 0 && s[i] != s[sa[j - 1] + k])
                    sp[0][j] = k--, j = pos[sa[j] + 1];
            for (int k = 1, pw = 1; pw < n; k++, pw <= 1) {
                sp[k].assign(n, 0);
            }
        }
    }
}

```

```

    for (int l = 0; l + pw < n; l++)
        sp[k][l] = min(sp[k - 1][l], sp[k - 1][l + pw]);
}

int lcp(int l, int r) {
    if (l == r)
        return n - 1;
    tie(l, r) = minmax(pos[l], pos[r]);
    int k = __lg(r - l);
    return min(sp[k][l + 1], sp[k][r - (1 << k) + 1]);
}

auto at(int i, int j) {
    return sa[i] + j < n ? s[sa[i] + j] : 'z' + 1;
}

int count(T& t) {
    int l = 0, r = n - 1;
    for (i, 0, sz(t)) {
        int p = l, q = r;
        for (int k = n; k > 0; k >= 1) {
            while (p + k < r && at(p + k, i) < t[i])
                p += k;
            while (q - k > l && t[i] < at(q - k, i))
                q -= k;
        }
        l = (at(p, i) == t[i] ? p : p + 1);
        r = (at(q, i) == t[i] ? q : q - 1);
        if (at(l, i) != t[i] && at(r, i) != t[i] || l > r)
            return 0;
    }
    return r - l + 1;
}

bool compare(ii a, ii b) {
    // s[a.f ... a.s] < s[b.f ... b.s]
    int common = lcp(a.f, b.f);
    int szA = a.s - a.f + 1, szB = b.s - b.f + 1;
    if (common >= min(szA, szB))
        return tie(szA, a) < tie(szB, b);
    return s[a.f + common] < s[b.f + common];
}
};

```

15.8 Trie

```

struct Trie {
    struct Node : map<char, int> {
        bool isWord = false;
    };

    vector<Node> trie;

    Trie(int n = 1) {
        trie.reserve(n), newNode();
    }

    int inline newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    void insert(string& s, int u = 0) {
        for (char c : s) {
            if (!trie[u][c])
                trie[u][c] = newNode();
            u = trie[u][c];
        }
        trie[u].isWord = true;
    }
}

```

```

}

bool find(string& s, int u = 0) {
    for (char c : s) {
        if (!trie[u].count(c))
            return false;
        u = trie[u][c];
    }
    return trie[u].isWord;
}

Node& operator[](int u) {
    return trie[u];
}
};

```

15.9 Aho Corasick $\mathcal{O}(\sum s_i)$

```

struct AhoCorasick {
    struct Node : map<char, int> {
        int link = 0, up = 0;
        int cnt = 0, isWord = 0;
    };

    vector<Node> trie;

    AhoCorasick(int n = 1) {
        trie.reserve(n), newNode();
    }

    int newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    void insert(string& s, int u = 0) {
        for (char c : s) {
            if (!trie[u][c])
                trie[u][c] = newNode();
            u = trie[u][c];
        }
        trie[u].cnt++, trie[u].isWord = 1;
    }

    int next(int u, char c) {
        while (u && !trie[u].count(c))
            u = trie[u].link;
        return trie[u][c];
    }

    void pushLinks() {
        queue<int> qu;
        qu.push(0);
        while (!qu.empty()) {
            int u = qu.front();
            qu.pop();
            for (auto& [c, v] : trie[u]) {
                int l = (trie[v].link = u ? next(trie[u].link, c) : 0);
                trie[v].cnt += trie[l].cnt;
                trie[v].up = trie[l].isWord ? l : trie[l].up;
                qu.push(v);
            }
        }
    }

    template <class F>
    void goUp(int u, F f) {
        for (; u != 0; u = trie[u].up)
            f(u);
    }
}

```



```

int match(string& s, int u = 0) {
    int ans = 0;
    for (char c : s) {
        u = next(u, c);
        ans += trie[u].cnt;
    }
    return ans;
}

```

```

Node& operator[](int u) {
    return trie[u];
}
};

```

15.10 Eertree $\mathcal{O}(\sum s_i)$

```

struct Eertree {
    struct Node : map<char, int> {
        int link = 0, len = 0;
    };

    vector<Node> trie;
    string s = "$";
    int last;

    Eertree(int n = 1) {
        trie.reserve(n), last = newNode(), newNode();
        trie[0].link = 1, trie[1].len = -1;
    }

    int newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    int next(int u) {
        while (s[sz(s) - trie[u].len - 2] != s.back())
            u = trie[u].link;
        return u;
    }

    void extend(char c) {
        s.push_back(c);
        last = next(last);
        if (!trie[last][c]) {
            int v = newNode();
            trie[v].len = trie[last].len + 2;
            trie[v].link = trie[next(trie[last].link)][c];
            trie[last][c] = v;
        }
        last = trie[last][c];
    }

    Node& operator[](int u) {
        return trie[u];
    }

    void substringOccurrences() {
        for (u, sz(s), 0)
            trie[trie[u].link].occ += trie[u].occ;
    }

    lli occurrences(string& s, int u = 0) {
        for (char c : s) {
            if (!trie[u].count(c))
                return 0;
            u = trie[u][c];
        }
        return trie[u].occ;
    }
}

```

```

};

```

15.11 Suffix automaton $\mathcal{O}(\sum s_i)$

- $sam[u].len - sam[sam[u].link].len = \text{distinct strings}$
- Number of different substrings (dp) $\mathcal{O}(\sum s_i)$

$$diff(u) = 1 + \sum_{v \in trie[u]} diff(v)$$

- Total length of all different substrings (2 x dp)

$$totLen(u) = \sum_{v \in trie[u]} diff(v) + totLen(v)$$

- Leftmost occurrence $\mathcal{O}(|s|)$ $trie[u].pos = trie[u].len - 1$ if it is **clone** then $trie[clone].pos = trie[q].pos$
- All occurrence positions
- Smallest cyclic shift $\mathcal{O}(|2 * s|)$ Construct sam of $s + s$, find the lexicographically smallest path of $sz(s)$
- Shortest non-appearing string $\mathcal{O}(|s|)$

$$nonAppearing(u) = \min_{v \in trie[u]} nonAppearing(v) + 1$$

```

struct SuffixAutomaton {
    struct Node : map<char, int> {
        int link = -1, len = 0;
    };

    vector<Node> trie;
    int last;

    SuffixAutomaton(int n = 1) {
        trie.reserve(2 * n), last = newNode();
    }

    int newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    void extend(char c) {
        int u = newNode();
        trie[u].len = trie[last].len + 1;
        int p = last;
        while (p != -1 && !trie[p].count(c)) {
            trie[p][c] = u;
            p = trie[p].link;
        }
        if (p == -1)
            trie[u].link = 0;
        else {
            int q = trie[p][c];
            if (trie[p].len + 1 == trie[q].len)
                trie[u].link = q;
            else {
                int clone = newNode();
                trie[clone] = trie[q];
                trie[clone].len = trie[p].len + 1;
                while (p != -1 && trie[p][c] == q) {
                    trie[p][c] = clone;
                    p = trie[p].link;
                }
                trie[q].link = trie[u].link = clone;
            }
        }
        last = u;
    }

    string kthSubstring(lli kth, int u = 0) {
        // number of different substrings (dp)
    }
}

```

```

string s = "";
while (kth > 0)
    for (auto& [c, v] : trie[u]) {
        if (kth <= diff(v)) {
            s.pb(c), kth--, u = v;
            break;
        }
        kth -= diff(v);
    }
return s;
}

void substringOccurrences() {
    // trie[u].occ = 1, trie[clone].occ = 0
    vector<int> who(sz(trie) - 1);
    iota(all(who), 1);
    sort(all(who), [&](int u, int v) {
        return trie[u].len > trie[v].len;
    });
    for (int u : who) {
        int l = trie[u].link;
        trie[l].occ += trie[u].occ;
    }
}

lli occurrences(string& s, int u = 0) {
    for (char c : s) {
        if (!trie[u].count(c))
            return 0;
        u = trie[u][c];
    }
    return trie[u].occ;
}

int longestCommonSubstring(string& s, int u = 0) {
    int mx = 0, len = 0;
    for (char c : s) {
        while (u && !trie[u].count(c)) {
            u = trie[u].link;
            len = trie[u].len;
        }
        if (trie[u].count(c))
            u = trie[u][c], len++;
        mx = max(mx, len);
    }
    return mx;
}

string smallestCyclicShift(int n, int u = 0) {
    string s = "";
    for (i, 0, n) {
        char c = trie[u].begin()->f;
        s += c;
        u = trie[u][c];
    }
    return s;
}

int leftmost(string& s, int u = 0) {
    for (char c : s) {
        if (!trie[u].count(c))
            return -1;
        u = trie[u][c];
    }
    return trie[u].pos - sz(s) + 1;
}

Node& operator[](int u) {
    return trie[u];
}
};

```