

Contents

1	Data structures	3	6	Game Theory	16
1.1	Disjoint set with rollback	3	6.1	Grundy Numbers	16
1.2	Min-Max queue	3	7	Combinatorics	16
1.3	Sparse table	3	7.1	Factorial	16
1.4	Squirtle decomposition	3	7.2	Factorial mod <i>smallPrime</i>	16
1.5	In-Out trick	3	7.3	Lucas theorem	17
1.6	Parallel binary search	3	7.4	Stars and bars	17
1.7	Mo's algorithm	4	7.5	N choose K	17
1.8	Static to dynamic	4	7.6	Catalan	17
1.9	Disjoint intervals	4	7.7	Burnside's lemma	17
1.10	Ordered tree	4	7.8	Prime factors of N!	17
1.11	Unordered tree	5	8	Number Theory	17
1.12	D-dimensional Fenwick tree	5	8.1	Goldbach conjecture	17
1.13	Dynamic segment tree	5	8.2	Prime numbers distribution	17
1.14	Persistent segment tree	5	8.3	Sieve of Eratosthenes	17
1.15	Wavelet tree	5	8.4	Phi of euler	17
1.16	Li Chao tree	6	8.5	Miller-Rabin	17
1.17	Explicit Treap	6	8.6	Pollard-Rho	18
1.18	Implicit Treap	7	8.7	Amount of divisors	18
1.19	Splay tree	7	8.8	Bézout's identity	18
2	Graphs	7	8.9	GCD	18
2.1	Tarjan algorithm (SCC)	7	8.10	LCM	18
2.2	Kosaraju algorithm (SCC)	8	8.11	Euclid	18
2.3	Two Sat	8	8.12	Chinese remainder theorem	18
2.4	Topological sort	8	9	Math	18
2.5	Cutpoints and Bridges	8	9.1	Progressions	18
2.6	Detect a cycle	8	9.2	Mod multiplication	18
2.7	Euler tour for Mo's in a tree	9	9.3	Fpow	18
2.8	Lowest common ancestor (LCA)	9	9.4	Fibonacci	18
2.9	Isomorphism	9	10	Bit tricks	19
2.10	Guni	9	10.1	Bitset	19
2.11	Centroid decomposition	9	10.2	Real	19
2.12	Heavy-light decomposition	9	11	Points	19
2.13	Link-Cut tree	10	11.1	Points	19
3	Flows	10	11.2	Angle between vectors	19
3.1	Dinic $\mathcal{O}(\min(E \cdot \text{flow}, V^2 E))$	10	11.3	Closest pair of points	19
3.2	Min cost flow $\mathcal{O}(\min(E \cdot \text{flow}, V^2 E))$	11	11.4	Projection	19
3.3	Hopcroft-Karp $\mathcal{O}(E\sqrt{V})$	11	12	Lines and segments	20
3.4	Hungarian $\mathcal{O}(N^3)$	12	12.1	Line	20
4	Strings	12	12.2	Segment	20
4.1	Hash	12	12.3	Distance point segment	20
4.2	KMP	12	12.4	Distance segment segment	20
4.3	KMP automaton	12	13	Circles	20
4.4	Z algorithm	13	13.1	Circle	20
4.5	Manacher algorithm	13	13.2	Distance point circle	21
4.6	Suffix array	13	14	Polygons	21
4.7	Suffix automaton	13	14.1	Area of polygon	21
4.8	Aho corasick	14	14.2	Convex-Hull	21
4.9	Eertree	15	14.3	Cut polygon by a line	21
5	Dynamic Programming	15	14.4	Perimeter	21
5.1	All submasks of a mask	15	14.5	Point in polygon	21
5.2	Matrix Chain Multiplication	15	15	Geometry misc	21
5.3	Digit DP	15	15.1	Radial order	21
5.4	Knapsack 0/1	15	15.2	Sort along a line	22
5.5	Convex Hull Trick $\mathcal{O}(n^2) \Rightarrow \mathcal{O}(n)$	15			
5.6	Divide and conquer $\mathcal{O}(kn^2) \Rightarrow \mathcal{O}(k \cdot n \log n)$	16			
5.7	Knuth optimization $\mathcal{O}(n^3) \Rightarrow \mathcal{O}(n^2)$	16			

Think twice, code once

Template

tem.cpp

```
#pragma GCC optimize("Ofast,unroll-loops,no-stack-protector")
#include <bits/stdc++.h>
using namespace std;

#ifdef LOCAL
#include "debug.h"
#else
#define debug(...)
#endif

#define df(b, e) ((b) > (e))
#define fore(i, b, e) for (auto i = (b) - df(b, e); i != e - df(b, e); i += 1 - 2 * df(b, e))
#define sz(x) int(x.size())
#define all(x) begin(x), end(x)
#define f first
#define s second
#define pb push_back

using lli = long long;
using ld = long double;
using ii = pair<int, int>;
using vi = vector<int>;

int main() {
    cin.tie(0) -> sync_with_stdio(0), cout.tie(0);
    // solve the problem here D:
    return 0;
}

debug.h

template <class A, class B>
ostream & operator << (ostream &os, const pair<A, B> &p) {
    return os << "(" << p.first << ", " << p.second << "
        )";
}

template <class A, class B, class C>
basic_ostream<A, B> & operator << (basic_ostream<A, B>
    &os, const C &c) {
    os << "[";
    for (const auto &x : c)
        os << ", " + 2 * (&x == &begin(c)) << x;
    return os << "]";
}

void print(string s) { cout << endl; }

template <class H, class... T>
void print(string s, const H &h, const T&... t) {
    const static string reset = "\033[0m", blue = "\033[
        1;34m", purple = "\033[3;95m";
    bool ok = 1;
    do {
        if (s[0] == '\0') ok = 0;
        else cout << blue << s[0] << reset;
        s = s.substr(1);
    } while (s.size() && s[0] != ',');
    if (ok) cout << ": " << purple << h << reset;
    print(s, t...);
}
```

Randoms

```
mt19937 rng(chrono::steady_clock::now().
    time_since_epoch().count());
```

```
template <class T>
T ran(T l, T r) {
    return uniform_int_distribution<T>(l, r)(rng);
}
```

Fastio

```
char gc() { return getchar_unlocked(); }

void readInt() {}
template <class H, class... T>
void readInt(H &h, T&&... t) {
    char c, s = 1;
    while (isspace(c = gc()));
    if (c == '-') s = -1, c = gc();
    for (h = c - '0'; isdigit(c = gc()); h = h * 10 + c
        - '0');
    h *= s;
    readInt(t...);
}

void readFloat() {}
template <class H, class... T>
void readFloat(H &h, T&&... t) {
    int c, s = 1, fp = 0, fpl = 1;
    while (isspace(c = gc()));
    if (c == '-') s = -1, c = gc();
    for (h = c - '0'; isdigit(c = gc()); h = h * 10 + c
        - '0');
    h *= s;
    if (h == '.')
        for (; isdigit(c = gc()); fp = fp * 10 + c - '0',
            fpl *= 10);
    h += (double)fp / fpl;
    readFloat(t...);
}
```

Compilation (gedit ~/.zshenv)

```
touch a_in{1..9} // make files a_in1, a_in2,..., a_in9
tee {a..m}.cpp < tem.cpp // "" with tem.cpp like base
cat > a_in1 // write on file a_in1
gedit a_in1 // open file a_in1
rm -r a.cpp // deletes file a.cpp :'
```

```
red='\x1B[0;31m'
green='\x1B[0;32m'
noColor='\x1B[0m'
alias flags='-Wall -Wextra -Wshadow -
    D_GLIBCXX_ASSERTIONS -fmax-errors=3 -O2 -w'
go() { g++ --std=c++11 $2 ${flags} $1.cpp && ./a.out }
debug() { go $1 -DLOCAL < $2 }
run() { go $1 "" < $2 }
```

```
random() { // Make small test cases!!!
    g++ --std=c++11 $1.cpp -o prog
    g++ --std=c++11 gen.cpp -o gen
    g++ --std=c++11 brute.cpp -o brute
    for ((i = 1; i <= 200; i++)); do
        printf "Test case #${i}"
        ./gen > in
        diff -uwi <(. /prog < in) <(. /brute < in) > $1_diff
        if [[ ! $? -eq 0 ]]; then
            printf "${red} Wrong answer ${noColor}\n"
            break
        else
            printf "${green} Accepted ${noColor}\n"
        fi
    done
}
```

```
test() {
```

```

g++ --std=c++11 $1.cpp -o prog
for ((i = 1; i <= 50; i++)); do
[[ -f $1_in$i ]] || break
printf "Test case #i"
diff -uwi <./prog < $1_in$i $1_out$i > $1_diff
if [[ ! $? -eq 0 ]]; then
    printf "${red} Wrong answer ${noColor}\n"
else
    printf "${green} Accepted ${noColor}\n"
fi
done
}

```

Bump allocator

```

static char buf[450 << 20];
void* operator new(size_t s) {
    static size_t i = sizeof buf; assert(s < i);
    return (void *) &buf[i -= s];
}
void operator delete(void *) {}

```

1 Data structures

1.1 Disjoint set with rollback

```

struct Dsu {
    vi par, tot;
    stack<ii> mem;

    Dsu(int n = 1) : par(n + 1), tot(n + 1, 1) {
        iota(all(par), 0);
    }

    int find(int u) {
        return par[u] == u ? u : find(par[u]);
    }

    void unite(int u, int v) {
        u = find(u), v = find(v);
        if (u != v) {
            if (tot[u] < tot[v])
                swap(u, v);
            mem.emplace(u, v);
            tot[u] += tot[v];
            par[v] = u;
        }
    }

    void rollback() {
        auto [u, v] = mem.top();
        mem.pop();
        if (u != -1) {
            tot[u] -= tot[v];
            par[v] = v;
        }
    }
};

```

1.2 Min-Max queue

```

template <class T>
struct MinQueue : deque< pair<T, int> > {
    // add a element to the right {val, pos}
    void add(T val, int pos) {
        while (!empty() && back().f >= val)
            pop_back();
        emplace_back(val, pos);
    }
    // remove all less than pos
    void rem(int pos) {
        while (front().s < pos)
            pop_front();
    }
}

```

```

T qmin() { return front().f; }
};

```

1.3 Sparse table

```

template <class T, class F = function<T(const T&,
    const T&)>>
struct Sparse {
    int n;
    vector<vector<T>> sp;
    F f;

    Sparse(vector<T> &a, const F &f) : n(sz(a)), sp(1 +
        __lg(n)), f(f) {
        sp[0] = a;
        for (int k = 1; (1 << k) <= n; k++) {
            sp[k].resize(n - (1 << k) + 1);
            fore (l, 0, sz(sp[k])) {
                int r = l + (1 << (k - 1));
                sp[k][l] = f(sp[k - 1][l], sp[k - 1][r]);
            }
        }
    }

    T query(int l, int r) {
        int k = __lg(r - l + 1);
        return f(sp[k][l], sp[k][r - (1 << k) + 1]);
    }
};

```

1.4 Squirtle decomposition

The perfect block size is *squirtle* of N



```

int blo[N], cnt[N][B], a[N];

void update(int i, int x) {
    cnt[blo[i]][x]--;
    a[i] = x;
    cnt[blo[i]][x]++;
}

int query(int l, int r, int x) {
    int tot = 0;
    while (l <= r)
        if (l % B == 0 && l + B - 1 <= r) {
            tot += cnt[blo[l]][x];
            l += B;
        } else {
            tot += (a[l] == x);
            l++;
        }
    return tot;
}

```

1.5 In-Out trick

```

vector<int> in[N], out[N];
vector<Query> queries;

fore (x, 0, N) {
    for (int i : in[x])
        add(queries[i]);
    // solve
    for (int i : out[x])
        rem(queries[i]);
}

```

1.6 Parallel binary search

```

int lo[Q], hi[Q];
queue<int> solve[N];
vector<Query> queries;

```

```

fore (it, 0, 1 + __lg(N)) {
    fore (i, 0, sz(queries))
        if (lo[i] != hi[i]) {
            int mid = (lo[i] + hi[i]) / 2;
            solve[mid].emplace(i);
        }
    fore (x, 0, n) {
        // simulate
        while (!solve[x].empty()) {
            int i = solve[x].front();
            solve[x].pop();
            if (can(queries[i]))
                hi[i] = x;
            else
                lo[i] = x + 1;
        }
    }
}

```

1.7 Mo's algorithm

```

vector<Query> queries;
// N = 1e6, so aprox. sqrt(N) +/- C
uniform_int_distribution<int> dis(970, 1030);
const int blo = dis(rng);
sort(all(queries), [&](Query a, Query b) {
    const int ga = a.l / blo, gb = b.l / blo;
    if (ga == gb)
        return (ga & 1) ? a.r < b.r : a.r > b.r;
    return a.l < b.l;
});
int l = queries[0].l, r = l - 1;
for (Query &q : queries) {
    while (r < q.r)
        add(++r);
    while (r > q.r)
        rem(r--);
    while (l < q.l)
        rem(l++);
    while (l > q.l)
        add(--l);
    ans[q.i] = solve();
}

```

To make it faster, change the order to *hilbert(l, r)*

```

lli hilbert(int x, int y, int pw = 21, int rot = 0) {
    if (pw == 0)
        return 0;
    int hpw = 1 << (pw - 1);
    int k = ((x < hpw ? y < hpw ? 0 : 3 : y < hpw ? 1 : 2) + rot) & 3;
    const int d[4] = {3, 0, 0, 1};
    lli a = 1LL << ((pw << 1) - 2);
    lli b = hilbert(x & (x ^ hpw), y & (y ^ hpw), pw - 1, (rot + d[k]) & 3);
    return k * a + (d[k] ? a - b - 1 : b);
}

```

Mo's algorithm with updates in $\mathcal{O}(n^{\frac{5}{3}})$

- Choose a *block* of size $n^{\frac{2}{3}}$
- Do a normal Mo's algorithm, in the *Query* definition add an extra variable for the *updatesSoFar*
- Sort the queries by the order $(l/block, r/block, updatesSoFar)$
- If the update lies inside the current query, update the data structure properly

```

struct Update {
    int pos, prv, nxt;
};

```

```

void undo(Update &u) {
    if (l <= u.pos && u.pos <= r) {
        rem(u.pos);
        a[u.pos] = u.prv;
        add(u.pos);
    } else {
        a[u.pos] = u.prv;
    }
}

```

- Solve the problem :D

```

l = queries[0].l, r = l - 1, upd = sz(updates) - 1;
for (Query &q : queries) {
    while (upd < q.upd)
        dodo(updates[++upd]);
    while (upd > q.upd)
        undo(updates[upd--]);
    // write down the normal Mo's algorithm
}

```

1.8 Static to dynamic

```

template <class Black, class T>
struct StaticDynamic {
    Black box[LogN];
    vector<T> st[LogN];

    void insert(T &x) {
        int p = 0;
        fore (i, 0, LogN)
            if (st[i].empty()) {
                p = i;
                break;
            }
        st[p].pb(x);
        fore (i, 0, p) {
            st[p].insert(st[p].end(), all(st[i]));
            box[i].clear(), st[i].clear();
        }
        for (auto y : st[p])
            box[p].insert(y);
        box[p].init();
    }
};

```

1.9 Disjoint intervals

```

struct Range {
    int l, r;
    bool operator < (const Range& rge) const {
        return l < rge.l;
    }
};

struct DisjointIntervals : set<Range> {
    void add(Range rge) {
        iterator p = lower_bound(rge), q = p;
        if (p != begin() && rge.l <= (--p)->r)
            rge.l = p->l, --q;
        for (; q != end() && q->l <= rge.r; erase(q++))
            rge.r = max(rge.r, q->r);
        insert(rge);
    }

    void add(int l, int r) {
        add(Range{l, r});
    }
};

```

1.10 Ordered tree

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

```

```

template <class K, class V = null_type>
using ordered_tree = tree<K, V, less<K>, rb_tree_tag,
    tree_order_statistics_node_update>;
// less_equal<K> for multiset, multimap (?)
#define rank order_of_key
#define kth find_by_order

```

1.11 Unordered tree

```

struct chash {
    const uint64_t C = uint64_t(2e18 * 3) + 71;
    const int R = rng();
    uint64_t operator()(uint64_t x) const {
        return __builtin_bswap64((x ^ R) * C);
    };

    template <class K, class V = null_type>
    using unordered_tree = gp_hash_table<K, V, chash>;

```

1.12 D-dimensional Fenwick tree

```

template <class T, int ...N>
struct Fenwick {
    T v = 0;
    void update(T v) { this->v += v; }
    T query() { return v; }
};

template <class T, int N, int ...M>
struct Fenwick<T, N, M...> {
    #define lsb(x) (x & -x)
    Fenwick<T, M...> fenw[N + 1];

    template <typename... Args>
    void update(int i, Args... args) {
        for (; i <= N; i += lsb(i))
            fenw[i].update(args...);
    }

    template <typename... Args>
    T query(int l, int r, Args... args) {
        T v = 0;
        for (; r > 0; r -= lsb(r))
            v += fenw[r].query(args...);
        for (--l; l > 0; l -= lsb(l))
            v -= fenw[l].query(args...);
        return v;
    }
};

```

1.13 Dynamic segment tree

```

struct Dyn {
    int l, r;
    lli sum = 0;
    Dyn *ls, *rs;

    Dyn(int l, int r) : l(l), r(r), ls(0), rs(0) {}

    void pull() {
        sum = (ls ? ls->sum : 0);
        sum += (rs ? rs->sum : 0);
    }

    void update(int p, lli v) {
        if (l == r) {
            sum += v;
            return;
        }
        int m = (l + r) >> 1;
        if (p <= m) {
            if (!ls) ls = new Dyn(l, m);
            ls->update(p, v);

```

```

        } else {
            if (!rs) rs = new Dyn(m + 1, r);
            rs->update(p, v);
        }
        pull();
    }
};

```

```

lli qsum(int ll, int rr) {
    if (rr < l || r < ll || r < l)
        return 0;
    if (ll <= l && r <= rr)
        return sum;
    int m = (l + r) >> 1;
    return (ls ? ls->qsum(ll, rr) : 0) +
        (rs ? rs->qsum(ll, rr) : 0);
}
};

```

1.14 Persistent segment tree

```

struct Per {
    int l, r;
    lli sum = 0;
    Per *ls, *rs;

    Per(int l, int r) : l(l), r(r), ls(0), rs(0) {}

    Per* pull() {
        sum = ls->sum + rs->sum;
        return this;
    }

    void build() {
        if (l == r)
            return;
        int m = (l + r) >> 1;
        (ls = new Per(l, m))->build();
        (rs = new Per(m + 1, r))->build();
        pull();
    }

    Per* update(int p, lli v) {
        if (p < l || r < p)
            return this;
        Per* t = new Per(l, r);
        if (l == r) {
            t->sum = v;
            return t;
        }
        t->ls = ls->update(p, v);
        t->rs = rs->update(p, v);
        return t->pull();
    }

    lli qsum(int ll, int rr) {
        if (r < ll || rr < l)
            return 0;
        if (ll <= l && r <= rr)
            return sum;
        return ls->qsum(ll, rr) + rs->qsum(ll, rr);
    }
};

```

1.15 Wavelet tree

```

struct Wav {
    #define iter int* // vector<int>::iterator
    int lo, hi;
    Wav *ls, *rs;
    vi amt;

    Wav(int lo, int hi) : lo(lo), hi(hi), ls(0), rs(0)

```

```

    {}

void build(iter b, iter e) { // array 1-indexed
    if (lo == hi || b == e)
        return;
    amt.reserve(e - b + 1);
    amt.pb(0);
    int m = (lo + hi) >> 1;
    for (auto it = b; it != e; it++)
        amt.pb(amt.back() + (*it <= m));
    auto p = stable_partition(b, e, [&](int x) {
        return x <= m;
    });
    (ls = new Wav(lo, m))->build(b, p);
    (rs = new Wav(m + 1, hi))->build(p, e);
}

int kth(int l, int r, int k) {
    if (r < l)
        return 0;
    if (lo == hi)
        return lo;
    if (k <= amt[r] - amt[l - 1])
        return ls->kth(amt[l - 1] + 1, amt[r], k);
    return rs->kth(l - amt[l - 1], r - amt[r], k - amt
        [r] + amt[l - 1]);
}

int leq(int l, int r, int mx) {
    if (r < l || mx < lo)
        return 0;
    if (hi <= mx)
        return r - l + 1;
    return ls->leq(amt[l - 1] + 1, amt[r], mx) +
        rs->leq(l - amt[l - 1], r - amt[r], mx);
}
};

```

1.16 Li Chao tree

```

struct Fun {
    lli m = 0, c = inf;
    lli operator()(lli x) const { return m * x + c; }
};

struct LiChao {
    Fun f;
    lli l, r;
    LiChao *ls, *rs;

    LiChao(lli l, lli r) : l(l), r(r), ls(0), rs(0) {}

    void add(Fun &g) {
        if (f(l) <= g(l) && f(r) <= g(r))
            return;
        if (g(l) < f(l) && g(r) < f(r)) {
            f = g;
            return;
        }
        lli m = (l + r) >> 1;
        if (g(m) < f(m))
            swap(f, g);
        if (g(l) <= f(l))
            ls = ls ? (ls->add(g), ls) : new LiChao(l, m, g);
        else
            rs = rs ? (rs->add(g), rs) : new LiChao(m + 1, r,
                g);
    }

    lli query(lli x) {
        if (l == r)

```

```

        return f(x);
        lli m = (l + r) >> 1;
        if (x <= m)
            return min(f(x), ls ? ls->query(x) : inf);
        return min(f(x), rs ? rs->query(x) : inf);
    }
};

```

1.17 Explicit Treap

```

typedef struct Node* Treap;
struct Node {
    Treap ch[2] = {0, 0}, p = 0;
    uint32_t pri = rng();
    int sz = 1, rev = 0;
    int val, sum = 0;

    void push() {
        if (rev) {
            swap(ch[0], ch[1]);
            for (auto ch : ch) if (ch != 0) {
                ch->rev ^= 1;
            }
            rev = 0;
        }
    }

    Treap pull() {
        #define gsz(t) (t ? t->sz : 0)
        #define gsum(t) (t ? t->sum : 0)
        sz = 1, sum = val;
        for (auto ch : ch) if (ch != 0) {
            ch->push();
            sz += ch->sz;
            sum += ch->sum;
            ch->p = this;
        }
        p = 0;
        return this;
    }

    Node(int val) : val(val) {}
};

pair<Treap, Treap> split(Treap t, int val) {
    // <= val goes to the left, > val to the right
    if (!t)
        return {t, t};
    t->push();
    if (val < t->val) {
        auto p = split(t->ch[0], val);
        t->ch[0] = p.s;
        return {p.f, t->pull()};
    } else {
        auto p = split(t->ch[1], val);
        t->ch[1] = p.f;
        return {t->pull(), p.s};
    }
}

Treap merge(Treap l, Treap r) {
    if (!l || !r)
        return l ? l : r;
    l->push(), r->push();
    if (l->pri > r->pri)
        return l->ch[1] = merge(l->ch[1], r), l->pull();
    else
        return r->ch[0] = merge(l, r->ch[0]), r->pull();
}

Treap qkth(Treap t, int k) { // 0-indexed

```

```

    if (!t)
        return t;
    t->push();
    int sz = gsz(t->ch[0]);
    if (sz == k)
        return t;
    return k < sz ? qkth(t->ch[0], k) : qkth(t->ch[1], k
        - sz - 1);
}

int qrank(Treap t, int val) { // 0-indexed
    if (!t)
        return -1;
    t->push();
    if (val < t->val)
        return qrank(t->ch[0], val);
    if (t->val == val)
        return gsz(t->ch[0]);
    return gsz(t->ch[0]) + qrank(t->ch[1], val) + 1;
}

Treap insert(Treap t, int val) {
    auto p1 = split(t, val);
    auto p2 = split(p1.f, val - 1);
    return merge(p2.f, merge(new Node(val), p1.s));
}

Treap erase(Treap t, int val) {
    auto p1 = split(t, val);
    auto p2 = split(p1.f, val - 1);
    return merge(p2.f, p1.s);
}

```

1.18 Implicit Treap

```

pair<Treap, Treap> splitsz(Treap t, int sz) {
    // <= sz goes to the left, > sz to the right
    if (!t)
        return {t, t};
    t->push();
    if (sz <= gsz(t->ch[0])) {
        auto p = splitsz(t->ch[0], sz);
        t->ch[0] = p.s;
        return {p.f, t->pull()};
    } else {
        auto p = splitsz(t->ch[1], sz - gsz(t->ch[0]) - 1);
        ;
        t->ch[1] = p.f;
        return {t->pull(), p.s};
    }
}

int pos(Treap t) {
    int sz = gsz(t->ch[0]);
    for (; t->p; t = t->p) {
        Treap p = t->p;
        if (p->ch[1] == t)
            sz += gsz(p->ch[0]) + 1;
    }
    return sz + 1;
}

```

1.19 Splay tree

```

typedef struct Node* Splay;
struct Node {
    Splay ch[2] = {0, 0}, p = 0;
    bool rev = 0;
    int sz = 1;

    int dir() {
        if (!p) return -2; // root of LCT component

```

```

        if (p->ch[0] == this) return 0; // left child
        if (p->ch[1] == this) return 1; // right child
        return -1; // root of current splay tree
    }

```

```

bool isRoot() { return dir() < 0; }

```

```

friend void add(Splay u, Splay v, int d) {
    if (v) v->p = u;
    if (d >= 0) u->ch[d] = v;
}

```

```

void rotate() {
    // assume p and p->p propagated
    assert(!isRoot());
    int x = dir();
    Splay g = p;
    add(g->p, this, g->dir());
    add(g, ch[x ^ 1], x);
    add(this, g, x ^ 1);
    g->pull(), pull();
}

```

```

void splay() {
    // bring this to top of splay tree
    while (!isRoot() && !p->isRoot()) {
        p->p->push(), p->push(), push();
        dir() == p->dir() ? p->rotate() : rotate();
        rotate();
    }
    if (!isRoot()) p->push(), push(), rotate();
    push(), pull();
}

```

```

void pull() {
    #define gsz(t) (t ? t->sz : 0)
    sz = 1 + gsz(ch[0]) + gsz(ch[1]);
}

```

```

void push() {
    if (rev) {
        swap(ch[0], ch[1]);
        for (auto ch : ch) if (ch) {
            ch->rev ^= 1;
        }
        rev = 0;
    }
}

```

```

void vsub(Splay t, bool add) {}
};

```

2 Graphs

2.1 Tarjan algorithm (SCC)

```

int tin[N], fup[N];
bitset<N> still;
stack<int> stk;
int timer = 0;

void tarjan(int u) {
    tin[u] = fup[u] = ++timer;
    still[u] = true;
    stk.push(u);
    for (int v : graph[u]) {
        if (!tin[v])
            tarjan(v);
        if (still[v])
            fup[u] = min(fup[u], fup[v]);
    }
    if (fup[u] == tin[u]) {

```

```

int v;
do {
    v = stk.top();
    stk.pop();
    still[v] = false;
    // u and v are in the same scc
} while (v != u);
}
}

```

2.2 Kosaraju algorithm (SCC)

```

int scc[N], k = 0;
char vis[N];
vi order;

void dfs1(int u) {
    vis[u] = 1;
    for (int v : graph[u])
        if (vis[v] != 1)
            dfs1(v);
    order.pb(u);
}

void dfs2(int u, int k) {
    vis[u] = 2, scc[u] = k;
    for (int v : rgraph[u]) // reverse graph
        if (vis[v] != 2)
            dfs2(v, k);
}

void kosaraju() {
    for (u, 1, n + 1)
        if (vis[u] != 1)
            dfs1(u);
    reverse(all(order));
    for (int u : order)
        if (vis[u] != 2)
            dfs2(u, ++k);
}

```

2.3 Two Sat

```

struct TwoSat {
    int n;
    vector<vi> imp;

    TwoSat(int _n) : n(_n + 1), imp(2 * n) {}

    void either(int a, int b) {
        a = max(2 * a, -1 - 2 * a);
        b = max(2 * b, -1 - 2 * b);
        imp[a ^ 1].pb(b);
        imp[b ^ 1].pb(a);
    }

    void implies(int a, int b) { either(~a, b); }
    void setVal(int a) { either(a, a); }

    vi solve() {
        int k = sz(imp);
        vi s, b, id(sz(imp));

        function<void(int)> dfs = [&](int u) {
            b.pb(id[u] = sz(s));
            s.pb(u);
            for (int v : imp[u]) {
                if (!id[v]) dfs(v);
                else while (id[v] < b.back()) b.pop_back();
            }
            if (id[u] == b.back())
                for (b.pop_back(), ++k; id[u] < sz(s); s.

```

```

                pop_back())
                    id[s.back()] = k;
        };

        for (u, 0, sz(imp))
            if (!id[u]) dfs(u);

        vi val(n);
        for (u, 0, n) {
            int x = 2 * u;
            if (id[x] == id[x ^ 1])
                return {};
            val[u] = id[x] < id[x ^ 1];
        }
        return val;
    }
};

```

2.4 Topological sort

```

vi order;
int indeg[N];

void topsort() { // first fill the indeg[]
    queue<int> qu;
    for (u, 1, n + 1)
        if (indeg[u] == 0)
            qu.push(u);
    while (!qu.empty()) {
        int u = qu.front();
        qu.pop();
        order.pb(u);
        for (int v : graph[u])
            if (--indeg[v] == 0)
                qu.push(v);
    }
}

```

2.5 Cutpoints and Bridges

```

int tin[N], fup[N], timer = 0;

void findWeakness(int u, int p = 0) {
    tin[u] = fup[u] = ++timer;
    int children = 0;
    for (int v : graph[u]) if (v != p) {
        if (!tin[v]) {
            ++children;
            findWeakness(v, u);
            fup[u] = min(fup[u], fup[v]);
            if (fup[v] >= tin[u] && p) // u is a cutpoint
                if (fup[v] > tin[u]) // bridge u -> v
                    ;
            fup[u] = min(fup[u], tin[v]);
        }
        if (!p && children > 1) // u is a cutpoint
            ;
    }
}

```

2.6 Detect a cycle

```

bool cycle(int u) {
    vis[u] = 1;
    for (int v : graph[u]) {
        if (vis[v] == 1)
            return true;
        if (!vis[v] && cycle(v))
            return true;
    }
    vis[u] = 2;
    return false;
}

```


2.7 Euler tour for Mo's in a tree

Mo's in a tree, extended euler tour $\text{tin}[u] = ++\text{timer}$, $\text{tout}[u]$

$= ++\text{timer}$

- $u = \text{lca}(u, v)$, $\text{query}(\text{tin}[u], \text{tin}[v])$
- $u \neq \text{lca}(u, v)$, $\text{query}(\text{tout}[u], \text{tin}[v]) + \text{query}(\text{tin}[\text{lca}], \text{tin}[\text{lca}])$

2.8 Lowest common ancestor (LCA)

```
const int LogN = 1 + __lg(N);
int par[LogN][N], dep[N];

void dfs(int u, int par[]) {
    for (int v : graph[u])
        if (v != par[u]) {
            par[v] = u;
            dep[v] = dep[u] + 1;
            dfs(v, par);
        }
}

int lca(int u, int v) {
    if (dep[u] > dep[v])
        swap(u, v);
    for (k, LogN, 0)
        if (dep[v] - dep[u] >= (1 << k))
            v = par[k][v];
    if (u == v)
        return u;
    for (k, LogN, 0)
        if (par[k][v] != par[k][u])
            u = par[k][u], v = par[k][v];
    return par[0][u];
}

int dist(int u, int v) {
    return dep[u] + dep[v] - 2 * dep[lca(u, v)];
}

void init(int r) {
    dfs(r, par[0]);
    for (k, 1, LogN)
        for (u, 1, n + 1)
            par[k][u] = par[k - 1][par[k - 1][u]];
}
```

2.9 Isomorphism

```
lli f(lli x) {
    // K * n <= 9e18
    static uniform_int_distribution<lli> uid(1, K);
    if (!mp.count(x))
        mp[x] = uid(rng);
    return mp[x];
}

lli hsh(int u, int p = 0) {
    dp[u] = h[u] = 0;
    for (int v : graph[u]) {
        if (v == p)
            continue;
        dp[u] += hsh(v, u);
    }
    return h[u] = f(dp[u]);
}
```

2.10 Guni

```
int cnt[C], color[N];
int sz[N];

int guni(int u, int p = 0) {
    sz[u] = 1;
    for (int &v : graph[u]) if (v != p) {
```

```
        sz[u] += guni(v, u);
        if (sz[v] > sz[graph[u][0]] || p == graph[u][0])
            swap(v, graph[u][0]);
    }
    return sz[u];
}
```

```
void add(int u, int p, int x, bool skip) {
    cnt[color[u]] += x;
    for (int i = skip; i < sz(graph[u]); i++) // don't
        change it with a fore!!!
        if (graph[u][i] != p)
            add(graph[u][i], u, x, 0);
}

void solve(int u, int p, bool keep = 0) {
    fore (i, sz(graph[u]), 0)
        if (graph[u][i] != p)
            solve(graph[u][i], u, !i);
    add(u, p, +1, 1); // add
    // now cnt[i] has how many times the color i appears
    // in the subtree of u
    if (!keep) add(u, p, -1, 0); // remove
}
```

2.11 Centroid decomposition

```
int cdp[N], sz[N];
bitset<N> rem;

int dfsz(int u, int p = 0) {
    sz[u] = 1;
    for (int v : graph[u])
        if (v != p && !rem[v])
            sz[u] += dfsz(v, u);
    return sz[u];
}

int centroid(int u, int n, int p = 0) {
    for (int v : graph[u])
        if (v != p && !rem[v] && 2 * sz[v] > n)
            return centroid(v, n, u);
    return u;
}

void solve(int u, int p = 0) {
    cdp[u] = centroid(u, dfsz(u)) = p;
    rem[u] = true;
    for (int v : graph[u])
        if (!rem[v])
            solve(v, u);
}
```

2.12 Heavy-light decomposition

```
int par[N], dep[N], sz[N], head[N], pos[N], who[N],
timer = 0;
Lazy* tree;

int dfs(int u) {
    sz[u] = 1, head[u] = 0;
    for (int &v : graph[u]) if (v != par[u]) {
        par[v] = u;
        dep[v] = dep[u] + 1;
        sz[u] += dfs(v);
        if (sz[v] > sz[graph[u][0]])
            swap(v, graph[u][0]);
    }
    return sz[u];
}

void hld(int u, int h) {
    head[u] = h, pos[u] = ++timer, who[timer] = u;
```

```

    for (int &v : graph[u])
        if (v != par[u])
            hld(v, v == graph[u][0] ? h : v);
}

template <class F>
void processPath(int u, int v, F f) {
    for (; head[u] != head[v]; v = par[head[v]]) {
        if (dep[head[u]] > dep[head[v]]) swap(u, v);
        f(pos[head[v]], pos[v]);
    }
    if (dep[u] > dep[v]) swap(u, v);
    if (u != v) f(pos[graph[u][0]], pos[v]);
    f(pos[u], pos[u]); // only if hld over vertices
}

void updatePath(int u, int v, lli z) {
    processPath(u, v, [&](int l, int r) {
        tree->update(l, r, z);
    });
}

lli queryPath(int u, int v) {
    lli sum = 0;
    processPath(u, v, [&](int l, int r) {
        sum += tree->qsum(l, r);
    });
    return sum;
}

```

2.13 Link-Cut tree

```

void access(Splay u) {
    // puts u on the preferred path, splay (right
    // subtree is empty)
    for (Splay v = u, pre = NULL; v; v = v->p) {
        v->splay(); // now pull virtual children
        if (pre) v->vsub(pre, false);
        if (v->ch[1]) v->vsub(v->ch[1], true);
        v->ch[1] = pre, v->pull(), pre = v;
    }
    u->splay();
}

void rootify(Splay u) {
    // make u root of LCT component
    access(u), u->rev ^= 1, access(u);
    assert(!u->ch[0] && !u->ch[1]);
}

Splay lca(Splay u, Splay v) {
    if (u == v) return u;
    access(u), access(v);
    if (!u->p) return NULL;
    return u->splay(), u->p ? u :
}

bool connected(Splay u, Splay v) {
    return lca(u, v) != NULL;
}

void link(Splay u, Splay v) { // make u parent of v
    if (!connected(u, v)) {
        rootify(v), access(u);
        add(v, u, 0), v->pull();
    }
}

void cut(Splay u) {
    // cut u from its parent
    access(u);

```

```

    u->ch[0]->p = u->ch[0] = NULL;
    u->pull();
}

void cut(Splay u, Splay v) { // if u, v are adjacent
    // in the tree
    cut(depth(u) > depth(v) ? u : v);
}

int depth(Splay u) {
    access(u);
    return gsz(u->ch[0]);
}

Splay getRoot(Splay u) { // get root of LCT component
    access(u);
    while (u->ch[0]) u = u->ch[0], u->push();
    return access(u), u;
}

Splay ancestor(Splay u, int k) {
    // get k-th parent on path to root
    k = depth(u) - k;
    assert(k >= 0);
    for (; u->push(); ) {
        int sz = gsz(u->ch[0]);
        if (sz == k) return access(u), u;
        if (sz < k) k -= sz + 1, u = u->ch[1];
        else u = u->ch[0];
    }
    assert(0);
}

Splay query(Splay u, Splay v) {
    return rootify(u), access(v), v;
}

```

3 Flows

3.1 Dinic $\mathcal{O}(\min(E \cdot \text{flow}, V^2 E))$

If the network is massive, try to compress it by looking for patterns.

```

template <class F>
struct Dinic {
    struct Edge {
        int v, inv;
        F cap, flow;
        Edge(int v, F cap, int inv) : v(v), cap(cap), flow
            (0), inv(inv) {}
    };

    F eps = (F) 1e-9;
    int s, t, n, m = 0;
    vector< vector<Edge> > g;
    vi dist, ptr;

    Dinic(int n) : n(n), g(n), dist(n), ptr(n), s(n - 2)
        , t(n - 1) {}

    void add(int u, int v, F cap) {
        g[u].pb(Edge(v, cap, sz(g[v])));
        g[v].pb(Edge(u, 0, sz(g[u]) - 1));
        m += 2;
    }

    bool bfs() {
        fill(all(dist), -1);
        queue<int> qu({s});
        dist[s] = 0;
        while (sz(qu) && dist[t] == -1) {
            int u = qu.front();

```

```

    qu.pop();
    for (Edge &e : g[u]) if (dist[e.v] == -1)
        if (e.cap - e.flow > eps) {
            dist[e.v] = dist[u] + 1;
            qu.push(e.v);
        }
    }
    return dist[t] != -1;
}

F dfs(int u, F flow = numeric_limits<F>::max()) {
    if (flow <= eps || u == t)
        return max<F>(0, flow);
    for (int &i = ptr[u]; i < sz(g[u]); i++) {
        Edge &e = g[u][i];
        if (e.cap - e.flow > eps && dist[u] + 1 == dist[e.v]) {
            F pushed = dfs(e.v, min<F>(flow, e.cap - e.flow));
            if (pushed > eps) {
                e.flow += pushed;
                g[e.v][e.inv].flow -= pushed;
                return pushed;
            }
        }
    }
    return 0;
}

F maxFlow() {
    F flow = 0;
    while (bfs()) {
        fill(all(ptr), 0);
        while (F pushed = dfs(s))
            flow += pushed;
    }
    return flow;
}
};

```

3.2 Min cost flow $\mathcal{O}(\min(E \cdot \text{flow}, V^2 E))$

If the network is massive, try to compress it by looking for patterns.

```

template <class C, class F>
struct Mcmf {
    struct Edge {
        int u, v, inv;
        F cap, flow;
        C cost;
        Edge(int u, int v, C cost, F cap, int inv) : u(u),
            v(v), cost(cost), cap(cap), flow(0), inv(inv) {}
    };

    F eps = (F) 1e-9;
    int s, t, n, m = 0;
    vector< vector<Edge> > g;
    vector<Edge*> prev;
    vector<C> cost;
    vi state;

    Mcmf(int n) : n(n), g(n), cost(n), state(n), prev(n),
        s(n - 2), t(n - 1) {}

    void add(int u, int v, C cost, F cap) {
        g[u].pb(Edge(u, v, cost, cap, sz(g[v])));
        g[v].pb(Edge(v, u, -cost, 0, sz(g[u]) - 1));
        m += 2;
    }

    bool bfs() {

```

```

        fill(all(state), 0);
        fill(all(cost), numeric_limits<C>::max());
        deque<int> qu;
        qu.push_back(s);
        state[s] = 1, cost[s] = 0;
        while (sz(qu)) {
            int u = qu.front(); qu.pop_front();
            state[u] = 2;
            for (Edge &e : g[u]) if (e.cap - e.flow > eps)
                if (cost[u] + e.cost < cost[e.v]) {
                    cost[e.v] = cost[u] + e.cost;
                    prev[e.v] = &e;
                    if (state[e.v] == 2 || (sz(qu) && cost[qu.front()] > cost[e.v]))
                        qu.push_front(e.v);
                    else if (state[e.v] == 0)
                        qu.push_back(e.v);
                    state[e.v] = 1;
                }
        }
        return cost[t] != numeric_limits<C>::max();
    }

    pair<C, F> minCostFlow() {
        C cost = 0; F flow = 0;
        while (bfs()) {
            F pushed = numeric_limits<F>::max();
            for (Edge* e = prev[t]; e != nullptr; e = prev[e->u])
                pushed = min(pushed, e->cap - e->flow);
            for (Edge* e = prev[t]; e != nullptr; e = prev[e->u]) {
                e->flow += pushed;
                g[e->v][e->inv].flow -= pushed;
                cost += e->cost * pushed;
            }
            flow += pushed;
        }
        return make_pair(cost, flow);
    }
};

```

3.3 Hopcroft-Karp $\mathcal{O}(E\sqrt{V})$

```

struct HopcroftKarp {
    int n, m = 0;
    vector<vi> g;
    vi dist, match;

    HopcroftKarp(int _n) : n(_n + 5), g(n), dist(n),
        match(n, 0) {} // 1-indexed!!

    void add(int u, int v) {
        g[u].pb(v), g[v].pb(u);
        m += 2;
    }

    bool bfs() {
        queue<int> qu;
        fill(all(dist), -1);
        for (u = 1, n)
            if (!match[u])
                dist[u] = 0, qu.push(u);
        while (!qu.empty()) {
            int u = qu.front(); qu.pop();
            for (int v : g[u])
                if (dist[match[v]] == -1) {
                    dist[match[v]] = dist[u] + 1;
                    if (match[v])
                        qu.push(match[v]);
                }
        }
    }
}

```

```

    return dist[0] != -1;
}

bool dfs(int u) {
    for (int v : g[u])
        if (!match[v] || (dist[u] + 1 == dist[match[v]]
            && dfs(match[v]))) {
            match[u] = v, match[v] = u;
            return 1;
        }
    dist[u] = 1 << 30;
    return 0;
}

int maxMatching() {
    int tot = 0;
    while (bfs())
        for (u, 1, n)
            tot += match[u] ? 0 : dfs(u);
    return tot;
}
};

```

3.4 Hungarian $\mathcal{O}(N^3)$

n jobs, m people

```

template <class C>
pair<C, vi> Hungarian(vector< vector<C> > &a) {
    int n = sz(a), m = sz(a[0]), p, q, j, k; // n <= m
    vector<C> fx(n, numeric_limits<C>::min()), fy(m, 0);
    vi x(n, -1), y(m, -1);
    for (i, 0, n)
        for (j, 0, m)
            fx[i] = max(fx[i], a[i][j]);
    for (i, 0, n) {
        vi t(m, -1), s(n + 1, i);
        for (p = q = 0; p <= q && x[i] < 0; p++)
            for (k = s[p], j = 0; j < m && x[i] < 0; j++)
                if (abs(fx[k] + fy[j] - a[k][j]) < eps && t[j]
                    < 0) {
                    s[++q] = y[j], t[j] = k;
                    if (s[q] < 0) for (p = j; p >= 0; j = p)
                        y[j] = k = t[j], p = x[k], x[k] = j;
                }
        if (x[i] < 0) {
            C d = numeric_limits<C>::max();
            for (k, 0, q + 1)
                for (j, 0, m) if (t[j] < 0)
                    d = min(d, fx[s[k]] + fy[j] - a[s[k]][j]);
            for (j, 0, m)
                fy[j] += (t[j] < 0 ? 0 : d);
            for (k, 0, q + 1)
                fx[s[k]] -= d;
            i--;
        }
    }
    C cost = 0;
    for (i, 0, n) cost += a[i][x[i]];
    return make_pair(cost, x);
}

```

4 Strings

4.1 Hash

```

vi mod = {999727999, 99992867, 100000123, 100002193,
    100003211, 100008223, 100009999, 100027163,
    107077777};

struct H : array<lli, 2> {
    #define oper(op) friend H operator op (H a, H b) { \
        for (i, 0, sz(a)) a[i] = (a[i] op b[i] + mod[i]) % \
            mod[i]; \
        return a; }
}

```

```

    oper(+) oper(-) oper(*)
} pw[N], ipw[N];

struct Hash {
    vector<H> h;

    Hash(string &s) : h(sz(s) + 1) {
        for (i, 0, sz(s)) {
            int x = s[i] - 'a' + 1;
            h[i + 1] = h[i] + pw[i] * H{x, x};
        }

        H cut(int l, int r) {
            return (h[r + 1] - h[l]) * ipw[l];
        }
    };
}

```

```

const int P = uniform_int_distribution<int>(27, min(
    mod[0], mod[1]) - 1)(rng);
pw[0] = ipw[0] = {1, 1};
H Q = {inv(P, mod[0]), inv(P, mod[1])};
for (i, 1, N) {
    pw[i] = pw[i - 1] * H{P, P};
    ipw[i] = ipw[i - 1] * Q;
}

```

// Save {l, r} in the struct and when you do a cut

```

H merge(vector<H> &cuts) {
    F f = {0, 0};
    for (i, sz(cuts), 0) {
        F g = cuts[i];
        f = g + f * pw[g.r - g.l + 1];
    }
    return f;
}

```

4.2 KMP

period = $n - p[n - 1]$, period(abcabc) = 3, $n \bmod \text{period} \equiv 0$

```

vi lps(string &s) {
    vi p(sz(s), 0);
    int j = 0;
    for (i, 1, sz(s)) {
        while (j && s[i] != s[j])
            j = p[j - 1];
        j += (s[i] == s[j]);
        p[i] = j;
    }
    return p;
}

// how many times t occurs in s
int kmp(string &s, string &t) {
    vi p = lps(t);
    int j = 0, tot = 0;
    for (i, 0, sz(s)) {
        while (j && s[i] != t[j])
            j = p[j - 1];
        if (s[i] == t[j])
            j++;
        if (j == sz(t))
            tot++; // pos: i - sz(t) + 1;
    }
    return tot;
}

```

4.3 KMP automaton

```

int go[N][A];

void kmpAutomaton(string &s) {
    s += "$";
    vi p = lps(s);
}

```

```

fore (i, 0, sz(s))
    fore (c, 0, A) {
        if (i && s[i] != 'a' + c)
            go[i][c] = go[p[i - 1]][c];
        else
            go[i][c] = i + ('a' + c == s[i]);
    }
s.pop_back();
}

```

4.4 Z algorithm

```

vi zf(string &s) {
    vi z(sz(s), 0);
    for (int i = 1, l = 0, r = 0; i < sz(s); i++) {
        if (i <= r)
            z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < sz(s) && s[i + z[i]] == s[z[i]])
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    return z;
}

```

4.5 Manacher algorithm

```

vector<vi> manacher(string &s) {
    vector<vi> pal(2, vi(sz(s), 0));
    fore (k, 0, 2) {
        int l = 0, r = 0;
        fore (i, 0, sz(s)) {
            int t = r - i + !k;
            if (i < r)
                pal[k][i] = min(t, pal[k][l + t]);
            int p = i - pal[k][i], q = i + pal[k][i] - !k;
            while (p >= 1 && q + 1 < sz(s) && s[p - 1] == s[q + 1])
                ++pal[k][i], --p, ++q;
            if (q > r)
                l = p, r = q;
        }
    }
    return pal;
}

```

4.6 Suffix array

- Duplicates $\sum_{i=1}^n lcp[i]$
- Longest Common Substring of various strings
Add *notUsed* characters between strings, i.e. $a+\$+b+\#+c$
Use two-pointers to find a range $[l, r]$ such that all *notUsed* characters are present, then $query(lcp[l + 1], \dots, lcp[r])$ for that window is the common length.

```

struct SuffixArray {
    int n;
    string s;
    vi sa, lcp;

    SuffixArray(string &s) : n(sz(s) + 1), s(s), sa(n),
        lcp(n) {
        vi top(max(256, n)), rk(n);
        fore (i, 0, n)
            top[rk[i] = s[i] & 255]++;
        partial_sum(all(top), top.begin());
        fore (i, 0, n)
            sa[--top[rk[i]]] = i;
        vi sb(n);
        for (int len = 1, j; len < n; len <= 1) {
            fore (i, 0, n) {
                j = (sa[i] - len + n) % n;
                sb[top[rk[j]]++] = j;
            }
        }
    }
}

```

```

sa[sb[top[0] = 0]] = j = 0;
fore (i, 1, n) {
    if (rk[sb[i]] != rk[sb[i - 1]] || rk[sb[i] +
        len] != rk[sb[i - 1] + len])
        top[++j] = i;
    sa[sb[i]] = j;
}
copy(all(sa), rk.begin());
copy(all(sb), sa.begin());
if (j >= n - 1)
    break;
}
for (int i = 0, j = rk[lcp[0] = 0], k = 0; i < n -
    1; i++, k++)
    while (k >= 0 && s[i] != s[sa[j - 1] + k])
        lcp[j] = k--, j = rk[sa[j] + 1];
}

char at(int i, int j) {
    int k = sa[i] + j;
    return k < n ? s[k] : 'z' + 1;
}

int count(string &t) {
    ii lo(0, n - 1), hi(0, n - 1);
    fore (i, 0, sz(t)) {
        while (lo.f + 1 < lo.s) {
            int mid = (lo.f + lo.s) / 2;
            (at(mid, i) < t[i] ? lo.f : lo.s) = mid;
        }
        while (hi.f + 1 < hi.s) {
            int mid = (hi.f + hi.s) / 2;
            (t[i] < at(mid, i) ? hi.s : hi.f) = mid;
        }
        int p1 = (at(lo.f, i) == t[i] ? lo.f : lo.s);
        int p2 = (at(hi.s, i) == t[i] ? hi.s : hi.f);
        if (at(p1, i) != t[i] || at(p2, i) != t[i] || p1
            > p2)
            return 0;
        lo = hi = ii(p1, p2);
    }
    return lo.s - lo.f + 1;
}
}

```

4.7 Suffix automaton

- $sam[u].len - sam[sam[u].link].len = \text{distinct strings}$
- Number of different substrings (dp)

$$diff(u) = 1 + \sum_{v \in trie[u]} diff(v)$$

- Total length of all different substrings (2 x dp)

$$totLen(u) = \sum_{v \in trie[u]} diff(v) + totLen(v)$$

- Leftmost occurrence $trie[u].pos = trie[u].len - 1$
if it is **clone** then $trie[clone].pos = trie[q].pos$
- All occurrence positions
- Smallest cyclic shift
Construct sam of $s + s$, find the lexicographically smallest path of $sz(s)$
- Shortest non-appearing string

$$nonAppearing(u) = \min_{v \in trie[u]} nonAppearing(v) + 1$$

```

struct SuffixAutomaton {
    struct Node : map<char, int> {
        int link = -1, len = 0;
    };
}

```

```

vector<Node> trie;
int last;

SuffixAutomaton() { last = newNode(); }

int newNode() {
    trie.pb({});
    return sz(trie) - 1;
}

void extend(char c) {
    int u = newNode();
    trie[u].len = trie[last].len + 1;
    int p = last;
    while (p != -1 && !trie[p].count(c)) {
        trie[p][c] = u;
        p = trie[p].link;
    }
    if (p == -1)
        trie[u].link = 0;
    else {
        int q = trie[p][c];
        if (trie[p].len + 1 == trie[q].len)
            trie[u].link = q;
        else {
            int clone = newNode();
            trie[clone] = trie[q];
            trie[clone].len = trie[p].len + 1;
            while (p != -1 && trie[p][c] == q) {
                trie[p][c] = clone;
                p = trie[p].link;
            }
            trie[q].link = trie[u].link = clone;
        }
    }
    last = u;
}

string kthSubstring(lli kth, int u = 0) {
    // number of different substrings (dp)
    string s = "";
    while (kth > 0)
        for (auto &[c, v] : trie[u]) {
            if (kth <= diff(v)) {
                s.pb(c), kth--, u = v;
                break;
            }
            kth -= diff(v);
        }
    return s;
}

void occurs() {
    // trie[u].occ = 1, trie[clone].occ = 0
    vi who;
    for (u, 1, sz(trie))
        who.pb(u);
    sort(all(who), [&](int u, int v) {
        return trie[u].len > trie[v].len;
    });
    for (int u : who) {
        int l = trie[u].link;
        trie[l].occ += trie[u].occ;
    }
}

lli queryOccurrences(string &s, int u = 0) {
    for (char c : s) {
        if (!trie[u].count(c))
            return 0;
    }
}

```

```

        u = trie[u][c];
    }
    return trie[u].occ;
}

int longestCommonSubstring(string &s, int u = 0) {
    int mx = 0, clen = 0;
    for (char c : s) {
        while (u && !trie[u].count(c)) {
            u = trie[u].link;
            clen = trie[u].len;
        }
        if (trie[u].count(c))
            u = trie[u][c], clen++;
        mx = max(mx, clen);
    }
    return mx;
}

string smallestCyclicShift(int n, int u = 0) {
    string s = "";
    for (i, 0, n) {
        char c = trie[u].begin()->f;
        s += c;
        u = trie[u][c];
    }
    return s;
}

int leftmost(string &s, int u = 0) {
    for (char c : s) {
        if (!trie[u].count(c))
            return -1;
        u = trie[u][c];
    }
    return trie[u].pos - sz(s) + 1;
}

Node& operator [](int u) {
    return trie[u];
}
};

```

4.8 Aho corasick

```

struct AhoCorasick {
    struct Node : map<char, int> {
        int link = 0, out = 0;
        int cnt = 0, isw = 0;
    };

    vector<Node> trie;

    AhoCorasick() { newNode(); }

    int newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    void insert(string &s, int u = 0) {
        for (char c : s) {
            if (!trie[u][c])
                trie[u][c] = newNode();
            u = trie[u][c];
        }
        trie[u].cnt++, trie[u].isw = 1;
    }

    int go(int u, char c) {
        while (u && !trie[u].count(c))
            u = trie[u].link;
    }
}

```

```

    return trie[u][c];
}

void pushLinks() {
    queue<int> qu;
    qu.push(0);
    while (!qu.empty()) {
        int u = qu.front();
        qu.pop();
        for (auto &[c, v] : trie[u]) {
            int l = (trie[v].link == u ? go(trie[u].link, c) : 0);
            trie[v].cnt += trie[l].cnt;
            trie[v].out = trie[l].isw ? l : trie[l].out;
            qu.push(v);
        }
    }

    int match(string &s, int u = 0) {
        int ans = 0;
        for (char c : s) {
            u = go(u, c);
            ans += trie[u].cnt;
            for (int x = u; x != 0; x = trie[x].out)
                // pass over all elements of the implicit vector
        }
        return ans;
    }

    Node& operator [](int u) {
        return trie[u];
    }
};

```

4.9 Eertree

```

struct Eertree {
    struct Node : map<char, int> {
        int link = 0, len = 0;
    };

    vector<Node> trie;
    string s = "$";
    int last;

    Eertree() {
        last = newNode(), newNode();
        trie[0].link = 1, trie[1].len = -1;
    }

    int newNode() {
        trie.pb({});
        return sz(trie) - 1;
    }

    int go(int u) {
        while (s[sz(s) - trie[u].len - 2] != s.back())
            u = trie[u].link;
        return u;
    }

    void extend(char c) {
        s += c;
        int u = go(last);
        if (!trie[u][c]) {
            int v = newNode();
            trie[v].len = trie[u].len + 2;
            trie[v].link = trie[go(trie[u].link)][c];
            trie[u][c] = v;
        }
    }
};

```

```

    }
    last = trie[u][c];
}

Node& operator [](int u) {
    return trie[u];
}
};

```

5 Dynamic Programming

5.1 All submasks of a mask

```
for (int B = A; B > 0; B = (B - 1) & A)
```

5.2 Matrix Chain Multiplication

```

int dp(int l, int r) {
    if (l > r)
        return 0LL;
    int &ans = mem[l][r];
    if (!done[l][r]) {
        done[l][r] = true, ans = inf;
        for (k, l, r + 1) // split in [l, k] [k + 1, r]
            ans = min(ans, dp(l, k) + dp(k + 1, r) + add);
    }
    return ans;
}

```

5.3 Digit DP

Counts the amount of numbers in $[l, r]$ such are divisible by k . (flag *nonzero* is for different lengths)
It can be reduced to $dp(i, x, small)$, and has to be solve like $f(r) - f(l - 1)$

```

#define state [i][x][small][big][nonzero]
int dp(int i, int x, bool small, bool big, bool nonzero) {
    if (i == sz(r))
        return x % k == 0 && nonzero;
    int &ans = mem[state];
    if (done[state] != timer) {
        done[state] = timer;
        ans = 0;
        int lo = small ? 0 : l[i] - '0';
        int hi = big ? 9 : r[i] - '0';
        for (y, lo, max(lo, hi) + 1) {
            bool small2 = small | (y > lo);
            bool big2 = big | (y < hi);
            bool nonzero2 = nonzero | (x > 0);
            ans += dp(i + 1, (x * 10 + y) % k, small2, big2, nonzero2);
        }
    }
    return ans;
}

```

5.4 Knapsack 0/1

```

for (auto &cur : items)
    for (w, W + 1, cur.w) // [cur.w, W]
        umax(dp[w], dp[w - cur.w] + cur.cost);

```

5.5 Convex Hull Trick $\mathcal{O}(n^2) \Rightarrow \mathcal{O}(n)$

$dp[i] = \min_{j < i} (dp[j] + b[j] * a[i])$
 $dp[i][j] = \min_{k < j} (dp[i - 1][k] + b[k] * a[j])$
 $b[j] \geq b[j + 1]$ optionally $a[i] \leq a[i + 1]$

```

// for doubles, use inf = 1/.0, div(a,b) = a / b
struct Line {
    mutable lli m, c, p;
    bool operator < (const Line &l) const { return m < l.m; }
    bool operator < (lli x) const { return p < x; }
    lli operator ()(lli x) const { return m * x + c; }
};

```

```

struct DynamicHull : multiset<Line, less<>> {
    lli div(lli a, lli b) {
        return a / b - ((a ^ b) < 0 && a % b);
    }

    bool isect(iterator x, iterator y) {
        if (y == end())
            return x->p = inf, 0;
        if (x->m == y->m)
            x->p = (x->c > y->c ? inf : -inf);
        else
            x->p = div(x->c - y->c, y->m - x->m);
        return x->p >= y->p;
    }

    void add(lli m, lli c) {
        auto z = insert({m, c, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }

    lli query(lli x) {
        if (empty()) return 0LL;
        auto f = *lower_bound(x);
        return f(x);
    }
};

```

5.6 Divide and conquer $\mathcal{O}(kn^2) \Rightarrow \mathcal{O}(k \cdot n \log n)$

Split the array of size n into k continuous groups. $k \leq n$
 $cost(a, c) + cost(b, d) \leq cost(a, d) + cost(b, c)$ with $a \leq b \leq c \leq d$

```

void dc(int cut, int l, int r, int optl, int optr) {
    if (r < l)
        return;
    int mid = (l + r) / 2;
    pair<lli, int> best = {inf, -1};
    for (p, optl, min(mid, optr) + 1) {
        lli nxt = dp[~cut & 1][p - 1] + cost(p, mid);
        if (nxt < best.f)
            best = {nxt, p};
    }
    dp[cut & 1][mid] = best.f;
    int opt = best.s;
    dc(cut, l, mid - 1, optl, opt);
    dc(cut, mid + 1, r, opt, optr);
}

for (i, 1, n + 1)
    dp[1][i] = cost(1, i);
for (cut, 2, k + 1)
    dc(cut, cut, n, cut, n);

```

5.7 Knuth optimization $\mathcal{O}(n^3) \Rightarrow \mathcal{O}(n^2)$

$dp[l][r] = \min_{l \leq k \leq r} \{dp[l][k] + dp[k][r]\} + cost(l, r)$

```

for (len, 1, n + 1)
    for (l, 0, n) {
        int r = l + len - 1;
        if (r > n - 1)
            break;
        if (len <= 2) {
            dp[l][r] = 0;
            opt[l][r] = l;
            continue;
        }
    }

```

```

    }
    dp[l][r] = inf;
    for (k, opt[l][r - 1], opt[l + 1][r] + 1) {
        lli cur = dp[l][k] + dp[k][r] + cost(l, r);
        if (cur < dp[l][r]) {
            dp[l][r] = cur;
            opt[l][r] = k;
        }
    }
}

```

6 Game Theory

6.1 Grundy Numbers

If the moves are consecutive $S = \{1, 2, 3, \dots, x\}$ the game can be solved like $stackSize \pmod{x+1} \neq 0$

```

int mem[N];

int mex(set<int> &st) {
    int x = 0;
    while (st.count(x))
        x++;
    return x;
}

int grundy(int n) {
    if (n < 0)
        return inf;
    if (n == 0)
        return 0;
    int &g = mem[n];
    if (g == -1) {
        set<int> st;
        for (int x : {a, b})
            st.insert(grundy(n - x));
        g = mex(st);
    }
    return g;
}

```

7 Combinatorics

Combinatorics table		
Number	Factorial	Catalan
0	1	1
1	1	1
2	2	2
3	6	5
4	24	14
5	120	42
6	720	132
7	5,040	429
8	40,320	1,430
9	362,880	4,862
10	3,628,800	16,796
11	39,916,800	58,786
12	479,001,600	208,012
13	6,227,020,800	742,900

7.1 Factorial

```

fac[0] = 1LL;
for (i, 1, N)
    fac[i] = lli(i) * fac[i - 1] % mod;
ifac[N - 1] = fpow(fac[N - 1], mod - 2);
for (i, N - 1, 0)
    ifac[i] = lli(i + 1) * ifac[i + 1] % mod;

```

7.2 Factorial mod *smallPrime*


```

lli facMod(lli n, int p) {
    lli r = 1LL;
    for (; n > 1; n /= p) {
        r = (r * ((n / p) % 2 ? p - 1 : 1)) % p;
        fore (i, 2, n % p + 1)
            r = r * i % p;
    }
    return r % p;
}

```

7.3 Lucas theorem

Changes $\binom{n}{k} \bmod p$, with $n \geq 2e6, k \geq 2e6$ and $p \leq 1e7$

$$\binom{n}{k} \equiv \prod_{i=0}^n \binom{n_i}{k_i} \bmod p$$

```

lli lucas(lli n, lli k) {
    if (k == 0)
        return 1LL;
    return lucas(n / mod, k / mod) * choose(n % mod, k %
        mod) % mod;
}

```

7.4 Stars and bars

Enclosing n objects in k boxes

$$\binom{n+k-1}{k-1} = \binom{n+k-1}{n}$$

7.5 N choose K

$$\binom{n}{k} = \binom{n-1}{k-1} + \binom{n-1}{k}$$

$$\binom{n}{k_1, k_2, \dots, k_m} = \frac{n!}{k_1! * k_2! * \dots * k_m!}$$

```

lli choose(int n, int k) {
    if (n < 0 || k < 0 || n < k)
        return 0LL;
    return fac[n] * ifac[k] % mod * ifac[n - k] % mod;
}

```

```

lli choose(int n, int k) {
    double r = 1;
    fore (i, 1, k + 1)
        r = r * (n - k + i) / i;
    return lli(r + 0.01);
}

```

7.6 Catalan

```

catalan[0] = 1LL;
fore (i, 0, N) {
    catalan[i + 1] = catalan[i] * lli(4 * i + 2) % mod *
        fpow(i + 2, mod - 2) % mod;
}

```

7.7 Burnside's lemma

$$|classes| = \frac{1}{|G|} \cdot \sum_{x \in G} f(x)$$

7.8 Prime factors of N!

```

vector< pair<lli, int> > factorialFactors(lli n) {
    vector< pair<lli, int> > fac;
    for (lli p : primes) {
        if (n < p)
            break;
        lli mul = 1LL, k = 0;
        while (mul <= n / p) {
            mul *= p;

```

```

            k += n / mul;
        }
        fac.emplace_back(p, k);
    }
    return fac;
}

```

8 Number Theory

8.1 Goldbach conjecture

- All number ≥ 6 can be written as sum of 3 *primes*
- All even number > 2 can be written as sum of 2 *primes*

8.2 Prime numbers distribution

Amount of primes approximately $\frac{n}{\ln(n)}$

8.3 Sieve of Eratosthenes

Numbers up to $2e8$

```

int erat[N >> 6];
#define bit(i) ((i >> 1) & 31)
#define prime(i) !(erat[i >> 6] >> bit(i) & 1)

void bitSieve() {
    for (int i = 3; i * i < N; i += 2) if (prime(i))
        for (int j = i * i; j < N; j += (i << 1))
            erat[j >> 6] |= 1 << bit(j);
}

```

To factorize divide x by $factor[x]$ until is equal to 1

```

void factorizeSieve() {
    iota(factor, factor + N, 0);
    for (int i = 2; i * i < N; i++) if (factor[i] == i)
        for (int j = i * i; j < N; j += i)
            factor[j] = i;
}

```

Use it if you need a huge amount of $phi[x]$ up to some N

```

void phiSieve() {
    isp.set(); // bitset<N> is faster
    iota(phi, phi + N, 0);
    fore (i, 2, N) if (isp[i])
        for (int j = i; j < N; j += i) {
            isp[j] = (i == j);
            phi[j] /= i;
            phi[j] *= i - 1;
        }
}

```

8.4 Phi of euler

```

lli phi(lli n) {
    if (n == 1)
        return 0;
    lli r = n;
    for (lli i = 2; i * i <= n; i++)
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            r -= r / i;
        }
    if (n > 1)
        r -= r / n;
    return r;
}

```

8.5 Miller-Rabin

```

bool miller(lli n) {
    if (n < 2 || n % 6 % 4 != 1)
        return (n | 1) == 3;
    auto compo = [&](lli p, lli d, lli n, lli k) {
        lli x = fpow(p % n, d, n), i = k;
        while (x != 1 && x != n - 1 && p % n && i--)

```

```

    x = mul(x, x, n);
    return x != n - 1 && i != k;
}
int k = __builtin_ctzll(n - 1);
lli d = n >> k;
for (lli p : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37}) {
    if (compo(p, d, n, k))
        return 0;
    if (compo(2 + rng() % (n - 3), d, n, k))
        return 0;
}
return 1;
}

```

8.6 Pollard-Rho

```

lli rho(lli n) {
    while (1) {
        lli x = 2 + rng() % (n - 3), c = 1 + rng() % 20;
        auto f = [&](lli x) { return (mul(x, x, n) + c) % n; };
        lli y = f(x), g;
        while ((g = __gcd(n + y - x, n)) == 1)
            x = f(x), y = f(f(y));
        if (g != n) return g;
    }
    return -1;
}

```

```

void pollard(lli n, map<lli, int> &fac) {
    if (n == 1) return;
    if (n % 2 == 0) {
        fac[2]++;
        pollard(n / 2, fac);
        return;
    }
    if (miller(n)) {
        fac[n]++;
        return;
    }
    lli x = rho(n);
    pollard(x, fac);
    pollard(n / x, fac);
}

```

8.7 Amount of divisors

```

lli divs(lli n) {
    lli cnt = 1LL;
    for (lli p : primes) {
        if (p * p * p > n)
            break;
        if (n % p == 0) {
            lli k = 0;
            while (n > 1 && n % p == 0)
                n /= p, ++k;
            cnt *= (k + 1);
        }
    }
    lli sq = mysqrt(n); // A binary search, the last x *
                        // x <= n
    if (miller(n))
        cnt *= 2;
    else if (sq * sq == n && miller(sq))
        cnt *= 3;
    else if (n > 1)
        cnt *= 4;
    return cnt;
}

```

8.8 Bézout's identity

$a_1 * x_1 + a_2 * x_2 + \dots + a_n * x_n = g$

$g = \gcd(a_1, a_2, \dots, a_n)$

8.9 GCD

$a \leq b; \gcd(a + k, b + k) = \gcd(b - a, a + k)$

8.10 LCM

$x = p * lcm(a_1, a_2, \dots, a_k) + q, 0 \leq q \leq lcm(a_1, a_2, \dots, a_k)$
 $x \pmod{a_i} \equiv q \pmod{a_i} \text{ as } a_i \mid lcm(a_1, a_2, \dots, a_k)$

8.11 Euclid

```

pair<lli, lli> euclid(lli a, lli b) {
    if (b == 0)
        return {1, 0};
    auto p = euclid(b, a % b);
    return {p.s, p.f - a / b * p.s};
}

```

8.12 Chinese remainder theorem

```

pair<lli, lli> crt(pair<lli, lli> a, pair<lli, lli> b)
{
    if (a.s < b.s)
        swap(a, b);
    auto p = euclid(a.s, b.s);
    lli g = a.s * p.f + b.s * p.s, l = a.s / g * b.s;
    if ((b.f - a.f) % g != 0)
        return {-1, -1}; // no solution
    p.f = a.f + (b.f - a.f) % b.s * p.f % b.s / g * a.s;
    return {p.f + (p.f < 0) * l, l};
}

```

9 Math

9.1 Progressions

Arithmetic progressions

$$a_n = a_1 + (n - 1) * diff$$

$$\sum_{i=1}^n a_i = n * \frac{a_1 + a_n}{2}$$

Geometric progressions

$$a_n = a_1 * r^{n-1}$$

$$\sum_{k=1}^n a_1 * r^k = a_1 * \left(\frac{r^{n+1} - 1}{r - 1} \right) : r \neq 1$$

9.2 Mod multiplication

```

lli mul(lli x, lli y, lli mod) {
    lli r = 0LL;
    for (x %= mod; y > 0; y >>= 1) {
        if (y & 1) r = (r + x) % mod;
        x = (x + x) % mod;
    }
    return r;
}

```

9.3 Fpow

```

lli fpow(lli x, lli y, lli mod) {
    lli r = 1;
    for (; y > 0; y >>= 1) {
        if (y & 1) r = mul(r, x, mod);
        x = mul(x, x, mod);
    }
    return r;
}

```

9.4 Fibonacci

$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n = \begin{bmatrix} fib_{n+1} & fib_n \\ fib_n & fib_{n-1} \end{bmatrix}$$

10 Bit tricks

Bits++	
Operations on <i>int</i>	Function
<code>x & -x</code>	Least significant bit in <i>x</i>
<code>__lg(x)</code>	Most significant bit in <i>x</i>
<code>c = x&-x, r = x+c; ((r^x) >> 2)/c r</code>	Next number after <i>x</i> with same number of bits set
__builtin	Function
<code>popcount(x)</code>	Amount of 1's in <i>x</i>
<code>clz(x)</code>	0's to the left of biggest bit
<code>ctz(x)</code>	0's to the right of smallest bit

10.1 Bitset

Bitset<Size>	
Operation	Function
<code>_Find_first()</code>	Least significant bit
<code>_Find_next(id)</code>	First set bit after index <i>id</i>
<code>any(), none(), all()</code>	Just what the expression says
<code>set(), reset(), flip()</code>	Just what the expression says x2
<code>to_string('.', 'A')</code>	Print 011010 like .AA.A.

10.2 Real

```
const ld eps = 1e-9;
#define eq(a, b) (abs((a) - (b)) <= +eps)
#define neq(a, b) (!eq(a, b))
#define geq(a, b) ((a) - (b) >= -eps)
#define leq(a, b) ((a) - (b) <= +eps)
#define ge(a, b) ((a) - (b) > +eps)
#define le(a, b) ((a) - (b) < -eps)
```

11 Points

11.1 Points

```
int sgn(ld x) { return x > 0 ? 1 : (x < 0 ? -1 : 0); }
```

```
struct Pt {
    ld x, y;
    explicit Pt(ld x = 0, ld y = 0) : x(x), y(y) {}
    Pt operator + (Pt p) const { return Pt(x + p.x, y + p.y); }
    Pt operator - (Pt p) const { return Pt(x - p.x, y - p.y); }
    Pt operator * (ld k) const { return Pt(x * k, y * k); }
    Pt operator / (ld k) const { return Pt(x / k, y / k); }
};
```

```
ld dot(Pt p) const {
    // 0 if vectors are orthogonal
    // - if vectors are pointing in opposite directions
    // + if vectors are pointing in the same direction
    return x * p.x + y * p.y;
}
```

```
ld cross(Pt p) const {
    // 0 if collinear
    // - if b is to the right of a
    // + if b is to the left of a
    // gives you 2 * area
    return x * p.y - y * p.x;
}
```

```
ld norm() const { return x * x + y * y; }
ld length() const { return sqrtl(norm()); }
```

```
ld angle() {
    ld ang = atan2(y, x);
    return ang + (ang < 0 ? 2 * pi : 0);
}
```

```
}
```

```
Pt perp() const { return Pt(-y, x); }
Pt unit() const { return (*this) / length(); }
Pt rotate(ld angle) const {
    // counter-clockwise rotation in radians
    // degree = radian * 180 / pi
    return Pt(x * cos(angle) - y * sin(angle), x * sin(angle) + y * cos(angle));
}
```

```
bool operator == (Pt p) const { return eq(x, p.x) && eq(y, p.y); }
bool operator != (Pt p) const { return neq(x, p.x) || neq(y, p.y); }
friend ostream &operator << (ostream &os, const Pt &p) { return os << "(" << p.x << ", " << p.y << ")"; }
friend istream &operator >> (istream &is, Pt &p) { return cin >> p.x >> p.y; }
```

```
int cuad() const {
    if (x > 0 && y >= 0) return 0;
    if (x <= 0 && y > 0) return 1;
    if (x < 0 && y <= 0) return 2;
    if (x >= 0 && y < 0) return 3;
    assert(x == 0 && y == 0);
    return -1;
}
};
```

```
ld ccw(Pt a, Pt b, Pt c) {
    return (b - a).cross(c - a);
}
```

11.2 Angle between vectors

```
double angleBetween(Pt a, Pt b) {
    double x = a.dot(b) / a.length() / b.length();
    return acosl(max(-1.0, min(1.0, x)));
}
```

11.3 Closest pair of points

```
pair<Pt, Pt> closestPairOfPoints(Poly &pts) {
    sort(all(pts), [&](Pt a, Pt b) {
        return le(a.y, b.y);
    });
    set<Pt> st;
    ld ans = inf;
    Pt p, q;
    int pos = 0;
    for (i, 0, sz(pts)) {
        while (pos < i && geq(pts[i].y - pts[pos].y, ans))
            st.erase(pts[pos++]);
        auto lo = st.lower_bound(Pt{pts[i].x - ans - eps, -inf});
        auto hi = st.upper_bound(Pt{pts[i].x + ans + eps, -inf});
        for (auto it = lo; it != hi; ++it) {
            ld d = (pts[i] - *it).length();
            if (le(d, ans))
                ans = d, p = pts[i], q = *it;
        }
        st.insert(pts[i]);
    }
    return {p, q};
}
```

11.4 Projection

```
ld proj(Pt a, Pt b) {
    return a.dot(b) / b.length();
}
```

12 Lines and segments

12.1 Line

```
struct Line {
    Pt a, b, v;

    Line() {}
    Line(Pt a, Pt b) : a(a), b(b), v((b - a).unit()) {}

    bool contains(Pt p) {
        return eq((p - a).cross(v), 0);
    }

    int intersects(Line l) {
        if (eq(v.cross(l.v), 0)) // -1: infinite
            intersection, 0: none
        return eq((l.a - a).cross(v), 0) ? -1 : 0;
        return 1; // 1 point intersection
    }

    int intersects(Seg s) {
        if (eq(v.cross(s.v), 0)) // -1: infinite
            intersection, 0: none
        return eq((s.a - a).cross(v), 0) ? -1 : 0;
        return sgn(v.cross(s.a - a)) != sgn(v.cross(s.b - a));
    }

    bool parallel(Line l) {
        return eq(v.cross(l.v), 0);
    }

    template <class T>
    Pt intersection(T t) {
        return a + v * ((t.a - a).cross(t.v) / v.cross(t.v));
    }

    Pt projection(Pt p) {
        return a + v * proj(p - a, v);
    }

    Pt reflection(Pt p) {
        return a * 2 - p + v * 2 * proj(p - a, v);
    }
};
```

12.2 Segment

```
struct Seg {
    Pt a, b, v;

    Seg() {}
    Seg(Pt a, Pt b) : a(a), b(b), v(b - a) {}

    bool contains(Pt p) {
        return eq(v.cross(p - a), 0) && leq((a - p).dot(b - p), 0);
    }

    int intersects(Seg s) {
        int t1 = sgn(v.cross(s.a - a)), t2 = sgn(v.cross(s.b - a));
        if (t1 == t2)
            return t1 == 0 && (contains(s.a) || contains(s.b) || s.contains(a) || s.contains(b)) ? -1 : 0;
        return sgn(s.v.cross(a - s.a)) != sgn(s.v.cross(b - s.a));
    }

    template <class T>
```

```
Pt intersection(T t) {
    return a + v * ((t.a - a).cross(t.v) / v.cross(t.v));
};
```

12.3 Distance point segment

```
ld distance(Pt p, Seg s) {
    if (le((p - s.a).dot(s.b - s.a), 0))
        return (p - s.a).length();
    if (le((p - s.b).dot(s.a - s.b), 0))
        return (p - s.b).length();
    return abs((s.a - p).cross(s.b - p) / (s.b - s.a).length());
}
```

12.4 Distance segment segment

```
ld distance(Seg a, Seg b) {
    if (a.intersects(b))
        return 0.0;
    return min({distance(a.a, b), distance(a.b, b), distance(b.a, a), distance(b.b, a)});
}
```

13 Circles

13.1 Circle

```
struct Cir {
    #define sq(x) (x) * (x)
    Pt o;
    ld r;
    Cir(ld x, ld y, ld r) : o(x, y), r(r) {}
    Cir(Pt o, ld r) : o(o), r(r) {}

    int inside(Cir c) {
        // circleInsideCircle
        // -1: internally, 0: overlap, 1: inside
        ld l = r - c.r - (o - c.o).length();
        return ge(l, 0) ? 1 : eq(l, 0) ? -1 : 0;
    }

    int outside(Cir c) {
        // circleOutsideCircle
        // -1: externally, 0: overlap, 1: outside
        ld l = (o - c.o).length() - r - c.r;
        return ge(l, 0) ? 1 : eq(l, 0) ? -1 : 0;
    }

    int contains(Pt p) {
        // pointInCircle
        // -1: perimeter, 0: outside, 1: inside
        ld l = (p - c.o).length() - r;
        return le(l, 0) ? 1 : eq(l, 0) ? -1 : 0;
    }

    Pt projection(Pt p) {
        // projectionPointCircle
        // point outside the circle
        return o + (p - o).unit() * r;
    }

    pair<Pt, Pt> tangency(Pt p) {
        // pointsOfTangency
        // point outside the circle
        Pt v = (p - o).unit() * r;
        ld d2 = (p - o).norm(), d = sqrt(d2);
        Pt v1 = v * (r / d), v2 = v.perp() * (sqrt(d2 - r * r) / d);
        return {c + v1 - v2, c + v1 + v2};
    }
};
```

```

vector<Pt> intersection(Cir c) {
    // intersectionCircles
    Pt d = c.o - o;
    ld d2 = d.norm();
    if (eq(d2, 0)) return {} // concentric circles
    ld pd = (d2 + r * r - c.r * c.r) / 2;
    ld h2 = r * r - pd * pd / d2;
    Pt p = o + d * pd / d2;
    if (eq(h2, 0)) return {p}; // circles touch at one
        point
    if (le(h2, 0)) return {}; // circles don't
        intersect
    Pt u = d.perp() * sqrt(h2 / d2);
    return {p - u, p + u}; // circles intersects twice
}

```

```

template <class T>
vector<Pt> intersection(T t) {
    // intersectLineCircle and intersectSegmentCircle
    // for a segment you need to check that the point
        lies on the segment
    ld h2 = sq(r) - sq(t.v.cross(o - t.a)) / t.v.norm
        ();
    Pt p = t.a + t.v * l.v.dot(o - t.a) / t.v.norm();
    if (eq(h2, 0)) return {p}; // line tangent to
        circle
    if (le(h2, 0)) return {}; // no intersection
    Pt u = t.v.unit() * sqrt(h2);
    return {p - u, p + u}; // two points of
        intersection (chord)
}

```

```

Cir get(Pt a, Pt b, Pt c) {
    // getCircle
    // find circle that passes through points a, b, c
    Line ab((a + b) / 2, (b - a).perp());
    Line cb((c + b) / 2, (c - b).perp());
    Pt p = ab.intersection(cb);
    return Cir(p, (p - a).length());
}
};

```

13.2 Distance point circle

```

ld distance(Pt p, Cir c) {
    // distancePointCircle
    return max(ld(0), (p - c.o).length() - c.r);
}

```

14 Polygons

14.1 Area of polygon

```

ld area(const Poly &pts) {
    ld sum = 0;
    for (i, 0, sz(pts))
        sum += pts[i].cross(pts[(i + 1) % sz(pts)]);
    return abs(sum / 2);
}

```

14.2 Convex-Hull

```

Poly convexHull(Poly pts) {
    Poly low, up;
    sort(all(pts), [&](Pt a, Pt b) {
        return a.x == b.x ? a.y < b.y : a.x < b.x;
    });
    pts.erase(unique(all(pts)), pts.end());
    if (sz(pts) <= 2)
        return pts;
    for (i, 0, sz(pts)) {
        while (sz(low) >= 2 && (low.end()[-1] - low.end()[-
            2]).cross(pts[i] - low.end()[-1]) <= 0)
            low.pop_back();
    }
}

```

```

        low.pb(pts[i]);
    }
    for (i, sz(pts), 0) {
        while (sz(up) >= 2 && (up.end()[-1] - up.end()[-2])
            .cross(pts[i] - up.end()[-1]) <= 0)
            up.pop_back();
        up.pb(pts[i]);
    }
    low.pop_back(), up.pop_back();
    low.insert(low.end(), all(up));
    return low;
}

```

14.3 Cut polygon by a line

```

Poly cut(const Poly &pts, Line l) {
    Poly ans;
    int n = sz(pts);
    for (i, 0, n) {
        int j = (i + 1) % n;
        if (geq(l.v.cross(pts[i] - l.a), 0)) // left
            ans.pb(pts[i]);
        Seg s(pts[i], pts[j]);
        if (l.intersects(s) == 1) {
            Pt p = l.intersection(s);
            if (p != pts[i] && p != pts[j])
                ans.pb(p);
        }
    }
    return ans;
}

```

14.4 Perimeter

```

ld perimeter(const Poly &pts){
    ld sum = 0;
    for (i, 0, sz(pts))
        sum += (pts[(i + 1) % sz(pts)] - pts[i]).length();
    return sum;
}

```

14.5 Point in polygon

```

int contains(const Poly &pts, Pt p) {
    int rays = 0, n = sz(pts);
    for (i, 0, n) {
        Pt a = pts[i], b = pts[(i + 1) % n];
        if (ge(a.y, b.y))
            swap(a, b);
        if (Seg(a, b).contains(p))
            return -1; // lies on the perimeter
        rays ^= (leq(a.y, p.y) && le(p.y, b.y) && ge((a -
            p).cross(b - p), 0));
    }
    return rays & 1; // odd: inside, even: out
}

```

15 Geometry misc

15.1 Radial order

```

struct Radial {
    Pt c;
    Radial(Pt c) : c(c) {}

    bool cmp(Pt a, Pt b) {
        if (a.cuad() == b.cuad())
            return a.y * b.x < a.x * b.y;
        return a.cuad() < b.cuad();
    }

    bool operator()(Pt a, Pt b) const {
        return cmp(a - c, b - c);
    }
};

```

15.2 Sort along a line

```
void sortAlongLine(vector<Pt> &pts, Line l){  
    sort(all(pts), [&](Pt a, Pt b){  
        return a.dot(l.v) < b.dot(l.v);  
    });  
}
```