# Planning Techniques: POP

Dra. Mª Dolores Rodríguez Moreno





# Objectives

#### **Specific Objectives**

Understand POP techniques

#### **Source**

- D. Weld. An Introduction to Least Commitment Planning. AI Magazine, 1994
- Eva Onaindia De La Rivaherrera. Planificación Automática. Videos. UPV. https://media.upv.es/



- Motivation
- Definition
- POP tree
- UCPOP
- Conclusions



#### Motivation

- Having a totally ordered list of steps is restrictive
- Can we only do something if it's necessary?
- POP uses the principle of least commitment: never making a choice unless required to do so



- Motivation
- Definition
- POP tree
- UCPOP
- POP planners
- Conclusions



### Definition (I)

- Perform PSS
- Partial Plan:  $\mathcal{P} = (\mathcal{A}, \mathcal{O}, \mathcal{L}, \mathcal{OC}, \mathcal{UL})$  Action, Ordering constraints, causal Link, Open Conditions (flaws), Unsafe Links
- Backward search
- Each node has:
  - Partially instantiated actions
  - Set of constraints
  - Process stops if the solution is found, after several refinements (adding new operators)



#### Definition (II)

- The planning algorithm implements the *least commitment* technique
  - Only essential planning decisions are saved because it is not necessary to commit
  - The causal link structure is responsible for storing them
    - 3 fields: producer, consumer and the proposition
  - As can be actions that threaten it, we can apply:
    - Demotion: add the restriction before the step that threats it
    - Promotion: add the restriction after the step that threats it
    - Separation: add the restriction to the variable binding
    - Confrontation: add the negation to the conditional effects
- Examples: UCPOP, Cassandra, ZENO, VHPOP








- Motivation
- Definition
- POP tree
- POP planners
- UCPOP
- Conclusions




### POP tree (I)













#### POP tree (III)

- The initial plan is created from the initial state description and the goal description by creating two "pseudo-steps:"
  - Start
    - P: none
    - E: all positive literals defining the initial state
  - Finish
    - P: literals defining the conjunctive goal to be achieved
    - E: none
- Then creating the initial plan as: Start -----> Finish
- Searching for a Solution in Plan Space





- Motivation
- Definition
- POP tree
- POP planners
- UCPOP
- Conclusions



### **POP Planners**

- UCPOP
- Cassandra
- ZENO
- VHPOP




- Motivation
- Definition
- POP tree
- POP planners
- UCPOP: example
- Conclusions




### UCPOP(I)

#### \*start\*

(on c a) (clear b) (clear c) (on a table) (on b table)




After adding a causal link to support (on B C), the plan is as shown and agenda contains  $\{(clear\ B)\ (clear\ C)\ (on\ B\ Table)\ (on\ A\ B)\}$  as open propositions.




After adding a causal link to support (clear B), the plan has two causal links and agenda is set to {(clear C) (on B Table) (on A B)}.







#### UCPOP (II)




Since the move-A action could possibly precede the move-B action, it threatens the link labeled (clear B) as indicated by the dashed line.





### UCPOP (III)




After promoting the threatening action, the plan's actions are totally ordered.





# UCPOP (IV)







- Motivation
- Definition
- POP tree
- UCPOP
- Conclusions



#### Conclusions

- Idea
  - Work on several subgoals independently
  - Solve them with subplans
  - Combine the subplans
  - Flexibility in ordering the subplans
- Least Commitment strategy: delaying a choice during search
- Causal links lead to early pruning of portions of the search space because of irresolvable conflicts



# ToDo example

- Goal: Set the table, i.e., on(Tablecloth) ^ out(Glasses) ^ out(Plates) ^ out(Silverware)
- Initial State: clear(Table)
- Operators:
  - Lay-tablecloth
    P: clear(Table)
    E: on(Tablecloth), ~clear(Table)
  - Put-out(x)
    - P: none
    - E: out(x), ~clear(Table)



