

State Management



Christian Wenz

@chwenz




Demo



Know the cookie, hijack the session





Cookies are sent via HTTP headers

Cookies are bound to domain, path

Sessions use cookies for identifier storage



Securing Cookies

Use HTTPS

Set **secure**
cookie flag

Set **HttpOnly**
cookie flag



```
session_start();
```

```
$_SESSION['name'] = 'value';
```

```
if (isset($_SESSION['name']))  
{  
    echo htmlspecialchars(  
        $_SESSION['name']);  
}
```

◀ Initialize session support, create cookie

◀ Store data in session

◀ Read data from session



```
session.save_handler = files  
session.save_path = "/tmp"  
  
session.use_cookies = 1  
  
session.name = PHPSESSID  
  
session.auto_start = 0  
  
session.gc_maxlifetime = 1440
```

Basic php.ini Session Settings

Found in [Session] section



Attacks Against Sessions



Session Hijacking



Session Fixation



Prevent Cross-Site Scripting (XSS)!

Store user information in session (headers, IP address)

Change session ID with
`session_regenerate_id()`

Require login prior to „dangerous“ actions





```
session.use_strict_mode = 1  
session.cookie_secure = 1  
session.use_only_cookies = 1  
session.cookie_httponly = 1  
session.hash_function = 1  
session.hash_bits_per_character = 6
```

Secure PHP Session Configuration

Set in php.ini



Redirect to HTTP



Strict-Transport-Security:

max-age=31536000; includeSubDomains; preload

HTTP Strict Transport Security (HSTS)

Forces browser to only use HTTPS from now on

Google Chrome maintains preload list

Add domain via <https://hstspreload.appspot.com/>



Summary



Cookies are easy to manipulate

Try to detect session hijacking

Use HSTS to make stealing (session) cookies harder

