

GMSE: an R package for generalised management strategy evaluation

Supporting Information 1

*A. Bradley Duthie, Jeremy J. Cusack, Isabel L. Jones, Erlend B. Nilsen, Rocío Pozo, O.
Sarobidy Rakotonarivo, Bram Van Moorter, and Nils Bunnefeld*

2017-11-07

Extended introduction to the genetic algorithm applied in GMSE

A genetic algorithm is called in the predefined GMSE manager and user models to simulate human decision making. As of GMSE version 0.3.1.9, this includes one independent call to the genetic algorithm for each decision-making agent in every GMSE time step. Therefore, one run of the genetic algorithm occurs to simulate the manager's policy setting decisions in each time step (unless otherwise defined through non-default `manage_freq` values greater than 1), and one run occurs to simulate each individual user's action decisions in each time step (unless otherwise defined through non-default `group_think = TRUE`, in which case one user makes decisions that all other users follow identically. Each run of the genetic algorithm mimics the evolution by natural selection of a population of potential manager or user strategies over multiple generations, with the highest fitness strategy in the terminal generation being selected as the one that the manager or user decides to implement. For clarity, as in the main text, we use 'time step' to refer to a full GMSE cycle (in which multiple genetic algorithms may be run) and 'generation' to refer to a single, non-overlapping, generation of potential strategies that evolve within a genetic algorithm (see Figure 1 of the main text). Below, we explain the genetic algorithm in detail, as it occurs in GMSE v0.3.1.9 (future versions of GMSE might expand upon this framework). We first explain the key data structures used, then provide an overview of how a population of strategies is initialised, and the subsequent processes of crossover, mutation, cost constraint, fitness evaluation, tournament selection, and replacement. We then explain the fitness functions of managers and users in more detail.

Key data structures used

The focal data structure used for tracking manager and user decisions is a three dimensional array, which we will call `ACTION` (also returned as `user_array` by `gmse_apply`). Rows of `ACTION` correspond to the entities affected by actions (resources, landscape properties, or potentially other agents), and columns correspond either to properties of the affected entities, or to the actions potentially allocated to them. Each layer of `ACTION` corresponds to a unique agent, the first of which is the manager; additional layers correspond to users. Below shows an `ACTION` array for a GMSE model with one manager and two users.

```
## , , Manager_Actions
##
##           Act Type_1 Type_2 Type_3      Util. U_land U_loc. Score Cull
## Resource   -2      1      0      0 1000.00000      0      0      0      0
## Landscape  -1      1      0      0   0.00000      0      0      0      0
## Res_cost    1      1      0      0   92.97052      0      0     10    110
## U1_cost     2      1      0      0   0.00000      0      0      0      0
## U2_cost     3      1      0      0   0.00000      0      0      0      0
##           Castrate Feed Help_off None
## Resource      0      0      0      0
## Landscape      0      0      0      0
```

```

43 ## Res_cost      10  10      10  10
44 ## U1_cost       0   0       0   0
45 ## U2_cost       0   0       0   0
46 ##
47 ## , , User_1_Actions
48 ##
49 ##           Act Type_1 Type_2 Type_3 Util. U_land U_loc. Score Cull Castrate
50 ## Resource    -2     1     0     0  -1     0     0     0     9     0
51 ## Landscape   -1     1     0     0   0     0     0     0     0     0
52 ## Res_cost     1     1     0     0   0     0     0     0     0     0
53 ## U1_cost      2     1     0     0   0     0     0     0     0     0
54 ## U2_cost      3     1     0     0   0     0     0     0     0     0
55 ##           Feed Help_off None
56 ## Resource     0         0   0
57 ## Landscape     0         0   1
58 ## Res_cost     0         0   0
59 ## U1_cost       0         0   0
60 ## U2_cost       0         0   0
61 ##
62 ## , , User_2_Actions
63 ##
64 ##           Act Type_1 Type_2 Type_3 Util. U_land U_loc. Score Cull Castrate
65 ## Resource    -2     1     0     0  -1     0     0     0     9     0
66 ## Landscape   -1     1     0     0   0     0     0     0     0     0
67 ## Res_cost     1     1     0     0   0     0     0     0     0     0
68 ## U1_cost      2     1     0     0   0     0     0     0     0     0
69 ## U2_cost      3     1     0     0   0     0     0     0     0     0
70 ##           Feed Help_off None
71 ## Resource     0         0   0
72 ## Landscape     0         0   0
73 ## Res_cost     0         0   0
74 ## U1_cost       0         0   0
75 ## U2_cost       0         0   0

```

The above array holds all of the information on manager and user actions. The first seven columns contain information about which entities are affected, and how they are affected. The first column **Act** identifies the type of action being performed; a value of -2 defines a direct action to a resource (e.g., culling of the resource), and a value of -1 defines direct action to a landscape (e.g., increasing yield). Positive values are currently only meaningful for **Manager_Actions**, where a value of 1 defines an action setting a uniform cost of users' direct actions on resources (i.e., costs where **Act** = -2 for **User_1_Actions** and **User_2_Actions**). All other values for **Act** are meaningless in GMSE 0.3.1.9, but might be expanded upon in future versions to allow for modification of specific user costs enacted by managers (i.e., managers having different policies for different users) or other users (e.g., users increasing the costs of other users' actions due to conflict or cooperation). Similarly, columns 2-4 refer to resource or landscape types, but only **Type_1** = 1, **Type_2** = 0, and **Type_3** = 0 are allowed in GMSE v0.3.1.9 (i.e., only one type of resource is permitted). Future versions might allow for different resource types (e.g., **Type_1** might be used to designate species, and **Type_2** and **Type_3** could designate stage or sex). For the rest of this supporting information, we will therefore focus only on rows 1-3 of **ACTION**. Column 5 **Util.** of **ACTION** defines the utility associated with the resource (where **Act** = -2) or landscape (where **Act** = -1). For managers, the target resource abundance set with the GMSE argument **manage_target** is found in row 1 (1000 in **ACTION** above); for users, the value in row 1 identifies whether resources are preferred to increase (if positive) or decrease (if negative). Values of column 5 in row 2 similarly identify whether landscape cell output is preferred by users to increase or decrease (managers do not currently have preferences for landscape output). Of special note is row 3 for **Manager_Actions**, which defines the marginal utility of resources; that is, the adjustment to resource abundance that the manager will

attempt to make based on the `manage_target` and the estimated abundance produced by the observation model (in the case of the above, resource abundance is estimated at ca 907.03, so the manager will set policy in attempt to change the population size by ca 92.97 resources). Column 6 `U_land` defines whether or not the utility attached to the resource or landscape output depends on it being on a landscape cell that is owned by the acting user. Related, column 7 `U_loc.` defines whether or not actions can be performed only on a landscape cell that is owned by the acting user. Hence values of columns 6 and 7 are binary, and affected by the `land_ownership` argument in `gmse`. Finally, columns 8-13 correspond to specific actions, either direct (where `Act < 0`) or indirect by setting policy (for row 3 of `Manager_Actions` where `Act = 1`). The last column 13 `None` corresponds with no actions. See GMSE documentation for details about the effects of each action.

Constraints on the values that elements in the `ACTION` array can take are defined by a `COST` array (also returned as `manager_array` by `gmse_apply`) of dimensions identical to `ACTION`. Elements of `COST` define how many units from the `manager_budget` or `user_budget` are needed to perform a single action; a `minimum_cost` for actions is defined as an argument in GMSE (10 by default). All values in `COST` columns 1-7 are set to 10001, one higher than the highest possible `manager_budget` or `user_budget`, so neither can affect resource types or utilities. Columns 8-13 are also set to 10001, except where actions are allowed. Below shows the `COST` array that corresponds to the above `ACTION` array.

```
## , , Manager_Actions
##
##           Act Type_1 Type_2 Type_3 Util. U_land U_loc. Score Cull
## Resource  10001  10001  10001  10001 10001  10001  10001 10001 10001
## Landscape 10001  10001  10001  10001 10001  10001  10001 10001 10001
## Res_cost   10001  10001  10001  10001 10001  10001  10001 10001  10
## U1_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
## U2_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
##           Castrate  Feed Help_off  None
## Resource          10001 10001      10001  10
## Landscape         10001 10001      10001  10
## Res_cost          10001 10001      10001  10
## U1_cost           10001 10001      10001 10001
## U2_cost           10001 10001      10001 10001
##
## , , User_1_Actions
##
##           Act Type_1 Type_2 Type_3 Util. U_land U_loc. Score Cull
## Resource  10001  10001  10001  10001 10001  10001  10001 10001  110
## Landscape 10001  10001  10001  10001 10001  10001  10001 10001 10001
## Res_cost   10001  10001  10001  10001 10001  10001  10001 10001 10001
## U1_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
## U2_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
##           Castrate  Feed Help_off  None
## Resource          10001 10001      10001  10
## Landscape         10001 10001      10001  10
## Res_cost          10001 10001      10001 10001
## U1_cost           10001 10001      10001 10001
## U2_cost           10001 10001      10001 10001
##
## , , User_2_Actions
##
##           Act Type_1 Type_2 Type_3 Util. U_land U_loc. Score Cull
## Resource  10001  10001  10001  10001 10001  10001  10001 10001  110
## Landscape 10001  10001  10001  10001 10001  10001  10001 10001 10001
## Res_cost   10001  10001  10001  10001 10001  10001  10001 10001 10001
```

```

149 ## U1_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
150 ## U2_cost    10001  10001  10001  10001 10001  10001  10001 10001 10001
151 ##           Castrate  Feed Help_off  None
152 ## Resource    10001 10001    10001   10
153 ## Landscape    10001 10001    10001   10
154 ## Res_cost     10001 10001    10001 10001
155 ## U1_cost      10001 10001    10001 10001
156 ## U2_cost      10001 10001    10001 10001

```

Note that in default GMSE parameters, `culling = TRUE`, but all other actions are false. Hence the `Cull` column 9 is the only column besides column 13 `None` in which cost is less than 10001. Manager's actions in `ACTION` directly affect the cost of users performing one of the five possible actions on resources (columns 8-12). This can be verified in `ACTION` where the manager has set the cost of scaring to 110, and the corresponding `COST` of resource culling (row 1) is 110 for both users. The cost of the manager affecting the cost of user actions is always set to the `minimum_cost`; here the default 10 is used. This `minimum_cost` also defines cost values for `None`, in which the user or manager does nothing, as might occur if the manager wants to permit culling and therefore does not want to invest any of their `manager_budget` to increasing the cost of culling. Both `ACTION` and `COST` are updated in each time step unless `manage_freq > 1`, in which case `COST` and `Manager_Actions` in `ACTION` are updated at the frequency defined.

General overview of key aspects of the genetic algorithm

The genetic algorithm updates a single layer of the `ACTION` array, which defines to the decisions of a single agent (either the manager or a user). The corresponding layer of the `COST` array remains unchanged, and serves only to ensure that `ACTION` values do not exceed `manager_budget` or `user_budget` for managers and users, respectively. The genetic algorithm proceeds by first initialising a large population of new `ACTION` layers. In each generation, these layers crossover and mutate, generating variation in agent decisions; costs constrain this variation from exceeding a maximum budget, then the fitness of each layer is evaluated based on how much it increases the agent's utility. A tournament is used to select high fitness layers, and these selected layers become the new generation of layers; generations continue until a minimum number of generations (`ga_mingen`) have passed and a convergence criteria is satisfied such that the increase in mean fitness from the previous generation is below the threshold `converge_crit`.

Initialisation

At the start of each genetic algorithm, a population of size `ga_popsiz` is initialised (hereafter the `POPULATION` array). This population is held in a 3D array of `ga_popsiz` layers. Each layer includes an identical number of rows and columns as in `ACTION`, and one layer defines a single 'individual' in the population. The first seven columns of `ACTION` are replicated exactly for all individuals, and remain unchanged throughout the genetic algorithm thereby preserving the information about which entities are affected by actions in a given row. The remaining columns are either also replicated exactly as in `ACTION` (i.e., initialised to be the same decisions as in a previous time step), or randomly seeded with values given the constraints of `manager_budget` or `user_budget` (i.e., initialised to random decision making). The number of exact replicates initialised is set using `ga_seedrep` (if `ga_seedrep ≥ ga_popsiz`, then all individuals are seeded as replicates). After the `POPULATION` of `ga_popsiz` individuals is initialised, a loop simulating the adaptive evolution of `POPULATION` in non-overlapping generations begins.

Crossover

A single generation of the genetic algorithm begins with a uniform crossover (Hamblin, 2013), by which actions of individuals in `POPULATION` are randomly swapped with some probability. To implement crossover, each

individual selects a partner, then exchanges corresponding array elements affecting agent actions (columns 8-13) with their partner at a fixed probability of `ga_crossover`.

Mutation

Cost constraint

Fitness evaluation

Tournament selection

Replacement

Detailed explanation of manager and user fitness functions

Manager fitness function

User fitness function

Thanks for the clarification regarding the equation. I'll try to answer as best as I can – apologies if this has been unclear. At the broadest scale, the equation for user fitness would be on L367 in the `strategy_fitness` function (<https://github.com/bradduthie/gmse/blob/master/src/game.c#L376>). Here's what's going on: Users are predicting how their actions will change the quantities of things in the model (either resources or landscape output), and these changes are individually multiplied by the users' utilities for that thing. The change multiplied by utility for each thing is summed across all things to get a value for fitness. Note that positive change times positive utility, and negative change times negative utility, will increase fitness (i.e., increasing the thing users want more of and decreasing the things they want less of). Hence, an equation describing user fitness would be the below,

$$F_{user} = \sum_{i=1}^N \Delta A_i \times U_i$$

.

Where F_{user} is user fitness, N is the total number of things that might be of interest (at the moment $N = 2$ in GMSE, one resource and, potentially, one landscape value), ΔA_i is the change in the abundance of thing i , and U_i is the utility of thing i from the perspective of the user (apologies for the LaTeX code – attached a PNG of the conversion). I want to stress though that I would not consider this equation to be central to the GMSE framework – if someone else has a better approach for defining fitness, or defining any of the terms listed above, or wants to expand upon it to include new things, then that would be awesome! The above just works well as a heuristic tool to get users to act in such a way as to maximise their interests in harvesting or getting more crop yield (as is my intent), but it's not based on first principles and I don't claim it to be particularly special.

The values of ΔA_i are calculated for resources and the landscape in the functions `res_to_counts` and `land_to_counts`, respectively (and U_i is specified a priori in the model depending on other parameters – namely `land_ownership`). Again, a bit of heuristic is needed here because there cannot be any perfect way of exactly predicting how a users actions will increase or decrease resources – there are too many complex factors (e.g., behaviour of other stakeholders, demographic stochasticity, movement of resources on the landscape, and interactions between resources and the landscape). Even if we could include all of these things somehow, it would be a bit unrealistic in that real stakeholders would never have this much information. The predicted direct effect of actions on resources is shown in lines 268-272 (<https://github.com/bradduthie/gmse/blob/master/src/game.c#L268-272>)

230 //github.com/bradduthie/gmse/blob/master/src/game.c#L268), and the array ‘jaco’ (a sort of Jacobian
231 matrix) accounts for interactions between landscape and resources on line 286. Something similar happens in
232 the land_to_counts function. The manager’s genetic algorithm works in a similar way (the above equation
233 applies), but with the need to dynamically update utility values based on current resource abundance, and to
234 account for the predicted actions of users in finding ΔA_i .

235 References

236 Hamblin, S. (2013). On the practical usage of genetic algorithms in ecology and evolution. *Methods in Ecology*
237 *and Evolution*, 4:184–194.