

Management frequency and extinction risk

GMSE: an R package for generalised management strategy evaluation (Supporting Information 5)

A. Bradley Duthie^{1,3}, Jeremy J. Cusack¹, Isabel L. Jones¹, Jeroen Minderman¹, Erlend B. Nilsen², Rocío A. Pozo¹, O. Sarobidy Rakotonarivo¹, Bram Van Moorter², and Nils Bunnefeld¹

[1] Biological and Environmental Sciences, University of Stirling, Stirling, UK [2] Norwegian Institute for Nature Research, Trondheim, Norway [3] alexander.duthie@stir.ac.uk

The individual-based approach of default GMSE submodels

The default submodels of GMSE (`resource`, `observation`, `manager`, `user`) are individual-based (also called ‘agent-based’), meaning that they model discrete individuals (resources or agents), which in GMSE are represented by individual table rows (`RESOURCES`, `AGENTS`, `OBSERVATION`) or layers of three-dimensional arrays (`COST`, `ACTION`). Individual-based models (IBMs) have been a useful approach in ecology for decades (Uchmański and Grimm, 1996; Grimm, 1999), providing both a pragmatic tool for the mechanistic modelling of complex populations and a powerful technique for theoretical investigation. A key advantage of the individual-based modelling approach is the discrete nature of individuals, which allows for detailed trait variation and complex interactions among individuals. In GMSE, some of the most important traits for resources include types, ages, demographic parameter values, locations, etc., and for agents (manager and users), traits include different types, utilities, budgets, etc. The traits that resources and managers have can potentially affect their interactions, and default GMSE submodels take advantage of this by simulating interactions explicitly on a landscape (see [S17](#) for an introduction to GMSE default data structures).

Replicate simulations as a tool for model inference

Modelling complex interactions among discrete individuals mechanistically typically causes some degree of stochasticity in IBMs (in the code, this is caused by the sampling of random values, which determine probabilistically whether or not events such as birth or death occur for individuals), reflecting the uncertainty that is inherent to complex systems. We can see a simple example of this by calling `gmse_apply` under the same default conditions twice.

```
rand_eg_1 <- gmse_apply();
print(rand_eg_1);

## $resource_results
## [1] 1106
##
## $observation_results
## [1] 1201.814
##
## $manager_results
##      resource_type scaring culling castration feeding help_offspring
## policy_1          1      NA      73         NA         NA         NA
##
## $user_results
##      resource_type scaring culling castration feeding help_offspring
## Manager          1      NA       0         NA         NA         NA
```

```
## user_1      1      NA      13      NA      NA      NA
## user_2      1      NA      13      NA      NA      NA
## user_3      1      NA      13      NA      NA      NA
## user_4      1      NA      13      NA      NA      NA
##           tend_crops kill_crops
## Manager      NA      NA
## user_1      NA      NA
## user_2      NA      NA
## user_3      NA      NA
## user_4      NA      NA
```

Although the second call to `gmse_apply` has identical initial conditions, because resource demographics (e.g., birth and death) and agent decision making (e.g., policy generation and user actions) is not deterministic, a slightly different result is obtained.

```
rand_eg_2 <- gmse_apply();
print(rand_eg_2);
```

```
## $resource_results
## [1] 1118
##
## $observation_results
## [1] 1315.193
##
## $manager_results
##           resource_type scaring culling castration feeding help_offspring
## policy_1      1      NA      62      NA      NA      NA
##
## $user_results
##           resource_type scaring culling castration feeding help_offspring
## Manager      1      NA      0      NA      NA      NA
## user_1      1      NA      16      NA      NA      NA
## user_2      1      NA      16      NA      NA      NA
## user_3      1      NA      16      NA      NA      NA
## user_4      1      NA      16      NA      NA      NA
##           tend_crops kill_crops
## Manager      NA      NA
## user_1      NA      NA
## user_2      NA      NA
## user_3      NA      NA
## user_4      NA      NA
```

To make meaningful model inferences, it is often necessary to replicate simulations under the same initial conditions to understand the range of predicted outcomes for a particular set of parameter values. This can be computationally intense, but it can also lead to a more robust understanding of the range of dynamics that might be expected in a system. Additionally, when parameter values are unknown but believed to be important, replicate simulations can be applied across a range of values to understand how a particular parameter might affect system dynamics. Below, we show how to use the `gmse_replicates` function to simulate a simple example of a managed population that is hunted by users. This function calls `gmse` multiple times and aggregates the results from replicate simulations into a single table.

For a single simulation, the `gmse_table` function prints out key information from a `gmse` simulation result. The example provided in the GMSE documentation is below.

```
gmse_sim <- gmse(time_max = 10, plotting = FALSE);
```

```
## [1] "Initialising simulations ... "
```

```
sim_table <- gmse_table(gmse_sim = gmse_sim);
print(sim_table)
```

```
##      time_step resources estimate cost_culling cost_unused act_culling
## [1,]         1      1091  997.7324          53          57          72
## [2,]         2      1115  657.5964         110           0          36
## [3,]         3      1215 1587.3016          10         100         300
## [4,]         4      1082  907.0295         106           4          36
## [5,]         5      1224 1088.4354          30          80         132
## [6,]         6      1435 1519.2744          10         100         368
## [7,]         7      1274 1337.8685          10         100         400
## [8,]         8      1039 1088.4354          31          79         128
## [9,]         9      1076 1111.1111          22          88         180
##      act_unused harvested
## [1,]          5         72
## [2,]          3         36
## [3,]        100        300
## [4,]          7         36
## [5,]          1        132
## [6,]         31        368
## [7,]          0        400
## [8,]          0        128
## [9,]          2        180
```

We can also only record the last time step in `gmse_table`.

```
sim_table_last <- gmse_table(gmse_sim = gmse_sim, all_time = FALSE);
print(sim_table_last)
```

```
##      time_step      resources      estimate cost_culling cost_unused
##          9.000      1076.000      1111.111      22.000      88.000
## act_culling act_unused harvested
##        180.000         2.000      180.000
```

The `gmse_replicates` function replicates multiple simulations under the same initial conditions, then returns a table showing the values of all simulations. This can be useful, for example, for testing how often a population is expected to go to extinction or carrying capacity under a given set of parameter values.

References

- Grimm, V. (1999). Ten years of individual-based modelling in ecology: what have we learned and what could we learn in the future? *Ecological Modelling*, 115(2-3):129–148.
- Uchmański, J. and Grimm, V. (1996). Individual-based modelling in ecology: what makes the difference? *Trends in Ecology & Evolution*, 11(10):437–441.