

# V7 L19WA

## Entertainment Line

### Specifications

Panel Size	19" (483 mm)
Viewable Size	410 x 257 mm
Panel Specification	CMO Panel
Recommended Resolution	1440 x 900 Super Wide Viewing Angle
Colours max.	16.2 Mio
Brightness typ.	300 cd/m <sup>2</sup>
Contrast Ratio typ.	500:1
Viewing Angle H/V	150°/130°
Response Time typ.	8 (2/6) ms
Features	Speakers, Kensington® Security Port, Silver-Black Design
Adjustment	Auto-Setup, Brightness, Contrast Ratio, Clock, Phase, H/V-Position, Sharpness, Color, OSD Position, Language, Audio, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz
Horizontal Frequency	30 - 82 kHz
Vertical Frequency	56 - 76 Hz
Video Bandwidth	135 Mhz
Input Signal	RGB analog
Input Terminal	15pin D-Sub
Plug & Play	DDC2B
Power Management	VESA DPMS, DVI DMPM, ENERGY STAR
Power Consumption On/Off	43/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD	
with stand	469 x 369 x 190 mm
without stand	469 x 315 x 60 mm
packaging	538 x 470 x 158 mm
Weight without/with stand	4.5 kg
incl. packaging	6.4 kg
Tilt	-2° - 20°
Storage/Operating Temperature	5-35°/-20-55°C, Humidity: 20-80/20-85%
Wallmountable	VESA 75 x 75 mm
Certifications & Standards	CE, TÜV/GS, UL, CSA, TCO '03, ISO 13406-2
Supplied Accessories	12 language manual CD-Tom, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 3, dark <= 3, total <= 7
Service	3 years on-site



DISPLAYS  
FOR you

VIDEASEVEN

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7 Videoseven. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request. Issue: 11/2005