

Java

Inheritance

Max Langer, Leonard Follner, Alexander Hesse

6. November 2016

Java-Kurs

Overview

1. Last session

Visibilities

Arrays

Multi-Dimensional Array

Philosophic stuff

2. Inheritance

Inheritance

Constructor

Implicit Inheritance

Last session

Visibilities

- public
- private
- protected

Visibilities

```
1
2      public class Student {
3          public String getName() {
4              return "Peter";
5          }
6
7          private String getFavouritePorn() {
8              return "...";
9          }
10     }
11
12     // [...]
13     exampleStudent.getName(); // Works!
14     exampleStudent.getFavouritePorn(); // Error
15
16
```

Array

An array is a data-type that can hold a **fixed number** of elements. An Element can be any simple data-type or object.

```
1    public static void main(String[] args) {  
2  
3        int[] intArray = new int[10];  
4        intArray[8] = 7; // assign 7 to the 9th element  
5        intArray[9] = 8; // assign 8 to the last element  
6  
7        System.out.println(intArray[8]); // prints: 7  
8    }  
9
```

You can access every element via an index. A n-element array has indexes from 0 to (n-1).

Array Initialization

You can initialize an array with a set of elements.

```
1  public static void main(String[] args) {  
2  
3      int[] intArray = {3, 2, 7};  
4  
5      System.out.println(intArray[0]); // prints: 3  
6      System.out.println(intArray[1]); // prints: 2  
7      System.out.println(intArray[2]); // prints: 7  
8  }  
9
```

Alternative Declaration

There two possible positions for the square brackets.

```
1 public static void main(String[] args) {  
2  
3     // version 1  
4     int[] intArray1 = new int[10];  
5  
6     // version 2  
7     int intArray2[] = new int[10];  
8 }  
9
```


2-Dimensional Array

Arrays work with more than one dimension. An m-dimensional array has m indexes for one element.

```
1    public static void main(String[] args) {  
2  
3        // an array with 100 elements  
4        int[][] intArray = new int[10][10];  
5  
6        intArray[0][0] = 0;  
7        intArray[0][9] = 9;  
8        intArray[9][9] = 99;  
9    }
```

Assignment with Loops

Loops are often used to assign elements in arrays.

```
1      public static void main(String[] args) {  
2  
3          int[][] intArray = new int[10][10];  
4  
5          for(int i = 0; i < 10; i++) {  
6              for(int j = 0; j < 10; j++) {  
7                  intArray[i][j] = i*10 + j;  
8              }  
9          }  
10     }  
11
```

Arrays with objects

Loops are often used to assign elements in arrays.

```
1      public static void main(String[] args) {  
2  
3          int[][] studentArray = new Student[10][10];  
4  
5          for(int i = 0; i < 10; i++) {  
6              for(int j = 0; j < 10; j++) {  
7                  intArray[i][j] = new Student();  
8              }  
9          }  
10     }  
11
```

Inheritance

A special Delivery

Our class *Letter* is a kind of *Delivery* denoted by the keyword **extends**.

- *Letter* is a **subclass** of the class *Delivery*
- *Delivery* is the **superclass** of the class *Letter*

```
1 public class Letter extends Delivery {  
2  
3 }  
4
```

As mentioned implicitly above a class can has multiple subclasses.
But a class can only inherit directly from one superclass.

Example

We have the classes: *PostOffice*, *Delivery* and *Letter*. They will be used for every example in this section and they will grow over time.

```
1      public class Delivery {
2
3          private String address;
4          private String sender;
5
6          public void setAddress(String addr) {
7              address = addr;
8          }
9
10         public void setSender(String snd) {
11             sender = snd;
12         }
13
14         public void printAddress() {
15             System.out.println(this.address);
16         }
17     }
```

Inherited Methods

The class *Letter* also inherits all methods from the superclass *Delivery*.

```
1      public class PostOffice {  
2  
3          public static void main(String[] args) {  
4  
5              Letter letter = new Letter();  
6  
7              letter.setAddress("cafe ascii, Dresden");  
8  
9              letter.printAddress();  
10             // prints: cafe ascii, Dresden  
11         }  
12     }  
13
```

Override Methods

The method `printAddress()` is now additionally defined in *Letter*.

```
1      public class Letter extends Delivery {  
2  
3          @Override  
4          public void printAddress() {  
5              System.out.println("a letter for " + this.address);  
6          }  
7      }  
8
```

@Override is an annotation. It helps the programmer to identify overwritten methods. It is not necessary for running the code but improves readability. What annotations else can we discuss in a future lesson.

Override Methods

Now the method `printAddress()` defined in *Letter* will be used instead of the method defined in the superclass *Delivery*.

```
1      public class PostOffice {  
2  
3          public static void main(String[] args) {  
4  
5              Letter letter = new Letter();  
6  
7              letter.setAddress("cafe ascii, Dresden");  
8  
9              letter.printAddress();  
10             // prints: a letter for cafe ascii, Dresden  
11         }  
12     }  
13
```

Super()

If we define a **constructor with arguments** in *Delivery* we have to define a constructor with the same list of arguments in every subclass.

```
1      public class Delivery {
2
3          private String address;
4          private String sender;
5
6          public Delivery(String address, String sender) {
7              this.address = address;
8              this.sender = sender;
9          }
10
11         public void printAddress() {
12             System.out.println(address);
13         }
14     }
15
```

Super()

For the constructor in the subclass *Letter* we can use `super()` to call the constructor from the superclass.

```
1      public class Letter extends Delivery {  
2  
3          public Letter(String address, String sender) {  
4              super(address, sender);  
5          }  
6  
7          @Override  
8          public void printAddress() {  
9              System.out.println("a letter for " + this.address);  
10         }  
11     }  
12
```

Super() - Test

```
1 public class PostOffice {  
2  
3     public static void main(String[] args) {  
4         Letter letter =  
5             new Letter("cafe ascii, Dresden", "");  
6  
7         letter.printAddress();  
8         // prints: a letter for cafe ascii, Dresden  
9     }  
10 }  
11
```

Object

Every class is a subclass from the class *Object*. Therefore every class inherits methods from *Object*.

See <http://docs.oracle.com/javase/7/docs/api/java/lang/Object.html> for a full reference of the class *Object*.

toString()

Letter is a subclass of *Object*. Therefore *Letter* inherits the method `toString()` from *Object*.

`System.out.println(argument)` will call `argument.toString()` to receive a printable `String`.

```
1      public class PostOffice {
2
3          public static void main(String[] args) {
4              Letter letter =
5                  new Letter("cafe ascii, Dresden", "");
6
7              System.out.println(letter);
8              // prints: Letter@_some_HEX-value_
9              // for example: Letter@4536ad4d
10         }
11     }
```

Override toString()

```
1 public class Letter extends Delivery {  
2  
3     public Letter(String address, String sender) {  
4         super(address, sender);  
5     }  
6  
7     @Override  
8     public String toString() {  
9         return "a letter for " + this.address;  
10    }  
11 }  
12
```

Override toString() - Test

```
1 public class PostOffice {  
2  
3     public static void main(String[] args) {  
4         Letter letter =  
5             new Letter("cafe ascii, Dresden", "");  
6  
7         System.out.println(letter);  
8         // a letter for cafe ascii, Dresden  
9     }  
10 }  
11
```


Images stolen at:

- **BMW Series** Taken from bmwblog.com
- **CD-Player** Taken from wikimedia.com, Uploaded by Ukexpat