



An artificial neural network optimized by grey wolf optimizer for prediction of hourly wind speed in Tamil Nadu, India

Ahmet Cevahir Cinar^{a,*}, Narayanan Natarajan^b

^a Department of Computer Engineering, Faculty of Technology, Selçuk University, Konya, Turkey

^b Department of Civil Engineering, Dr. Mahalingam College of Engineering and Technology, Pollachi - 642003, Tamil Nadu, India

ARTICLE INFO

Keywords:

Artificial neural network
Evolutionary algorithms
Swarm intelligence
Wind speed prediction
Metaheuristics

ABSTRACT

The growing population has tremendously increased the daily energy demand all around the world. India is the second-most crowded nation in the world with approximately 1.4 billion people. New and renewable energy is on the agenda of India and in 2021 India possesses the fourth-largest installed capacity of wind power. Accurate prediction of wind speed is vital in wind farm design and operation. In this work, an hourly wind speed prediction with an artificial neural network optimized by a metaheuristics approach is conducted. A feed-forward (FF) multi-layer perceptron (MLP) artificial neural network (ANN) is used for the prediction of the hourly wind speed. In this study, 38 years of hourly wind data belonging to 5 cities (Ambur, Hosur, Kumbakonam, Nagapattinam, and Pudukottai) were used. These cities have different specific properties such as latitude, longitude, and altitude. The FF MLP ANN is optimized by 9 state-of-art metaheuristic algorithms. In this work, Artificial Bee Colony (ABC), Ant Colony Optimization (ACO), Biogeography Based Optimization (BBO), Evolutionary Strategy (ES), Genetic Algorithm (GA), Grey-Wolf-Optimizer (GWO), Population-Based Incremental Learning (PBIL), Particle Swarm Optimization (PSO), Tree-Seed Algorithm (TSA) have been used to optimize the weights of the ANN. GWO outperforms other metaheuristic algorithms in the prediction of wind speed with a FF MLP ANN model, with a success percentage rate of approximately 3% to 10,000%.

1. Introduction

India is witnessing several encounters in fulfilling the ever-rising energy demands from different sections of society. Population explosion, environmental pollution, socio-economic crises, rapid industrialization, and urbanization are some of the causes of the surge in energy demand. Exhaustion of the non-renewable energy sources and the need for environmental sustainability has urged scientists and researchers to explore novel non-conventional energy sources such as wind, solar, tidal, geothermal, biogas, biofuels, etc. Renewable energy has shown tremendous development worldwide with substantial progress in wind and solar photovoltaic in the last decade (IEA, 2012). The total power generated by non-conventional energy has attained 2351 Gigawatts (GW) globally in 2018. Among the various renewable energy sources, wind energy seems to be a favorable resource due to its abundance, environment-friendliness, ease of harvestability, and affordability

(Rehman, 2004, 2020). India possesses the fourth highest mounted capacity of wind power after China, the USA, and Germany, with 37.7 GW as of December 2020.¹ India has planned to attain 60 GW of power from wind by the year 2022.² To efficiently use this wind energy, it is mandatory to assess the locations with high prospective for wind energy and predict the wind speed (WS) characteristics in such regions. Moreover, precise estimation of WS is vital in the wind farm design and operation (Liu et al., 2018).

Metaheuristic algorithms are widely used in many areas of the research field. Genetic Algorithm (GA), Population-Based Incremental Learning (PBIL), and Evolutionary Strategy (ES) have mimicked the evolutionary operators such as crossover and mutation. Grey-Wolf-Optimizer (GWO), Artificial Bee Colony (ABC), Particle Swarm Optimization (PSO), Biogeography Based Optimization (BBO), and Ant Colony Optimization (ACO) are inspired by animal behaviors such as hunting, feeding, and exploring the new areas. The Tree-Seed Algorithm

* Corresponding author.

E-mail address: accinar@selcuk.edu.tr (A.C. Cinar).

¹ <https://mnre.gov.in/wind/current-status/> (Accessed on 9th March 2021)

² <https://indien.um.dk/en/innovation/sector-updates/renewable-energy/wind-energy-in-india/#:~:text=India%20has%20the%204th%20largest,m%20hub%2Dheight%20in%20India.> (Accessed on 9th March 2021)

<https://doi.org/10.1016/j.iswa.2022.200138>

Received 18 January 2022; Received in revised form 2 May 2022; Accepted 5 October 2022

Available online 12 October 2022

2667-3053/© 2022 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).

Table 1

The geographical information of the selected sites.

S. No.	Location	Latitude (°N)	Longitude (°E)	Altitude (m)
1	Ambur	12.78	78.71	324
2	Hosur	12.74	77.82	872
3	Kumbakonam	10.96	79.38	32
4	Nagapattinam	10.76	79.84	9
5	Pudukottai	10.38	78.80	101

(TSA) (Gharehchopogh, 2022) is a newly developed metaheuristic that mimics the relationship between trees and their seeds. All these algorithms start with a random population and use various techniques and local search mechanisms (Koçer & Uymaz, 2021) to find the optimum values of the given optimization problem.

In this work, ABC, ACO, BBO, ES, GA, GWO, PSO, PBIL, and TSA have been used to optimize the weights of the ANN. Nine hybrid algorithms, namely, ANN-ABC, ANN-ACO, ANN-BBO, ANN-ES, ANN-GA, ANN-GWO, ANN-PBIL, ANN-PSO, and ANN-TSA have been adopted in forecasting the wind speed at five stations located in the state of Tamil Nadu, India. The main aim of this work is to present the comparison of the feed-forward multi-layer perceptron artificial neural network models which are optimized by 9 state-of-the-art metaheuristic algorithms.

The organization of the paper is as follows: The related works, study area and data description are given in Sections 2 and 3, respectively. The proposed artificial neural network optimized by metaheuristics and the experimental setup are presented in Sections 4 and 5, respectively. The results and discussion are given in Section 6. The paper is concluded

with Section 7.

2. Related works

Wind speed prediction (WSP) is carried out using statistical, artificial intelligence, and hybrid models. Statistical methods are generally adopted for short-term WSP, and historical data is employed for the determination of the WS. Statistical methods can be both linear as well as non-linear. Commonly used statistical methods for WSP include autoregressive (AR) (Poggi et al., 2003), linear regression (Kani et al., 2008), moving average (MA) (Riahy & Abedi, 2008), Kalman filter (Shamshad et al., 2005; Erdem & Shi, 2011), Auto-Regressive Moving Average (ARMA) (Cassola & Burlando, 2012), Markov Chain (Kavasseri & Seetharaman, 2009), Auto-Regressive Integrated Moving Average (ARIMA) (Zuluaga et al., 2015), Seasonal ARIMA (Al Dhaheri et al., 2017). If the non-linearity is prominent in the collected data, the prediction results by the above-mentioned methods will not be satisfactory (Zhang et al., 2016). In such cases, non-linear models like nonlinear autoregressive

Table 2

Statistical analysis of the data.

S. No	Location	Mean WS (m/s)	Maximum WS (m/s)	Standard deviation (m/s)
1	Ambur	5.41	9.36	1.24
2	Hosur	5.47	9.74	1.36
3	Kumbakonam	5.75	8.72	1.08
4	Nagapattinam	6.26	8.96	1.14
5	Pudukottai	5.30	8.48	1.02

**Fig. 1.** Location of the selected sites in Tamil Nadu.




Fig. 2. Design of FF MLP ANN.




Fig. 3. The proposed artificial neural network optimized by the metaheuristics approach.

Table 3

The experimental results of Ambur.

Ambur	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Mean	2.01E-02	6.60E+00	8.48E-03	1.18E+01	3.96E-02	5.68E-03	5.84E+00	4.84E+00	4.09E+00
Best	4.51E-03	3.47E-01	8.48E-03	4.16E-01	4.62E-03	4.51E-03	2.30E-01	1.57E-02	2.17E-02
Worst	1.16E-01	2.04E+01	8.48E-03	5.77E+01	3.48E-01	1.09E-02	2.70E+01	3.42E+01	1.77E+01
SD	2.56E-02	6.01E+00	1.76E-18	1.24E+01	7.18E-02	1.42E-03	7.23E+00	6.62E+00	3.96E+00
Median	1.13E-02	4.65E+00	8.48E-03	9.21E+00	9.56E-03	5.08E-03	4.00E+00	2.22E+00	2.34E+00
Mean Time	700.89	579.19	587.28	721.36	578.16	580.00	592.85	579.10	738.48
Friedman Rank	2.83	7.27	2.67	7.83	3.10	1.43	6.67	6.60	6.60
MSE test	0.0038	0.2773	0.0086	0.47	0.0039	0.0038	0.2673	0.0162	0.0238




Fig. 4. Visualization of the experimental results of Ambur.

Table 4

The experimental results of Hosur.

Hosur	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Mean	1.82E-02	7.60E+00	7.08E-03	1.81E+01	2.44E-02	6.26E-03	6.80E+00	5.12E+00	3.10E+00
Best	4.26E-03	2.28E-01	7.08E-03	2.03E-01	4.49E-03	4.28E-03	2.19E-01	1.55E-01	2.03E-01
Worst	8.22E-02	3.34E+01	7.08E-03	5.65E+01	1.16E-01	1.46E-02	2.90E+01	1.84E+01	6.83E+00
SD	2.13E-02	7.88E+00	4.41E-18	1.35E+01	2.95E-02	2.37E-03	6.85E+00	4.30E+00	2.18E+00
Median	9.63E-03	4.82E+00	7.08E-03	1.59E+01	8.55E-03	5.35E-03	3.67E+00	3.93E+00	2.65E+00
Mean Time	702.16	575.13	591.64	732.43	577.52	573.36	584.08	577.10	752.52
Friedman Rank	2.77	7.00	2.47	8.23	3.00	1.77	6.73	6.70	6.33
MSE test	0.0046	0.221	0.0078	0.1964	0.0049	0.0046	0.2116	0.1548	0.1968

(NAR) and nonlinear autoregressive exogenous (NARX) models tend to perform better (Cadenas et al., 2016; Karasu et al., 2017a, b).

Soft computing methods have been used in the recent past due to their self-learning abilities and hence can approximate the non-linear functions (Catalão et al., 2009; Chang et al., 2017). The most widely used methods to predict the WS include different types of Artificial Neural Network (ANN) like Multi-Layer Perceptron (MLP) (Ak et al., 2018), Back Propagation Neural Network (BPNN) (Wang et al., 2016), Long Short Term Memory (LSTM) (Hu & Chen, 2018; Liu et al., 2018), Radial Basis Function (RBF) (Zhang et al., 2016), Recurrent Neural Network (RNN) (Qian-Li et al., 2008), Elman Neural Network (ENN) (Liu et al., 2015), Convolution Neural Network (CNN) (Mehrkanoon, 2019), Wavelet Neural Network (Xiao et al., 2017). Apart from ANN, there are other techniques like Support Vector Machine (SVM) (Mohandes et al., 2004; Liu et al., 2014; Gani et al., 2016), fuzzy logic (FL) (Damousis et al., 2004), Bayesian maximum entropy approach (Baydaroglu & Kocak, 2019) and extreme learning machine (Peng et al., 2017; Hu & Chen, 2018; Liu et al., 2018). Even though the soft computing models have the capability to acquire knowledge from the historical data, identify the patterns to describe the relationship prevalent in the past data, and provide imminent predictions, they possess some drawbacks. These models may easily fail due to local optimum or over-fitting, thus exhibiting a low rate of convergence and difficulty in

determination of some of the critical parameters (Bashir & El-Hawary, 2009; Yu et al., 2017; Wang et al., 2018, 2019).

To combat these shortcomings, optimization algorithms were introduced. These algorithms provide a potential role in enhancing the performance of the ANN models. These are generally denoted as hybrid or combined models. Especially, ANN models have been improved using various optimization algorithms in the past. It is evident from the literature (Cinar, 2020; Turkoglu & Kaya, 2020) that the performance of ANN has improved considerably with the help of optimization algorithms.

Gao and Billinton (2009) proposed a model to simulate hourly WS using an ARMA model, in which the optimum random number of seeds was selected by GA. Li et al. (2009) coupled BPNN with GA to optimize the structure, bias, and weights of the neural network. Welch et al. (2009) proposed Recurrent Neural Networks (RNN) trained with PSO for short-term WSP. Alanis et al. (2012) developed a model using Extended Kalman Filter (EKF) and Particle Swarm Optimization (PSO) for the training process of Recurrent MLP for wind prediction. Islam et al. (2017) proposed two ANN hybrid systems using GA and PSO, namely GA-ANN and PSO-ANN for vertical extrapolation of WS. Khosravi et al. (2018) adopted three models to predict the WS, namely, multilayer feed-forward neural network (MLFFNN), Support Vector Regression (SVR) with Radial Basis Function (RBF), and adaptive neuro-fuzzy




Fig. 5. Visualization of the experimental results of Hosur.

Table 5

The experimental results of Kumbakonam.

Kumbakonam	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Mean	1.10E-02	5.51E+00	2.68E-02	1.37E+01	1.18E-02	7.27E-03	5.76E+00	3.74E+00	3.36E+00
Best	3.52E-03	6.09E-01	2.68E-02	4.89E-01	3.49E-03	3.53E-03	1.53E-01	4.63E-02	2.28E-01
Worst	4.71E-02	1.60E+01	2.68E-02	6.09E+01	7.50E-02	3.72E-02	1.87E+01	1.41E+01	1.39E+01
SD	9.58E-03	4.02E+00	5.76E-18	1.49E+01	1.43E-02	7.71E-03	4.94E+00	3.69E+00	3.02E+00
Median	7.65E-03	4.58E+00	2.68E-02	8.52E+00	7.34E-03	4.50E-03	4.29E+00	2.55E+00	2.42E+00
Mean Time	691.77	569.58	586.12	724.05	568.99	571.84	578.20	566.72	743.17
Friedman Rank	2.30	7.17	3.80	8.10	2.27	1.63	7.10	6.40	6.23
MSE test	0.1336	0.1336	0.1336	0.5441	0.0043	0.0044	0.1336	0.1336	0.1336

inference system (ANFIS) coupled with PSO to predict the WS and direction in Bushehr, Iran. [Jawad et al. \(2018\)](#) developed a hybrid model by combining GA-based non-linear AR with exogenous inputs for neural network short term and medium term WSP.

[Gani et al. \(2016\)](#) adopted a new hybrid approach by integrating of SVM and firefly algorithm (FFA) for WSP on a daily and monthly basis. The approach was found to perform accurately for monthly scales since a lot of fluctuations were observed on the daily basis. [Deo et al. \(2018\)](#) adopted a novel approach to construct an MLP hybrid model integrated with FFA trained with a limited set of historical data for a set of stations located nearby to predict the WS at target sites of north-west Iran.

[Du et al. \(2017\)](#) used a multi-objective ant lion optimization algorithm to optimize the initial weights between layers and thresholds of the ENN for refining the accuracy of WSP. [Wang et al. \(2017\)](#) used the Multi-Objective Whale Optimization Algorithm (MOWOA) to optimize the weights and thresholds of the ENN so as to accurately predict the WS. They compared the obtained results with Multi-Objective Ant Lion Optimizer and Multi-Objective Drangonfly Algorithm (MODA) and concluded that the MOWOA optimized ENN outperforms other models. [Samadianfard et al. \(2020\)](#) utilized the combination of MLP with Whale optimization algorithm (WOA) for forecasting the WS at specific stations in the north of Iran with a limited dataset. They compared the results of MLP-WOA with MLP-GA and standalone MLP, and found that MLP-WOA

outperformed the other models. [Sağ and Abdullah Jalil Jalil \(2021\)](#) use a vortex search algorithm for optimizing the ANN. [Turkoglu and Kaya \(2020\)](#) used an artificial algae algorithm for optimizing the ANN.

3. Study area and data description

Tamil Nadu is a state situated in the southernmost part of India. Five cities selected for this study include Ambur, Hosur, Kumbakonam, Nagapattinam, and Pudukottai. The geographical information of the selected sites is provided in [Table 1](#) and the location of these is illustrated in [Fig. 1](#).

It can be observed from [Table 1](#) that the cities chosen for this study are located at different altitudes ranging from 9 m to 872 m.

WS speed data from 1980 to 2018 was collected for this study from the MERRA-2 reanalysis database (NASA). The statistical analysis of the WS data from these sites is provided in [Table 2](#) below.

The mean WS ranges from 5.41 m/s to 6.26 m/s. A maximum WS of 9.74 m/s is observed at Hosur. The standard deviation is the least at Pudukkotai and the largest at Hosur.




Fig. 6. Visualization of the experimental results of Kumbakonam.

Table 6

The experimental results of Nagapattinam.

Nagapattinam	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Mean	1.95E-02	6.12E+00	1.85E-01	1.31E+01	3.18E-02	3.36E-03	8.18E+00	3.92E+00	4.02E+00
Best	2.09E-03	1.60E-01	1.85E-01	5.64E-01	2.10E-03	2.07E-03	2.08E-03	2.27E-01	1.68E-01
Worst	1.48E-01	1.45E+01	1.85E-01	4.43E+01	2.73E-01	7.49E-03	3.27E+01	1.42E+01	1.37E+01
SD	3.24E-02	4.43E+00	0.00E+00	1.02E+01	5.35E-02	1.36E-03	7.70E+00	3.63E+00	3.53E+00
Median	8.83E-03	6.10E+00	1.85E-01	1.25E+01	1.10E-02	3.07E-03	6.09E+00	2.61E+00	3.30E+00
Mean Time	698.31	571.75	586.40	714.56	572.50	574.62	583.61	574.12	735.36
Friedman Rank	2.27	7.20	4.10	8.03	2.63	1.27	6.97	6.37	6.17
MSE test	0.0019	0.1911	0.2204	0.652	0.0019	0.0019	0.0019	0.2199	0.1957

4. Proposed artificial neural network optimized by metaheuristics

In this work, 9 metaheuristic algorithms are used for optimizing the weights and biases of a feed-forward (FF) multi-layer perceptron (MLP) artificial neural network (ANN). The detailed architecture of the FF MLP ANN is given in Fig. 2.

The input is the current hour WS, and the output is the next hour WS. In Cinar (2020), Cinar suggested that time series prediction with ANN with 15 hidden nodes produced eligible solutions. The same FF MLP ANN structure is used for the time series prediction in this study. 46 decision variables in the search range $[-10, +10]$ are optimized by 9 metaheuristic algorithms. The detailed scheme of the suggested artificial neural network optimized by the metaheuristics approach is given in Fig. 3.

In Fig. 3, in the first phase, the training data is loaded. In the second phase, the FF MLP ANN is constructed. In the third phase, the FF MLP ANN parameters are optimized by 9 metaheuristic algorithms. In the fourth and fifth phases, the optimized FF MLP ANN is constructed, and test data is introduced. Finally, in the sixth phase, the mean square error (MSE) value for test data is reported.

5. Experimental setup

The WS (m/s) data at 50 m height observed in Indian cities (Ambur, Hosur, Kumbakonam, Nagapattinam, and Pudukkottai) between 01/01/1980 and 31/08/2018 were used in the experiments. The dataset was split into training and test. The values between 01/01/1980 and 31/12/2009 were used as a training dataset. The values between 01/01/2010 and 31/08/2018 were used as a testing dataset. The total dataset sample size is 338,952 for each city, out of which 262,991 values were used in training and 75,961 values were used in testing. Approximately 78% of data was used as a training dataset and 22% of data were used as a testing dataset. MSE is used as a statistical parameter to assess the performance metric. The formula of MSE is given in Eq. (1).

$$\frac{1}{n} \sum_{i=1}^n (O_i - P_i)^2 \quad (1)$$

Where n is the sample size, O_i is the observed value, P_i is the predicted value. The parameters of the 9 metaheuristic algorithms are the same as that of Cinar (2020). To avoid repetition, the readers are requested to refer to the same. 30 different runs were conducted on a PC with Intel(R) Core(TM) i5-9400F CPU @ 2.90 GHz and 8 GB of RAM. All experimental processes were performed using the MATLAB program. The population




Fig. 7. Visualization of the experimental results of Nagapattinam.

Table 7

The experimental results of Pudukkottai.

Pudukkottai	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Mean	2.09E-02	7.33E+00	1.09E-01	1.75E+01	2.68E-02	6.09E-03	7.37E+00	4.23E+00	4.22E+00
Best	4.37E-03	4.74E-01	1.09E-01	1.50E-01	4.55E-03	4.37E-03	2.08E-01	6.84E-02	1.21E-01
Worst	9.77E-02	3.59E+01	1.09E-01	8.52E+01	1.15E-01	1.56E-02	2.67E+01	2.91E+01	1.31E+01
SD	2.14E-02	8.62E+00	0.00E+00	1.68E+01	2.85E-02	2.34E-03	6.79E+00	5.62E+00	3.52E+00
Median	1.47E-02	5.22E+00	1.09E-01	1.43E+01	1.47E-02	5.12E-03	5.16E+00	2.20E+00	3.42E+00
Mean Time	676.62	554.65	578.92	691.94	554.25	554.50	566.57	554.72	715.20
Friedman Rank	2.20	7.10	4.00	7.77	2.50	1.33	7.20	6.40	6.50
MSE test	0.0055	0.5902	0.1642	0.1374	0.0057	0.0055	0.1795	0.0870	0.1496

size (N) is considered as 40. The maximum iteration number is considered as 50. The maximum function evaluation number is fixed as 2000. The dimension (D) is considered as 46.

6. Results and discussions

In Tables 3-7, training MSE values are reported as Mean, Best, Worst, Standard Deviation (SD), and Median along the rows. The Mean Time refers to the mean runtime consumed for each method. The Friedman Rank indicates the Friedman's test value. The MSE test refers to the MSE values of the testing results of the method.

The experimental results of Ambur are given in Table 3 and the visualization of the experimental results of Ambur is shown in Fig. 4. ANN-ACO, ANN-ES, and ANN-PBIL produced higher MSE values for test data. The best method is ANN-ABC, and the second-best is ANN-GWO. ANN-BBO is trapped in the same local optima in all runs, and ANN-ABC is observed to be slower than ANN-GWO.

The experimental results of Hosur are given in Table 4 and the visualization of the experimental results of Hosur is shown in Fig. 5. ANN-ACO, ANN-ES, ANN-PBIL, ANN-PSO, and ANN-TSA produced higher MSE values for the test data. The best methods are ANN-ABC and ANN-GWO in terms of the MSE test. ANN-BBO is trapped in the same local optima in all runs, and ANN-ABC is observed to be slower than

ANN-GWO.

The experimental results of Kumbakonam are given in Table 5 and the visualization of the experimental results of Kumbakonam is shown in Fig. 6. ANN-ABC, ANN-ACO, ANN-BBO, ANN-ES, ANN-PBIL, ANN-PSO, and ANN-TSA produced higher MSE values for test data. The best method is ANN-GA and the second method is ANN-GWO in terms of MSE test. ANN-BBO is trapped in the same local optima in all runs, and ANN-GA is observed to be faster compared to ANN-GWO.

The experimental results of Nagapattinam are given in Table 6 and the visualization of the experimental results of Nagapattinam is shown in Fig. 7. ANN-ACO, ANN-BBO, ANN-ES, ANN-PSO, and ANN-TSA produced higher MSE values for test data. The best methods are ANN-ABC, ANN-GA, ANN-GWO, and ANN-PBIL in terms of MSE test. ANN-BBO is trapped in the same local optima in all runs. ANN-GA is faster than ANN-ABC, ANN-GWO, and ANN-PBIL.

The experimental results of Pudukkottai are given in Table 7 and the visualization of the experimental results of Pudukkottai is shown in Fig. 8. ANN-ACO, ANN-BBO, ANN-ES, ANN-PBIL, ANN-PSO, and ANN-TSA produced higher MSE values for test data. The best methods are ANN-ABC and ANN-GWO in terms of MSE test. ANN-BBO is trapped in the same local optima in all runs, and ANN-GWO is observed to be faster than ANN-ABC. The Friedman's test values are provided in Table 8 and the comparison of the same has been illustrated in Fig. 9.



Fig. 8. Visualization of the experimental results of Pudukkotai.

Table 8

The Friedman's test values.

Friedman Rank	ANN-ABC	ANN-ACO	ANN-BBO	ANN-ES	ANN-GA	ANN-GWO	ANN-PBIL	ANN-PSO	ANN-TSA
Ambur	2.83	7.27	2.67	7.83	3.10	1.43	6.67	6.60	6.60
Hosur	2.77	7.00	2.47	8.23	3.00	1.77	6.73	6.70	6.33
Kumbakonam	2.30	7.17	3.80	8.10	2.27	1.63	7.10	6.40	6.23
Nagapattinam	2.27	7.20	4.10	8.03	2.63	1.27	6.97	6.37	6.17
Pudukkotai	2.20	7.10	4.00	7.77	2.50	1.33	7.20	6.40	6.50
Mean	2.47	7.15	3.41	7.99	2.70	1.49	6.93	6.49	6.37




Fig. 9. Comparison of Friedman's test values for the proposed hybrid models.

According to Tables 3-8 and Fig. 9, the best approach is ANN-GWO. The second one is ANN-ABC and the third one is ANN-GA. ANN-GWO has high exploration and exploitation capability due to its individual organization.

The comparison of classification error rate values for all the models is

shown in Fig. 10. The best approach is ANN-GWO. The second one is ANN-GA and the third one is ANN-ABC.

The success percentage of ANN-GWO vs. other models in terms of classification error rate is shown in Fig. 11. GWO outperforms the other metaheuristic algorithms in the prediction of wind speed with a FF MLP




Fig. 10. Comparison of classification error rate values for all models.




Fig. 11. The success percentage of ANN-GWO vs. other models.

ANN, with a success percentage rate of approximately 3% to 10,000%.

7. Conclusion

In this study, a feed-forward (FF) multi-layer perceptron (MLP) artificial neural network (ANN) is used for the prediction of the hourly WS. For conducting the numerical experiments, 38 years of hourly wind speed data belonging to 5 cities (Ambur, Hosur, Kumbakonam, Nagapattinam, and Pudukkottai) were used. These cities have different specific properties such as latitude, longitude, and altitude. The FF MLP ANN is optimized by 9 state-of-art metaheuristic algorithms. In this work, Artificial Bee Colony (ABC), Ant Colony Optimization (ACO), Biogeography Based Optimization (BBO), Evolutionary Strategy (ES), Genetic

Algorithm (GA), Grey-Wolf-Optimizer (GWO), Population-Based Incremental Learning (PBIL), Particle Swarm Optimization (PSO), Tree-Seed Algorithm (TSA) have been used to optimize the weights of the ANN. The main aim of this work is to present the comparison of the feed-forward multi-layer perceptron artificial neural network models which are optimized by 9 state-of-the-art metaheuristic algorithms. All these algorithms start with a random population and use various techniques and mechanisms to find the optimum values of the given optimization problem. The obtained experimental results show that GWO provided the most accurate output in terms of mean square error (MSE), Friedman's test value, mean training error rate, and execution time. GWO has five steps of the hunting mechanism of the grey wolf which are its social hierarchy, prey encircling, chasing, prey attacking, and prey searching.

These phases produce more accurate solutions, balance exploration and exploitation in the optimization process.

Statements and Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

All data generated or analysed during this study are included in this published article.

Competing interests

The authors declare that they have no competing interests.

Funding

The authors did not receive support from any organization for the submitted work.

CRediT authorship contribution statement

Ahmet Cevahir Cinar: Software, Validation, Visualization, Supervision, Writing – original draft, Writing – review & editing. **Narayanan Natarajan:** Investigation, Conceptualization, Methodology, Data curation, Writing – original draft, Visualization, Writing – review & editing.

Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

References

- Ak, R., Li, Y.-F., Vitelli, V., & Zio, E. (2018). Adequacy assessment of a wind-integrated system using neural network-based interval predictions of wind power generation and load. *International Journal of Electrical Power & Energy Systems*, 95, 213–226.
- Al Dhaheer, K., Woon, W. L., & Aung, Z. (2017). Wind speed forecasting using statistical and machine learning methods: A case study in the UAE. In *International workshop on data analytics for renewable energy integration*. Springer.
- Alanis, A. Y., Simetti, C., Ricalde, L. J., & Odone, F. (2012). A wind speed neural model with particle swarm optimization Kalman learning. In *World automation congress 2012*. IEEE.
- Bashir, Z., & El-Hawary, M. (2009). Applying wavelets to short-term load forecasting using PSO-based neural networks. *IEEE Transactions on Power Systems*, 24(1), 20–27.
- Baydaroglu, Ö., & Koçak, K. (2019). Spatiotemporal analysis of wind speed via the Bayesian maximum entropy approach. *Environmental Earth Sciences*, 78(1), 17.
- Cadenas, E., Rivera, W., Campos-Amezcu, R., & Heard, C. (2016). Wind speed prediction using a univariate ARIMA model and a multivariate NARX model. *Energies*, 9(2), 109.
- Cassola, F., & Burlando, M. (2012). Wind speed and wind energy forecast through Kalman filtering of numerical weather prediction model output. *Applied energy*, 99, 154–166.
- Catalão, J. P. d. S., Pousinho, H. M. I., & Mendes, V. M. F. (2009). An artificial neural network approach for short-term wind power forecasting in Portugal. In *2009 15th International conference on intelligent system applications to power systems*. IEEE.
- Chang, G., Lu, H., Chang, Y., & Lee, Y. (2017). An improved neural network-based approach for short-term wind speed and power forecast. *Renewable energy*, 105, 301–311.
- Cinar, A. C. (2020). Training feed-forward multi-layer perceptron artificial neural networks with a tree-seed algorithm. *Arabian Journal for Science and Engineering*, 45 (12), 10915–10938.
- Damouisi, I. G., Alexiadis, M. C., Theocharis, J. B., & Dokopoulos, P. S. (2004). A fuzzy model for wind speed prediction and power generation in wind parks using spatial correlation. *IEEE Transactions on Energy Conversion*, 19(2), 352–361.
- Deo, R. C., Ghorbani, M. A., Samadianfard, S., Maraseni, T., Bilgili, M., & Biazar, M. (2018). Multi-layer perceptron hybrid model integrated with the firefly optimizer algorithm for windspeed prediction of target site using a limited set of neighboring reference station data. *Renewable Energy*, 116, 309–323.
- Du, P., Wang, J., Guo, Z., & Yang, W. (2017). Research and application of a novel hybrid forecasting system based on multi-objective optimization for wind speed forecasting. *Energy Conversion and Management*, 150, 90–107.
- Erdem, E., & Shi, J. (2011). ARMA based approaches for forecasting the tuple of wind speed and direction. *Applied Energy*, 88(4), 1405–1414.
- Gani, A., Mohammadi, K., Shamsirband, S., Altameem, T. A., Petković, D., & Ch, S. (2016). A combined method to estimate wind speed distribution based on integrating the support vector machine with firefly algorithm. *Environmental Progress & Sustainable Energy*, 35(3), 867–875.
- Gao, Y., & Billinton, R. (2009). Adequacy assessment of generating systems containing wind power considering wind speed correlation. *IET Renewable Power Generation*, 3 (2), 217–226.
- Gharehchopogh, F. S. (2022). Advances in Tree seed algorithm: A comprehensive survey. *Archives of Computational Methods in Engineering*, 1–24.
- Hu, Y.-L., & Chen, L. (2018). A nonlinear hybrid wind speed forecasting model using LSTM network, hysteretic ELM and Differential Evolution algorithm. *Energy Conversion and Management*, 173, 123–142.
- IEA (2012). *World energy outlook 2012*. Paris.
- Islam, M. S., Mohandes, M., & Rehman, S. (2017). Vertical extrapolation of wind speed using artificial neural network hybrid system. *Neural Computing and Applications*, 28 (8), 2351–2361.
- Jawad, M., Ali, S. M., Khan, B., Mehmood, C. A., Farid, U., Ullah, Z., et al. (2018). Genetic algorithm-based non-linear auto-regressive with exogenous inputs neural network short-term and medium-term uncertainty modelling and prediction for electrical load and wind speed. *The Journal of Engineering*, (8), 721–729. 2018.
- Kani, S. P., Mousavi, S., Kaviani, A. K., & Riahy, G. (2008). A new integrated approach for very short-term wind speed prediction using linear regression among ANN and Markov Chain. In *Proceeding on international conference on power system analysis, control and optimization*.
- Karasu, S., Altan, A., Saraç, Z., & Hacıoğlu, R. (2017a). Estimation of fast varied wind speed based on NARX neural network by using curve fitting. *International Journal of Energy Applications and Technologies*, 4(3), 137–146.
- Karasu, S., Altan, A., Saraç, Z., & Hacıoğlu, R. (2017b). Prediction of wind speed with non-linear autoregressive (NAR) neural networks. In *2017 25th Signal processing and communications applications conference (SIU)*. IEEE.
- Kavasseri, R. G., & Seetharaman, K. (2009). Day-ahead wind speed forecasting using f-ARIMA models. *Renewable Energy*, 34(5), 1388–1393.
- Khosravi, A., Koury, R., Machado, L., & Pabon, J. (2018). Prediction of wind speed and wind direction using artificial neural network, support vector regression and adaptive neuro-fuzzy inference system. *Sustainable Energy Technologies and Assessments*, 25, 146–160.
- Koçer, H. G., & Uymaz, S. A. (2021). A novel local search method for LSGO with golden ratio and dynamic search step. *Soft Computing*, 25(3), 2115–2130.
- Li, X., Liu, Y., & Xin, W. (2009). Wind speed prediction based on genetic neural network. In *2009 4th IEEE Conference on industrial electronics and applications*. IEEE.
- Liu, D., Niu, D., Wang, H., & Fan, L. (2014). Short-term wind speed forecasting using wavelet transform and support vector machines optimized by genetic algorithm. *Renewable Energy*, 62, 592–597.
- Liu, H., Mi, X., & Li, Y. (2018). Smart deep learning based wind speed prediction model using wavelet packet decomposition, convolutional neural network and convolutional long short term memory network. *Energy Conversion and Management*, 166, 120–131.
- Liu, H., Tian, H.-q., Liang, X.-f., & Li, Y.-f. (2015). Wind speed forecasting approach using secondary decomposition algorithm and Elman neural networks. *Applied Energy*, 157, 183–194.
- Mehrkanoun, S. (2019). Deep shared representation learning for weather elements forecasting. *Knowledge-Based Systems*, 179, 120–128.
- Mohandes, M. A., Halawani, T. O., Rehman, S., & Hussain, A. A. (2004). Support vector machines for wind speed prediction. *Renewable energy*, 29(6), 939–947.
- Peng, T., Zhou, J., Zhang, C., & Zheng, Y. (2017). Multi-step ahead wind speed forecasting using a hybrid model based on two-stage decomposition technique and AdaBoost-extreme learning machine. *Energy Conversion and Management*, 153, 589–602.
- Poggi, P., Muselli, M., Notton, G., Cristofari, C., & Louche, A. (2003). Forecasting and simulating wind speed in Corsica by using an autoregressive model. *Energy Conversion and Management*, 44(20), 3177–3196.
- Qian-Li, M., Qi-Lun, Z., Hong, P., Tan-Wei, Z., & Jiang-Wei, Q. (2008). Multi-step-prediction of chaotic time series based on co-evolutionary recurrent neural network. *Chinese Physics B*, 17(2), 536.
- Rehman, S. (2004). Wind energy resources assessment for Yanbo, Saudi Arabia. *Energy Conversion and Management*, 45, 2019–2032, 13–14.
- Rehman, S., Natarajan, N., Vasudevan, M., & Alhems, L. M. (2020). Assessment of wind energy potential across varying topographical features of Tamil Nadu, India. *Energy Exploration & Exploitation*, 38(1), 175–200.
- Riahy, G., & Abedi, M. (2008). Short term wind speed forecasting for wind turbine applications using linear prediction method. *Renewable Energy*, 33(1), 35–41.
- Sağ, T., & Abdullah Jalil Jalil, Z. (2021). Vortex search optimization algorithm for training of feed-forward neural network. *International Journal of Machine Learning and Cybernetics*, 12(5), 1517–1544.
- Samadianfard, S., Hashemi, S., Kargar, K., Izadyar, M., Mostafaeipour, A., Mosavi, A., et al. (2020). Wind speed prediction using a hybrid model of the multi-layer perceptron and whale optimization algorithm. *Energy Reports*, 6, 1147–1159.

- Shamshad, A., Bawadi, M., Hussin, W. W., Majid, T., & Sanusi, S. (2005). First and second order Markov chain models for synthetic generation of wind speed time series. *Energy*, 30(5), 693–708.
- Turkoglu, B., & Kaya, E. (2020). Training multi-layer perceptron with artificial algae algorithm. *Engineering Science and Technology, an International Journal*, 23(6), 1342–1350.
- Wang, J., Du, P., Niu, T., & Yang, W. (2017). A novel hybrid system based on a new proposed algorithm—Multi-objective whale optimization algorithm for wind speed forecasting. *Applied energy*, 208, 344–360.
- Wang, J., Wu, C., & Niu, T. (2019). A novel system for wind speed forecasting based on multi-objective optimization and echo state network. *Sustainability*, 11(2), 526.
- Wang, J., Yang, W., Du, P., & Niu, T. (2018). A novel hybrid forecasting system of wind speed based on a newly developed multi-objective sine cosine algorithm. *Energy Conversion and Management*, 163, 134–150.
- Wang, S., Zhang, N., Wu, L., & Wang, Y. (2016). Wind speed forecasting based on the hybrid ensemble empirical mode decomposition and GA-BP neural network method. *Renewable Energy*, 94, 629–636.
- Welch, R. L., Ruffing, S. M., & Venayagamoorthy, G. K. (2009). Comparison of feedforward and feedback neural network architectures for short term wind speed prediction, 2009. In *International joint conference on neural networks*. IEEE.
- Xiao, L., Shao, W., Yu, M., Ma, J., & Jin, C. (2017). Research and application of a hybrid wavelet neural network model with the improved cuckoo search algorithm for electrical power system forecasting. *Applied energy*, 198, 203–222.
- Yu, C., Li, Y., & Zhang, M. (2017). Comparative study on three new hybrid models using Elman neural network and empirical mode decomposition based technologies improved by singular spectrum analysis for hour-ahead wind speed forecasting. *Energy Conversion and Management*, 147, 75–85.
- Zhang, C., Wei, H., Xie, L., Shen, Y., & Zhang, K. (2016a). Direct interval forecasting of wind speed using radial basis function neural networks in a multi-objective optimization framework. *Neurocomputing*, 205, 53–63.
- Zuluaga, C. D., Alvarez, M. A., & Giraldo, E. (2015). Short-term wind speed prediction based on robust Kalman filtering: An experimental comparison. *Applied Energy*, 156, 321–330.