Perfect Graph Recognition and Coloring Dni Magistranta

Adrian Siwiec

December 05, 2019

References

"The strong perfect graph theorem"

Maria Chudnovsky, Neil Robertson, Paul Seymour, Robin Thomas https://arxiv.org/abs/math/0212070

"A polynomial algorithm for recognizing perfect graphs"

Gérard Cornuéjols, Xinming Liu, Kristina Vušković https://ieeexplore.ieee.org/document/1238177

"Recognizing Berge Graphs"

Maria Chudnovsky, Gérard Cornuéjols, Xinming Liu, Paul Seymour, Kristina Vušković

https://link.springer.com/article/10.1007/s00493-005-0012-8

"Colouring perfect graphs with bounded clique number"

Maria Chudnovsky, Aurélie Lagoutte, Paul Seymour, Sophie Spirkl https://arxiv.org/abs/1707.03747

Perfect Graphs

Perfect Graphs

A graph is *perfect* if the chromatic number of every induced subgraph equals the size of its largest clique.

Perfect Graphs

Perfect Graphs

A graph is *perfect* if the chromatic number of every induced subgraph equals the size of its largest clique.

Perfect Graphs are interesting

In all perfect graphs, the graph coloring problem, maximum clique problem, and maximum independent set problem can all be solved in polynomial time. (Grötschel, Lovász, Schrijver 1988)

Perfect Graphs

Perfect Graphs

A graph is *perfect* if the chromatic number of every induced subgraph equals the size of its largest clique.

Perfect Graphs are interesting

In all perfect graphs, the graph coloring problem, maximum clique problem, and maximum independent set problem can all be solved in polynomial time. (Grötschel, Lovász, Schrijver 1988)

Families of graphs that are perfect

- Bipartite graphs
- Line graphs of bipartite graphs
- Chordal graphs
- Comparability graphs
- .

Strong Perfect Graph Theorem

Perfect Graphs

A graph is *perfect* if the chromatic number of every induced subgraph equals the size of its largest clique.

Berge Graphs

A graph is *Berge* if no induced subgraph of G is an odd cycle of length at least five or the complement of one.

Strong Perfect Graph Theorem

Perfect Graphs

A graph is *perfect* if the chromatic number of every induced subgraph equals the size of its largest clique.

Berge Graphs

A graph is *Berge* if no induced subgraph of G is an odd cycle of length at least five or the complement of one.

Strong Perfect Graph Theorem

A graph G is Perfect if and only if it is Berge.

Recognizing Berge Graphs - an overview of an overview

An odd hole

An odd hole in G is an induced subgraph of G that is a cycle of odd length at least five.

A graph G is Berge if G and its complement both have no odd hole.

Algorithm

The idea of our algorithm is to decompose the input graph G into a polynomial number of simpler graphs $G_1, ..., G_m$ so that:

- G is odd-hole-free if and only if every G_i is odd-hole-free.
- G it is easy to check if G_i is odd-hole-free.

Decompositions

2-join

A graph G has a 2-join $V_1|V_2$ with special sets (A_1,A_2,B_1,B_2) if $A_i,B_i\subset V_i$, every vertex of A_1 is adjacent to every vertex of A_2 , every vertex of B_1 is adjacent to every vertex of B_2 and there are no other adjacencies between V_1 and V_2 .

Double Star

A set S of vertices is a double star if S contains two adjacent vertices u and v such that $S \subseteq N(u) \cup N(v)$.

Double-star cutsets pose a problem.

Perfect Graph Colouring

Skew Partitions

A skew partition in G is a partition (A, B) of V(G), such that G[A] is not connected and $\overline{G}[B]$ is not connected.

Decomposition Theorem

Every Berge graph either admits a balanced skew partition, or admits one of two other decompositions, or it belongs to one of five well-understood classes.

Goals

Goals

- Implement Berge Graph recognition algorithm.
 - Compare with existing Java implementation.
 - Are there any other implementations to compare to?
- Implement Perfect Graph colouring algorithm.
 - Compare with existing linear programming solutions.