Access

1.) users
Purpose: Main account record for every platform user.

Primary Key

- user_id uuid pk - Unique user identifier

Fields

- email varchar(255) null - User email
- mobile_number varchar(20) null - User mobile number
- password_hash text null - Hashed password for local auth
- first_name varchar(100) not null - Given name
- last_name varchar(100) not null - Family name
- display_name varchar(150) null - Public-facing display name
- profile_photo_url text null - Profile image URL
- is_email_verified boolean not null default false - Email verification flag
- is_mobile_verified boolean not null default false - Mobile verification flag
- account_status text not null - Account state, e.g. ACTIVE, SUSPENDED, DEACTIVATED
- last_login_at timestamptz null - Most recent login timestamp
- created_at timestamptz not null default now() - Record creation timestamp
- updated_at timestamptz not null default now() - Record update timestamp

Unique Constraints

- unique (email) where email is not null
- unique (mobile_number) where mobile_number is not null

Notes

- Add a check so at least one of email or mobile_number exists.

2.) roles
Purpose: Master list of system roles.

Primary Key

- role_id uuid pk - Unique role identifier

Fields

- role_code varchar(50) not null - Stable code, e.g. FARMER, BUYER, DISTRIBUTOR, ADMIN
- role_name varchar(100) not null - Human-readable role name
- description text null - Short explanation of the role
- created_at timestamptz not null default now()

Unique Constraints

- unique (role_code)
- unique (role_name)

3.) user_roles
Purpose: Junction table allowing one user to have multiple roles.

Primary Key

- user_role_id uuid pk - Unique user-role assignment identifier

Foreign Keys

- user_id uuid not null fk -> users.user_id
- role_id uuid not null fk -> roles.role_id

Fields

- assigned_at timestamptz not null default now() - When role was assigned
- is_active boolean not null default true - Whether role assignment is active
- created_at timestamptz not null default now()

Unique Constraints

- unique (user_id, role_id)

User Profiles and Verification

4.) farmer_profiles
Purpose: Farmer-specific profile and farm identity data.

Primary Key

- farmer_profile_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id

Fields

- farm_name varchar(150) not null - Farm or seller name
- bio text null - Farmer bio/background
- farm_location_text text not null - Main farm location
- farm_latitude numeric(9,6) null - Optional map latitude
- farm_longitude numeric(9,6) null - Optional map longitude
- years_of_experience integer null - Farming experience in years
- is_public boolean not null default true - Whether profile is visible in marketplace
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (user_id)

5.) buyer_profiles
Purpose: Buyer business profile data.

Primary Key

- buyer_profile_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id

Fields

- business_name varchar(150) not null - Buyer business name
- contact_person_name varchar(150) not null - Main contact person
- business_type varchar(100) not null - Restaurant, market, reseller, etc.
- business_location_text text not null - Main business address/location
- business_latitude numeric(9,6) null
- business_longitude numeric(9,6) null
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (user_id)

6.) distributor_profiles
Purpose: Distributor operational profile data.

Primary Key

- distributor_profile_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id

Fields

- fleet_display_name varchar(150) not null - Public distributor/fleet name
- license_number varchar(100) null - Professional/operating identifier if needed
- base_location_text text not null - Base operating location
- base_latitude numeric(9,6) null
- base_longitude numeric(9,6) null
- is_available boolean not null default true - Distributor availability flag
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (user_id)
- unique (license_number) where license_number is not null

7.) kyc_applications
Purpose: KYC application submitted per user-role combination.

Primary Key

- kyc_application_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id
- role_id uuid not null fk -> roles.role_id

Fields

- application_status text not null - PENDING, APPROVED, REJECTED, RESUBMISSION_REQUIRED
- submitted_at timestamptz not null default now() - Submission time
- reviewed_at timestamptz null - Final decision time

- final_remarks text null - Final admin remarks
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- None at DB level if multiple reapplications are allowed
- If only one active application per user-role is allowed, enforce partial unique index on (user_id, role_id) where status in active states

---

8.) kyc_documents
Purpose: Metadata of uploaded KYC files tied to an application.

Primary Key

- kyc_document_id uuid pk

Foreign Keys

- kyc_application_id uuid not null fk -> kyc_applications.kyc_application_id

Fields

- document_type varchar(100) not null - Valid ID, business permit, etc.
- file_url text not null - S3 or storage URL
- file_name varchar(255) not null - Original file name
- mime_type varchar(100) not null - File MIME type
- file_size_bytes bigint null - File size
- document_status text not null default 'PENDING' - PENDING, APPROVED, REJECTED
- rejection_reason text null - Reason if rejected
- uploaded_at timestamptz not null default now()
- created_at timestamptz not null default now()

Unique Constraints

- None

9.) kyc_reviews
Purpose: Admin review history for KYC applications.

Primary Key

- kyc_review_id uuid pk

Foreign Keys

- kyc_application_id uuid not null fk -> kyc_applications.kyc_application_id
- reviewed_by_user_id uuid not null fk -> users.user_id

Fields

- review_action text not null - APPROVED, REJECTED, REQUESTED_RESUBMISSION
- remarks text null - Admin remarks
- reviewed_at timestamptz not null default now()
- created_at timestamptz not null default now()

Unique Constraints

- None

Marketplace

10.) produce_categories
Purpose: Master list of produce categories.

Primary Key

- produce_category_id uuid pk

Fields

- category_name varchar(100) not null - Category name
- description text null - Category description
- created_at timestamptz not null default now()

Unique Constraints

- unique (category_name)

11.) produce_listings
Purpose: Main produce listing created by a farmer.

Primary Key

- produce_listing_id uuid pk

Foreign Keys

- farmer_profile_id uuid not null fk -> farmer_profiles.farmer_profile_id
- produce_category_id uuid not null fk -> produce_categories.produce_category_id

Fields

- listing_title varchar(150) not null - Listing title
- produce_name varchar(150) not null - Product name
- description text null - Listing description
- price_per_kg numeric(12,2) not null - Current selling price per kg
- minimum_order_kg numeric(12,3) not null default 1.000 - Minimum orderable kg
- maximum_order_kg numeric(12,3) null - Optional max orderable kg
- listing_status text not null - DRAFT, ACTIVE, INACTIVE, SOLD_OUT, ARCHIVED
- primary_location_text text not null - Main fulfillment location
- primary_latitude numeric(9,6) null
- primary_longitude numeric(9,6) null
- is_premium_boosted boolean not null default false - Premium ranking flag
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- None

12.) produce_listing_images
Purpose: Images attached to a listing.

Primary Key

- produce_listing_image_id uuid pk

Foreign Keys

- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- image_url text not null - Storage URL
- display_order integer not null default 1 - Sort order
- is_primary boolean not null default false - Primary listing image
- created_at timestamptz not null default now()

Unique Constraints

- unique (produce_listing_id, display_order)

13.) produce_inventory_batches
Purpose: Harvest/stock records tied to a listing.

Primary Key

- produce_inventory_batch_id uuid pk

Foreign Keys

- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- batch_code varchar(100) null - Internal batch reference
- estimated_harvest_date date null - Expected harvest date
- actual_harvest_date date null - Actual harvest date
- available_quantity_kg numeric(12,3) not null - Available stock in kg
- reserved_quantity_kg numeric(12,3) not null default 0.000 - Reserved stock in kg
- inventory_status text not null - PLANNED, AVAILABLE, RESERVED, DEPLETED
- notes text null - Batch notes
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (produce_listing_id, batch_code) where batch_code is not null

---

14.) listing_price_history
Purpose: Historical price change records.

Primary Key

- listing_price_history_id uuid pk

Foreign Keys

- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- old_price_per_kg numeric(12,2) not null - Previous price
- new_price_per_kg numeric(12,2) not null - Updated price
- changed_by_user_id uuid null fk -> users.user_id - User who changed price

- effective_at timestamptz not null default now() - When new price became effective
- created_at timestamptz not null default now()

Unique Constraints

- None

15.) listing_availability_windows
Purpose: Specific dates or ranges when listing is actually available.

Primary Key

- listing_availability_window_id uuid pk

Foreign Keys

- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- available_from_date date not null - Start date of availability
- available_to_date date not null - End date of availability
- notes text null - Optional note on availability
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- None

Notes

- Add a check: available_to_date >= available_from_date

Vehicles

16.) vehicle_types
Purpose: Master list of supported vehicle types and base capacity.

Primary Key

- vehicle_type_id uuid pk

Fields

- vehicle_type_name varchar(100) not null - Vehicle name, e.g. Motorcycle, Van, Truck
- description text null - Description
- max_capacity_kg numeric(12,3) not null - Capacity in kg
- is_active boolean not null default true
- created_at timestamptz not null default now()

Unique Constraints

- unique (vehicle_type_name)

17.) farmer_listing_vehicle_types
Purpose: Allowed delivery vehicle types per listing.

Primary Key

- farmer_listing_vehicle_type_id uuid pk

Foreign Keys

- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id
- vehicle_type_id uuid not null fk -> vehicle_types.vehicle_type_id

Fields

- created_at timestamptz not null default now()

Unique Constraints

- unique (produce_listing_id, vehicle_type_id)

Orders

18.) orders
Purpose: Main buyer transaction record.

Primary Key

- order_id uuid pk

Foreign Keys

- buyer_user_id uuid not null fk -> users.user_id

Fields

- order_number varchar(50) not null - Human-readable order reference
- order_status text not null - PENDING_DOWNPAYMENT, CONFIRMED, PREPARING, PICKED_UP, IN_TRANSIT, ARRIVED, COMPLETED, CANCELLED
- downpayment_due_amount numeric(12,2) not null - Required downpayment
- downpayment_paid_amount numeric(12,2) not null default 0.00 - Actual downpayment paid
- final_payment_due_amount numeric(12,2) not null - Remaining balance
- final_payment_paid_amount numeric(12,2) not null default 0.00 - Actual final amount paid
- subtotal_amount numeric(12,2) not null - Sum of line items
- delivery_fee_amount numeric(12,2) not null default 0.00 - Delivery fee
- platform_fee_amount numeric(12,2) not null default 0.00 - System fee
- refund_amount numeric(12,2) not null default 0.00 - Refund amount if any
- delivery_location_text text not null - Delivery destination
- delivery_latitude numeric(9,6) null
- delivery_longitude numeric(9,6) null
- requested_delivery_date date null - Buyer preferred date
- downpayment_paid_at timestamptz null - When order became counted/confirmed
- completed_at timestamptz null - Completion time
- cancelled_at timestamptz null - Cancellation time
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (order_number)

19.) order_items
Purpose: Listing line items inside an order.

Primary Key

- order_item_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id
- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- quantity_kg numeric(12,3) not null - Ordered weight in kg
- unit_price_per_kg numeric(12,2) not null - Snapshotted unit price
- line_subtotal_amount numeric(12,2) not null - Line subtotal

- listing_title_snapshot varchar(150) not null - Snapshot title for history
- produce_name_snapshot varchar(150) not null - Snapshot product name
- farmer_profile_id uuid not null fk -> farmer_profiles.farmer_profile_id - Snapshotted listing owner reference
- created_at timestamptz not null default now()

Unique Constraints

- None

20.) order_status_history
Purpose: Timeline of order status updates.

Primary Key

- order_status_history_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id
- triggered_by_user_id uuid null fk -> users.user_id

Fields

- from_status text null - Previous status
- to_status text not null - New status
- remarks text null - Optional note
- created_at timestamptz not null default now()

Unique Constraints

- None

21.) order_cancellations
Purpose: Cancellation record and refund basis.

Primary Key

- order_cancellation_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id

- cancelled_by_user_id uuid not null fk -> users.user_id

Fields

- cancelled_by_role_code varchar(50) not null - BUYER or FARMER
- cancellation_reason text not null - Stated reason
- cancelled_at timestamptz not null default now() - Cancellation timestamp
- refund_policy_applied text not null - WITHIN_3_BUSINESS_DAYS, AFTER_3_BUSINESS_DAYS, FARMER_FAULT_FULL_REFUND
- refund_percentage numeric(5,2) not null default 0.00 - Refund rate
- refund_amount numeric(12,2) not null default 0.00 - Refund amount
- farmer_kept_amount numeric(12,2) not null default 0.00 - Farmer compensation
- platform_kept_amount numeric(12,2) not null default 0.00 - Platform retained amount
- created_at timestamptz not null default now()

Unique Constraints

- unique (order_id)

22.) carts
Purpose: Active buyer cart.

Primary Key

- cart_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id

Fields

- cart_status text not null default 'ACTIVE' - ACTIVE, CONVERTED, ABANDONED
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (user_id)

23.) cart_items
Purpose: Items currently in cart.

Primary Key

- cart_item_id uuid pk

Foreign Keys

- cart_id uuid not null fk -> carts.cart_id
- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id

Fields

- quantity_kg numeric(12,3) not null - Desired quantity in kg
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (cart_id, produce_listing_id)

Payments, Escrow, Wallet

24.) wallets
Purpose: Wallet account per user.

Primary Key

- wallet_id uuid pk

Foreign Keys

- user_id uuid not null fk -> users.user_id

Fields

- available_balance numeric(12,2) not null default 0.00 - Spendable balance
- held_balance numeric(12,2) not null default 0.00 - Escrow/held balance
- wallet_status text not null default 'ACTIVE' - ACTIVE, FROZEN, CLOSED
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (user_id)

25.) wallet_transactions
Purpose: Wallet ledger entries.

Primary Key

- wallet_transaction_id uuid pk

Foreign Keys

- wallet_id uuid not null fk -> wallets.wallet_id
- payment_id uuid null fk -> payments.payment_id
- escrow_transaction_id uuid null fk -> escrow_transactions.escrow_transaction_id
- farmer_payout_id uuid null fk -> farmer_payouts.farmer_payout_id

Fields

- transaction_type text not null - CREDIT, DEBIT, HOLD, RELEASE, REFUND, PAYOUT
- amount numeric(12,2) not null - Ledger amount
- balance_before numeric(12,2) not null - Balance before transaction
- balance_after numeric(12,2) not null - Balance after transaction
- reference_code varchar(100) null - External or internal reference
- remarks text null - Explanation
- created_at timestamptz not null default now()

Unique Constraints

- None

26.) payments
Purpose: Payment records for downpayment, final payment, refunds.

Primary Key

- payment_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id

Fields

- payment_type text not null - DOWNPAYMENT, FINAL_PAYMENT, REFUND
- payment_method text not null - GCASH, COD_CASH_TO_DISTRIBUTOR, WALLET
- payment_status text not null - PENDING, SUCCESS, FAILED, CANCELLED
- amount numeric(12,2) not null - Payment amount

- external_reference varchar(150) null - Payment gateway/reference
- paid_at timestamptz null - Actual successful payment time
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- None

27.) escrow_transactions
Purpose: Escrow hold, release, forfeiture, refund records.

Primary Key

- escrow_transaction_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id
- payment_id uuid null fk -> payments.payment_id
- farmer_payout_id uuid null fk -> farmer_payouts.farmer_payout_id

Fields

- escrow_action text not null - HOLD, RELEASE_TO_FARMER, REFUND_TO_BUYER, FORFEIT_TO_FARMER, PLATFORM_CUT
- amount numeric(12,2) not null - Escrow action amount
- action_status text not null - PENDING, COMPLETED, FAILED
- acted_at timestamptz not null default now() - When action occurred
- remarks text null - Optional explanation
- created_at timestamptz not null default now()

Unique Constraints

- None

28.) farmer_payouts
Purpose: Payout released to farmer for an order.

Primary Key

- farmer_payout_id uuid pk

Foreign Keys

- farmer_profile_id uuid not null fk -> farmer_profiles.farmer_profile_id
- order_id uuid not null fk -> orders.order_id

Fields

- gross_amount numeric(12,2) not null - Total due before deductions
- platform_fee_amount numeric(12,2) not null default 0.00 - Platform cut
- net_amount numeric(12,2) not null - Final payout amount
- payout_status text not null - PENDING, RELEASED, FAILED
- released_at timestamptz null - Release time
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (order_id, farmer_profile_id)

Logistics

29.) deliveries
Purpose: Delivery trip that can carry one or more orders.

Primary Key

- delivery_id uuid pk

Foreign Keys

- vehicle_type_id uuid not null fk -> vehicle_types.vehicle_type_id

Fields

- delivery_code varchar(50) not null - Human-readable delivery reference
- delivery_status text not null - PLANNED, ASSIGNED, PICKED_UP, IN_TRANSIT, ARRIVED, COMPLETED, CANCELLED
- planned_pickup_date timestamptz null - Planned pickup time
- actual_pickup_at timestamptz null - Actual pickup time
- actual_arrival_at timestamptz null - Actual arrival time
- total_reserved_capacity_kg numeric(12,3) not null default 0.000 - Reserved combined load
- notes text null - Delivery notes
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (delivery_code)

30.) delivery_orders
Purpose: Junction table linking orders to a delivery trip.

Primary Key

- delivery_order_id uuid pk

Foreign Keys

- delivery_id uuid not null fk -> deliveries.delivery_id
- order_id uuid not null fk -> orders.order_id

Fields

- reserved_capacity_kg numeric(12,3) not null - Capacity consumed by this order
- created_at timestamptz not null default now()

Unique Constraints

- unique (delivery_id, order_id)
- unique (order_id) if each order can belong to only one delivery at a time

---

31.) delivery_assignments
Purpose: Distributor assignment history for deliveries.

Primary Key

- delivery_assignment_id uuid pk

Foreign Keys

- delivery_id uuid not null fk -> deliveries.delivery_id
- distributor_user_id uuid not null fk -> users.user_id

Fields

- assignment_status text not null - ASSIGNED, ACCEPTED, REPLACED, COMPLETED, CANCELLED
- assigned_at timestamptz not null default now() - Assignment time
- ended_at timestamptz null - End time if replaced/cancelled

- created_at timestamptz not null default now()

Unique Constraints

- None
- Usually enforce one active assignment per delivery with a partial unique index

---

32.) delivery_status_history
Purpose: Delivery status timeline.

Primary Key

- delivery_status_history_id uuid pk

Foreign Keys

- delivery_id uuid not null fk -> deliveries.delivery_id
- triggered_by_user_id uuid null fk -> users.user_id

Fields

- from_status text null - Previous status
- to_status text not null - New status
- remarks text null - Optional note
- created_at timestamptz not null default now()

Unique Constraints

- None

Quality Assurance

33.) qa_reports
Purpose: QA report per order within a delivery.

Primary Key

- qa_report_id uuid pk

Foreign Keys

- delivery_id uuid not null fk -> deliveries.delivery_id
- order_id uuid not null fk -> orders.order_id
- submitted_by_user_id uuid not null fk -> users.user_id

Fields

- qa_stage text not null - AT_PICKUP, AT_DELIVERY
- fresh_percent numeric(5,2) not null - Fresh percentage
- damaged_percent numeric(5,2) not null - Damaged percentage
- expected_quantity_kg numeric(12,3) not null - Expected quantity
- actual_quantity_kg numeric(12,3) not null - Actual quantity
- overall_condition text not null - EXCELLENT, GOOD, FAIR, POOR, REJECTED
- notes text null - QA notes
- submitted_at timestamptz not null default now()
- created_at timestamptz not null default now()

Unique Constraints

- Optional: unique (delivery_id, order_id, qa_stage) if only one report per stage per order

Notes

- Add a check that fresh_percent + damaged_percent <= 100.00

34.) qa_report_images
Purpose: Photo evidence for QA.

Primary Key

- qa_report_image_id uuid pk

Foreign Keys

- qa_report_id uuid not null fk -> qa_reports.qa_report_id

Fields

- image_url text not null - Storage URL
- display_order integer not null default 1 - Sort order
- created_at timestamptz not null default now()

Unique Constraints

- unique (qa_report_id, display_order)

35.) qa_issue_flags
Purpose: Issues flagged during QA.

Primary Key

- qa_issue_flag_id uuid pk

Foreign Keys

- qa_report_id uuid not null fk -> qa_reports.qa_report_id

Fields

- issue_type varchar(100) not null - Damage, spoilage, quantity shortage, etc.
- severity text not null - LOW, MEDIUM, HIGH, CRITICAL
- description text not null - Issue details
- created_at timestamptz not null default now()

Unique Constraints

- None

Messaging

36.) conversations
Purpose: One order-specific group chat.

Primary Key

- conversation_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id

Fields

- conversation_status text not null default 'ACTIVE' - ACTIVE, CLOSED
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- unique (order_id)

37.) conversation_participants
Purpose: Users inside a conversation.

Primary Key

- conversation_participant_id uuid pk

Foreign Keys

- conversation_id uuid not null fk -> conversations.conversation_id
- user_id uuid not null fk -> users.user_id

Fields

- participant_role_code varchar(50) not null - FARMER, BUYER, DISTRIBUTOR, ADMIN
- joined_at timestamptz not null default now()
- left_at timestamptz null
- created_at timestamptz not null default now()

Unique Constraints

- unique (conversation_id, user_id)

38.) messages
Purpose: Messages sent inside a conversation.

Primary Key

- message_id uuid pk

Foreign Keys

- conversation_id uuid not null fk -> conversations.conversation_id
- sender_user_id uuid not null fk -> users.user_id

Fields

- message_body text not null - Message content
- message_type text not null default 'TEXT' - TEXT, SYSTEM_NOTICE
- sent_at timestamptz not null default now()
- edited_at timestamptz null
- deleted_at timestamptz null
- created_at timestamptz not null default now()

Unique Constraints

- None

Reviews

39.) reviews
Purpose: Verified review after successful completed order.

Primary Key

- review_id uuid pk

Foreign Keys

- order_id uuid not null fk -> orders.order_id
- produce_listing_id uuid not null fk -> produce_listings.produce_listing_id
- reviewer_user_id uuid not null fk -> users.user_id

Fields

- star_rating smallint not null - Required stars, usually 1 to 5
- review_text text null - Optional description
- review_status text not null default 'PUBLISHED' - PUBLISHED, HIDDEN
- created_at timestamptz not null default now()
- updated_at timestamptz not null default now()

Unique Constraints

- Recommended: unique (order_id, produce_listing_id, reviewer_user_id)

Notes

- Add a check: star_rating between 1 and 5

Logs

40.) audit_logs
Purpose: Traceability for sensitive actions.

Primary Key

- audit_log_id uuid pk

Foreign Keys

- actor_user_id uuid null fk -> users.user_id

Fields

- entity_type varchar(100) not null - Table/domain acted on
- entity_id uuid null - Record identifier acted on
- action_type varchar(100) not null - CREATE, UPDATE, DELETE, APPROVE, REJECT, etc.
- action_summary text not null - Short explanation of what happened
- metadata jsonb null - Extra structured context
- ip_address inet null - Origin IP if relevant
- user_agent text null - Caller/client info
- created_at timestamptz not null default now()

Unique Constraints

- None