

Toy Model For Hyperfine Measurement

Adriano Del Vincio, Germano Bonomi,
Simone Stracka

University of Brescia, INFN Pisa

December 6, 2023




Scheme of the Simulation

Scheme of the Monte Carlo Toy for generating the events

Loop from 0 to Ntrials

Inner Loop: from 0 to Repetition



In this simulation, the data are created and analyzed using
RDataFrame framework.



A brief introduction about the Monte Carlo

We have developed a Monte Carlo Toy that produces two .root dataset files. The variables are columns of values that are shown in the figure below:

* Row *	* runNumber *	* random.ra *	* delay.del *	* frequence *	* type.type *	* radius.ra *
*****	*****	*****	*****	*****	*****	*****
* 0 *	* 0 *	* 0.4849736 *	* 2.4987087 *	* -25 *	* 2 *	* 2.8792768 *
* 1 *	* 1 *	* 0.2899349 *	* -1.685450 *	* 15 *	* 0 *	* 2.0739069 *
* 2 *	* 1 *	* 0.0197818 *	* -1.685450 *	* 15 *	* 0 *	* 1.8959179 *
* 3 *	* 1 *	* 0.2412478 *	* -1.685450 *	* 15 *	* 0 *	* 2.8919173 *
* 4 *	* 1 *	* 0.3846191 *	* -1.685450 *	* 15 *	* 0 *	* 3.3842529 *
* 5 *	* 1 *	* 0.4549068 *	* -1.685450 *	* 15 *	* 0 *	* 1.9130180 *
* 6 *	* 1 *	* 0.3739825 *	* -1.685450 *	* 15 *	* 0 *	* 1.6047382 *

Figure: Structure of the dataset.

- *runNumber*: identifies which run the event belong to (from 0 to *Repetition* - 1)
- *random*: values uniform distributed from 0 to 1, can be used to randomize the selection or for sub-sampling in the data
- *delay*: store the onset delay
- *frequence*: the frequency of the event
- *type*: type of the event: 0 annihilation on the walls, 1 residual gas annihilation, 2 cosmic event
- *radius*: radius of the annihilation vertex.

A brief introduction about the Monte Carlo

The Annihilation on the walls are generated as function of the frequency, using the two line-shapes of the transitions ($c \rightarrow b$) and ($d \rightarrow a$). The Annihilation on the residual gas and the cosmic background are generated uniformly on the frequency spectrum. All the parameters of the simulation are loaded from the `ToyConfiguration.txt` file. The parameters are chosen to reproduce the runs 4b.



```
Nstack = 20
NHbar = 14
Repetition = 5
# cosmic rate is expressed in event/second
CosmicRate = 0.051028571
Efficiency = 1
pwall_cb = 1
pwall_ad = 1
C = 0.5
FrequencyStep = 5
TimeStep = 8
SweepStep = 24
# The following are in kHz units
x_cb_start = 0
x_cb_end = 40
x_cb_peak = 20
x_da_start = 1420000
x_da_peak = 1420020
x_da_end = 1420040
delay = 2.5
```

Figure: Parameters of the Toy.





Triangular Line-shape Pdfs

For this first use of the toy, we have chosen simple line-shapes, triangular with a symmetric rise and fall.



Triangular Line-shapes Simulation

We sample at the given frequency step of 5 kHz the Pdfs, to simulate the experimental line-shapes. We applied the onset finding algorithm to this distribution.




The onset is fixed at $f = 0$ kHz. In this sample the cosmic background is set to zero.



A simple Onset finding Algorithm

The first algorithm that is tested is quite simple: **the onset is identified by the first bin with a content over a given threshold ($> N\mu_{cosmic}$)**¹

Before showing the plot with the simulated data, it is useful to remind how this algorithm deals with the frequency step:






The expected bin content is given evaluating the lineShape at each frequency step (+ 5 kHz, +10kHz ...).

With onset fixed at 0, and a linear line-shape, the first bin with an expected number of counts different from 0 will be the one at 5 kHz (bias).

¹Where the μ_{cosmic} is computed from the Poisson distribution of the cosmic counts expected per bin.




Consistency Check 1

We have tested the algorithm with a dataset without cosmic background and delay fixed to zero. The algorithm identifies the onset at frequency 5 kHz.




Consistency Check 2

We have tested the algorithm with a dataset without cosmic background. The delay is uniform distributed in -2.5 kHz and 2.5 kHz.






Consistency Check 2

With the delay, two bins ($frequency = 0$ kHz and $frequency = 5$ kHz) are populated.






algorithm test: threshold $> 3\mu_{\text{cosmic}}$

In this case, we have applied the algorithm to simulated data with cosmic background (using a rate of $0.051 \frac{\text{event}}{\text{s}}$, from passcut1). Each bin has an expected cosmic background of $\text{dwelltime} \cdot \text{rate} = 0.408$. The delay is uniform distributed in -2.5 kHz and 2.5 kHz .






algorithm test: threshold $> 5\mu_{\text{cosmic}}$

In this case, we have applied the algorithm to simulated data with cosmic background (using a rate of $0.051 \frac{\text{event}}{\text{s}}$, from passcut1). Each bin has an expected cosmic content of $\text{dwelltime} \cdot \text{rate} = 0.408$. The delay is uniform distributed in -2.5 kHz and 2.5 kHz .



algorithm test: threshold $> 8\mu_{\text{cosmic}}$

In this case, we have applied the algorithm to simulated data with cosmic background (using a rate of $0.051 \frac{\text{event}}{\text{s}}$, from passcut1). Each bin has an expected cosmic content of $\text{dwelltime} \cdot \text{rate} = 0.408$. The delay is uniform distributed in -2.5 kHz and 2.5 kHz .



Next step

- different line-shapes (e.g. quadratic rise, etc.)
- different onset-finding algorithm
- simulation of repetition/runs with Bfield drift.

Improvements of the week (24/11/30 - 24/12/07)

- Implemented the onset-finding algorithm of 2017 (*first* > 0, *second* > 1)
- Simulation with a lineShape following the `run 69373` (lineShape with high statistics).
- Implementation and test of different onset finding algorithms.

Fit to the data of run 69373

The lineShape is fitted using a Cruijff function, which takes into account the asymmetry of the left-right tails, ($model = N \cdot \exp(\frac{-(x-x_0)^2}{2\sigma_{0,1}+k_{0,1}(x-x_0)^2})$)





Figure: On top plot, the black line represents data and the red line the fit with the Cruijff function.



The Cruiff function is used in the simulation to generate the data. **The Cruiff is truncated at $f_0 = 175$ kHz.** In this way the onset of the lineshape is unambiguously determined. The new model is:

$$model = \begin{cases} baseline & f \leq 175 \text{ kHz} \\ N \cdot \exp\left(\frac{-(x-x_0)^2}{2\sigma_0 + k_0(x-x_0)^2}\right) & 175 \text{ kHz} < f \leq x_0 \\ N \cdot \exp\left(\frac{-(x-x_0)^2}{2\sigma_1 + k_1(x-x_0)^2}\right) & f > x_0 \end{cases} \quad (1)$$



Discretization of the lineshape



Here we plot the discretized lineshape, obtained sampling the Cuijff function with the optimal parameters by the fit of the previous slide. The lineshape is discretized into a series of 50 points, with a increment step of 5 kHz. The starting frequency is $f = 160$ kHz



Then discretized lineshapes here represents the model which the simulation programs uses to generate the data.

Generate Counts for each frequency

For illustration purposes, in this plot we show the distribution for a single run with an artificially high number of antihydrogen (50000 in the following plot, and omne single stack), without adding the cosmic background:



Parameters of the Simulation

We have studied the case of the series of run 4b. The parameters of the simulation are:

- $N_{stack} = 20$.
- $N_{\overline{H}} = 14$.
- $SweepSteps = 24$.
- $Repetition = 5$.
- $TimeStep = 8\text{ s}$
- $FrequencyStep = 5\text{ kHz}$.
- $\mu_{cosmic} = 0.051\text{ s}^{-1}$.
- $delay = \pm 2.5\text{ kHz}$.

The percentage of events of annihilation to residual gas is set to zero. The amount of anti-hydrogen is divided equally for the two transition c-b and d-a.

The first algorithm that we test is the one applied to the data taking of 2017. The onset is estimated taking the frequency which fulfills the criteria

$$f_i : bin(i) > 0; bin(i + 1) > 1 \quad (2)$$




a second version of the same algorithm is implemented, analyzing the frequencies in decreasing order (reversed algorithm):

$$f_i : bin(i) < 2; bin(i - 1) < 1$$




test 2017 algorithm

The algorithm is tested for $N_{\text{trial}} = 1000$. In this first scenario the cosmic events are removed from the data.






test 2017 algorithm

The algorithm is tested for $N_{\text{trial}} = 1000$. The cosmic background is fixed to 0.41 events per frequency.






test 2017 algorithm (reversed)

The algorithm is tested for $N_{\text{trial}} = 1000$. In this scenario the cosmic background is removed.



test 2017 algorithm (reversed)

The algorithm is tested for $N_{\text{trial}} = 1000$. The cosmic background is fixed to 0.41 events per frequency.



Other strategies

We have tested other ... different algorithms, that can be useful to identify the onset. The first algorithm identifies the onset as the first frequency with counts over threshold:

$$f_i : bin_i > Threshold \quad (4)$$

The second algorithm is a constant fraction discriminator. It works similarly to the previous algorithm, except for the fact that the threshold is computed each time as:

$$threshold = p \cdot \max\{bin_i\} \quad (5)$$

where p is a parameter of the algorithm, in the range (0,1).

In the end, we have tested another algorithm (*sumNeighbors*), defined in this way:

$$f_i : bin_i + bin_{i+1} + bin_{i+2} > 3 \cdot (\mu_{cosmic} + n \cdot \sigma_{cosmic}) \quad (6)$$

Results

algorithms	μ [kHz]	σ [kHz]	μ [kHz]	σ [kHz]
2017 (> 0 ; > 1)	-0.18	9.7	-0.445	14.1
2017 reversed (< 2 ; < 1)	-0.285	10.1	-0.34	12.8
threshold (> 1)	+0.025	11.5	+0.005	16.72
threshold (> 2)	-0.06	9.56	+0.67	14.08
threshold (> 3)	-0.1	7.48	-0.07	9.96
const. fraction ($p = 10\%$)	-0.02	11.56	0.19	16.66
const. fraction ($p = 20\%$)	-0.215	9.05	0.55	13.06
const. fraction ($p = 30\%$)	+0.08	7.43	0.05	8.84
sumNeighbors ($n = 1$)	-0.425	8.83	0.005	12.69
sumNeighbors ($n = 2$)	-0.19	7.03	0.07	9.61

Table: Result of the simulation for $N_{\text{trials}} = 1000$. In the first two column the cosmic background is removed from the data. The last two columns contains the result of the simulation adding the cosmic background. The μ and σ are the quantities computed from the distribution of $(\text{onset}_2 - \text{onset}_1) - MC_{\text{truth}}$.