


Tuve un pequeño problema por ese tanto lío de código, pero al final se ve como cargo los dos .jar






Dejo otra con la consola por si acaso

```
🔯 ssh.cloud.google.com/v2/ssh/projects/proyecto-arquitectura-453119/zones/europe-southwest1-b/instances/elastic-practica?authuser=0&hl=en_US&projectNu...
                                                                                                                                                                                                                 Q
 🐾 ssh.doud.google.com/v2/ssh/projects/proyecto-arquitectura-453119/zones/europe-southwest1-b/instances/elastic-practica?authuser=0&hl=en_U... 🔯
  SSH-in-browser
                                                                                                                                                       👲 UPLOAD FILE 👤 DOWNLOAD FILE 🔳 🥅 🔅
        - default
         - file
   policy:
      type: size-limit
size: 256mb
    strategy:
      type: numeric
max: 10
#
    layout:
       type: json
# Logs queries sent to Elasticsearch.
#logging.loggers:
    - name: elasticsearch.query level: debug
# Logs http responses.
#logging.loggers:
# - name: http.server.response
       level: debug
# Logs system usage information.
#logs system
#logging.loggers:
# - name: metrics.ops
       level: debug
\ensuremath{\text{\#}} 
 Enables debug logging on the browser (dev console)
#logging.browser.root:
    level: debug
# ------ System: Other ------- # The path where Kibana stores persistent data not saved in Elasticsearch. Defaults to data
# Specifies the path where Kibana creates the process ID file.
pid.file: /run/kibana/kibana.pid
\# Set the interval in milliseconds to sample system and process performance \# metrics. Minimum is 100ms. Defaults to 5000ms.
#ops.interval: 5000
# Specifies locale to be used for all localizable strings, dates and number formats.
# Supported languages are the following: English (default) "en", Chinese "zh-CN", Japanese "ja-JP", French "fr-FR".
#i18n.locale: "en"
# ======= Frequently used (Optional)=======
# The number of documents migrated at a time.
# If Kibana can't start up or upgrade due to an Elasticsearch `circuit_breaking_exception`,
# use a smaller batchSize value to reduce the memory pressure. Defaults to 1000 objects per batch.
#migrations.batchSize: 1000
# The maximum payload size for indexing batches of upgraded saved objects.
# To avoid migrations failing due to a 413 Request Entity Too Large response from Elasticsearch.
# This value should be lower than or equal to your Elasticsearch cluster's `http.max_content_length`
# configuration option. Default: 100mb
#migrations.maxBatchSizeBytes: 100mb
# The number of times to retry temporary migration failures. Increase the setting
# if migrations fail frequently with a message such as `Unable to complete the [...] step after # 15 attempts, terminating`. Defaults to 15 #migrations.retryAttempts: 15
# ----- Search Autocomplete -----
# Time in milliseconds to wait for autocomplete suggestions from Elasticsearch.
# This value must be a whole number greater than zero. Defaults to 1000ms
#unifiedSearch.autocomplete.valueSuggestions.timeout: 1000
\# Maximum number of documents loaded by each shard to generate autocomplete suggestions. \# This value must be a whole number greater than zero. Defaults to 100\_000
#unifiedSearch.autocomplete.valueSuggestions.terminateAfter: 100000
server.host: 0.0.0.0
adrilopezrobles@elastic-practica:~$ sudo nano /etc/elasticsearch/elasticsearch.yml adrilopezrobles@elastic-practica:~$
```





Entregable 5

