#### NPTEL MOOC

### PROGRAMMING, DATA STRUCTURES AND ALGORITHMS IN PYTHON

Week 3, Lecture 7

Madhavan Mukund, Chennai Mathematical Institute http://www.cmi.ac.in/~madhavan


#### How to sort?


- \* You are a Teaching Assistant for a course
- \* The instructor gives you a stack of exam answer papers with marks, ordered randomly
- \* Your task is to arrange them in descending order


### Strategy 2


- \* First paper: put in a new stack
- \* Second paper:
  - \* Lower marks than first? Place below first paper Higher marks than first? Place above first paper
- \* Third paper
  - \* Insert into the correct position with respect to first two papers
- Do this for each subsequent paper:
   insert into correct position in new sorted stack


74 32






















#### Insertion Sort

- \* Start building a sorted sequence with one element
- \* Pick up next unsorted element and insert it into its correct place in the already sorted sequence


```
def InsertionSort(seq):
for sliceEnd in range(len(seq)):
 # Build longer and longer sorted slices
 # In each iteration seq[0:sliceEnd] already sorted
 # Move first element after sorted slice left
 # till it is in the correct place
  pos = sliceEnd
 while pos > 0 and seq[pos] < seq[pos-1]:
    (seq[pos], seq[pos-1]) = (seq[pos-1], seq[pos])
    pos = pos-1
```




74 32




32 74



32 74




32 74




32 55 74 89 21 64







32 55




89




21 32



21 32



21 32



### Analysis of Insertion Sort

- \* Inserting a new value in sorted segment of length k requires upto k steps in the worst case
- \* In each iteration, sorted segment in which to insert increased by 1
- \*  $T(n) = 1 + 2 + ... + n-1 = n(n-1)/2 = O(n^2)$