



TC 5033

Deep Learning

Convolutional Neural Networks

Team Members:

- A01200230 - Armando Bringas Corpus

Activity 2b: Building a CNN for CIFAR10 dataset with PyTorch

- Objective

The main goal of this activity is to further your understanding of Convolutional Neural Networks (CNNs) by building one using PyTorch. You will apply this architecture to the famous CIFAR10 dataset, taking what you've learned from the guide code that replicated the Fully Connected model in PyTorch (Activity 2a).

- Instructions This activity requires submission in teams of 3 or 4 members. Submissions from smaller or larger teams will not be accepted unless prior approval has been granted (only due to exceptional circumstances). While teamwork is encouraged, each member is expected to contribute individually to the assignment. The final submission should feature the best arguments and solutions from each team member. Only one person per team needs to submit the completed work, but it is imperative that the names of all team members are listed in a Markdown cell at the very beginning of the notebook (either the first or second cell). Failure to include all team member names will result in the grade being awarded solely to the individual who submitted the assignment, with zero points given to other team members (no exceptions will be made to this rule).

Understand the Guide Code: Review the guide code from Activity 2a that implemented a Fully Connected model in PyTorch. Note how PyTorch makes it easier to implement neural networks.

Familiarize Yourself with CNNs: Take some time to understand their architecture and the rationale behind using convolutional layers.

Prepare the Dataset: Use PyTorch's DataLoader to manage the dataset. Make sure the data is appropriately preprocessed for a CNN.

Design the CNN Architecture: Create a new architecture that incorporates convolutional layers. Use PyTorch modules like nn.Conv2d, nn.MaxPool2d, and others to build your network.

Training Loop and Backpropagation: Implement the training loop, leveraging PyTorch's autograd for backpropagation. Keep track of relevant performance metrics.

Analyze and Document: Use Markdown cells to explain your architectural decisions, performance results, and any challenges you faced. Compare this model with your previous Fully Connected model in terms of performance and efficiency.

- Evaluation Criteria
 - Understanding of CNN architecture and its application to the CIFAR10 dataset
 - Code Readability and Comments
 - Appropriateness and efficiency of the chosen CNN architecture
 - Correct implementation of Training Loop and Accuracy Function
 - Model's performance metrics on the CIFAR10 dataset (at least 65% accuracy)
 - Quality of Markdown documentation
- Submission

Submit via Canvas your Jupyter Notebook with the CNN implemented in PyTorch. Your submission should include well-commented code and Markdown cells that provide a comprehensive view of your design decisions, performance metrics, and learnings.

'2.1.0'

True

```
NVIDIA GeForce GTX 1650
(7, 5)
_CudaDeviceProperties(name='NVIDIA GeForce GTX 1650', major=7, minor=5, total_memory=4095MB,
multi_processor_count=14)
```

Download Cifar10 dataset

```
Files already downloaded and verified
Files already downloaded and verified
Files already downloaded and verified
```

Dataset CIFAR10

Number of datapoints: 50000

Root location: data/cifar10_data

Split: Train

StandardTransform

Transform: Compose(
 ToTensor()
 Normalize(mean=[0.491, 0.482, 0.447], std=[0.247, 0.243, 0.261])
)

64


Using GPUs

cuda

Show Images

La imagen muestreada representa un: automobile





Calculate Accuracy

Training Loop

Linear model

Model Hyperparameters

Neural Network Architecture:

Input -> Flatten -> Linear -> ReLU -> Linear -> ReLU -> Linear -> Output

This architecture is a sequence of layers configured to process input data for classification tasks.

Train model and get accuracy

Epoch: 0	costo: 1.3296	accuracy: 0.4536
Epoch: 1	costo: 1.9087	accuracy: 0.4926
Epoch: 2	costo: 1.2613	accuracy: 0.5078
Epoch: 3	costo: 1.9224	accuracy: 0.5274
Epoch: 4	costo: 1.3760	accuracy: 0.5270
Epoch: 5	costo: 1.1816	accuracy: 0.5324
Epoch: 6	costo: 1.1088	accuracy: 0.5256
Epoch: 7	costo: 0.8616	accuracy: 0.5200
Epoch: 8	costo: 0.6553	accuracy: 0.5274
Epoch: 9	costo: 1.0837	accuracy: 0.5416

0.5222

Sequential CNN

Model Hyperparameters

Input -> Conv2d -> ReLU -> Conv2d -> ReLU -> MaxPool2d -> Flatten -> Linear -> Output

This architecture represents a convolutional neural network (CNN) designed for processing image data.

Epoch: 0	costo: 1.5983	accuracy: 0.4938
Epoch: 1	costo: 1.7619	accuracy: 0.5366
Epoch: 2	costo: 1.3108	accuracy: 0.5618
Epoch: 3	costo: 1.2336	accuracy: 0.5820
Epoch: 4	costo: 1.2264	accuracy: 0.5846
Epoch: 5	costo: 1.6059	accuracy: 0.5964
Epoch: 6	costo: 1.2219	accuracy: 0.6076
Epoch: 7	costo: 0.7529	accuracy: 0.6144
Epoch: 8	costo: 0.6677	accuracy: 0.6234
Epoch: 9	costo: 1.3023	accuracy: 0.6346

0.6216

OOP Approach and performance improvement

Model Hyperparameters

Neural Network Architecture:

Input -> Conv2d -> BatchNorm2d -> ReLU -> Conv2d -> BatchNorm2d -> ReLU -> Flatten -> Linear -> Output

This architecture represents a simple convolutional neural network (CNN) designed for processing image data.

Epoch: 0	costo: 1.2241	accuracy: 0.6782
Epoch: 1	costo: 0.8293	accuracy: 0.7264
Epoch: 2	costo: 0.2341	accuracy: 0.7516
Epoch: 3	costo: 0.6276	accuracy: 0.7682
Epoch: 4	costo: 0.5623	accuracy: 0.7342
Epoch: 5	costo: 0.0709	accuracy: 0.7702
Epoch: 6	costo: 0.2689	accuracy: 0.7776
Epoch: 7	costo: 0.4365	accuracy: 0.7770
Epoch: 8	costo: 0.0238	accuracy: 0.7662
Epoch: 9	costo: 0.0676	accuracy: 0.7586
Epoch: 10	costo: 0.0808	accuracy: 0.7284
Epoch: 11	costo: 0.0470	accuracy: 0.7476
Epoch: 12	costo: 0.0633	accuracy: 0.7704
Epoch: 13	costo: 0.0117	accuracy: 0.7736
Epoch: 14	costo: 0.0077	accuracy: 0.7724
Epoch: 15	costo: 0.0515	accuracy: 0.7848
Epoch: 16	costo: 0.0040	accuracy: 0.7398
Epoch: 17	costo: 0.0037	accuracy: 0.7714
Epoch: 18	costo: 0.0046	accuracy: 0.7764
Epoch: 19	costo: 0.1167	accuracy: 0.7848

0.7924

The model's final performance on the ASL dataset achieved an accuracy of 79.24%. The convolutional network architecture, utilizing an OOP approach with batch normalization, outperformed the preceding linear and sequential models.