

Replacement Tubing

Chemical tubing in a variety of diameters, lengths, and materials



Model	O.D. Dimension	I.D. Dimension	Material	PSI / Bar @ 73°F (22°C)	Max Temp
R00097	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE	300 PSI / 20.6 Bar	200°F / 93°C
R00097-100	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE	300 PSI / 20.6 Bar	200°F / 93°C
R00267	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE	400 PSI / 27.5 Bar	225°F / 107°C
R00267-100	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE	400 PSI / 27.5 Bar	225°F / 107°C
R00122	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	PE	200 PSI / 13.7 Bar	200°F / 93°C
R00122-100	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	PE	200 PSI / 13.7 Bar	200°F / 93°C
R00151	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	PE Black UV	200 PSI / 13.7 Bar	200°F / 93°C
R00151-100	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	PE Black UV	200 PSI / 13.7 Bar	200°F / 93°C
R00167	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE Black UV	300 PSI / 20.6 Bar	200°F / 93°C
R00167-100	1/4" (.25) 6.35mm	1/8" (.125) 3.175mm	PE Black UV	300 PSI / 20.6 Bar	200°F / 93°C
R00255	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	Clear Vinyl	Suction / prime only	175°F / 79°C
R00255-100	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	Clear Vinyl	Suction / prime only	175°F / 79°C
R00268	3/8" (.375) 9.525mm	1/4" (.25) 6.35mm	PVDF	250 PSI / 17.2 Bar	250°F / 121°C

Note: Model code "-100" = 100' roll. Remaining is per foot.

