

# Falcon<sup>®</sup> 4620

*Rugged Vehicle Mount Computer*

## Vehicle Mount Wireless Windows Computer

Designed for the harshest environments of the warehouse or loading dock, the Falcon 4620 features your choice of the latest Microsoft Windows operating system coupled with a powerful 800 Mhz processor. PSC's radio independent support means you have a choice of 2.4Ghz 802.11b radios including Cisco Aironet, Lucent/Proxim Orinoco, and Symbol Spectrum24 HR.

## Big Features in a Compact Package

The Falcon 4620 boasts a stunning 12.1" TFT SVGA color touchscreen display, yet the installed system is similar in size to many 10" competing models. The 12.1" screen is ideal for touchscreen applications, and features a bright 420 NIT display, providing great readability both indoors and out.

The 800Mhz processor combined with up to 512MB RAM provides the performance necessary for the most complex applications. Integrated wired Ethernet allows easy initial loading of the operating system and applications. And the shock resistant 20GB hard disk drive provides ample storage space, or for ultra-rugged applications, a 2GB Flash with no moving parts is available.

## Ruggedized & Freezer Rated

Featuring an IP65 sealing rating combined with Military Specification ruggedization, the Falcon 4620 can operate in the toughest warehouse environments. The ability to operate in freezers to -30C without an expensive and power hungry heater provides a huge advantage over the competition. An optional NEMA 4 sealed 84-key keyboard with integrated mouse provides input flexibility.

## Integration with PSC PowerScan Lasers

The Falcon 4620 was designed to allow PSC lasers (including PowerScan RF) to directly connect to the base computer, without requiring an external power connection. This allows easy integration with both wired and wireless bar code scanners.

## Unique Modular Mounting System

The base unit includes a low-profile fully adjustable mounting bracket. The flexible design allows a keyboard bracket to be attached directly to the base bracket, conserving valuable space. The optional scanner attachment allows a PSC PowerScan RF laser to be mounted to either side of the vehicle computer.

## Software Support

The Falcon 4620 offers a choice of any of the leading Microsoft Windows Operating Systems including Embedded Windows XP, XP Professional and Windows 2000. Optional terminal emulation support is provided for VT100/220 and IBM 5250 & 3270. Optional support for a virtual on-screen keyboard is also provided.

### Features

- 12.1" TFT Color Touchscreen SVGA Display
- Compact Form Factor Takes Similar Space as 10" Models
- Powerful 800Mhz Processor
- Choice of Microsoft Windows Operating System
- PSC PowerScan RF Integration
- Choice of 802.11b Radios
- IP 65 Sealed Enclosure
- Operates in -30C Freezers without a Heater
- Internal DC Power Supply
- Rugged Milled Aluminum Enclosure
- Choice of Keyboards (optional)



# Specifications

Falcon® 4620

## System

### Operating System:

Windows XP Embedded (standard)  
Windows XP Pro (optional)  
Windows 2000 (optional)

### Processor:

VIA C3 800Mhz

### Memory

128 MB RAM Standard  
256 or 512 MB RAM Optional  
256KB Flash (BIOS)

### Sound:

PCI Audio (line input and outputs)

### Graphics:

32MB Video RAM

### Storage:

Hard Disk 20 GB, 2.5" ATA/IDE (standard)  
Flash Disk 2 GB (optional)

### Communication Ports:

2 Serial ports RS 232C (115 Kb/s max)  
Com 1: 12VDC on pin 9  
2 USB 1.1 A (USB Floppy or CDROM Boot Support)  
1 Ethernet 10/100-TX, RJ45  
1 Mouse/Keyboard port (PS/2)  
Buzzer, Mic, CD in and line out stereo

### PC Card Slots:

2 type II or 1 type III (PCMCIA)

### Speaker:

Internal Beeper: 85dB @ 10cm

### Radio Support:

Requires certified Type II PC Card Format,  
2.4Ghz Spread Spectrum 802.11b.

Radios Supported: Cisco Aironet 802.11b,  
Lucent/Proxim Orinoco 802.11b,  
Symbol Spectrum24 HR

Use integrated antenna PC Card or  
optional external antenna

### Software Support:

Terminal Emulation for  
VT100/220, IBM 3270/5250

### Bar Code Scanner Support:

Serial or PS/2  
Decoded Lasers; PSC PowerScan (RF & Cabled)  
and most 3<sup>rd</sup> party scanners supported.

PowerScan RF option includes mounting  
bracket and serial cable with power provided  
by base computer

## Safety & Regulatory

### Electrical:

FCC: Part 15, Class B, EN55022  
UL: UL94, Class VO

### International Safety:

CE Vehicle, FCC light industry

## Mechanical

### Dimensions:

12.5" (w) x 10" (h) x 2.5" (d)

31.75cm x 25.4cm x 6.35cm

### Weight:

9.3 lbs / 4.2 kg

(excluding brackets & keyboard)

### Display

12.1" (30.7cm) diagonal, TFT Color; 800 x 600

SVGA, 420 NITS

Resistive Touch Screen

### Keyboards

Choice of separate tethered keyboards  
(keyboard mount available)

NEMA 4 sealed 84-key with 2 button pointing  
device, 12 FN Keys

Commercial Grade 84-key with 12 FN Keys

### Construction

Enclosure: Precision Milled Aluminum

## Electrical

### Power Supply:

9-36 VDC Internal Power Supply

32-80 VDC External Power Converter (optional)

110/220V AC/DC Power Supply (optional)

Internal Lithium Battery Backup

(BIOS & Clock only)

### Power Consumption:

25W average; 40W maximum

## Environmental

### Temperature rating

Operating: -4°F to +122°F (-20°C to +50°C)

-supports intermittent periods at -30°C (-22°F)

Storage: -22°F to +167°F (-30°C to +75°C)

### Humidity:

10 - 95% RH, non-condensing

### Sealing:

IP65  
MILSPEC: 810C, 810E



## Available Accessories

- Keyboards
- PowerScan™ RF
- PowerScan wired
- Mounting brackets  
(for keyboard & PowerScan)
- RF Cards
- Flash Disk
- Power Adapters

### PSC Inc.

959 Terry Street  
Eugene OR 97402-9150 USA  
Tel: 800 695 5700 or 541 683 5700  
Fax: 541 345 7140

### Specifications are subject to change without notice.

Additional information concerning this product or other PSC products  
and services can be found at the PSC website: [www.pscnet.com](http://www.pscnet.com),  
or contact your PSC representative for more information.



### PSC Worldwide Sales and Service locations

Australia - NSW Tel: 61 2 9878 8999 Fax: 61 2 9878 8688	Belgium Tel: 32 2 414 74 09 Fax: 32 2 410 11 63	Brazil Tel: 55 11 5507 7721 Fax: 55 11 5507 7696
---	---	--

Germany Tel: 49 6151 93580 Fax: 49 6151 935897	Hong Kong Tel: 852 25846210 Fax: 852 25210291	India Tel: 91 11 24621586 Fax: 91 11 24641662
--	---	---

Sweden Tel: 46 4010 84 92 Fax: 46 4010 84 91	United Kingdom Tel: 44 1923 809500 Fax: 44 1923 809505
--	--

Chile Tel: 562-339-7000 Fax: 562-339-7985	China Tel: 86 10 6857 9048 Fax: 86 10 6857 8699	China - South Tel: 86 20 8765 9955 Fax: 86 20 8765 9955
---	---	---

Italy Tel: 39 039 629031 Fax: 39 039 6859496	Japan Tel: 81 3 3491 6761 Fax: 81 3 3491 6656	Latin America Tel: 1 305 539 0111 Fax: 1 305 539 0206
--	---	---

France Tel: 33 1 64 86 71 00 Fax: 33 1 64 46 72 44
--

Singapore Tel: 65 435 1311 Fax: 65 226 1242	Spain Tel: 34 91 746 28 60 Fax: 34 91 742 35 33
---	---