

SLATE v0.1

Say less. Keep the relation. Ask once. Wait.

NEW CONCEPT

THEN WAIT

Opportunity cost: value of the next-best feasible alternative forgone.
One room. Choose clinic. Library was the best feasible option forgone.
What value did this choice give up?

CONTRAST

THEN WAIT

Own price changes, other demand determinants fixed: movement.
Another demand determinant changes: shift.
Income rose for a normal good; its price stayed fixed.
Movement or shift, and why?

PROCEDURE / KEEP CODE VISIBLE

THEN WAIT

```
int x = 5;  
x = x + 1;  
Read old x. Add 1. Store the result in x.  
Fresh: int y = 3; y = y + 4;  
What is y afterward?
```

REPAIR

THEN WAIT

You counted indices from 1. Java array indices start at 0.
Fresh: `int[] a = {6, 8, 1};`
What is `a[1]`?

COMPACT / AFTER RECONSTRUCTION

$P(A|B) = P(A \text{ and } B) / P(B)$, with $P(B) > 0$.
Given B: restrict to B. Keep the denominator bound.

INDEPENDENT USE

THEN WAIT

Alarm components: 8 defective, 18 nondefective.
Select uniformly among alarm components.
Probability of defect? Explain the denominator.

REMEMBER

Keep conditions, units, exact syntax, and relation direction.
Help produces assisted evidence. Use a fresh no-hint task to check independence.
New code, equations, and diagrams need persistent accessible support in voice.
Short wording and two immediate passes do not prove delayed learning.
Later: fresh tasks in ordinary wording, without SLATE support.