Living Documentation

Table of Contents

1. Introduction	1
2. Summary	2
3. Features	3
3.1. Cukedoctor Converter	3
3.1.1. Scenario: Convert features output into documentation	3
3.2. Ordering	
3.2.1. Scenario: Default ordering	
3.2.2. Scenario: Custom ordering	6
3.3. Documentation introduction chapter	8
3.3.1. Scenario: Introduction chapter in classpath	8
3.4. Enrich features	10
3.4.1. Scenario: DocSting enrichment	10
3.4.2. Scenario: Comments enrichment	12

Chapter 1. Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and Asciidoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

- Living documentation should be readable and highlight your software features;
 - Most bdd tools generate reports and not a truly documentation.
- Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of cucumber json output files;
 - In the 'worst case' to enhance your documentation you will need to know a bit of asciidoc markup.

In the subsequent chapters you will see a documentation which is generated by the output of Cukedoctor's BDD tests, a real bdd living documentation.

Chapter 2. Summary

S	cenario	s				Steps				Featu	res: 4
Passed	Failed	Total	Passed	Failed	Skippe d	Pendin g	Undefi ned	Missin g	Total	Durati on	Status
				Cu	kedoctor	Convert	er				
1	0	1	3	0	0	0	0	0	3	02s 747ms	passed
					0rde	ring					
2	0	2	6	0	0	0	0	0	6	074ms	passed
			D	ocumenta	tion int	roductio	on chapte	er er			
1	0	1	4	0	0	0	0	0	4	025ms	passed
					Enrich	features					
2	0	2	6	0	0	0	0	0	6	115ms	passed
					Tot	als					
6	0	6	19	0	0	0	0	0	19	02s	961ms

Chapter 3. Features

3.1. Cukedoctor Converter

In order to have awesome *living documentation* As a bdd developer

I want to use **Cukedoctor** to convert my cucumber test results into living documentation

3.1.1. Scenario: Convert features output into documentation

Given

The following two features: d (01s 108ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

When

I convert their json output report using cukedoctor converter **★** (01s 637ms)

To generate cucumber .json output files just execute your *BDD* tests with **json** formatter, example:



@RunWith(Cucumber.class)
@CucumberOptions(plugin = {"json:target/cucumber.json"})



plugin option replaced **format** option which was deprecated in newer cucumber versions.

Then

I should have awesome living documentation **▲** (001ms)

Documentation

Summary

S	cenario	os				Steps				Featu	ıres: 2
Passed	Failed	Total	Passed	Failed	Skippe d	Pendin g	Undefi ned	Missin g	Total	Durati on	Status
					Feat	ure1					
1	0	1	1	0	0	0	0	0	1	647ms	passed
					Feat	ure2					
1	0	1	1	0	0	0	0	0	1	000ms	passed
					Tot	als					
2	0	2	2	0	0	0	0	0	2	64	7ms

Features

Feature1

Scenario: Scenario feature 1

Given scenario step **d** (647ms)

Feature2

Scenario: Scenario feature 2

Given scenario step **d** (000ms)

3.2. Ordering

In order to have features ordered in living documentation As a bdd developer I want to control the order of features in my documentation

3.2.1. Scenario: Default ordering

Given

The following two features: **★** (000ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

When

I convert them using default order de (025ms)

Then

Features should be ordered by name in resulting documentation documentation (000ms)

Feature1

Scenario: Scenario feature 1

Given

scenario step 🛍 (647ms)

Feature2

Scenario: Scenario feature 2

Given

scenario step 🛍 (000ms)

3.2.2. Scenario: Custom ordering

Given

The following two features: **★** (000ms)

#order: 2

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

#order: 1

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step



Ordering is done using feature comment 'order:'

When

I convert them using comment order do (048ms)

Then

Features should be ordered respecting order comment d (000ms)

Feature2

Scenario: Scenario feature 2

Given

scenario step de (000ms)

Feature1

Scenario: Scenario feature 1

Given

scenario step 🛍 (313ms)

3.3. Documentation introduction chapter

In order to have an introduction chapter in my documentation As a bdd developer

I want to be able to provide an asciidoc based document which introduces my software

3.3.1. Scenario: Introduction chapter in classpath

Given

The following two features: d (000ms)

Feature: Feature1

Scenario: Scenario feature 1

Given scenario step

Feature: Feature2

Scenario: Scenario feature 2

Given scenario step

And

The following asciidoc document is on your application classpath d (024ms)

Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and Asciidoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

Living documentation should be readable and highlight your software features;

Most bdd tools generate reports and not a truly documentation.

Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of cucumber json output files;

In the 'worst case' to enhance your documentation you will need to know a bit of asciidoc markup.



The introduction file must be named **intro-chapter.adoc** and can be in any package of your application

Ç

By default Cukedoctor will look into application folders but you can make Cukedoctor look into external folder by setting the following system property:

System.setProperty("INTRO_CHAPTER_DIR","/home/some/external/folder");

When

Bdd tests results are converted into documentation by Cukedoctor documentation by Cukedoctor (000ms)

Then

Resulting documentation should have the provided introduction chapter documentation should have a specific documentation of the provided documentation of th

Documentation

Introduction

Cukedoctor is a **Living documentation** tool which integrates Cucumber and Asciidoctor in order to convert your *BDD* tests results into an awesome documentation.

Here are some design principles:

Living documentation should be readable and highlight your software features;

Most bdd tools generate reports and not a truly documentation.

Cukedoctor **do not** introduce a new API that you need to learn, instead it operates on top of cucumber json output files;

In the 'worst case' to enhance your documentation you will need to know a bit of asciidoc markup.

Summary

Scenar	rios		Steps						Featur	es: 2
Passe d	Faile d	Total	Passe d	Faile d	Skipp ed	Pendi ng	Unde fined	Total	Durat ion	Status

					Feat	ure1					
1	0	1	1	0	0	0	0	0	1	647m s	passe d
					Feat	ure2					
1	0	1	1	0	0	0	0	0	1	000m s	passe d
					To	tals					
2	0	2	2	0	0	0	0	0	2	647ms	

Features

Feature1

Scenario: Scenario feature 1

Given scenario step **d** (647ms)

Feature2

Scenario: Scenario feature 2

3.4. Enrich features

In order to have awesome *living documentation*As a bdd developer
I want to render asciidoc markup inside my features

3.4.1. Scenario: DocSting enrichment

Asciidoc markup can be used in feature **DocStrings**. To do so you need to enable it by using **cukector-dicrete** comment on the feature.

The following two features: d (000ms)

```
Feature: Enrich feature
  Scenario: Render source code
    # cukedoctor-discrete
   Given the following source code in docstrings
 [source, java]
 public int sum(int x, int y){
  int result = x + y;
  return result; (1)
 }
 <1> We can have callouts in living documentation
  Scenario: Render table
    # cukedoctor-discrete
   Given the following table
 11 11 11
  |===
  | Cell in column 1, row 1 | Cell in column 2, row 1
  | Cell in column 1, row 2 | Cell in column 2, row 2
  | Cell in column 1, row 3 | Cell in column 2, row 3
 |===
11 11 11
```

When

I convert docstring enriched json output using cukedoctor converter doc47ms)

Then

DocString asciidoc output must be rendered in my documentation **▲** (000ms)

Discrete class feature

Scenario: Render source code

```
Given
the following source code  (267ms)

public int sum(int x, int y){
   int result = x + y;
   return result;  1)
}
① We can have callouts in living documentation>
```

Scenario: Render table

e following table 🛍 (000ms)	
; following table • (ooonts)	
Coll in column 1 years 1	Call in column 2 years 1
Cell in column 1, row 1	Cell in column 2, row 1
Cell in column 1, row 2	Cell in column 2, row 2
Cell in column 1, row 3	Cell in column 2, row 3

3.4.2. Scenario: Comments enrichment

12

Asciidoc markup can be used in feature comments. To do so you need to surround asciidoc markup by **curly brackets**;.

```
Given

The following feature with asciidoc markup in comments: 

(000ms)
```

```
Scenario: Adding numbers
You can *asciidoc markup* in _feature_ #description#.

NOTE: This is a very important feature!

#{IMPORTANT: Asciidoc markup inside *steps* must be surrounded by *curly brackets*.}

Given I have numbers 1 and 2

# {NOTE: Steps comments are placed *before* each steps so this comment is for the *WHEN* step.}

When I sum the numbers

# {* this is a list of itens inside a feature step}

# {* there is no multiline comment in gherkin}

# {** second level list item}
Then I should have 3 as result
```

When

I convert enriched feature json output using cukedoctor **d** (067ms)

Then

Calculator

Scenario: Adding numbers

You can use **asciidoc markup** in *feature* description.



This is a very important feature!

Given

I have numbers 1 and 2 i (114ms)



Asciidoc markup inside **steps** must be surrounded by **curly brackets**.

When

I sum the numbers de (000ms)



Steps comments are placed **before** each steps so this comment is for the **WHEN** step.

Then

I should have 3 as result **★** (001ms)

this is a list of itens inside a feature step there is no multiline comment in gherkin second level list item