

asciidoctor-documentation

Table of Contents

Summary	1
Features	2
Cross References	2
Scenario: Create a cross reference from an AsciiDoc cell to a section	2
Scenario: Create a cross reference using the target section title	3
Scenario: Create a cross reference using the target reftext	4
Scenario: Create a cross reference using the formatted target title	5
Open Blocks	6
Scenario: Render an open block that contains a paragraph to HTML	7
Scenario: Render an open block that contains a paragraph to DocBook	7
Scenario: Render an open block that contains a paragraph to HTML (alt)	8
Scenario: Render an open block that contains a paragraph to DocBook (alt)	9
Scenario: Render an open block that contains a list to HTML	10
Open Blocks	11
Scenario: Render a pass block without performing substitutions by default to HTML	11
Scenario: Render a pass block without performing substitutions by default to DocBook	12
Scenario: Render a pass block performing explicit substitutions to HTML	13
Text Formatting	14
Scenario: Convert text that contains superscript and subscript characters	14
Scenario: Convert text that has ex-inline literal formatting	15
Scenario: Convert text that has ex-inline monospaced formatting	16

Summary

Scenarios			Steps							Features: 4	
Passed	Failed	Total	Passed	Failed	Skipped	Pending	Undefined	Missing	Total	Duration	Status
Cross References											
4	0	4	12	0	0	0	0	0	12	028ms	passed
Open Blocks											
5	0	5	15	0	0	0	0	0	15	043ms	passed
Open Blocks											
3	0	3	9	0	0	0	0	0	9	003ms	passed
Text Formatting											
3	0	3	9	0	0	0	0	0	9	003ms	passed
Totals											
15	0	15	45	0	0	0	0	0	45	079ms	

Features

Cross References

In order to create links to other sections
As a writer
I want to be able to use a cross reference macro

Scenario: Create a cross reference from an AsciiDoc cell to a section

Given

the AsciiDoc source 🍌 (000ms)

```
|===  
a|See <<_install>>  
|===  
  
== Install  
  
Instructions go here.
```

When

it is converted to html 🍌 (002ms)

Then

the result should match the HTML structure 🍌 (005ms)

```
table.tableblock.frame-all.grid-all.spread  
  colgroup  
    col style='width: 100%;'  
  tbody  
    tr  
      td.tableblock.halign-left.valign-top  
        div  
          .paragraph: p  
            'See  
            a href='#_install' Install  
        .sect1  
          h2#_install Install  
        .sectionbody  
          .paragraph: p Instructions go here.
```

Scenario: Create a cross reference using the target section title

Given

the AsciiDoc source 🍌 (000ms)

```
== Section One  
  
content  
  
== Section Two  
  
refer to <<Section One>>
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML structure 🍌 (004ms)

```
.sect1  
  h2#_section_one Section One  
  .sectionbody: .paragraph: p content  
.sect1  
  h2#_section_two Section Two  
  .sectionbody: .paragraph: p  
    'refer to  
    a href='#_section_one' Section One
```

Scenario: Create a cross reference using the target ref text

Given

the AsciiDoc source 🍌 (000ms)

```
[reftext="the first section"]  
== Section One  
  
content  
  
== Section Two  
  
refer to <<the first section>>
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML structure 🍌 (005ms)

```
.sect1  
  h2#_section_one Section One  
  .sectionbody: .paragraph: p content  
.sect1  
  h2#_section_two Section Two  
  .sectionbody: .paragraph: p  
    'refer to  
    a href='#_section_one' the first section
```

Scenario: Create a cross reference using the formatted target title

Given

the AsciiDoc source 🍌 (000ms)

```
== Section *One*

content

== Section Two

refer to <<Section *One*>>
```

When

it is converted to html 🍌 (001ms)

Then

the result should match the HTML structure 🍌 (005ms)

```
.sect1
  h2#_section_strong_one_strong
    'Section
    strong One
  .sectionbody: .paragraph: p content
.sect1
  h2#_section_two Section Two
  .sectionbody: .paragraph: p
    'refer to
    a href='#_section_strong_one_strong'
    'Section
    strong One
```

Open Blocks

In order to group content in a generic container

As a writer

I want to be able to wrap content in an open block

Scenario: Render an open block that contains a paragraph to HTML

Given

the AsciiDoc source 🍌 (000ms)

```
--  
A paragraph in an open block.  
--
```

When

it is converted to html 🍌 (008ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<div class="openblock">  
<div class="content">  
<div class="paragraph">  
<p>A paragraph in an open block.</p>  
</div>  
</div>  
</div>
```

Scenario: Render an open block that contains a paragraph to DocBook

Given

the AsciiDoc source 🍌 (000ms)

```
--  
A paragraph in an open block.  
--
```

When

it is converted to docbook 🍌 (003ms)

Then

the result should match the XML source 🍌 (000ms)

```
<simpara>A paragraph in an open block.</simpara>
```

Scenario: Render an open block that contains a paragraph to HTML (alt)

Given

the AsciiDoc source 🍌 (000ms)

```
--  
A paragraph in an open block.  
--
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML structure 🍌 (019ms)

```
.openblock  
  .content  
    .paragraph  
      p A paragraph in an open block.
```

Scenario: Render an open block that contains a paragraph to DocBook (alt)

Given

the AsciiDoc source 🍌 (000ms)

```
--  
A paragraph in an open block.  
--
```

When

it is converted to docbook 🍌 (000ms)

Then

the result should match the XML structure 🍌 (003ms)

```
simpara A paragraph in an open block.
```

Scenario: Render an open block that contains a list to HTML

Given

the AsciiDoc source 🍌 (000ms)

```
--  
* one  
* two  
* three  
--
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML structure 🍌 (004ms)

```
.openblock  
  .content  
    .ulist  
      ul  
        li: p one  
        li: p two  
        li: p three
```

Open Blocks

In order to pass content through unprocessed
As a writer
I want to be able to mark passthrough content using a pass block

Scenario: Render a pass block without performing substitutions by default to HTML

Given

the AsciiDoc source 🍌 (000ms)

```
:name: value  
  
++++  
<p>{name}</p>  
  
image:tiger.png[]  
++++
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<p>{name}</p>  
  
image:tiger.png[]
```

Scenario: Render a pass block without performing substitutions by default to DocBook

Given

the AsciiDoc source 👍 (000ms)

```
:name: value  
  
++++  
<simpara>{name}</simpara>  
  
image:tiger.png[]  
++++
```

When

it is converted to docbook 👍 (000ms)

Then

the result should match the XML source 👍 (000ms)

```
<simpara>{name}</simpara>  
  
image:tiger.png[]
```

Scenario: Render a pass block performing explicit substitutions to HTML

Given

the AsciiDoc source 🍌 (000ms)

```
:name: value  
  
[subs="attributes,macros"]  
++++  
<p>{name}</p>  
  
image:tiger.png[]  
++++
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<p>value</p>  
  
<span class="image"></span>
```

Text Formatting

In order to apply formatting to the text

As a writer

I want to be able to markup inline text with formatting characters

Scenario: Convert text that contains superscript and subscript characters

Given

the AsciiDoc source 🍌 (000ms)

```
_v_~rocket~ is the value
^3^He is the isotope
log~4~x^n^ is the expression
M^me^ White is the address
the 10^th^ point has coordinate (x~10~, y~10~)
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<div class="paragraph">
<p><em>v</em><sub>rocket</sub> is the value
<sup>3</sup>He is the isotope
log<sub>4</sub>x<sup>n</sup> is the expression
M<sup>me</sup> White is the address
the 10<sup>th</sup> point has coordinate (x<sub>10</sub>,
y<sub>10</sub>)</p>
</div>
```

Scenario: Convert text that has ex-inline literal formatting

Given

the AsciiDoc source 🍌 (000ms)

```
Use [x-]`{asciidoctor-version}` to print the version of AsciiDoctor.
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<div class="paragraph">
<p>Use <code>{asciidoctor-version}</code> to print the version of
AsciiDoctor.</p>
</div>
```

Scenario: Convert text that has ex-inline monospaced formatting

Given

the AsciiDoc source 🍌 (000ms)

```
The document is assumed to be encoded as [x-]+{encoding}+.
```

When

it is converted to html 🍌 (000ms)

Then

the result should match the HTML source 🍌 (000ms)

```
<div class="paragraph">
<p>The document is assumed to be encoded as <code>UTF-8</code>.</p>
</div>
```