

cucumber-documentation

Table of Contents

Summary	1
Features	6
After Hooks	6
Background	6
Scenario Outline: Retrieve the status of a scenario as a symbol	6
Scenario Outline: Retrieve the status of a scenario as a symbol	7
Scenario Outline: Retrieve the status of a scenario as a symbol	7
Scenario: Check the failed status of a scenario in a hook	8
Scenario: Make a scenario fail from an After hook	9
Scenario: After hooks are executed in reverse order of definition	10
Alle bruker ikke UTF-8	11
Scenario: Dette bør gå bra	11
Around hooks	11
Scenario: A single Around hook	12
Scenario: Multiple Around hooks	13
Scenario: Mixing Around, Before, and After hooks	15
Scenario: Around hooks with tags	16
Scenario: Around hooks with scenario outlines	18
Scenario: Around Hooks and the Custom World	19
Background	20
Background	21
Scenario: run a specific scenario with a background	26
Scenario: run a feature with a background that passes	27
Scenario: run a feature with scenario outlines that has a background that passes	27
Scenario: run a feature with scenario outlines that has a background that passes	28
Scenario: run a feature with a background that fails	29
Scenario: run a feature with scenario outlines that has a background that fails	30
Scenario: run a feature with a background that is pending	31
Scenario: background passes with first scenario but fails with second	32
Scenario: background passes with first outline scenario but fails with second	33
Scenario: background passes with first outline scenario but fails with second (--expand)	34
Scenario: background with multiline args	35
Before Hook	37
Scenario: Examine names of scenario and feature	37
Scenario: Examine names of scenario outline and feature	38
Choosing the language from the feature file header	39
Scenario: LOLCAT	40
Cucumber --work-in-progress switch	40

Background	40
Background: A passing and a pending feature	40
Scenario: Pass with Failing Scenarios	41
Scenario: Pass with Undefined Scenarios	42
Scenario: Pass with Undefined Scenarios	43
Scenario: Fail with Passing Scenarios	44
Scenario: Fail with Passing Scenario Outline	45
Custom Formatter	46
Background	46
Scenario: Use the new API	47
Scenario: Use the legacy API.....	47
Scenario: Use both	48
Custom filter	49
Scenario: Add a custom filter via AfterConfiguration hook	49
Debug formatter	50
Background	50
Scenario: title	51
Doc strings	52
Scenario: Plain text Docstring	52
Scenario: DocString with interesting content type	53
Dry Run	54
Scenario: With a failing step	54
Scenario: In strict mode.....	55
Scenario: In strict mode with an undefined step	56
ERB configuration	57
Background	57
Scenario: ERB is used in the wire file which references an environment variable that is not set	58
Scenario: ERB is used in the wire file which references an environment variable	58
Exception in After Block	59
Background	59
Scenario: Handle Exception in standard scenario step and carry on	60
Scenario: Handle Exception in scenario outline table row and carry on	61
Scenario: Handle Exception using the progress format	63
Exception in AfterStep Block	63
Background	63
Scenario: Handle Exception in standard scenario step and carry on	64
Scenario: Handle Exception in scenario outline table row and carry on	65
Exception in Before Block	67
Background	67
Scenario: Handle Exception in standard scenario step and carry on	67
Scenario: Handle Exception in Before hook for Scenario with Background	68

Scenario: Handle Exception using the progress format	69
Exceptions in Around Hooks	70
Scenario: Exception before the test case is run	70
Scenario: Exception after the test case is run	71
Excluding ruby and feature files from runs	72
Scenario: exclude ruby files	73
Scenario: my own formatter	73
Getting started	75
Scenario: Run Cucumber in an empty directory	75
Scenario: Accidentally run Cucumber in a folder with Ruby files in it.	75
HTML output formatter	76
Background	76
Scenario: an scenario outline, one undefined step, one random example, expand flag on ...	78
Scenario Outline: an scenario outline, one pending step	78
Scenario Outline: an scenario outline, one pending step	78
Scenario Outline: an scenario outline, one pending step	79
Scenario Outline: an scenario outline, one pending step	79
Scenario: when using a profile the html shouldn't include 'Using the default profile...'	80
Scenario: a feature with a failing background step	80
Handle unexpected response	81
Background	81
Scenario: Unexpected response	81
Hooks execute in defined order	82
Background	82
Scenario: Around hooks cover background steps	83
Scenario: All hooks execute in expected order	83
Invoke message	84
Background	84
Scenario: Invoke a step definition which is pending	85
Scenario: Invoke a step definition which passes	85
Scenario: Invoke a step definition which fails	86
Scenario: Invoke a step definition which takes string arguments (and passes)	87
Scenario: Invoke a step definition which takes regular and table arguments (and passes) ...	88
Scenario: Invoke a scenario outline step	89
JSON output formatter	90
Background	90
Scenario: one feature, one passing scenario, one failing scenario	93
Scenario: one feature, one passing scenario, one failing scenario with prettyfied json	95
Scenario: DocString	97
Scenario: embedding screenshot	99
Scenario: scenario outline	101

Scenario: print from step definition.....	102
Scenario: scenario outline expanded.....	104
Scenario: embedding data directly.....	106
Scenario: handle output from hooks	108
JUnit output formatter	109
Background	110
Scenario: one feature, one passing scenario, one failing scenario	111
Scenario: one feature in a subdirectory, one passing scenario, one failing scenario	113
Scenario: pending and undefined steps are reported as skipped.....	115
Scenario: pending and undefined steps with strict option should fail	115
Scenario: run all features	117
Scenario: show correct error message if no --out is passed	117
Scenario: strict mode, one feature, one scenario outline, four examples: one passing, one failing, one pending, one undefined	117
Scenario: strict mode with --expand option, one feature, one scenario outline, four examples: one passing, one failing, one pending, one undefined	119
Language help	121
Scenario: Get help for Portuguese language	122
Scenario: List languages	122
List step defs as json	123
Background	123
Scenario: Two Ruby step definitions, in the same file	123
Scenario: Non-default directory structure	124
Loading the steps users expect	125
Nested Steps	126
Background	126
Scenario: Use #steps to call several steps at once	127
Scenario: Use #step to call a single step.....	127
Scenario: Use #steps to call a table	128
Scenario: Use #steps to call a multi-line string	129
Scenario: Backtrace doesn't skip nested steps.....	130
Scenario: Undefined nested step.....	131
Nested Steps in I18n	132
Background	133
Scenario: Use #steps to call several steps at once	133
Nested Steps with either table or doc string	134
Background	134
Scenario: Use #step with table.....	134
Scenario: Use #step with docstring.....	135
Scenario: Use #step with docstring and content-type	135
One line step definitions	136

Scenario: Call a method in World directly from a step def	136
Scenario: Call a method on an actor in the World directly from a step def	137
Scenario: Using options directly gets a deprecation warning	139
Scenario: Changing the output format	139
Scenario: feature directories read from configuration	140
Pretty formatter - Printing messages	140
Background	140
Scenario: Delayed messages feature	142
Scenario: Non-delayed messages feature (progress formatter)	145
Pretty output formatter	145
Background	145
Scenario: an scenario outline, one undefined step, one random example, expand flag on ...	145
Scenario: when using a profile the output should include 'Using the default profile...'	146
Scenario: Hook output should be printed before hook exception	146
Profiles	147
Background	148
Background: Basic App	148
Scenario: Explicitly defining a profile to run	148
Scenario: Explicitly defining a profile defined in an ERB formatted file	149
Scenario: Defining multiple profiles to run	149
Scenario: Arguments passed in but no profile specified	150
Scenario: Trying to use a missing profile	150
Scenario Outline: Disabling the default profile	150
Scenario Outline: Disabling the default profile	151
Scenario: Overriding the profile's features to run	151
Scenario: Overriding the profile's formatter	152
Scenario Outline: Showing profiles when listing failing scenarios	152
Scenario Outline: Showing profiles when listing failing scenarios	152
Progress output formatter	153
Background	153
Scenario: an scenario outline, one undefined step, one random example, expand flag on ...	153
Scenario: when using a profile the output should include 'Using the default profile...'	154
Rake task	154
Background	154
Scenario: rake task with a defined profile	155
Scenario: rake task without a profile	155
Scenario: rake task with a defined profile and cucumber_opts	156
Scenario: respect requires	157
Scenario: feature files with spaces	158
Raketask	159
Background	159

Scenario: Passing feature	160
Scenario: Failing feature	160
Randomize	161
Background	161
Scenario: Run scenarios in order	162
Scenario: Run scenarios randomized	162
Requiring extra step files	163
Rerun formatter	164
Background	165
Scenario: Exit code is zero	165
Scenario: Exit code is zero in the dry-run mode	166
Scenario: Exit code is not zero, regular scenario	166
Scenario: Exit code is not zero, scenario outlines	167
Scenario: Exit code is not zero, failing background	168
Scenario: Exit code is not zero, failing background with scenario outline	169
Scenario: Exit code is not zero, scenario outlines with expand	170
Run Cli::Main with existing Runtime	171
Scenario: Run a single feature	171
Background	172
Scenario: Matching Feature names	173
Scenario: Matching Scenario names	174
Scenario: Matching Scenario Outline names	174
Scenario: Matching Example block names	175
Run specific scenarios	175
Background	176
Scenario: Two scenarios, run just one of them	176
Scenario: Use @-notation to specify a file containing feature file list	177
Scenario: Specify order of scenarios	177
Running multiple formatters	178
Background	178
Scenario: Multiple formatters and outputs	179
Scenario: Two formatters to stdout	179
Scenario: Two formatters to stdout when using a profile	180
Scenario outlines	180
Background	181
Scenario: Run scenario outline with filtering on outline name	182
Scenario: Run scenario outline steps only	183
Scenario: Run single failing scenario outline table row	184
Scenario: Run all with progress formatter	185
Scenario outlines --expand option	186
Set up a default load path	188

Scenario: ./lib is included in the \$LOAD_PATH	188
Showing differences to expected output.	188
Scenario: Run single failing scenario with default diff enabled	188
Skip Scenario	189
Scenario: With a passing step	190
Scenario: Use legacy API from a hook	190
Snippets	191
Scenario: Snippet for undefined step with a pystring	191
Scenario: Snippet for undefined step with a step table	192
Snippets message	193
Background	193
Scenario: Wire server returns snippets for a step that didn't match	194
State	195
Scenario: Set an ivar in one scenario, use it in the next step	195
Step matches message	196
Background	197
Scenario: Dry run finds no step match	197
Scenario: Dry run finds a step match	198
Scenario: Step matches returns details about the remote step definition	198
Strict mode	199
Background	199
Scenario: Fail with --strict due to undefined step	200
Scenario: Fail with --strict due to pending step	200
Scenario: Succeed with --strict	200
Table diffing	201
Scenario: Extra row	201
Tag logic	202
Background	202
Scenario: ANDing tags	203
Scenario: ORing tags	203
Scenario: Negative tags	204
Scenario: Run with limited tag count, blowing it on scenario	205
Scenario: Run with limited tag count, blowing it via feature inheritance	205
Scenario: Run with limited tag count using negative tag, blowing it via a tag that is not run	205
Scenario: Limiting with tags which do not exist in the features	205
Tagged hooks	206
Background	206
Scenario: omit tagged hook	207
Scenario: omit tagged hook	208
Scenario: Omit example hook	208
Transforms	209

Background	209
Scenario: Basic Transform	210
Scenario: Re-use Transform's Regular Expression	211
Unicode in tables	211
Usage formatter	212
Background	212
Scenario: Run with --format usage	213
Scenario: Run with --expand --format usage	214
Scenario: Run with --format stepdefs	215
Using descriptions to give features context	216
Background	216
Scenario: Everything with a description	216
Scenario: Use some *	218
Wire protocol table diffing	219
Background	219
Scenario: Invoke a step definition tries to diff the table and fails	220
Scenario: Invoke a step definition tries to diff the table and passes	221
Scenario: Invoke a step definition which successfully diffs a table but then fails	222
Scenario: Invoke a step definition which asks for an immediate diff that fails	223
Wire protocol tags	223
Background	223
Scenario: Run a scenario	224
Scenario: Run a scenario outline example	225
Wire protocol timeouts	226
Background	226
Scenario: Try to talk to a server that's not there	226
Scenario: Invoke a step definition that takes longer than its timeout	226

Summary

Scenarios			Steps							Features: 68	
Passed	Failed	Total	Passed	Failed	Skipped	Pending	Undefined	Missing	Total	Duration	Status
After Hooks											
12	0	12	30	0	0	0	0	0	30	084ms	passed
Alle bruker ikke UTF-8											
1	0	1	2	0	0	0	0	0	2	000ms	passed
Around hooks											
6	0	6	30	0	0	0	0	0	30	03s758ms	passed
Background											
22	0	22	144	0	0	0	0	0	144	03s064ms	passed
Before Hook											
2	0	2	8	0	0	0	0	0	8	045ms	passed
Choosing the language from the feature file header											
1	0	1	3	0	0	0	0	0	3	011ms	passed
Cucumber --work-in-progress switch											
10	0	10	31	0	0	0	0	0	31	03s151ms	passed
Custom Formatter											
6	0	6	15	0	0	0	0	0	15	027ms	passed
Custom filter											
1	0	1	4	0	0	0	0	0	4	009ms	passed
Debug formatter											
2	0	2	5	0	0	0	0	0	5	008ms	passed
Doc strings											
2	0	2	8	0	0	0	0	0	8	021ms	passed
Dry Run											
3	0	3	11	0	0	0	0	0	11	046ms	passed
ERB configuration											
4	0	4	11	0	0	0	0	0	11	143ms	passed
Exception in After Block											
6	0	6	18	0	0	0	0	0	18	01s243ms	passed
Exception in AfterStep Block											
4	0	4	12	0	0	0	0	0	12	047ms	passed

Scenarios				Steps						Features: 68	
Exception in Before Block											
6	0	6	15	0	0	0	0	0	15	651ms	passed
Exceptions in Around Hooks											
2	0	2	10	0	0	0	0	0	10	021ms	passed
Excluding ruby and feature files from runs											
1	0	1	11	0	0	0	0	0	11	008ms	passed
Formatter-API:-Step-file-path-and-line-number-(Issue-.pdf											
1	0	1	5	0	0	0	0	0	5	007ms	passed
Getting started											
2	0	2	8	0	0	0	0	0	8	616ms	passed
HTML output formatter											
14	0	14	53	0	0	0	0	0	53	166ms	passed
Handle unexpected response											
2	0	2	5	0	0	0	0	0	5	071ms	passed
Hooks execute in defined order											
4	0	4	12	0	0	0	0	0	12	01s 217ms	passed
Invoke message											
12	0	12	37	0	0	0	0	0	37	02s 210ms	passed
JSON output formatter											
18	0	18	102	0	0	0	0	0	102	05s 007ms	passed
JUnit output formatter											
16	0	16	73	0	0	0	0	0	73	05s 387ms	passed
Language help											
2	0	2	4	0	0	0	0	0	4	014ms	passed
List step defs as json											
4	0	4	8	0	0	0	0	0	8	01s 223ms	passed
Loading the steps users expect											
1	0	1	4	0	0	0	0	0	4	007ms	passed
Nested Steps											
12	0	12	33	0	0	0	0	0	33	683ms	passed
Nested Steps in I18n											
2	0	2	5	0	0	0	0	0	5	014ms	passed
Nested Steps with either table or doc string											

Scenarios			Steps							Features: 68	
6	0	6	15	0	0	0	0	0	15	033ms	passed
One line step definitions											
2	0	2	8	0	0	0	0	0	8	017ms	passed
Post-Configuration-Hook-[.pdf											
3	0	3	11	0	0	0	0	0	11	640ms	passed
Pretty formatter - Printing messages											
4	0	4	13	0	0	0	0	0	13	549ms	passed
Pretty output formatter											
6	0	6	15	0	0	0	0	0	15	054ms	passed
Profiles											
22	0	22	77	0	0	0	0	0	77	127ms	passed
Progress output formatter											
4	0	4	8	0	0	0	0	0	8	022ms	passed
Rake task											
10	0	10	27	0	0	0	0	0	27	05s 848ms	passed
Raketask											
4	0	4	11	0	0	0	0	0	11	03s 824ms	passed
Randomize											
4	0	4	9	0	0	0	0	0	9	713ms	passed
Requiring extra step files											
1	0	1	4	0	0	0	0	0	4	012ms	passed
Rerun formatter											
14	0	14	30	0	0	0	0	0	30	097ms	passed
Run Cli::Main with existing Runtime											
1	0	1	5	0	0	0	0	0	5	615ms	passed
[Run-feature-elements-matching-a-name-with---name/-n]											
8	0	8	20	0	0	0	0	0	20	050ms	passed
Run specific scenarios											
6	0	6	13	0	0	0	0	0	13	026ms	passed
Running multiple formatters											
6	0	6	12	0	0	0	0	0	12	01s 830ms	passed
Scenario outlines											
8	0	8	16	0	0	0	0	0	16	02s 431ms	passed

Scenarios			Steps							Features: 68	
Scenario outlines --expand option											
1	0	1	4	0	0	0	0	0	4	013ms	passed
Set up a default load path											
1	0	1	4	0	0	0	0	0	4	010ms	passed
Showing differences to expected output											
1	0	1	4	0	0	0	0	0	4	023ms	passed
Skip Scenario											
2	0	2	10	0	0	0	0	0	10	023ms	passed
Snippets											
2	0	2	6	0	0	0	0	0	6	017ms	passed
Snippets message											
2	0	2	7	0	0	0	0	0	7	914ms	passed
State											
1	0	1	4	0	0	0	0	0	4	015ms	passed
Step matches message											
6	0	6	16	0	0	0	0	0	16	112ms	passed
Strict mode											
6	0	6	14	0	0	0	0	0	14	046ms	passed
Table diffing											
1	0	1	4	0	0	0	0	0	4	016ms	passed
Tag logic											
14	0	14	21	0	0	0	0	0	21	051ms	passed
Tagged hooks											
7	0	7	20	0	0	0	0	0	20	054ms	passed
Transforms											
4	0	4	10	0	0	0	0	0	10	023ms	passed
Unicode in tables											
1	0	1	3	0	0	0	0	0	3	606ms	passed
Usage formatter											
6	0	6	12	0	0	0	0	0	12	060ms	passed
Using descriptions to give features context											
2	0	2	5	0	0	0	0	0	5	022ms	passed
[Using-star-notation-instead-of-Given/When/Then]											
1	0	1	5	0	0	0	0	0	5	012ms	passed
Wire protocol table diffing											

Scenarios			Steps							Features: 68	
8	0	8	21	0	0	0	0	0	21	02s 723ms	passed
Wire protocol tags											
4	0	4	12	0	0	0	0	0	12	304ms	passed
Wire protocol timeouts											
4	0	4	11	0	0	0	0	0	11	928ms	passed
Totals											
364	0	364	1204	0	0	0	0	0	1204	51s 856ms	

Features

After Hooks

After hooks can be used to clean up any state you've altered during your scenario, or to check the status of the scenario and act accordingly.

You can ask a scenario whether it has failed, for example.

Mind you, even if it hasn't failed yet, you can still make the scenario fail if your After hook throws an error.

Background

Given

the standard step definitions 🍌 (000ms)

Scenario Outline: Retrieve the status of a scenario as a symbol

Given

a file named "features/support/debug_hook.rb" with: 🍌 (000ms)

```
After do |scenario|
  puts scenario.status.inspect
end
```

And

a file named "features/result.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step passes
```

When

I run `cucumber -f progress` 🍌 (015ms)

Then

the output should contain "passed" 🍌 (000ms)

Scenario Outline: Retrieve the status of a scenario as a symbol

Given

a file named "features/support/debug_hook.rb" with: 🍌 (000ms)

```
After do |scenario|  
  puts scenario.status.inspect  
end
```

And

a file named "features/result.feature" with: 🍌 (000ms)

```
Feature:  
  Scenario:  
    Given this step fails
```

When

I run `cucumber -f progress` 🍌 (015ms)

Then

the output should contain "failed" 🍌 (000ms)

Scenario Outline: Retrieve the status of a scenario as a symbol

Given

a file named "features/support/debug_hook.rb" with: 🍌 (000ms)

```
After do |scenario|  
  puts scenario.status.inspect  
end
```

And

a file named "features/result.feature" with: 🍌 (000ms)

```
Feature:  
  Scenario:  
    Given this step is pending
```

When

I run `cucumber -f progress` 🍌 (013ms)

Then

the output should contain "pending" 🍌 (000ms)

Scenario: Check the failed status of a scenario in a hook

Given

a file named "features/support/debug_hook.rb" with: 🍌 (000ms)

```
After do |scenario|
  if scenario.failed?
    puts "eek"
  end
end
```

And

a file named "features/fail.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step fails
```

When

I run `cucumber -f progress` 🍌 (012ms)

Then

the output should contain: 🍌 (000ms)

```
eek
```

Scenario: Make a scenario fail from an After hook

Given

a file named "features/support/bad_hook.rb" with: 🍌 (000ms)

```
After do
  fail 'yikes'
end
```

And

a file named "features/pass.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step passes
```

When

I run `cucumber -f pretty` 🍌 (011ms)

Then

it should fail with: 🍌 (000ms)

```
Scenario:                # features/pass.feature:2
  Given this step passes # features/step_definitions/steps.rb:1
    yikes (RuntimeError)
    ./features/support/bad_hook.rb:2:in `After'
```

Scenario: After hooks are executed in reverse order of definition

Given

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
After do
  puts "First"
end
```

```
After do
  puts "Second"
end
```

And

a file named "features/pass.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step passes
```

When

I run `cucumber -f progress` 🍌 (007ms)

Then

the output should contain: 🍌 (000ms)

Second

First

Alle bruker ikke UTF-8

Scenario: Dette bør gå bra

Når

jeg drikker en "øl" 🍌 (000ms)

Så

skal de andre si "skål" 🍌 (000ms)

Around hooks

In order to support transactional scenarios for database libraries that provide only a block syntax for transactions, Cucumber should permit definition of Around hooks.

Scenario: A single Around hook

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Then /^the hook is called$/ do
  expect($hook_called).to be true
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  $hook_called = true
  block.call
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: Around hooks
  Scenario: using hook
    Then the hook is called
```

When

I run `cucumber features/f.feature` 🍌 (605ms)

Then

it should pass with: 🍌 (001ms)

```
Feature: Around hooks

  Scenario: using hook      # features/f.feature:2
    Then the hook is called # features/step_definitions/steps.rb:1

1 scenario (1 passed)
1 step (1 passed)
```

Scenario: Multiple Around hooks

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (001ms)

```
Then /^the hooks are called in the correct order$/ do
  expect($hooks_called).to eq ['A', 'B', 'C']
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'A'
  block.call
end
```

```
Around do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'B'
  block.call
end
```

```
Around do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'C'
  block.call
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: Around hooks
  Scenario: using multiple hooks
    Then the hooks are called in the correct order
```

When

I run `cucumber features/f.feature` 🍌 (607ms)

Then

it should pass with: 🍌 (000ms)

Feature: Around hooks

```
Scenario: using multiple hooks # features/f.feature:2
  Then the hooks are called in the correct order #
features/step_definitions/steps.rb:1
```

```
1 scenario (1 passed)
1 step (1 passed)
```

Scenario: Mixing Around, Before, and After hooks

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Then /^the Around hook is called around Before and After hooks$/ do
  expect($hooks_called).to eq ['Around', 'Before']
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'Around'
  block.call
  $hooks_called << 'Around'
  $hooks_called.should == ['Around', 'Before', 'After', 'Around'] #TODO: Find out
  why this fails using the new rspec expect syntax.
end
```

```
Before do |scenario|
  $hooks_called ||= []
  $hooks_called << 'Before'
end
```

```
After do |scenario|
  $hooks_called ||= []
  $hooks_called << 'After'
  expect($hooks_called).to eq ['Around', 'Before', 'After']
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

Feature: Around hooks

Scenario: Mixing Around, Before, and After hooks

Then the Around hook is called around Before and After hooks

When

I run `cucumber features/f.feature` 🍌 (607ms)

Then

it should pass with: 🍌 (001ms)

Feature: Around hooks

Scenario: Mixing Around, Before, and After hooks #
features/f.feature:2

Then the Around hook is called around Before and After hooks #
features/step_definitions/steps.rb:1

1 scenario (1 passed)

1 step (1 passed)

Scenario: Around hooks with tags

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Then /^the Around hooks with matching tags are called$/ do
  expect($hooks_called).to eq ['one', 'one or two']
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```

Around('@one') do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'one'
  block.call
end

Around('@one,@two') do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'one or two'
  block.call
end

Around('@one', '@two') do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'one and two'
  block.call
end

Around('@two') do |scenario, block|
  $hooks_called ||= []
  $hooks_called << 'two'
  block.call
end

```

And

a file named "features/f.feature" with: 🍌 (000ms)

```

Feature: Around hooks
  @one
  Scenario: Around hooks with tags
    Then the Around hooks with matching tags are called

```

When

I run `cucumber -q -t @one features/f.feature` 🍌 (708ms)

Then

it should pass with: 🍌 (000ms)

```

Feature: Around hooks

  @one
  Scenario: Around hooks with tags
    Then the Around hooks with matching tags are called

1 scenario (1 passed)
1 step (1 passed)

```

Scenario: Around hooks with scenario outlines

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Then /^the hook is called$/ do
  expect($hook_called).to be true
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  $hook_called = true
  block.call
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: Around hooks with scenario outlines
  Scenario Outline: using hook
    Then the hook is called
```

Examples:

	Number	
	one	
	two	

When

I run `cucumber features/f.feature` 🍌 (607ms)

Then

it should pass with: 🍌 (001ms)

Feature: Around hooks with scenario outlines

Scenario Outline: using hook # features/f.feature:2
Then the hook is called # features/f.feature:3

Examples:

	Number	
	one	
	two	

2 scenarios (2 passed)

2 steps (2 passed)

Scenario: Around Hooks and the Custom World

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Then /^the world should be available in the hook$/ do
  $previous_world = self
  expect($hook_world).to eq(self)
end

Then /^what$/ do
  expect($hook_world).not_to eq($previous_world)
end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  $hook_world = self
  block.call
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: Around hooks
  Scenario: using hook
    Then the world should be available in the hook

  Scenario: using the same hook
    Then what
```

When

I run `cucumber features/f.feature` 🍌 (608ms)

Then

it should pass 🍌 (000ms)

Background

Often you find that several scenarios in the same feature start with a common context.

Cucumber provides a mechanism for this, by providing a **Background** keyword where you can specify steps that should be run before each scenario in the feature. Typically these will be **Given** steps, but you can use any steps that you need to.

Hint: if you find that some of the scenarios don't fit the background, consider splitting them into a separate feature.

Background

Given

a file named "features/passing_background.feature" with: 🍌 (000ms)

```
Feature: Passing background sample
```

```
Background:
```

```
  Given '10' cukes
```

```
Scenario: passing background
```

```
  Then I should have '10' cukes
```

```
Scenario: another passing background
```

```
  Then I should have '10' cukes
```

And

a file named "features/scenario_outline_passing_background.feature" with: 🍌 (000ms)

Feature: Passing background with scenario outlines sample

Background:

Given '10' cukes

Scenario Outline: passing background

Then I should have '<count>' cukes

Examples:

count
10

Scenario Outline: another passing background

Then I should have '<count>' cukes

Examples:

count
10

And

a file named "features/background_tagged_before_on_outline.feature" with: 🍌 (000ms)

@background_tagged_before_on_outline

Feature: Background tagged Before on Outline

Background:

Given this step passes

Scenario Outline: passing background

Then I should have '<count>' cukes

Examples:

count
888

And

a file named "features/failing_background.feature" with: 🍌 (000ms)

Feature: Failing background sample

Background:

Given this step raises an error
And '10' cukes

Scenario: failing background

Then I should have '10' cukes

Scenario: another failing background

Then I should have '10' cukes

And

a file named "features/scenario_outline_failing_background.feature" with: 🍌 (000ms)

Feature: Failing background with scenario outlines sample

Background:

Given this step raises an error

Scenario Outline: failing background

Then I should have '<count>' cukes

Examples:

count
10

Scenario Outline: another failing background

Then I should have '<count>' cukes

Examples:

count
10

And

a file named "features/pending_background.feature" with: 🍌 (000ms)

Feature: Pending background sample

Background:

Given this step is pending

Scenario: pending background

Then I should have '10' cukes

Scenario: another pending background

Then I should have '10' cukes

And

a file named "features/failing_background_after_success.feature" with: 🍌 (000ms)

Feature: Failing background after previously successful background sample

Background:

Given this step passes

And '10' global cukes

Scenario: passing background

Then I should have '10' global cukes

Scenario: failing background

Then I should have '10' global cukes

And

a file named "features/failing_background_after_success_outline.feature" with: 🍌 (000ms)

Feature: Failing background after previously successful background sample

Background:

Given this step passes

And '10' global cukes

Scenario Outline: passing background

Then I should have '<count>' global cukes

Examples:

	count	
	10	

Scenario Outline: failing background

Then I should have '<count>' global cukes

Examples:

	count	
	10	

And

a file named "features/multiline_args_background.feature" with: 🍌 (000ms)

Feature: Passing background with multiline args

Background:

Given table

|a|b|

|c|d|

And multiline string

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

Scenario: passing background

Then the table should be

|a|b|

|c|d|

Then the multiline string should be

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

Scenario: another passing background

Then the table should be

|a|b|

|c|d|

Then the multiline string should be

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

And

the standard step definitions 🍌 (000ms)

And

a file named "features/step_definitions/cuke_steps.rb" with: 🍌 (000ms)

```

Given /^'(.+)' cukes$/ do |cukes| x=1
  raise "We already have #{@cukes} cukes!" if @cukes
  @cukes = cukes
end

Given /^'(.+)' global cukes$/ do |cukes| x=1
  $scenario_runs ||= 0
  raise 'FAIL' if $scenario_runs >= 1
  $cukes = cukes
  $scenario_runs += 1
end

Then /^I should have '(.+)' global cukes$/ do |cukes| x=1
  expect($cukes).to eq cukes
end

Then /^I should have '(.+)' cukes$/ do |cukes| x=1
  expect(@cukes).to eq cukes
end

Before('@background_tagged_before_on_outline') do
  @cukes = '888'
end

After('@background_tagged_before_on_outline') do
  expect(@cukes).to eq '888'
end

```

Scenario: run a specific scenario with a background

When

I run `cucumber -q features/passing_background.feature:9` 🍌 (013ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: Passing background sample

Background:

Given '10' cukes

Scenario: another passing background

Then I should have '10' cukes

1 scenario (1 passed)

2 steps (2 passed)

Scenario: run a feature with a background that passes

When

I run `cucumber -q features/passing_background.feature` 🍌 (014ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: Passing background sample

Background:

Given '10' cukes

Scenario: passing background

Then I should have '10' cukes

Scenario: another passing background

Then I should have '10' cukes

2 scenarios (2 passed)

4 steps (4 passed)

Scenario: run a feature with scenario outlines that has a background that passes

When

I run `cucumber -q features/scenario_outline_passing_background.feature` 🍌 (012ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: Passing background with scenario outlines sample

Background:

Given '10' cukes

Scenario Outline: passing background

Then I should have '<count>' cukes

Examples:

	count	
	10	

Scenario Outline: another passing background

Then I should have '<count>' cukes

Examples:

	count	
	10	

2 scenarios (2 passed)

4 steps (4 passed)

Scenario: run a feature with scenario outlines that has a background that passes

When

I run `cucumber -q features/background_tagged_before_on_outline.feature` 🍌 (009ms)

Then

it should pass with exactly: 🍌 (000ms)

```
@background_tagged_before_on_outline
Feature: Background tagged Before on Outline
```

```
Background:
```

```
  Given this step passes
```

```
Scenario Outline: passing background
```

```
  Then I should have '<count>' cukes
```

```
Examples:
```

```
  | count |
  | 888   |
```

```
1 scenario (1 passed)
```

```
2 steps (2 passed)
```

Scenario: run a feature with a background that fails

tags: @spawn

When

I run `cucumber -q features/failing_background.feature` 🍌 (505ms)

Then

it should fail with exactly: 🍌 (001ms)

Feature: Failing background sample

Background:

Given this step raises an error
error (RuntimeError)

./features/step_definitions/steps.rb:2:in `/^this step raises an error\$/'
features/failing_background.feature:4:in `Given this step raises an error'
And '10' cukes

Scenario: failing background

Then I should have '10' cukes

Scenario: another failing background

Then I should have '10' cukes

Failing Scenarios:

cucumber features/failing_background.feature:7

cucumber features/failing_background.feature:10

2 scenarios (2 failed)

6 steps (2 failed, 4 skipped)

Scenario: run a feature with scenario outlines that has a background that fails

tags: @spawn

When

I run `cucumber -q features/scenario_outline_failing_background.feature` 🍌 (605ms)

Then

it should fail with exactly: 🍌 (001ms)

Feature: Failing background with scenario outlines sample

Background:

Given this step raises an error

error (RuntimeError)

`./features/step_definitions/steps.rb:2:in '/^this step raises an error$/'`

`features/scenario_outline_failing_background.feature:4:in 'Given this step raises an error'`

Scenario Outline: failing background

Then I should have '<count>' cukes

Examples:

	count	
	10	

Scenario Outline: another failing background

Then I should have '<count>' cukes

Examples:

	count	
	10	

Failing Scenarios:

`cucumber features/scenario_outline_failing_background.feature:10`

`cucumber features/scenario_outline_failing_background.feature:16`

2 scenarios (2 failed)

4 steps (2 failed, 2 skipped)

Scenario: run a feature with a background that is pending

When

I run `cucumber -q features/pending_background.feature` 🍌 (024ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: Pending background sample

Background:

Given this step is pending

TODO (Cucumber::Pending)

`./features/step_definitions/steps.rb:3:in '/^this step is pending$/'`

`features/pending_background.feature:4:in 'Given this step is pending'`

Scenario: pending background

Then I should have '10' cukes

Scenario: another pending background

Then I should have '10' cukes

2 scenarios (2 pending)

4 steps (2 skipped, 2 pending)

Scenario: background passes with first scenario but fails with second

tags: @spawn

When

I run `cucumber -q features/failing_background_after_success.feature` 🍌 (605ms)

Then

it should fail with exactly: 🍌 (001ms)

Feature: Failing background after previously successful background sample

Background:

Given this step passes

And '10' global cukes

Scenario: passing background

Then I should have '10' global cukes

Scenario: failing background

And '10' global cukes

FAIL (RuntimeError)

./features/step_definitions/cuke_steps.rb:8:in `/^'(.)' global cukes\$/'

features/failing_background_after_success.feature:5:in `And '10' global cukes'

Then I should have '10' global cukes

Failing Scenarios:

cucumber features/failing_background_after_success.feature:10

2 scenarios (1 failed, 1 passed)

6 steps (1 failed, 1 skipped, 4 passed)

Scenario: background passes with first outline scenario but fails with second

tags: @spawn

When

I run `cucumber -q features/failing_background_after_success_outline.feature` 🍌 (605ms)

Then

it should fail with exactly: 🍌 (001ms)

Feature: Failing background after previously successful background sample

Background:

Given this step passes

And '10' global cukes

Scenario Outline: passing background

Then I should have '<count>' global cukes

Examples:

count
10

Scenario Outline: failing background

Then I should have '<count>' global cukes

Examples:

count
10

FAIL (RuntimeError)

./features/step_definitions/cuke_steps.rb:8:in `/^'(.+)' global cukes\$/'

features/failing_background_after_success_outline.feature:5:in `And '10'

global cukes'

Failing Scenarios:

cucumber features/failing_background_after_success_outline.feature:19

2 scenarios (1 failed, 1 passed)

6 steps (1 failed, 1 skipped, 4 passed)

Scenario: background passes with first outline scenario but fails with second (--expand)

tags: @spawn

When

I run `cucumber -x -q features/failing_background_after_success_outline.feature` 🍌 (606ms)

Then

it should fail with exactly: 🍌 (000ms)

Feature: Failing background after previously successful background sample

Background:

Given this step passes

And '10' global cukes

Scenario Outline: passing background

Then I should have '<count>' global cukes

Examples:

Scenario: | 10 |

Then I should have '10' global cukes

Scenario Outline: failing background

Then I should have '<count>' global cukes

Examples:

Scenario: | 10 |

And '10' global cukes

FAIL (RuntimeError)

./features/step_definitions/cuke_steps.rb:8:in '/^(.+)' global cukes\$/'

features/failing_background_after_success_outline.feature:5:in 'And '10'

global cukes'

Then I should have '10' global cukes

Failing Scenarios:

cucumber features/failing_background_after_success_outline.feature:19

2 scenarios (1 failed, 1 passed)

6 steps (1 failed, 1 skipped, 4 passed)

Scenario: background with multiline args

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given /^table$/ do |table| x=1
  @table = table
end

Given /^multiline string$/ do |string| x=1
  @multiline = string
end

Then /^the table should be$/ do |table| x=1
  expect(@table.raw).to eq table.raw
end

Then /^the multiline string should be$/ do |string| x=1
  expect(@multiline).to eq string
end
```

When

I run `cucumber -q features/multiline_args_background.feature` 🍷 (025ms)

Then

it should pass with exactly: 🍷 (000ms)

Feature: Passing background with multiline args

Background:

Given table

	a		b	
--	---	--	---	--

	c		d	
--	---	--	---	--

And multiline string

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

Scenario: passing background

Then the table should be

	a		b	
--	---	--	---	--

	c		d	
--	---	--	---	--

Then the multiline string should be

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

Scenario: another passing background

Then the table should be

	a		b	
--	---	--	---	--

	c		d	
--	---	--	---	--

Then the multiline string should be

"""

I'm a cucumber and I'm okay.

I sleep all night and I test all day

"""

2 scenarios (2 passed)

8 steps (8 passed)

Before Hook

Scenario: Examine names of scenario and feature

Given

a file named "features/foo.feature" with: 🍌 (000ms)

Feature: Feature name

Scenario: Scenario name
Given a step

And

a file named "features/support/hook.rb" with: 🍌 (000ms)

```
names = []
Before do |scenario|
  expect(scenario).to_not respond_to(:scenario_outline)
  names << scenario.feature.name.split("\n").first
  names << scenario.name.split("\n").first
  if(names.size == 2)
    raise "NAMES:\n" + names.join("\n") + "\n"
  end
end
```

When

I run **cucumber** 🍌 (028ms)

Then

the output should contain: 🍌 (000ms)

NAMES:
Feature name
Scenario name

Scenario: Examine names of scenario outline and feature

Given

a file named "features/foo.feature" with: 🍌 (000ms)

```
Feature: Feature name
```

```
Scenario Outline: Scenario Outline name
```

```
Given a <placeholder>
```

```
Examples: Examples Table name
```

```
| <placeholder> |  
| step          |
```

And

a file named "features/support/hook.rb" with: 🍌 (000ms)

```
names = []  
Before do |scenario|  
  names << scenario.scenario_outline.feature.name.split("\n").first  
  names << scenario.scenario_outline.name.split("\n").first  
  names << scenario.name.split("\n").first  
  if(names.size == 3)  
    raise "NAMES:\n" + names.join("\n") + "\n"  
  end  
end
```

When

I run **cucumber** 🍌 (015ms)

Then

the output should contain: 🍌 (000ms)

```
NAMES:  
Feature name  
Scenario Outline name, Examples Table name (#1)  
Scenario Outline name, Examples Table name (#1)
```

Choosing the language from the feature file header

In order to simplify command line and settings in IDEs, Cucumber picks up the parser language from a **# language** comment at the beginning of any feature file. See the examples below for the exact syntax.

Scenario: LOLCAT

Given

a file named "features/lolcat.feature" with: 🍌 (000ms)

```
# language: en-lol
OH HAI: STUFFING
  B4: HUNGRY
    I CAN HAZ EMPTY BELLY
  MISHUN: CUKES
    DEN KTHXBAI
```

When

I run `cucumber -i features/lolcat.feature -q` 🍌 (010ms)

Then

it should pass with: 🍌 (000ms)

```
# language: en-lol
OH HAI: STUFFING

  B4: HUNGRY
    I CAN HAZ EMPTY BELLY

  MISHUN: CUKES
    DEN KTHXBAI

1 scenario (1 undefined)
2 steps (2 undefined)
```

Cucumber --work-in-progress switch

In order to ensure that feature scenarios do not pass until they are expected to
Developers should be able to run cucumber in a mode that

- will fail if any scenario passes completely
- will not fail otherwise

Background

Background: A passing and a pending feature

tags: @spawn

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/wip.feature" with: 🍌 (000ms)

```
Feature: WIP
  @failing
  Scenario: Failing
    Given this step raises an error

  @undefined
  Scenario: Undefined
    Given this step is undefined

  @pending
  Scenario: Pending
    Given this step is pending

  @passing
  Scenario: Passing
    Given this step passes
```

And

a file named "features/passing_outline.feature" with: 🍌 (000ms)

```
Feature: Not WIP
  Scenario Outline: Passing
    Given this step <what>

    Examples:
      | what |
      | passes |
```

Scenario: Pass with Failing Scenarios

tags: @spawn,@spawn

When

I run `cucumber -q -w -t @failing features/wip.feature` 🍌 (606ms)

Then

the stderr should not contain anything 🍌 (000ms)

Then

it should pass with: 🍌 (000ms)

Feature: WIP

@failing

Scenario: Failing

Given this step raises an error

error (RuntimeError)

./features/step_definitions/steps.rb:2:in `/^this step raises an error\$/'

features/wip.feature:4:in `Given this step raises an error'

Failing Scenarios:

cucumber features/wip.feature:3

1 scenario (1 failed)

1 step (1 failed)

And

the output should contain: 🍌 (000ms)

The --wip switch was used, so the failures were expected. All is good.

Scenario: Pass with Undefined Scenarios

tags: @spawn,@spawn

When

I run `cucumber -q -w -t @undefined features/wip.feature` 🍌 (608ms)

Then

it should pass with: 🍌 (000ms)

Feature: WIP

@undefined

Scenario: Undefined

Given this step is undefined

1 scenario (1 undefined)

1 step (1 undefined)

And

the output should contain: 🍌 (000ms)

The --wip switch was used, so the failures were expected. All is good.

Scenario: Pass with Undefined Scenarios

tags: @spawn,@spawn

When

I run `cucumber -q -w -t @pending features/wip.feature` 🍌 (606ms)

Then

it should pass with: 🍌 (001ms)

Feature: WIP

@pending

Scenario: Pending

Given this step is pending

TODO (Cucumber::Pending)

./features/step_definitions/steps.rb:3:in `/^this step is pending\$/'

features/wip.feature:12:in `Given this step is pending'

1 scenario (1 pending)

1 step (1 pending)

And

the output should contain: 🍌 (000ms)

The --wip switch was used, so the failures were expected. All is good.

Scenario: Fail with Passing Scenarios

tags: @spawn,@spawn

When

I run `cucumber -q -w -t @passing features/wip.feature` 🍌 (607ms)

Then

it should fail with: 🍌 (000ms)

Feature: WIP

@passing

Scenario: Passing

Given this step passes

1 scenario (1 passed)

1 step (1 passed)

And

the output should contain: 🍌 (000ms)

The --wip switch was used, so I didn't expect anything to pass. These scenarios passed:

(::) passed scenarios (::)

features/wip.feature:15:in 'Scenario: Passing'

Scenario: Fail with Passing Scenario Outline

tags: @spawn,@spawn

When

I run `cucumber -q -w features/passing_outline.feature` 🍌 (707ms)

Then

it should fail with: 🍌 (001ms)

Feature: Not WIP

Scenario Outline: Passing
Given this step <what>

Examples:

what
passes

1 scenario (1 passed)

1 step (1 passed)

And

the output should contain: 🍌 (000ms)

The --wip switch was used, so I didn't expect anything to pass. These scenarios passed:

(::) passed scenarios (::)

features/passing_outline.feature:7:in `Scenario Outline: Passing, Examples (#1)'

Custom Formatter

Background

Given

a file named "features/f.feature" with: 🍌 (000ms)

Feature: I'll use my own
Scenario: Just print me
Given this step passes

And

the standard step definitions 🍌 (000ms)

Scenario: Use the new API

Given

a file named "features/support/custom_formatter.rb" with: 🍌 (000ms)

```
module MyCustom
  class Formatter
    def initialize(runtime, io, options)
      @io = io
    end

    def before_test_case(test_case)
      feature = test_case.source.first
      scenario = test_case.source.last
      @io.puts feature.short_name.upcase
      @io.puts "  #{scenario.name.upcase}"
    end
  end
end
```

When

I run `cucumber features/f.feature --format MyCustom::Formatter` 🍌 (009ms)

Then

it should pass with exactly: 🍌 (000ms)

```
I'LL USE MY OWN
JUST PRINT ME
```

Scenario: Use the legacy API

Given

a file named "features/support/custom_legacy_formatter.rb" with: 🍌 (000ms)

```
module MyCustom
  class LegacyFormatter
    def initialize(runtime, io, options)
      @io = io
    end

    def before_feature(feature)
      @io.puts feature.short_name.upcase
    end

    def scenario_name(keyword, name, file_colon_line, source_indent)
      @io.puts "  #{name.upcase}"
    end
  end
end
```

When

I run `cucumber features/f.feature --format MyCustom::LegacyFormatter` 🍌 (008ms)

Then

it should pass with exactly: 🍌 (000ms)

```
I'LL USE MY OWN
JUST PRINT ME
```

Scenario: Use both

You can use a specific shim to opt-in to both APIs at once.

Given

a file named "features/support/custom_mixed_formatter.rb" with: 🍌 (000ms)

```
module MyCustom
  class MixedFormatter

    def initialize(runtime, io, options)
      @io = io
    end

    def before_test_case(test_case)
      feature = test_case.source.first
      @io.puts feature.short_name.upcase
    end

    def scenario_name(keyword, name, file_colon_line, source_indent)
      @io.puts "  #{name.upcase}"
    end
  end
end
```

When

I run `cucumber features/f.feature --format MyCustom::MixedFormatter` 🍌 (007ms)

Then

it should pass with exactly: 🍌 (000ms)

```
I'LL USE MY OWN
JUST PRINT ME
```

Custom filter

Scenario: Add a custom filter via AfterConfiguration hook

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature:  
  Scenario:  
    Given my special step
```

And

a file named "features/support/my_filter.rb" with: 🍌 (000ms)

```
require 'cucumber/core/filter'  
  
MakeAnythingPass = Cucumber::Core::Filter.new do  
  def test_case(test_case)  
    activated_steps = test_case.test_steps.map do |test_step|  
      test_step.with_action { }  
    end  
    test_case.with_steps(activated_steps).describe_to receiver  
  end  
end  
  
AfterConfiguration do |config|  
  config.filters << MakeAnythingPass.new  
end
```

When

I run `cucumber --strict` 🍌 (009ms)

Then

it should pass 🍌 (000ms)

Debug formatter

In order to help you easily visualise the listener API, you can use the `debug` formatter that prints the calls to the listener as a feature is run.

Background

Given

the standard step definitions 🍌 (000ms)

Scenario: title

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature:
Scenario:
Given this step passes

When

I run `cucumber -f debug` 🍌 (007ms)

Then

the stderr should not contain anything 🍌 (000ms)

Then

it should pass with: 🍌 (000ms)

```
before_test_case
before_features
before_feature
before_tags
after_tags
feature_name
before_test_step
after_test_step
before_test_step
before_feature_element
before_tags
after_tags
scenario_name
before_steps
before_step
before_step_result
step_name
after_step_result
after_step
after_test_step
after_steps
after_feature_element
after_test_case
after_feature
after_features
done
```

Doc strings

If you need to specify information in a scenario that won't fit on a single line, you can use a DocString.

A DocString follows a step, and starts and ends with three double quotes, like this:

```
When I ask to reset my password +
Then I should receive an email with: +
  """ +
  Dear bozo, +
  +
  Please click this link to reset your password +
  """ +
`` +
+
It's possible to annotate the DocString with the type of content it contains.
This is used by +
formatting tools like http://relishapp.com which will render the contents of the
DocString +
appropriately. You specify the content type after the triple quote, like this: +
+
``gherkin +
Given there is some Ruby code: +
  """ruby +
  puts "hello world" +
  """ +
`` +
+
You can read the content type from the argument passed into your step definition,
as shown +
in the example below.
```

Scenario: Plain text Docstring

Given

a scenario with a step that looks like this: 📌 (000ms)

```
Given I have a lot to say:
```

```
"""
```

```
One
```

```
Two
```

```
Three
```

```
"""
```

And

a step definition that looks like this: 📌 (000ms)

```
Given /say/ do |text|
```

```
  puts text
```

```
end
```

When

I run the feature with the progress formatter 📌 (010ms)

Then

the output should contain: 📌 (000ms)

```
One
```

```
Two
```

```
Three
```

Scenario: DocString with interesting content type

Given

a scenario with a step that looks like this: 🍌 (000ms)

Given I have some code for you:

```
""ruby
# hello
""
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /code/ do |text|
  puts text.content_type
end
```

When

I run the feature with the progress formatter 🍌 (008ms)

Then

the output should contain: 🍌 (000ms)

```
ruby
```

Dry Run

Dry run gives you a way to quickly scan your features without actually running them.

- Invokes formatters without executing the steps.
- This also omits the loading of your support/env.rb file if it exists.

Scenario: With a failing step

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature: test

Scenario:

Given this step fails

And

the standard step definitions 🍌 (000ms)

When

I run `cucumber --dry-run` 🍌 (020ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: test

Scenario: # features/test.feature:2

Given this step fails # features/step_definitions/steps.rb:4

1 scenario (1 skipped)

1 step (1 skipped)

Scenario: In strict mode

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature: test

Scenario:

Given this step fails

And

the standard step definitions 🍌 (000ms)

When

I run `cucumber --dry-run --strict` 🍌 (013ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: test

Scenario: # features/test.feature:2

Given this step fails # features/step_definitions/steps.rb:4

1 scenario (1 skipped)

1 step (1 skipped)

Scenario: In strict mode with an undefined step

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature: test

Scenario:

Given this step is undefined

When

I run `cucumber --dry-run --strict` 🍌 (009ms)

Then

it should fail with: 🍌 (000ms)

Feature: test

Scenario: # features/test.feature:2

Given this step is undefined # features/test.feature:3

Undefined step: "this step is undefined" (Cucumber::Undefined)

features/test.feature:3:in `Given this step is undefined'

1 scenario (1 undefined)

1 step (1 undefined)

ERB configuration

As a developer on server with multiple users

I want to be able to configure which port my wire server runs on

So that I can avoid port conflicts

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

Feature: High strung

Scenario: Wired

Given we're all wired

Scenario: ERB is used in the wire file which references an environment variable that is not set

tags: @wire,@wire

Given

a file named "features/step_definitions/server.wire" with: 🍌 (000ms)

```
host: localhost
port: <%= ENV['PORT'] || 12345 %>
```

And

there is a wire server running on port 12345 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber --dry-run --no-snippets -f progress` 🍌 (073ms)

Then

it should pass with: 🍌 (000ms)

U

```
1 scenario (1 undefined)
1 step (1 undefined)
```

Scenario: ERB is used in the wire file which references an environment variable

tags: @wire,@wire

Given

I have environment variable PORT set to "16816" 🍌 (000ms)

And

a file named "features/step_definitions/server.wire" with: 🍌 (000ms)

```
host: localhost  
port: <%= ENV['PORT'] || 12345 %>
```

And

there is a wire server running on port 16816 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber --dry-run --no-snippets -f progress` 🍌 (061ms)

Then

it should pass with: 🍌 (001ms)

```
U  
  
1 scenario (1 undefined)  
1 step (1 undefined)
```

Exception in After Block

In order to use custom assertions at the end of each scenario

As a developer

I want exceptions raised in After blocks to be handled gracefully and reported by the formatters

Background

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/step_definitions/naughty_steps.rb" with: 🍌 (000ms)

```
Given /^this step does something naughty$/ do x=1
  @naughty = true
end
```

And

a file named "features/support/env.rb" with: 🍌 (000ms)

```
class NaughtyScenarioException < Exception; end
After do
  if @naughty
    raise NaughtyScenarioException.new("This scenario has been very very
naughty")
  end
end
```

Scenario: Handle Exception in standard scenario step and carry on

tags: @spawn

Given

a file named "features/naughty_step_in_scenario.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Naughty Step

Given this step does something naughty

Scenario: Success

Given this step passes

When

I run `cucumber features` 🍌 (604ms)

Then

it should fail with: 🍌 (000ms)

Feature: Sample

```
Scenario: Naughty Step #
features/naughty_step_in_scenario.feature:3
  Given this step does something naughty #
features/step_definitions/naughty_steps.rb:1
    This scenario has been very very naughty (NaughtyScenarioException)
    ./features/support/env.rb:4:in `After'
```

```
Scenario: Success # features/naughty_step_in_scenario.feature:6
  Given this step passes # features/step_definitions/steps.rb:1
```

Failing Scenarios:

```
cucumber features/naughty_step_in_scenario.feature:3 # Scenario: Naughty Step
```

2 scenarios (1 failed, 1 passed)

2 steps (2 passed)

Scenario: Handle Exception in scenario outline table row and carry on

tags: @spawn

Given

a file named "features/naughty_step_in_scenario_outline.feature" with: 🍌 (000ms)

Feature: Sample

Scenario Outline: Naughty Step
Given this step <Might Work>

Examples:

Might Work	
passes	
does something naughty	
passes	

Scenario: Success
Given this step passes

When

I run `cucumber features -q` 🍌 (606ms)

Then

it should fail with: 🍌 (000ms)

Feature: Sample

Scenario Outline: Naughty Step
Given this step <Might Work>

Examples:

Might Work	
passes	
does something naughty	

This scenario has been very very naughty (NaughtyScenarioException)

./features/support/env.rb:4:in `After'

passes	
--------	--

Scenario: Success
Given this step passes

Failing Scenarios:

cucumber features/naughty_step_in_scenario_outline.feature:9

4 scenarios (1 failed, 3 passed)

4 steps (4 passed)

Scenario: Handle Exception using the progress format

Given

a file named "features/naughty_step_in_scenario.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Naughty Step

Given this step does something naughty

Scenario: Success

Given this step passes

When

I run `cucumber features --format progress` 🍌 (026ms)

Then

it should fail with: 🍌 (000ms)

.F.

Failing Scenarios:

cucumber features/naughty_step_in_scenario.feature:3 # Scenario: Naughty Step

2 scenarios (1 failed, 1 passed)

2 steps (2 passed)

Exception in AfterStep Block

In order to use custom assertions at the end of each step

As a developer

I want exceptions raised in AfterStep blocks to be handled gracefully and reported by the formatters

Background

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/step_definitions/naughty_steps.rb" with: 🍌 (000ms)

```
Given /^this step does something naughty$/ do x=1
  @naughty = true
end
```

And

a file named "features/support/env.rb" with: 🍌 (000ms)

```
class NaughtyStepException < Exception; end
AfterStep do
  if @naughty
    raise NaughtyStepException.new("This step has been very very naughty")
  end
end
```

Scenario: Handle Exception in standard scenario step and carry on

Given

a file named "features/naughty_step_in_scenario.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Naughty Step

Given this step does something naughty

Scenario: Success

Given this step passes

When

I run `cucumber features` 🍌 (021ms)

Then

it should fail with: 🍌 (000ms)

Feature: Sample

```
Scenario: Naughty Step #
features/naughty_step_in_scenario.feature:3
  Given this step does something naughty #
features/step_definitions/naughty_steps.rb:1
    This step has been very very naughty (NaughtyStepException)
    ./features/support/env.rb:4:in `AfterStep'
    features/naughty_step_in_scenario.feature:4:in `Given this step does
something naughty'
```

```
Scenario: Success # features/naughty_step_in_scenario.feature:6
  Given this step passes # features/step_definitions/steps.rb:1
```

Failing Scenarios:

```
cucumber features/naughty_step_in_scenario.feature:3 # Scenario: Naughty Step
```

2 scenarios (1 failed, 1 passed)

2 steps (2 passed)

Scenario: Handle Exception in scenario outline table row and carry on

Given

a file named "features/naughty_step_in_scenario_outline.feature" with: 🍌 (000ms)

Feature: Sample

Scenario Outline: Naughty Step
Given this step <Might Work>

Examples:

Might Work	
passes	
does something naughty	
passes	

Scenario: Success
Given this step passes

When

I run `cucumber features` 🍌 (022ms)

Then

it should fail with: 🍌 (000ms)

Feature: Sample

Scenario Outline: Naughty Step #
features/naughty_step_in_scenario_outline.feature:3
Given this step <Might Work> #
features/naughty_step_in_scenario_outline.feature:4

Examples:

Might Work	
passes	
does something naughty	

This step has been very very naughty (NaughtyStepException)
./features/support/env.rb:4:in `AfterStep'
features/naughty_step_in_scenario_outline.feature:9:in `Given this step
does something naughty'
features/naughty_step_in_scenario_outline.feature:4:in `Given this step
<Might Work>'
| passes |

Scenario: Success # features/naughty_step_in_scenario_outline.feature:12
Given this step passes # features/step_definitions/steps.rb:1

Failing Scenarios:

cucumber features/naughty_step_in_scenario_outline.feature:9 # Scenario Outline:
Naughty Step, Examples (#2)

4 scenarios (1 failed, 3 passed)
4 steps (4 passed)

Exception in Before Block

In order to know with confidence that my before blocks have run OK

As a developer

I want exceptions raised in Before blocks to be handled gracefully and reported by the formatters

Background

Given

the standard step definitions 🍷 (000ms)

And

a file named "features/support/env.rb" with: 🍷 (000ms)

```
class SomeSetupException < Exception; end
class BadStepException < Exception; end
Before do
  raise SomeSetupException.new("I cannot even start this scenario")
end
```

Scenario: Handle Exception in standard scenario step and carry on

tags: @spawn

Given

a file named "features/naughty_step_in_scenario.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Run a good step
Given this step passes

When

I run `cucumber features` 🍌 (605ms)

Then

it should fail with: 🍌 (001ms)

Feature: Sample

Scenario: Run a good step # features/naughty_step_in_scenario.feature:3
I cannot even start this scenario (SomeSetupException)
./features/support/env.rb:4:in `Before'
Given this step passes # features/step_definitions/steps.rb:1

Failing Scenarios:

cucumber features/naughty_step_in_scenario.feature:3 # Scenario: Run a good step

1 scenario (1 failed)

1 step (1 skipped)

Scenario: Handle Exception in Before hook for Scenario with Background

Given

a file named "features/naughty_step_in_before.feature" with: 🍌 (000ms)

Feature: Sample

Background:

Given this step passes

Scenario: Run a good step

Given this step passes

When

I run `cucumber features` 🍌 (023ms)

Then

it should fail with exactly: 🍌 (000ms)

Feature: Sample

Background: # features/naughty_step_in_before.feature:3

I cannot even start this scenario (SomeSetupException)

./features/support/env.rb:4:in `Before'

Given this step passes # features/step_definitions/steps.rb:1

Scenario: Run a good step # features/naughty_step_in_before.feature:6

Given this step passes # features/step_definitions/steps.rb:1

Failing Scenarios:

cucumber features/naughty_step_in_before.feature:6 # Scenario: Run a good step

1 scenario (1 failed)

2 steps (2 skipped)

0m0.012s

Scenario: Handle Exception using the progress format

Given

a file named "features/naughty_step_in_scenario.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Run a good step
Given this step passes

When

I run `cucumber features --format progress` 🍌 (016ms)

Then

it should fail with: 🍌 (000ms)

F-

Failing Scenarios:

cucumber features/naughty_step_in_scenario.feature:3 # Scenario: Run a good step

1 scenario (1 failed)

1 step (1 skipped)

Exceptions in Around Hooks

Around hooks are awkward beasts to handle internally.

Right now, if there's an error in your Around hook before you call `block.call`, we won't even print the steps for the scenario.

This is because that `block.call` invokes all the logic that would tell Cucumber's UI about the steps in your scenario. If we never reach that code, we'll never be told about them.

There's another scenario to consider, where the exception occurs after the steps have been run. How would we want to report in that case?

Scenario: Exception before the test case is run

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/support/env.rb" with: 🍌 (000ms)

```
Around do |scenario, block|  
  fail "this should be reported"  
  block.call  
end
```

And

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature:  
  Scenario:  
    Given this step passes
```

When

I run `cucumber -q` 🍌 (010ms)

Then

it should fail with exactly: 🍌 (000ms)

```
Feature:  
  
  Scenario:  
    this should be reported (RuntimeError)  
    ./features/support/env.rb:2:in `Around'  
  
Failing Scenarios:  
cucumber features/test.feature:2  
  
1 scenario (1 failed)  
0 steps
```

Scenario: Exception after the test case is run

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/support/env.rb" with: 🍌 (000ms)

```
Around do |scenario, block|
  block.call
  fail "this should be reported"
end
```

And

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step passes
```

When

I run `cucumber -q` 🍌 (009ms)

Then

it should fail with exactly: 🍌 (000ms)

```
Feature:

  Scenario:
    Given this step passes
      this should be reported (RuntimeError)
      ./features/support/env.rb:3:in `Around'

Failing Scenarios:
cucumber features/test.feature:2

1 scenario (1 failed)
1 step (1 passed)
```

Excluding ruby and feature files from runs

Developers are able to easily exclude files from cucumber runs

This is a nice feature to have in conjunction with profiles, so you can exclude certain environment files from certain runs.

Scenario: exclude ruby files

Given

an empty file named "features/support/dont_require_me.rb" 🍌 (000ms)

And

an empty file named "features/step_definitions/fooz.rb" 🍌 (000ms)

And

an empty file named "features/step_definitions/foof.rb" 🍌 (000ms)

And

an empty file named "features/step_definitions/foot.rb" 🍌 (000ms)

And

an empty file named "features/support/require_me.rb" 🍌 (000ms)

When

I run `cucumber features -q --verbose --exclude features/support/dont --exclude foo[zf]`
🍌 (007ms)

Then

"features/support/require_me.rb" should be required 🍌 (000ms)

And

"features/step_definitions/foot.rb" should be required 🍌 (000ms)

And

"features/support/dont_require_me.rb" should not be required 🍌 (000ms)

And

"features/step_definitions/foof.rb" should not be required 🍌 (000ms)

And

"features/step_definitions/fooz.rb" should not be required 🍌 (000ms)

[[Formatter-API:-Step-file-path-and-line-number-(Issue-#179), Formatter API: Step file path and line number (Issue #179)]] == **Formatter API: Step file path and line number (Issue #179)**

To all reporter to understand location of current executing step let's fetch this information from `step/step_invocation` and pass to reporters

Scenario: my own formatter

Given

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: I'll use my own
  because I'm worth it
Scenario: just print step current line and feature file name
  Given step at line 4
  Given step at line 5
```

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given(/^step at line (.*)$/) { |line| }
```

And

a file named "features/support/jb/formatter.rb" with: 🍌 (000ms)

```
module Jb
  class Formatter
    def initialize(runtime, io, options)
      @io = io
    end

    def before_step_result(keyword, step_match, multiline_arg, status, exception,
      source_indent, background, file_colon_line)
      @io.puts "step result event: #{file_colon_line}"
    end

    def step_name(keyword, step_match, status, source_indent, background,
      file_colon_line)
      @io.puts "step name event: #{file_colon_line}"
    end
  end
end
```

When

I run `cucumber features/f.feature --format Jb::Formatter` 🍌 (006ms)

Then

it should pass with exactly: 🍌 (000ms)

```
step result event: features/f.feature:4
step name event: features/f.feature:4
step result event: features/f.feature:5
step name event: features/f.feature:5
```

Getting started

To get started, just open a command prompt in an empty directory and run `cucumber`. You'll be prompted for what to do next.

Scenario: Run Cucumber in an empty directory

tags: @spawn

Given

a directory without standard Cucumber project directory structure 🍌 (000ms)

When

I run `cucumber` 🍌 (605ms)

Then

it should fail with: 🍌 (001ms)

No such file or directory - features. You can use `cucumber --init` to get started.

Scenario: Accidentally run Cucumber in a folder with Ruby files in it.

Given

a directory without standard Cucumber project directory structure 🍌 (000ms)

And

a file named "should_not_load.rb" with: 🍌 (000ms)

```
puts 'this will not be shown'
```

When

I run `cucumber` 🍌 (007ms)

Then

the exit status should be 2 🍌 (000ms)

And

the output should not contain: 🍌 (000ms)

```
this will not be shown
```

HTML output formatter

Background

Given

the standard step definitions 📌 (000ms)

And

a file named "features/scenario_outline_with_undefined_steps.feature" with: 📌 (000ms)

Feature:

Scenario Outline:

Given this step is undefined

Examples:

|foo|

|bar|

And

a file named "features/scenario_outline_with_pending_step.feature" with: 📌 (000ms)

Feature: Outline

Scenario Outline: Will it blend?

Given this step is pending

And other step

When I do something with <example>

Then I should see something

Examples:

| example |

| one |

| two |

| three |

And

a file named "features/failing_background_step.feature" with: 📌 (000ms)

Feature: Feature with failing background step

Background:

Given this step fails

Scenario:

When I do something

Then I should see something

Scenario: an scenario outline, one undefined step, one random example, expand flag on

When

I run `cucumber features/scenario_outline_with_undefined_steps.feature --format html --expand` 🍌 (020ms)

Then

it should pass 🍌 (003ms)

Scenario Outline: an scenario outline, one pending step

When

I run `cucumber features/scenario_outline_with_pending_step.feature --format html --expand` 🍌 (025ms)

Then

it should pass 🍌 (003ms)

And

the output should contain: 🍌 (004ms)

```
makeYellow('scenario_1')
```

And

the output should not contain: 🍌 (004ms)

```
makeRed('scenario_1')
```

Scenario Outline: an scenario outline, one pending step

When

I run `cucumber features/scenario_outline_with_pending_step.feature --format html` 🍌
(019ms)

Then

it should pass 🍌 (002ms)

And

the output should contain: 🍌 (003ms)

```
makeYellow('scenario_1')
```

And

the output should not contain: 🍌 (004ms)

```
makeRed('scenario_1')
```

Scenario Outline: an scenario outline, one pending step

When

I run `cucumber features/scenario_outline_with_undefined_steps.feature --format html --expand` 🍌 (007ms)

Then

it should pass 🍌 (002ms)

And

the output should contain: 🍌 (003ms)

```
makeYellow('scenario_1')
```

And

the output should not contain: 🍌 (003ms)

```
makeRed('scenario_1')
```

Scenario Outline: an scenario outline, one pending step

When

I run `cucumber features/scenario_outline_with_undefined_steps.feature --format html`
👍 (009ms)

Then

it should pass 👍 (002ms)

And

the output should contain: 👍 (003ms)

```
makeYellow('scenario_1')
```

And

the output should not contain: 👎 (003ms)

```
makeRed('scenario_1')
```

Scenario: when using a profile the html shouldn't include 'Using the default profile...'

And

a file named "cucumber.yml" with: 👍 (000ms)

```
default: -r features
```

When

I run `cucumber features/scenario_outline_with_undefined_steps.feature --profile default --format html` 👍 (009ms)

Then

it should pass 👍 (002ms)

And

the output should not contain: 👎 (003ms)

```
Using the default profile...
```

Scenario: a feature with a failing background step

When

I run `cucumber features/failing_background_step.feature --format html` 🍌 (010ms)

Then

the output should not contain: 🍌 (003ms)

```
makeRed('scenario_0')
```

And

the output should contain: 🍌 (003ms)

```
makeRed('background_0')
```

Handle unexpected response

When the server sends us back a message we don't understand, this is how Cucumber will behave.

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

```
Feature: High strung
  Scenario: Wired
    Given we're all wired
```

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

```
host: localhost
port: 54321
```

Scenario: Unexpected response

tags: @wire,@wire

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f pretty` 🍌 (068ms)

Then

the output should contain: 🍌 (000ms)

```
undefined method `handle_yikes'
```

Hooks execute in defined order

Background

tags: @spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given /^background step$/ do; $EventOrder.push(:background_step) end
Given /^scenario step$/ do; $EventOrder.push(:scenario_step) end
```

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
$EventOrder = []
Around('@around') do |scenario, block|
  $EventOrder.push :around_begin
  block.call
  $EventOrder.push :around_end
end
Before('@before') do
  $EventOrder.push :before
end
After('@after') do |scenario|
  $EventOrder.push :after
end
at_exit {
  puts "Event order: #{$EventOrder.join(' ')}"
}
```

And

a file named "features/around_hook_covers_background.feature" with: 🍌 (000ms)

```
@around
Feature: Around hooks cover background steps
  Background:
    Given background step
  Scenario:
    Given scenario step
```

And

a file named "features/all_hook_order.feature" with: 🍌 (000ms)

```
@around
@before
@after
Feature: All hooks execute in expected order
  Background:
    Given background step
  Scenario:
    Given scenario step
```

Scenario: Around hooks cover background steps

tags: @spawn,@spawn

When

I run `cucumber -o /dev/null features/around_hook_covers_background.feature` 🍌 (606ms)

Then

the output should contain: 🍌 (000ms)

```
Event order: around_begin background_step scenario_step around_end
```

Scenario: All hooks execute in expected order

tags: @spawn,@spawn

When

I run `cucumber -o /dev/null features/all_hook_order.feature` 🍌 (606ms)

Then

the output should contain: 🍌 (000ms)

Event order: around_begin before background_step scenario_step after around_end

Invoke message

Assuming a `StepMatch` was returned for a given step name, when it's time to invoke that step definition, Cucumber will send an invoke message.

The invoke message contains the ID of the step definition, as returned by the wire server in response to the `step_matches` call, along with the arguments that were parsed from the step name during the same `step_matches` call.

The wire server will normally reply one of the following:

- * `success`
- * `fail`
- * `pending` - optionally takes a message argument

This isn't quite the whole story: see also `table_diffing.feature`

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

```
Feature: High strung
  Scenario: Wired
    Given we're all wired
```

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

```
host: localhost
port: 54321
```

Scenario: Invoke a step definition which is pending

tags: @wire,@wire,@spawn

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (001ms)

When

I run `cucumber -f pretty -q` 🍌 (806ms)

And

it should pass with: 🍌 (001ms)

```
Feature: High strung

  Scenario: Wired
    Given we're all wired
      I'll do it later (Cucumber::Pending)
      features/wired.feature:3:in `Given we're all wired'

1 scenario (1 pending)
1 step (1 pending)
```

Scenario: Invoke a step definition which passes

tags: @wire,@wire

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber -f progress` 🍌 (140ms)

And

it should pass with: 🍌 (000ms)

.

1 scenario (1 passed)

1 step (1 passed)

Scenario: Invoke a step definition which fails

tags: @wire,@wire,@spawn

If an invoked step definition fails, it can return details of the exception in the reply to invoke. This causes a `Cucumber::WireSupport::WireException` to be raised.

Valid arguments are:

- `message` (mandatory)
- `exception`
- `backtrace`

See the specs for `Cucumber::WireSupport::WireException` for more details

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber -f progress` 🍌 (808ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should fail with: 🍌 (001ms)

F

(::) failed steps (::)

The wires are down (Some.Foreign.ExceptionType from localhost:54321)
features/wired.feature:3:in 'Given we're all wired'

Failing Scenarios:

cucumber features/wired.feature:2 # Scenario: Wired

1 scenario (1 failed)

1 step (1 failed)

Scenario: Invoke a step definition which takes string arguments (and passes)

tags: @wire,@wire

If the step definition at the end of the wire captures arguments, these are communicated back to Cucumber in the `step_matches` message.

Cucumber expects these `StepArguments` to be returned in the `StepMatch`. The keys have the following meanings:

- `val` - the value of the string captured for that argument from the step name passed in `step_matches`
- `pos` - the position within the step name that the argument was matched (used for formatter highlighting)

The argument values are then sent back by Cucumber in the `invoke` message.

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f progress` 🍌 (141ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (000ms)

.

1 scenario (1 passed)

1 step (1 passed)

Scenario: Invoke a step definition which takes regular and table arguments (and passes)

tags: @wire,@wire

If the step has a multiline table argument, it will be passed with the invoke message as an array of array of strings.

In this scenario our step definition takes two arguments - one captures the "we're" and the other takes the table.

Given

a file named "features/wired_on_tables.feature" with: 🍌 (000ms)

Feature: High strung

Scenario: Wired and more

Given we're all:

| wired |

| high |

| happy |

And

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f progress features/wired_on_tables.feature` 🍌 (139ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (001ms)

.

1 scenario (1 passed)

1 step (1 passed)

Scenario: Invoke a scenario outline step

tags: @wire,@wire

Given

a file named "features/wired_in_an_outline.feature" with: 🍌 (000ms)

Feature:

Scenario Outline:

Given we're all <arg>

Examples:

arg
wired

And

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f progress features/wired_in_an_outline.feature` 🍌 (146ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (000ms)

.

1 scenario (1 passed)

1 step (1 passed)

And

the wire server should have received the following messages: 🍌 (000ms)

JSON output formatter

In order to simplify processing of Cucumber features and results
Developers should be able to consume features as JSON

Background

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/one_passing_one_failing.feature" with: 📄 (000ms)

```
@a
Feature: One passing scenario, one failing scenario

  @b
  Scenario: Passing
    Given this step passes

  @c
  Scenario: Failing
    Given this step fails
```

And

a file named "features/step_definitions/json_steps.rb" with: 📄 (000ms)

```
Given /^I embed a screenshot/ do
  File.open("screenshot.png", "w") { |file| file << "foo" }
  embed "screenshot.png", "image/png"
end

Given /^I print from step definition/ do
  puts "from step definition"
end

Given /^I embed data directly/ do
  data = "YWJj"
  embed data, "mime-type;base64"
end
```

And

a file named "features/embed.feature" with: 📄 (000ms)

```
Feature: A screenshot feature

  Scenario:
    Given I embed a screenshot
```

And

a file named "features/outline.feature" with: 📄 (000ms)

Feature: An outline feature

Scenario Outline: outline
Given this step <status>

Examples: examples1
| status |
| passes |
| fails |

Examples: examples2
| status |
| passes |

And

a file named "features/print_from_step_definition.feature" with: 📄 (000ms)

Feature: A print from step definition feature

Scenario:
Given I print from step definition
And I print from step definition

And

a file named "features/print_from_step_definition.feature" with: 📄 (000ms)

Feature: A print from step definition feature

Scenario:
Given I print from step definition
And I print from step definition

And

a file named "features/embed_data_directly.feature" with: 📄 (000ms)

Feature: An embed data directly feature

Scenario:

Given I embed data directly

Scenario Outline:

Given I embed data directly

Examples:

dummy
1
2

And

a file named "features/out_scenario_out_scenario_outline.feature" with: 🍌 (000ms)

Feature:

Scenario:

Given this step passes

Scenario Outline:

Given this step <status>

Examples:

status
passes

Scenario: one feature, one passing scenario, one failing scenario

tags: @spawn

When

I run `cucumber --format json features/one_passing_one_failing.feature` 🍌 (605ms)

Then

it should fail with JSON: 🍌 (001ms)

```
[
  {
    "uri": "features/one_passing_one_failing.feature",
    "keyword": "Feature",
    "id": "one-passing-scenario,-one-failing-scenario",
    "name": "One passing scenario, one failing scenario",
    "line": 2,
    "description": "",
    "tags": [
      {
```

```

      "name": "@a",
      "line": 1
    }
  ],
  "elements": [
    {
      "keyword": "Scenario",
      "id": "one-passing-scenario,-one-failing-scenario;passing",
      "name": "Passing",
      "line": 5,
      "description": "",
      "tags": [
        {
          "name": "@a",
          "line": 1
        },
        {
          "name": "@b",
          "line": 4
        }
      ],
      "type": "scenario",
      "steps": [
        {
          "keyword": "Given ",
          "name": "this step passes",
          "line": 6,
          "match": {
            "location": "features/step_definitions/steps.rb:1"
          },
          "result": {
            "status": "passed",
            "duration": 1
          }
        }
      ]
    },
    {
      "keyword": "Scenario",
      "id": "one-passing-scenario,-one-failing-scenario;failing",
      "name": "Failing",
      "line": 9,
      "description": "",
      "tags": [
        {
          "name": "@a",
          "line": 1
        },
        {
          "name": "@c",
          "line": 8
        }
      ]
    }
  ]
}

```

```

    }
  ],
  "type": "scenario",
  "steps": [
    {
      "keyword": "Given ",
      "name": "this step fails",
      "line": 10,
      "match": {
        "location": "features/step_definitions/steps.rb:4"
      },
      "result": {
        "status": "failed",
        "error_message": "(RuntimeError)\n./features/step_definitions/steps.rb:4:in `/^this step fails$/'\nfeatures/one_passing_one_failing.feature:10:in `Given this step fails'",
        "duration": 1
      }
    }
  ]
}
]

```

Scenario: one feature, one passing scenario, one failing scenario with prettyfied json

tags: @spawn

When

I run `cucumber --format json_pretty features/one_passing_one_failing.feature` 🍌 (505ms)

Then

it should fail with JSON: 🍌 (002ms)

```

[
  {
    "uri": "features/one_passing_one_failing.feature",
    "keyword": "Feature",
    "id": "one-passing-scenario,-one-failing-scenario",
    "name": "One passing scenario, one failing scenario",
    "line": 2,
    "description": "",
    "tags": [
      {
        "name": "@a",

```



```

    "line": 1
  }
],
"elements": [
  {
    "keyword": "Scenario",
    "id": "one-passing-scenario,-one-failing-scenario;passing",
    "name": "Passing",
    "line": 5,
    "description": "",
    "tags": [
      {
        "name": "@a",
        "line": 1
      },
      {
        "name": "@b",
        "line": 4
      }
    ],
    "type": "scenario",
    "steps": [
      {
        "keyword": "Given ",
        "name": "this step passes",
        "line": 6,
        "match": {
          "location": "features/step_definitions/steps.rb:1"
        },
        "result": {
          "status": "passed",
          "duration": 1
        }
      }
    ]
  },
  {
    "keyword": "Scenario",
    "id": "one-passing-scenario,-one-failing-scenario;failing",
    "name": "Failing",
    "line": 9,
    "description": "",
    "tags": [
      {
        "name": "@a",
        "line": 1
      },
      {
        "name": "@c",
        "line": 8
      }
    ]
  }
]

```

```

],
"type": "scenario",
"steps": [
  {
    "keyword": "Given ",
    "name": "this step fails",
    "line": 10,
    "match": {
      "location": "features/step_definitions/steps.rb:4"
    },
    "result": {
      "status": "failed",
      "error_message": "
(RuntimeError)\n./features/step_definitions/steps.rb:4:in `/^this step
fails$/'\nfeatures/one_passing_one_failing.feature:10:in `Given this step
fails'",
      "duration": 1
    }
  }
]
}
]

```

Scenario: DocString

tags: @spawn

Given

a file named "features/doc_string.feature" with: 🍌 (000ms)

Feature: A DocString feature

Scenario:

Then I should fail with

"""

a string

"""

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```

Then /I should fail with/ do |s|
  raise RuntimeError, s
end

```

When

I run `cucumber --format json features/doc_string.feature` 🍌 (605ms)

Then

it should fail with JSON: 🍌 (001ms)

```
[
  {
    "id": "a-docstring-feature",
    "uri": "features/doc_string.feature",
    "keyword": "Feature",
    "name": "A DocString feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "a-docstring-feature;",
        "keyword": "Scenario",
        "name": "",
        "line": 3,
        "description": "",
        "type": "scenario",
        "steps": [
          {
            "keyword": "Then ",
            "name": "I should fail with",
            "line": 4,
            "doc_string": {
              "content_type": "",
              "value": "a string",
              "line": 5
            },
            "match": {
              "location": "features/step_definitions/steps.rb:1"
            },
            "result": {
              "status": "failed",
              "error_message": "a string
(RuntimeError)\n./features/step_definitions/steps.rb:2:in `/I should fail
with/'\nfeatures/doc_string.feature:4:in `Then I should fail with'",
              "duration": 1
            }
          }
        ]
      }
    ]
  }
]
```

Scenario: embedding screenshot

tags: @spawn

When

I run `cucumber -b --format json features/embed.feature` 🍌 (606ms)

Then

it should pass with JSON: 🍌 (001ms)

```
[
  {
    "uri": "features/embed.feature",
    "id": "a-screenshot-feature",
    "keyword": "Feature",
    "name": "A screenshot feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "a-screenshot-feature;",
        "keyword": "Scenario",
        "name": "",
        "line": 3,
        "description": "",
        "type": "scenario",
        "steps": [
          {
            "keyword": "Given ",
            "name": "I embed a screenshot",
            "line": 4,
            "embeddings": [
              {
                "mime_type": "image/png",
                "data": "Zm9v"
              }
            ],
            "match": {
              "location": "features/step_definitions/json_steps.rb:1"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          }
        ]
      }
    ]
  }
]
```

Scenario: scenario outline

tags: @spawn

When

I run `cucumber --format json features/outline.feature` 🍌 (606ms)

Then

it should fail with JSON: 🍌 (002ms)

```
[
  {
    "uri": "features/outline.feature",
    "id": "an-outline-feature",
    "keyword": "Feature",
    "name": "An outline feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "an-outline-feature;outline;examples1;2",
        "keyword": "Scenario Outline",
        "name": "outline",
        "description": "",
        "line": 8,
        "type": "scenario",
        "steps": [
          {
            "keyword": "Given ",
            "name": "this step passes",
            "line": 8,
            "match": {
              "location": "features/step_definitions/steps.rb:1"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          }
        ]
      }
    ],
  },
  {
    "id": "an-outline-feature;outline;examples1;3",
    "keyword": "Scenario Outline",
    "name": "outline",
    "description": "",
    "line": 9,
    "type": "scenario",
    "steps": [
```

```

    {
      "keyword": "Given ",
      "name": "this step fails",
      "line": 9,
      "match": {
        "location": "features/step_definitions/steps.rb:4"
      },
      "result": {
        "status": "failed",
        "error_message": "
(RuntimeError)\n./features/step_definitions/steps.rb:4:in `/^this step
fails$/'\nfeatures/outline.feature:9:in `Given this step
fails'\nfeatures/outline.feature:4:in `Given this step <status>'",
        "duration": 1
      }
    }
  ]
},
{
  "id": "an-outline-feature;outline;examples2;2",
  "keyword": "Scenario Outline",
  "name": "outline",
  "description": "",
  "line": 13,
  "type": "scenario",
  "steps": [
    {
      "keyword": "Given ",
      "name": "this step passes",
      "line": 13,
      "match": {
        "location": "features/step_definitions/steps.rb:1"
      },
      "result": {
        "status": "passed",
        "duration": 1
      }
    }
  ]
}
]
}
]

```

Scenario: print from step definition

When

I run `cucumber --format json features/print_from_step_definition.feature` 🍌 (013ms)

Then

it should pass with JSON: 🍌 (000ms)

```
[
  {
    "uri": "features/print_from_step_definition.feature",
    "id": "a-print-from-step-definition-feature",
    "keyword": "Feature",
    "name": "A print from step definition feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "a-print-from-step-definition-feature;",
        "keyword": "Scenario",
        "name": "",
        "line": 3,
        "description": "",
        "type": "scenario",
        "steps": [
          {
            "keyword": "Given ",
            "name": "I print from step definition",
            "line": 4,
            "output": [
              "from step definition"
            ],
            "match": {
              "location": "features/step_definitions/json_steps.rb:6"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          },
          {
            "keyword": "And ",
            "name": "I print from step definition",
            "line": 5,
            "output": [
              "from step definition"
            ],
            "match": {
              "location": "features/step_definitions/json_steps.rb:6"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          }
        ]
      }
    ]
  }
]
```



```
]
  }
]
}
```

Scenario: scenario outline expanded

tags: @spawn

When

I run `cucumber --expand --format json features/outline.feature` 🍌 (707ms)

Then

it should fail with JSON: 🍌 (002ms)

```
[
  {
    "uri": "features/outline.feature",
    "id": "an-outline-feature",
    "keyword": "Feature",
    "name": "An outline feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "an-outline-feature;outline;examples1;2",
        "keyword": "Scenario Outline",
        "name": "outline",
        "line": 8,
        "description": "",
        "type": "scenario",
        "steps": [
          {
            "keyword": "Given ",
            "name": "this step passes",
            "line": 8,
            "match": {
              "location": "features/step_definitions/steps.rb:1"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          }
        ]
      }
    ]
  },
  {
```

```

    "id": "an-outline-feature;outline;examples1;3",
    "keyword": "Scenario Outline",
    "name": "outline",
    "line": 9,
    "description": "",
    "type": "scenario",
    "steps": [
      {
        "keyword": "Given ",
        "name": "this step fails",
        "line": 9,
        "match": {
          "location": "features/step_definitions/steps.rb:4"
        },
        "result": {
          "status": "failed",
          "error_message" : "
(RuntimeError)\n./features/step_definitions/steps.rb:4:in `/^this step
fails$/'\nfeatures/outline.feature:9:in `Given this step
fails'\nfeatures/outline.feature:4:in `Given this step <status>'",
          "duration": 1
        }
      }
    ],
  },
  {
    "id": "an-outline-feature;outline;examples2;2",
    "keyword": "Scenario Outline",
    "name": "outline",
    "line": 13,
    "description": "",
    "type": "scenario",
    "steps": [
      {
        "keyword": "Given ",
        "name": "this step passes",
        "line": 13,
        "match": {
          "location": "features/step_definitions/steps.rb:1"
        },
        "result": {
          "status": "passed",
          "duration": 1
        }
      }
    ]
  }
]
}
]
}
]

```

Scenario: embedding data directly

tags: @spawn

When

I run `cucumber -b --format json -x features/embed_data_directly.feature` 🍷 (607ms)

Then

it should pass with JSON: 🍷 (002ms)

```
[
  {
    "uri": "features/embed_data_directly.feature",
    "id": "an-embed-data-directly-feature",
    "keyword": "Feature",
    "name": "An embed data directly feature",
    "line": 1,
    "description": "",
    "elements": [
      {
        "id": "an-embed-data-directly-feature;",
        "keyword": "Scenario",
        "name": "",
        "line": 3,
        "description": "",
        "type": "scenario",
        "steps": [
          {
            "keyword": "Given ",
            "name": "I embed data directly",
            "line": 4,
            "embeddings": [
              {
                "mime_type": "mime-type",
                "data": "YWJj"
              }
            ],
            "match": {
              "location": "features/step_definitions/json_steps.rb:10"
            },
            "result": {
              "status": "passed",
              "duration": 1
            }
          }
        ]
      }
    ],
    {
      "keyword": "Scenario Outline",
```

```

"name": "",
"line": 11,
"description": "",
"id": "an-embed-data-directly-feature;;;2",
"type": "scenario",
"steps": [
  {
    "keyword": "Given ",
    "name": "I embed data directly",
    "line": 11,
    "embeddings": [
      {
        "mime_type": "mime-type",
        "data": "YWJj"
      }
    ],
    "match": {
      "location": "features/step_definitions/json_steps.rb:10"
    },
    "result": {
      "status": "passed",
      "duration": 1
    }
  }
],
},
{
  "keyword": "Scenario Outline",
  "name": "",
  "line": 12,
  "description": "",
  "id": "an-embed-data-directly-feature;;;3",
  "type": "scenario",
  "steps": [
    {
      "keyword": "Given ",
      "name": "I embed data directly",
      "line": 12,
      "embeddings": [
        {
          "mime_type": "mime-type",
          "data": "YWJj"
        }
      ],
      "match": {
        "location": "features/step_definitions/json_steps.rb:10"
      },
      "result": {
        "status": "passed",
        "duration": 1
      }
    }
  ]
}

```

```
]
  }
  ]
  }
  ]
  }
```

Scenario: handle output from hooks

tags: @spawn

Given

a file named "features/step_definitions/output_steps.rb" with: 🍌 (000ms)

```
Before do
  puts "Before hook 1"
  embed "src", "mime_type", "label"
end
```

```
Before do
  puts "Before hook 2"
  embed "src", "mime_type", "label"
end
```

```
AfterStep do
  puts "AfterStep hook 1"
  embed "src", "mime_type", "label"
end
```

```
AfterStep do
  puts "AfterStep hook 2"
  embed "src", "mime_type", "label"
end
```

```
After do
  puts "After hook 1"
  embed "src", "mime_type", "label"
end
```

```
After do
  puts "After hook 2"
  embed "src", "mime_type", "label"
end
```

When

I run `cucumber --format json features/out_scenario_out_scenario_outline.feature` 🍌
(707ms)

Then

it should pass 🍌 (001ms)

JUnit output formatter

In order for developers to create test reports with ant
Cucumber should be able to output JUnit xml files

Background

tags: @spawn

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/one_passing_one_failing.feature" with: 🍌 (000ms)

Feature: One passing scenario, one failing scenario

Scenario: Passing

Given this step passes

Scenario: Failing

Given this step fails

And

a file named "features/some_subdirectory/one_passing_one_failing.feature" with: 🍌 (000ms)

Feature: Subdirectory - One passing scenario, one failing scenario

Scenario: Passing

Given this step passes

Scenario: Failing

Given this step fails

And

a file named "features/pending.feature" with: 🍌 (000ms)

Feature: Pending step

Scenario: Pending

Given this step is pending

Scenario: Undefined

Given this step is undefined

And

a file named "features/pending.feature" with: 🍌 (000ms)

Feature: Pending step

Scenario: Pending

Given this step is pending

Scenario: Undefined

Given this step is undefined

And

a file named "features/scenario_outline.feature" with: 🍌 (000ms)

Feature: Scenario outlines

Scenario Outline: Using scenario outlines

Given this step <type>

Examples:

type	
passes	
fails	
is pending	
is undefined	

Scenario: one feature, one passing scenario, one failing scenario

tags: @spawn,@spawn

When

I run `cucumber --format junit --out tmp/ features/one_passing_one_failing.feature` 🍌
(706ms)

Then

it should fail with: 🍌 (001ms)

And

the junit output file "tmp/TEST-features-one_passing_one_failing.xml" should contain: 🍌
(000ms)

```
<?xml version="1.0" encoding="UTF-8"?>
<testsuite failures="1" errors="0" skipped="0" tests="2" time="0.05" name="One
passing scenario, one failing scenario">
<testcase classname="One passing scenario, one failing scenario" name="Passing"
time="0.05">
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="One passing scenario, one failing scenario" name="Failing"
time="0.05">
  <failure message="failed Failing" type="failed">
    <![CDATA[Scenario: Failing
```

Given this step fails

Message:

]]>

```
    <![CDATA[ (RuntimeError)
./features/step_definitions/steps.rb:4:in `/^this step fails$/
features/one_passing_one_failing.feature:7:in `Given this step fails']]>
  </failure>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
</testsuite>
```

Scenario: one feature in a subdirectory, one passing scenario, one failing scenario

tags: @spawn,@spawn

When

```
I run cucumber --format junit --out tmp/  
features/some_subdirectory/one_passing_one_failing.feature --require features 🍌  
(607ms)
```

Then

it should fail with: 🍌 (000ms)

And

the junit output file "tmp/TEST-features-some_subdirectory-one_passing_one_failing.xml"
should contain: 🍌 (000ms)

```
<?xml version="1.0" encoding="UTF-8"?>  
<testsuite failures="1" errors="0" skipped="0" tests="2" time="0.05"  
name="Subdirectory - One passing scenario, one failing scenario">  
<testcase classname="Subdirectory - One passing scenario, one failing scenario"  
name="Passing" time="0.05">  
  <system-out>  
    <![CDATA[]]>  
  </system-out>  
  <system-err>  
    <![CDATA[]]>  
  </system-err>  
</testcase>  
<testcase classname="Subdirectory - One passing scenario, one failing scenario"  
name="Failing" time="0.05">  
  <failure message="failed Failing" type="failed">  
    <![CDATA[Scenario: Failing
```

Given this step fails

Message:

```
]]>  
  <![CDATA[ (RuntimeError)  
./features/step_definitions/steps.rb:4:in `/^this step fails$/'  
features/some_subdirectory/one_passing_one_failing.feature:7:in `Given this step  
fails' ]]>  
</failure>  
<system-out>  
  <![CDATA[]]>  
</system-out>  
<system-err>  
  <![CDATA[]]>  
</system-err>  
</testcase>  
</testsuite>
```

Scenario: pending and undefined steps are reported as skipped

tags: @spawn,@spawn

When

I run `cucumber --format junit --out tmp/ features/pending.feature` 🍌 (606ms)

Then

it should pass with: 🍌 (001ms)

And

the junit output file "tmp/TEST-features-pending.xml" should contain: 🍌 (000ms)

```
<?xml version="1.0" encoding="UTF-8"?>
<testsuite failures="0" errors="0" skipped="2" tests="2" time="0.05"
name="Pending step">
<testcase classname="Pending step" name="Pending" time="0.05">
  <skipped/>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="Pending step" name="Undefined" time="0.05">
  <skipped/>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
</testsuite>
```

Scenario: pending and undefined steps with strict option should fail

tags: @spawn,@spawn

When

I run `cucumber --format junit --out tmp/ features/pending.feature --strict` 🍌 (706ms)

Then

it should fail with: 🍌 (000ms)

And

the junit output file "tmp/TEST-features-pending.xml" should contain: 📌 (000ms)

```
<?xml version="1.0" encoding="UTF-8"?>
<testsuite failures="2" errors="0" skipped="0" tests="2" time="0.05"
name="Pending step">
<testcase classname="Pending step" name="Pending" time="0.05">
  <failure message="pending Pending" type="pending">
    <![CDATA[Scenario: Pending
```

Given this step is pending

Message:

```
]]>
  <![CDATA[TODO (Cucumber::Pending)
./features/step_definitions/steps.rb:3:in `/^this step is pending$/'
features/pending.feature:4:in `Given this step is pending']]>
</failure>
<system-out>
  <![CDATA[]]>
</system-out>
<system-err>
  <![CDATA[]]>
</system-err>
</testcase>
<testcase classname="Pending step" name="Undefined" time="0.05">
  <failure message="undefined Undefined" type="undefined">
    <![CDATA[Scenario: Undefined
```

Given this step is undefined

Message:

```
]]>
  <![CDATA[Undefined step: "this step is undefined"
(Cucumber::Core::Test::Result::Undefined)
features/pending.feature:7:in `Given this step is undefined']]>
</failure>
<system-out>
  <![CDATA[]]>
</system-out>
<system-err>
  <![CDATA[]]>
</system-err>
</testcase>
</testsuite>
```

Scenario: run all features

tags: @spawn,@spawn

When

I run `cucumber --format junit --out tmp/ features` 🍴 (707ms)

Then

it should fail with: 🍴 (001ms)

And

a file named "tmp/TEST-features-one_passing_one_failing.xml" should exist 🍴 (000ms)

And

a file named "tmp/TEST-features-pending.xml" should exist 🍴 (000ms)

Scenario: show correct error message if no --out is passed

tags: @spawn,@spawn

When

I run `cucumber --format junit features` 🍴 (607ms)

Then

the stderr should not contain: 🍴 (000ms)

```
can't convert .* into String \(TypeError\)
```

And

the stderr should contain: 🍴 (000ms)

```
You *must* specify --out DIR for the junit formatter
```

Scenario: strict mode, one feature, one scenario outline, four examples: one passing, one failing, one pending, one undefined

tags: @spawn,@spawn

When

I run `cucumber --strict --format junit --out tmp/ features/scenario_outline.feature` 🍴 (707ms)

Then

it should fail with: 📌 (000ms)

And

the junit output file "tmp/TEST-features-scenario_outline.xml" should contain: 📌 (000ms)

```
<?xml version="1.0" encoding="UTF-8"?>
<testsuite failures="3" errors="0" skipped="0" tests="4" time="0.05"
name="Scenario outlines">
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | passes |)" time="0.05">
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | fails |)" time="0.05">
  <failure message="failed Using scenario outlines (outline example : | fails |)"
type="failed">
    <![CDATA[Scenario Outline: Using scenario outlines
```

Example row: | fails |

Message:

```
]]>
  <![CDATA[ (RuntimeError)
./features/step_definitions/steps.rb:4:in `/^this step fails$/'
features/scenario_outline.feature:9:in `Given this step fails'
features/scenario_outline.feature:4:in `Given this step <type>']]]>
```

```
</failure>
<system-out>
  <![CDATA[]]>
</system-out>
<system-err>
  <![CDATA[]]>
</system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | is pending |)" time="0.05">
  <failure message="pending Using scenario outlines (outline example : | is
pending |)" type="pending">
    <![CDATA[Scenario Outline: Using scenario outlines
```

Example row: | is pending |

Message:

```
]]>
```

```

<![CDATA[TODO (Cucumber::Pending)
./features/step_definitions/steps.rb:3:in `/^this step is pending$/'
features/scenario_outline.feature:10:in `Given this step is pending'
features/scenario_outline.feature:4:in `Given this step <type>']]]>
</failure>
<system-out>
  <![CDATA[]]>
</system-out>
<system-err>
  <![CDATA[]]>
</system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | is undefined |)" time="0.05">
  <failure message="undefined Using scenario outlines (outline example : | is
undefined |)" type="undefined">
    <![CDATA[Scenario Outline: Using scenario outlines

Example row: | is undefined |

Message:
]]>
    <![CDATA[Undefined step: "this step is undefined"
(Cucumber::Core::Test::Result::Undefined)
features/scenario_outline.feature:11:in `Given this step is undefined'
features/scenario_outline.feature:4:in `Given this step <type>']]]>
  </failure>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
</testsuite>

```

Scenario: strict mode with --expand option, one feature, one scenario outline, four examples: one passing, one failing, one pending, one undefined

tags: @spawn,@spawn

When

I run `cucumber --strict --expand --format junit --out tmp/features/scenario_outline.feature` 🍌 (706ms)

Then

it should fail with exactly: 🍌 (000ms)

And

the junit output file "tmp/TEST-features-scenario_outline.xml" should contain: 🍌 (000ms)

```
<?xml version="1.0" encoding="UTF-8"?>
<testsuite failures="3" errors="0" skipped="0" tests="4" time="0.05"
name="Scenario outlines">
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | passes |)" time="0.05">
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | fails |)" time="0.05">
  <failure message="failed Using scenario outlines (outline example : | fails |)"
type="failed">
    <![CDATA[Scenario Outline: Using scenario outlines

Example row: | fails |

Message:
]]>
    <![CDATA[ (RuntimeError)
./features/step_definitions/steps.rb:4:in `/^this step fails$/'
features/scenario_outline.feature:9:in `Given this step fails'
features/scenario_outline.feature:4:in `Given this step <type>']]]>
  </failure>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | is pending |)" time="0.05">
  <failure message="pending Using scenario outlines (outline example : | is
pending |)" type="pending">
    <![CDATA[Scenario Outline: Using scenario outlines

Example row: | is pending |

Message:
]]>
    <![CDATA[TODO (Cucumber::Pending)
./features/step_definitions/steps.rb:3:in `/^this step is pending$/'
features/scenario_outline.feature:10:in `Given this step is pending'
```

```

features/scenario_outline.feature:4:in `Given this step <type>']]>
  </failure>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
<testcase classname="Scenario outlines" name="Using scenario outlines (outline
example : | is undefined |)" time="0.05">
  <failure message="undefined Using scenario outlines (outline example : | is
undefined |)" type="undefined">
    <![CDATA[Scenario Outline: Using scenario outlines

Example row: | is undefined |

Message:
]]>
    <![CDATA[Undefined step: "this step is undefined"
(Cucumber::Core::Test::Result::Undefined)
features/scenario_outline.feature:11:in `Given this step is undefined'
features/scenario_outline.feature:4:in `Given this step <type>']]>
  </failure>
  <system-out>
    <![CDATA[]]>
  </system-out>
  <system-err>
    <![CDATA[]]>
  </system-err>
</testcase>
</testsuite>

```

Language help

It's possible to ask cucumber which keywords are used for any particular language by running:

```
cucumber --i18n <language code> help
```

This will print a table showing all the different words we use for that language, to allow you to easily write features in any language you choose.

Scenario: Get help for Portuguese language

tags: @needs-many-fonts,@needs-many-fonts

When

I run `cucumber --i18n pt help` 🍌 (007ms)

Then

it should pass with: 🍌 (000ms)

```
| feature          | "Funcionalidade", "Característica", "Caracteristica"
|
| background      | "Contexto", "Cenário de Fundo", "Cenario de Fundo",
"Fundo"
|
| scenario        | "Cenário", "Cenario"
|
| scenario_outline | "Esquema do Cenário", "Esquema do Cenario", "Delinea
ção do Cenário", "Delineacao do Cenario"
|
| examples        | "Exemplos", "Cenários", "Cenarios"
|
| given           | "* ", "Dado ", "Dada ", "Dados ", "Dadas "
|
| when            | "* ", "Quando "
|
| then            | "* ", "Então ", "Entao "
|
| and             | "* ", "E "
|
| but             | "* ", "Mas "
|
| given (code)    | "Dado", "Dada", "Dados", "Dadas"
|
| when (code)     | "Quando"
|
| then (code)     | "Então", "Entao"
|
| and (code)      | "E"
|
| but (code)      | "Mas"
|
```

Scenario: List languages

tags: @needs-many-fonts,@needs-many-fonts

When

I run `cucumber --i18n help` 🍌 (006ms)

Then

cucumber lists all the supported languages 🍌 (001ms)

List step defs as json

In order to build tools on top of Cucumber

As a tool developer

I want to be able to query a features directory for all the step definitions it contains

Background

tags: @spawn

Given

a directory named "features" 🍌 (000ms)

Scenario: Two Ruby step definitions, in the same file

tags: @spawn,@spawn

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given(/foo/i) { }  
Given(/b.r/xm) { }
```

When

I run the following Ruby code: 🍌 (610ms)

```
require 'cucumber'  
puts Cucumber::StepDefinitions.new.to_json
```

Then

it should pass with JSON: 🍌 (000ms)

```
[  
  {"source": "foo", "flags": "i"},  
  {"source": "b.r", "flags": "mx"}  
]
```

Scenario: Non-default directory structure

tags: @spawn,@spawn

Given

a file named "my_weird/place/steps.rb" with: 🍌 (000ms)

```
Given(/foo/) { }  
Given(/b.r/x) { }
```

When

I run the following Ruby code: 🍌 (608ms)

```
require 'cucumber'  
puts Cucumber::StepDefinitions.new(:autoload_code_paths => ['my_weird']).to_json
```

Then

it should pass with JSON: 🍌 (001ms)

```
[  
  {"source": "foo", "flags": ""},  
  {"source": "b.r", "flags": "x"}  
]
```

Loading the steps users expect

As a User

In order to run features in subdirectories without having to pass extra options

I want cucumber to load all step files

Given

a file named "features/nesting/test.feature" with: 🍌 (000ms)

```
Feature: Feature in Subdirectory
  Scenario: A step not in the subdirectory
    Given not found in subdirectory
```

And

a file named "features/step_definitions/steps_no_in_subdirectory.rb" with: 🍌 (000ms)

```
Given(/^not found in subdirectory$/) { }
```

When

I run `cucumber -q features/nesting/test.feature` 🍌 (006ms)

Then

it should pass with: 🍌 (000ms)

```
Feature: Feature in Subdirectory

  Scenario: A step not in the subdirectory
    Given not found in subdirectory

1 scenario (1 passed)
1 step (1 passed)
```

Nested Steps

Background

Given

a scenario with a step that looks like this: 🍌 (000ms)

```
Given two turtles
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /a turtle/ do
  puts "turtle!"
end
```

Scenario: Use #steps to call several steps at once

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  steps %{
    Given a turtle
    And a turtle
  }
end
```

When

I run the feature with the progress formatter 🍌 (012ms)

Then

the output should contain: 🍌 (000ms)

```
turtle!

turtle!
```

Scenario: Use #step to call a single step

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  step "a turtle"
  step "a turtle"
end
```

When

I run the feature with the progress formatter 🍌 (007ms)

Then

the output should contain: 🍌 (000ms)

```
turtle!

turtle!
```

Scenario: Use #steps to call a table

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /turtles:/ do |table|
  table.hashes.each do |row|
    puts row[:name]
  end
end
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  steps %{
    Given turtles:
      | name      |
      | Sturm     |
      | Liouville |
  }
end
```

When

I run the feature with the progress formatter 🍌 (008ms)

Then

the output should contain: 🍌 (000ms)

Sturm

Liouville

Scenario: Use #steps to call a multi-line string

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  steps %Q{
    Given turtles:
      ""
      Sturm
      Liouville
      ""
  }
end
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /turtles:/ do |string|
  puts string
end
```

When

I run the feature with the progress formatter 🍌 (007ms)

Then

the output should contain: 🍌 (000ms)

```
Sturm
Liouville
```

Scenario: Backtrace doesn't skip nested steps

tags: @spawn

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  step "I have a couple turtles"
end

When(/I have a couple turtles/) { raise 'error' }
```

When

I run the feature with the progress formatter 🍌 (607ms)

Then

it should fail with: 🍌 (001ms)

```
error (RuntimeError)
./features/step_definitions/steps2.rb:5:in `/I have a couple turtles/'
./features/step_definitions/steps2.rb:2:in `/two turtles/'
features/test_feature_1.feature:3:in `Given two turtles'

Failing Scenarios:
cucumber features/test_feature_1.feature:2 # Scenario: Test Scenario 1

1 scenario (1 failed)
1 step (1 failed)
```

Scenario: Undefined nested step

Given

a file named "features/call_undefined_step_from_step_def.feature" with: 🍌 (000ms)

```
Feature: Calling undefined step

  Scenario: Call directly
    Given a step that calls an undefined step

  Scenario: Call via another
    Given a step that calls a step that calls an undefined step
```

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given /^a step that calls an undefined step$/ do
  step 'this does not exist'
end
```

```
Given /^a step that calls a step that calls an undefined step$/ do
  step 'a step that calls an undefined step'
end
```

When

I run `cucumber -q features/call_undefined_step_from_step_def.feature` 🍷 (032ms)

Then

it should fail with exactly: 🍷 (000ms)

Feature: Calling undefined step

Scenario: Call directly

Given a step that calls an undefined step

Undefined dynamic step: "this does not exist"

(Cucumber::UndefinedDynamicStep)

./features/step_definitions/steps.rb:2:in `/^a step that calls an undefined step\$/`

features/call_undefined_step_from_step_def.feature:4:in `Given a step that calls an undefined step`

Scenario: Call via another

Given a step that calls a step that calls an undefined step

Undefined dynamic step: "this does not exist"

(Cucumber::UndefinedDynamicStep)

./features/step_definitions/steps.rb:2:in `/^a step that calls an undefined step\$/`

./features/step_definitions/steps.rb:6:in `/^a step that calls a step that calls an undefined step\$/`

features/call_undefined_step_from_step_def.feature:7:in `Given a step that calls a step that calls an undefined step`

Failing Scenarios:

cucumber features/call_undefined_step_from_step_def.feature:3

cucumber features/call_undefined_step_from_step_def.feature:6

2 scenarios (2 failed)

2 steps (2 failed)

Nested Steps in I18n

Background

Given

a scenario with a step that looks like this in japanese: 🍌 (000ms)

```
前提 two turtles
```

And

a step definition that looks like this: 🍌 (000ms)

```
# -*- coding: utf-8 -*-  
前提 /a turtle/ do  
  puts "turtle!"  
end
```

Scenario: Use #steps to call several steps at once

Given

a step definition that looks like this: 🍌 (000ms)

```
# -*- coding: utf-8 -*-  
前提 /two turtles/ do  
  steps %{\br/>    前提 a turtle  
    かつ a turtle  
  }  
end
```

When

I run the feature with the progress formatter 🍌 (013ms)

Then

the output should contain: 🍌 (000ms)

```
turtle!  
  
turtle!
```

Nested Steps with either table or doc string

Background

Given

a scenario with a step that looks like this: 🍌 (000ms)

```
Given two turtles
```

Scenario: Use #step with table

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /turtles:/ do |table|
  table.hashes.each do |row|
    puts row[:name]
  end
end
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  step %{turtles:}, table(%{
    | name      |
    | Sturm     |
    | Liouville |
  })
end
```

When

I run the feature with the progress formatter 🍌 (010ms)

Then

the output should contain: 🍌 (000ms)

```
Sturm
```

```
Liouville
```

Scenario: Use #step with docstring

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  step %{turtles:}, "Sturm and Lioville"
end
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /turtles:/ do |text|
  puts text
end
```

When

I run the feature with the progress formatter 🍌 (009ms)

Then

the output should contain: 🍌 (002ms)

```
Sturm and Lioville
```

Scenario: Use #step with docstring and content-type

Given

a step definition that looks like this: 🍌 (000ms)

```
Given /two turtles/ do
  step %{turtles:}, doc_string('Sturm and Lioville','math')
end
```

And

a step definition that looks like this: 🍌 (000ms)

```
Given /turtles:/ do |text|
  puts text.content_type
end
```

When

I run the feature with the progress formatter 🍌 (008ms)

Then

the output should contain: 🍌 (000ms)

```
math
```

One line step definitions

Everybody knows you can do step definitions in Cucumber
but did you know you can do this?

Scenario: Call a method in World directly from a step def

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
module Driver
  def do_action
    @done = true
  end

  def assert_done
    expect(@done).to be true
  end
end
World(Driver)

When /I do the action/, :do_action
Then /The action should be done/, :assert_done
```

And

a file named "features/action.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    When I do the action
    Then the action should be done
```

When

I run **cucumber** 🍌 (008ms)

Then

it should pass 🍌 (000ms)

Scenario: Call a method on an actor in the World directly from a step def

Given

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
class Thing
  def do_action
    @done = true
  end

  def assert_done
    expect(@done).to be true
  end
end

module Driver
  def thing
    @thing ||= Thing.new
  end
end
World(Driver)

When /I do the action to the thing/, :do_action, :on => lambda { thing }
Then /The thing should be done/, :assert_done, :on => lambda { thing }
```

And

a file named "features/action.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    When I do the action to the thing
    Then the thing should be done
```

When

I run **cucumber** 🍌 (008ms)

Then

it should pass 🍌 (000ms)

[[Post-Configuration-Hook-[#423], Post Configuration Hook [#423]]] === **Post Configuration Hook [#423]**

In order to extend Cucumber

As a developer

I want to manipulate the Cucumber configuration after it has been created

Scenario: Using options directly gets a deprecation warning

tags: @spawn,@wip-jruby

Given

a file named "features/support/env.rb" with: 🍌 (000ms)

```
AfterConfiguration do |config|
  config.options[:blah]
end
```

When

I run **cucumber features** 🍌 (605ms)

Then

the stderr should contain: 🍌 (000ms)

Deprecated

Scenario: Changing the output format

Given

a file named "features/support/env.rb" with: 🍌 (000ms)

```
AfterConfiguration do |config|
  config.formats << ['html', config.out_stream]
end
```

When

I run **cucumber features** 🍌 (016ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

the output should contain: 🍌 (008ms)

html

Scenario: feature directories read from configuration

Given

a file named "features/support/env.rb" with: 🍌 (000ms)

```
AfterConfiguration do |config|
  config.out_stream << "AfterConfiguration hook read feature directories:
#{config.feature_dirs.join(', ')}"
end
```

When

I run `cucumber features` 🍌 (006ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

the output should contain: 🍌 (000ms)

```
AfterConfiguration hook read feature directories: features
```

Pretty formatter - Printing messages

When you want to print to Cucumber's output, just call `puts` from a step definition. Cucumber will grab the output and print it via the formatter that you're using.

Your message will be printed out after the step has run.

Background

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/step_definitions/puts_steps.rb" with: 🍌 (000ms)

```

Given /^I use puts with text "(.*)"/ do |ann|
  puts(ann)
end

Given /^I use multiple putss$/ do
  puts("Multiple")
  puts("Announce", "Me")
end

Given /^I use message (.+) in line (.+) (?:with result (.+))$/ do |ann, line,
result|
  puts("Last message") if line == "3"
  puts("Line: #{line}: #{ann}")
  fail if result =~ /fail/i
end

Given /^I use puts and step fails$/ do
  puts("Announce with fail")
  fail
end

Given /^I puts the world$/ do
  puts(self)
end

```

And

a file named "features/f.feature" with: 🍌 (000ms)

Feature:

Scenario:

Given I use puts with text "Ann"
And this step passes

Scenario:

Given I use multiple putss
And this step passes

Scenario Outline:

Given I use message <ann> in line <line>

Examples:

line	ann	
1	anno1	
2	anno2	
3	anno3	

Scenario:

Given I use puts and step fails
And this step passes

Scenario Outline:

Given I use message <ann> in line <line> with result <result>

Examples:

line	ann	result
1	anno1	fail
2	anno2	pass

And

a file named "features/puts_world.feature" with: 🍌 (000ms)

Feature: puts_world

Scenario: puts_world

Given I puts the world

Scenario: Delayed messages feature

tags: @spawn

When

I run `cucumber --quiet --format pretty features/f.feature` 🍌 (505ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

the output should contain: 🍌 (000ms)

Feature:

Scenario:

Given I use puts with text "Ann"

Ann

And this step passes

Scenario:

Given I use multiple putss

Multiple

Announce

Me

And this step passes

Scenario Outline:

Given I use message <ann> in line <line>

Examples:

line	ann	
1	anno1	
2	anno2	
3	anno3	

Scenario:

Given I use puts and step fails

Announce with fail

(RuntimeError)

./features/step_definitions/puts_steps.rb:18:in `/^I use puts and step fails\$/'

features/f.feature:21:in `Given I use puts and step fails'

And this step passes

Scenario Outline:

Given I use message <ann> in line <line> with result <result>

Examples:

line	ann	result
1	anno1	fail

Line: 1: anno1
(RuntimeError)

./features/step_definitions/puts_steps.rb:13:in `/^I use message (.+) in line (.+) (?::with result (.+))\$/'

features/f.feature:29:in `Given I use message anno1 in line 1 with result fail'

features/f.feature:25:in `Given I use message <ann> in line <line> with result <result>'

2	anno2	pass
---	-------	------

Line: 2: anno2

Scenario: Non-delayed messages feature (progress formatter)

When

I run `cucumber --format progress features/f.feature` 🍌 (040ms)

Then

the output should contain: 🍌 (000ms)

```
Ann
..
Multiple

Announce

Me
..UUU
Announce with fail
F-
Line: 1: anno1
F
Line: 2: anno2
.
```

Pretty output formatter

Background

Given

a file named "features/scenario_outline_with_undefined_steps.feature" with: 🍌 (000ms)

```
Feature:

  Scenario Outline:
    Given this step is undefined

  Examples:
    |foo|
    |bar|
```

Scenario: an scenario outline, one undefined step, one random example, expand flag on

When

I run `cucumber features/scenario_outline_with_undefined_steps.feature --format pretty --expand` 🍌 (017ms)

Then

it should pass 🍌 (000ms)

Scenario: when using a profile the output should include 'Using the default profile...'

And

a file named "cucumber.yml" with: 🍌 (000ms)

```
default: -r features
```

When

I run `cucumber --profile default --format pretty` 🍌 (018ms)

Then

it should pass 🍌 (000ms)

And

the output should contain: 🍌 (000ms)

```
Using the default profile...
```

Scenario: Hook output should be printed before hook exception

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature:
  Scenario:
    Given this step passes
```

And

a file named "features/step_definitions/output_steps.rb" with: 🍌 (000ms)

```
Before do
  puts "Before hook"
end

AfterStep do
  puts "AfterStep hook"
end

After do
  puts "After hook"
  raise "error"
end
```

When

I run `cucumber -q -f pretty features/test.feature` 🍌 (015ms)

Then

the stderr should not contain anything 🍌 (000ms)

Then

it should fail with: 🍌 (000ms)

Feature:

Scenario:

Before hook

Given this step passes

AfterStep hook

After hook

error (RuntimeError)

./features/step_definitions/output_steps.rb:11:in `After'

Failing Scenarios:

cucumber features/test.feature:2

1 scenario (1 failed)

1 step (1 passed)

Profiles

In order to save time and prevent carpal tunnel syndrome
Cucumber users can save and reuse commonly used cucumber flags in a 'cucumber.yml' file.
These named arguments are called profiles and the yml file should be in the root of your project.

Any cucumber argument is valid in a profile. To see all the available flags type 'cucumber --help'

For more information about profiles please see the wiki:

<http://wiki.github.com/cucumber/cucumber/cucumber.yml>

Background

Background: Basic App

Given

a file named "features/sample.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: this is a test

Given this step raises an error

And

an empty file named "features/support/env.rb" 🍌 (000ms)

And

an empty file named "features/support/super_env.rb" 🍌 (000ms)

And

the following profiles are defined: 🍌 (000ms)

default: features/sample.feature --require features/support/env.rb -v

super: features/sample.feature --require features/support/super_env.rb -v

Scenario: Explicitly defining a profile to run

When

I run `cucumber features/sample.feature --profile super` 🍌 (014ms)

Then

the output should contain: 🍌 (000ms)

Using the super profile...

And

exactly these files should be loaded: `features/support/super_env.rb` 🍌 (000ms)

Scenario: Explicitly defining a profile defined in an ERB formatted file

Given

the following profiles are defined: 🍌 (000ms)

```
<% requires = "--require features/support/super_env.rb" %>
super: <%= "features/sample.feature #{requires} -v" %>
```

When

I run `cucumber features/sample.feature --profile super` 🍌 (013ms)

Then

the output should contain: 🍌 (000ms)

Using the super profile...

And

exactly these files should be loaded: `features/support/super_env.rb` 🍌 (000ms)

Scenario: Defining multiple profiles to run

When

I run `cucumber features/sample.feature --profile default --profile super` 🍌 (013ms)

Then

the output should contain: 🍌 (000ms)

```
Using the default and super profiles...
```

And

exactly these files should be loaded: features/support/env.rb,
features/support/super_env.rb 🍌 (000ms)

Scenario: Arguments passed in but no profile specified

When

I run `cucumber -v` 🍌 (009ms)

Then

the default profile should be used 🍌 (000ms)

And

exactly these files should be loaded: features/support/env.rb 🍌 (000ms)

Scenario: Trying to use a missing profile

When

I run `cucumber -p foo` 🍌 (004ms)

Then

the stderr should contain: 🍌 (000ms)

```
Could not find profile: 'foo'
```

```
Defined profiles in cucumber.yml:
```

- * default
- * super

Scenario Outline: Disabling the default profile

When

I run `cucumber -v features/ -P` 🍌 (006ms)

Then

the output should contain: 🍌 (000ms)

Disabling profiles...

And

exactly these files should be loaded: features/support/env.rb,
features/support/super_env.rb 🍌 (000ms)

Scenario Outline: Disabling the default profile

When

I run `cucumber -v features/ --no-profile` 🍌 (006ms)

Then

the output should contain: 🍌 (000ms)

Disabling profiles...

And

exactly these files should be loaded: features/support/env.rb,
features/support/super_env.rb 🍌 (000ms)

Scenario: Overriding the profile's features to run

Given

a file named "features/another.feature" with: 🍌 (000ms)

Feature: Just this one should be ran

When

I run `cucumber -p default features/another.feature` 🍌 (007ms)

Then

exactly these features should be ran: features/another.feature 🍌 (000ms)

Scenario: Overriding the profile's formatter

You will most likely want to define a formatter in your default formatter. However, you often want to run your features with a different formatter yet still use the other the other arguments in the profile. Cucumber will allow you to do this by giving precedence to the formatter specified on the command line and override the one in the profile.

Given

the following profiles are defined: 🍌 (000ms)

```
default: features/sample.feature --require features/support/env.rb -v --format
profile
```

When

I run `cucumber features --format pretty` 🍌 (008ms)

Then

the output should contain: 🍌 (000ms)

```
Feature: Sample
```

Scenario Outline: Showing profiles when listing failing scenarios

Given

the standard step definitions 🍌 (000ms)

When

I run `cucumber -q -p super -p default -f pretty features/sample.feature --require features/step_definitions/steps.rb` 🍌 (015ms)

Then

it should fail with: 🍌 (000ms)

```
cucumber -p super features/sample.feature:2
```

Scenario Outline: Showing profiles when listing failing scenarios

Given

the standard step definitions 🍌 (000ms)

When

I run `cucumber -q -p super -p default -f progress features/sample.feature --require features/step_definitions/steps.rb` 🍌 (016ms)

Then

it should fail with: 🍌 (000ms)

```
cucumber -p super features/sample.feature:2
```

Progress output formatter

Background

Given

a file named "features/scenario_outline_with_undefined_steps.feature" with: 🍌 (000ms)

Feature:

Scenario Outline:

Given this step is undefined

Examples:

|foo|

|bar|

Scenario: an scenario outline, one undefined step, one random example, expand flag on

When

I run ``cucumber features/scenario_outline_with_undefined_steps.feature --format progress --expand`` 🍌 (009ms)

Then

it should pass 🍌 (000ms)

Scenario: when using a profile the output should include 'Using the default profile...'

And

a file named "cucumber.yml" with: 🍌 (000ms)

```
default: -r features
```

When

I run `cucumber --profile default --format progress` 🍌 (012ms)

Then

it should pass 🍌 (000ms)

And

the output should contain: 🍌 (000ms)

```
Using the default profile...
```

Rake task

In order to ease the development process
As a developer and CI server administrator
Cucumber features should be executable via Rake

Background

tags: @spawn

And

a file named "features/missing_step_definitions.feature" with: 🍌 (000ms)

```
Feature: Sample
```

```
  Scenario: Wanted
```

```
    Given I want to run this
```

```
  Scenario: Unwanted
```

```
    Given I don't want this ran
```

Scenario: rake task with a defined profile

tags: @spawn,@spawn

Given

the following profile is defined: 🍌 (000ms)

```
foo: --quiet --no-color features/missing_step_definitions.feature:3
```

And

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'

Cucumber::Rake::Task.new do |t|
  t.profile = "foo"
end
```

When

I run `rake cucumber` 🍌 (01s 206ms)

Then

it should pass with: 🍌 (000ms)

Feature: Sample

Scenario: Wanted

Given I want to run this

1 scenario (1 undefined)

1 step (1 undefined)

Scenario: rake task without a profile

tags: @spawn,@spawn

Given

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'

Cucumber::Rake::Task.new do |t|
  t.cucumber_opts = %w{--quiet --no-color}
end
```

When

I run `rake cucumber` 🍌 (01s 207ms)

Then

it should pass with: 🍌 (000ms)

```
Feature: Sample

  Scenario: Wanted
    Given I want to run this

  Scenario: Unwanted
    Given I don't want this ran

2 scenarios (2 undefined)
2 steps (2 undefined)
```

Scenario: rake task with a defined profile and cucumber_opts

tags: @spawn,@spawn

Given

the following profile is defined: 🍌 (000ms)

```
bar: ['features/missing_step_definitions.feature:3']
```

And

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'

Cucumber::Rake::Task.new do |t|
  t.profile = "bar"
  t.cucumber_opts = %w{--quiet --no-color}
end
```

When

I run `rake cucumber` 🍌 (01s 207ms)

Then

it should pass with: 🍌 (000ms)

Feature: Sample

Scenario: Wanted

Given I want to run this

1 scenario (1 undefined)

1 step (1 undefined)

Scenario: respect requires

tags: @spawn,@spawn

Given

an empty file named "features/support/env.rb" 🍌 (000ms)

And

an empty file named "features/support/dont_require_me.rb" 🍌 (000ms)

And

the following profile is defined: 🍌 (000ms)

```
no_bomb: features/missing_step_definitions.feature:3 --require
features/support/env.rb --verbose
```

And

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'

Cucumber::Rake::Task.new do |t|
  t.profile = "no_bomb"
  t.cucumber_opts = %w{--quiet --no-color}
end
```

When

I run `rake cucumber` 🍌 (01s 106ms)

Then

it should pass 🍌 (000ms)

And

the output should not contain: 🍌 (000ms)

```
* features/support/dont_require_me.rb
```

Scenario: feature files with spaces

tags: @spawn,@spawn

Given

a file named "features/spaces are nasty.feature" with: 🍌 (000ms)

Feature: The futures green

Scenario: Orange

Given this is missing

And

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'
```

```
Cucumber::Rake::Task.new do |t|  
  t.cucumber_opts = %w{--quiet --no-color}  
end
```

When

I run `rake cucumber` 🍌 (01s 108ms)

Then

it should pass with: 🍌 (001ms)

Feature: The futures green

Scenario: Orange

Given this is missing

Raketask

In order to use cucumber's rake task

As a Cuker

I do not want to see rake's backtraces when it fails

Also I want to get zero exit status code on failures

And non-zero exit status code when it passes

Background

tags: @spawn

Given

the standard step definitions 🍌 (000ms)

Given

a file named "features/passing_and_failing.feature" with: 🍌 (000ms)

Feature: Sample

Scenario: Passing

Given this step passes

Scenario: Failing

Given this step raises an error

Given

a file named "Rakefile" with: 🍌 (000ms)

```
require 'cucumber/rake/task'

SAMPLE_FEATURE_FILE = 'features/passing_and_failing.feature'

Cucumber::Rake::Task.new(:pass) do |t|
  t.cucumber_opts = "#{SAMPLE_FEATURE_FILE}:3"
end

Cucumber::Rake::Task.new(:fail) do |t|
  t.cucumber_opts = "#{SAMPLE_FEATURE_FILE}:6"
end
```

Scenario: Passing feature

tags: @spawn,@spawn

When

I run **bundle exec rake pass** 🍌 (01s 608ms)

Then

the exit status should be 0 🍌 (000ms)

Scenario: Failing feature

tags: @spawn,@spawn

When

I run `bundle exec rake fail` 🍷 (02s 210ms)

Then

the exit status should be 1 🍷 (000ms)

But

the output should not contain "rake aborted!" 🍷 (000ms)

Randomize

Use the `--order random` switch to run scenarios in random order.

This is especially helpful for detecting situations where you have state leaking between scenarios, which can cause flickering or fragile tests.

If you do find a random run that exposes dependencies between your tests, you can reproduce that run by using the seed that's printed at the end of the test run.

Background

Given

a file named "features/bad_practice.feature" with: 🍌 (000ms)

Feature: Bad practice

Scenario: Set state

Given I set some state

Scenario: Depend on state

When I depend on the state

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given(/^I set some state$/) do
  $global_state = "set"
end
```

```
Given(/^I depend on the state$/) do
  raise "I expect the state to be set!" unless $global_state == "set"
end
```

Scenario: Run scenarios in order

When

I run `cucumber` 🍌 (006ms)

Then

it should pass 🍌 (000ms)

Scenario: Run scenarios randomized

tags: @spawn

When

I run `cucumber --order random:41515` 🍴 (705ms)

Then

it should fail 🍴 (000ms)

And

the stdout should contain: 🍴 (000ms)

Randomized with seed 41515

Requiring extra step files

Cucumber allows you to require extra files using the `-r` option.

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature: Sample
  Scenario: Sample
    Given found in extra file
```

And

a file named "tmp/extras.rb" with: 🍌 (000ms)

```
Given(/^found in extra file$/) { }
```

When

I run `cucumber -q -r tmp/extras.rb features/test.feature` 🍌 (011ms)

Then

it should pass with: 🍌 (000ms)

```
Feature: Sample

  Scenario: Sample
    Given found in extra file

1 scenario (1 passed)
1 step (1 passed)
```

Rerun formatter

The rerun formatter writes an output that's perfect for passing to Cucumber when you want to rerun only the scenarios that prevented the exit code to be zero.

You can save off the rerun output to a file by using it like this:

```
cucumber -f rerun --out .cucumber.rerun
```

Now you can pass that file's content to Cucumber to tell it which scenarios to run:

```
cucumber \"cat .cucumber.rerun\"
```

This is useful when debugging in a large suite of features.

Background

Given

the standard step definitions 🍌 (000ms)

Scenario: Exit code is zero

Given

a file named "features/mixed.feature" with: 🍌 (000ms)

Feature: Mixed

Scenario:

Given this step is undefined

Scenario:

Given this step is pending

Scenario:

Given this step passes

When

I run `cucumber -f rerun` 🍌 (013ms)

Then

it should pass with exactly: 🍌 (000ms)

Scenario: Exit code is zero in the dry-run mode

Given

a file named "features/mixed.feature" with: 🍌 (000ms)

Feature: Mixed

Scenario:

Given this step fails

Scenario:

Given this step is undefined

Scenario:

Given this step is pending

Scenario:

Given this step passes

And

a file named "features/all_good.feature" with: 🍌 (000ms)

Feature: All good

Scenario:

Given this step passes

When

I run `cucumber -f rerun --dry-run` 🍌 (016ms)

Then

it should pass with exactly: 🍌 (000ms)

Scenario: Exit code is not zero, regular scenario

Given

a file named "features/mixed.feature" with: 🍌 (000ms)

Feature: Mixed

Scenario:

Given this step fails

Scenario:

Given this step is undefined

Scenario:

Given this step is pending

Scenario:

Given this step passes

And

a file named "features/all_good.feature" with: 🍌 (000ms)

Feature: All good

Scenario:

Given this step passes

When

I run `cucumber -f rerun --strict` 🍌 (016ms)

Then

it should fail with exactly: 🍌 (000ms)

features/mixed.feature:3:6:9

Scenario: Exit code is not zero, scenario outlines

For details see <https://github.com/cucumber/cucumber/issues/57>

Given

a file named "features/one_passing_one_failing.feature" with: 🍌 (000ms)

Feature: One passing example, one failing example

Scenario Outline:

Given this step <status>

Examples:

	status	
	passes	
	fails	

When

I run `cucumber -f rerun` 🍌 (010ms)

Then

it should fail with: 🍌 (000ms)

features/one_passing_one_failing.feature:9

Scenario: Exit code is not zero, failing background

Given

a file named "features/failing_background.feature" with: 🍌 (000ms)

Feature: Failing background sample

Background:

Given this step fails

Scenario: failing background

Then this step passes

Scenario: another failing background

Then this step passes

When

I run `cucumber -f rerun` 🍌 (012ms)

Then

it should fail with: 🍌 (000ms)

features/failing_background.feature:6:9

Scenario: Exit code is not zero, failing background with scenario outline

Given

a file named "features/failing_background_outline.feature" with: 🍌 (000ms)

Feature: Failing background sample with scenario outline

Background:

Given this step fails

Scenario Outline:

Then this step <status>

Examples:

	status	
	passes	
	passes	

When

I run `cucumber features/failing_background_outline.feature -r features -f rerun` 🍌
(011ms)

Then

it should fail with: 🍌 (000ms)

features/failing_background_outline.feature:11:12

Scenario: Exit code is not zero, scenario outlines with expand

For details see <https://github.com/cucumber/cucumber/issues/503>

Given

a file named "features/one_passing_one_failing.feature" with: 🍌 (000ms)

Feature: One passing example, one failing example

Scenario Outline:

Given this step <status>

Examples:

	status	
	passes	
	fails	

When

I run `cucumber --expand -f rerun` 🍌 (012ms)

Then

it should fail with: 🍌 (000ms)

features/one_passing_one_failing.feature:9

Run Cli::Main with existing Runtime

This is the API that Spork uses. It creates an existing runtime then calls `load_programming_language('rb')` on it to load the RbDsl. When the process forks, Spork then passes the runtime to `Cli::Main` to run it.

Scenario: Run a single feature

tags: @spawn,@spawn

Given

the standard step definitions 🍌 (000ms)

Given

a file named "features/success.feature" with: 🍌 (000ms)

Feature:
Scenario:
Given this step passes

When

I run the following Ruby code: 🍌 (607ms)

```
require 'cucumber'  
runtime = Cucumber::Runtime.new  
runtime.load_programming_language('rb')  
Cucumber::Cli::Main.new([]).execute!(runtime)
```

Then

it should pass 🍌 (000ms)

And

the output should contain: 🍌 (005ms)

Given this step passes

[[Run-feature-elements-matching-a-name-with---name/-n, Run feature elements matching a name with --name/-n]] == **Run feature elements matching a name with --name/-n**

The **--name NAME** option runs only scenarios which match a certain name. The NAME can be a substring of the names of Features, Scenarios, Scenario Outlines or Example blocks.

Background

Given

a file named "features/first.feature" with: 🍌 (000ms)

```
Feature: first feature
  Scenario: foo first
    Given missing
  Scenario: bar first
    Given missing
```

Given

a file named "features/second.feature" with: 🍌 (000ms)

```
Feature: second
  Scenario: foo second
    Given missing
  Scenario: bar second
    Given missing
```

Given

a file named "features/outline.feature" with: 🍌 (000ms)

```
Feature: outline
  Scenario Outline: baz outline
    Given outline step <name>

    Examples: quux example
      | name |
      | a   |
      | b   |
```

Scenario: Matching Feature names

When

I run `cucumber -q --name feature` 🍌 (012ms)

Then

it should pass with: 🍌 (000ms)

Feature: first feature

Scenario: foo first
Given missing

Scenario: bar first
Given missing

2 scenarios (2 undefined)
2 steps (2 undefined)

Scenario: Matching Scenario names

When

I run `cucumber -q --name foo` 🍌 (011ms)

Then

it should pass with: 🍌 (000ms)

Feature: first feature

Scenario: foo first
Given missing

Feature: second

Scenario: foo second
Given missing

2 scenarios (2 undefined)
2 steps (2 undefined)

Scenario: Matching Scenario Outline names

When

I run `cucumber -q --name baz` 🍌 (012ms)

Then

it should pass with: 🍌 (000ms)

Feature: outline

Scenario Outline: baz outline

Given outline step <name>

Examples: quux example

	name	
	a	
	b	

2 scenarios (2 undefined)

2 steps (2 undefined)

Scenario: Matching Example block names

When

I run `cucumber -q --name quux` 🍌 (010ms)

Then

it should pass with: 🍌 (000ms)

Feature: outline

Scenario Outline: baz outline

Given outline step <name>

Examples: quux example

	name	
	a	
	b	

2 scenarios (2 undefined)

2 steps (2 undefined)

Run specific scenarios

You can choose to run a specific scenario using the file:line format, or you can pass in a file with a list of scenarios using @-notation.

The line number can fall anywhere within the body of a scenario, including steps, tags, comments, description, data tables or doc strings.

For scenario outlines, if the line hits one example row, just that one will be run. Otherwise all examples in the table or outline will be run.

Background

Given

the standard step definitions 🍌 (000ms)

Scenario: Two scenarios, run just one of them

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature:

Scenario: Miss

Given this step is undefined

Scenario: Hit

Given this step passes

When

I run `cucumber features/test.feature:7 --format pretty --quiet` 🍌 (008ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature:

Scenario: Hit

Given this step passes

1 scenario (1 passed)

1 step (1 passed)

Scenario: Use @-notation to specify a file containing feature file list

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature: Sample
  Scenario: Passing
    Given this step passes
```

And

a file named "list-of-features.txt" with: 🍌 (000ms)

```
features/test.feature:2
```

When

I run `cucumber -q @list-of-features.txt` 🍌 (006ms)

Then

it should pass with: 🍌 (000ms)

```
Feature: Sample

  Scenario: Passing
    Given this step passes

1 scenario (1 passed)
1 step (1 passed)
```

Scenario: Specify order of scenarios

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature:

Scenario:

Given this step passes

Scenario:

Given this step fails

When

I run `cucumber features/test.feature:5 features/test.feature:3 -f progress` 🍌 (009ms)

Then

it should fail with: 🍌 (000ms)

F.

Running multiple formatters

When running cucumber, you are able to using multiple different formatters and redirect the output to text files.

Two formatters cannot both print to the same file (or to STDOUT)

Background

tags: @spawn

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature: Lots of undefined

Scenario: Implement me

Given it snows in Sahara

Given it's 40 degrees in Norway

And it's 40 degrees in Norway

When I stop procrastinating

And there is world peace

Scenario: Multiple formatters and outputs

tags: @spawn,@spawn

When

I run `cucumber --no-color --format progress --out progress.txt --format pretty --out pretty.txt --no-source --dry-run --no-snippets features/test.feature` 🍌 (606ms)

Then

the stderr should not contain anything 🍌 (006ms)

Then

the file "progress.txt" should contain: 🍌 (000ms)

```
UUUUU
```

```
1 scenario (1 undefined)
5 steps (5 undefined)
```

And

the file "pretty.txt" should contain: 🍌 (000ms)

```
Feature: Lots of undefined
```

```
Scenario: Implement me
  Given it snows in Sahara
  Given it's 40 degrees in Norway
  And it's 40 degrees in Norway
  When I stop procrastinating
  And there is world peace
```

```
1 scenario (1 undefined)
5 steps (5 undefined)
```

Scenario: Two formatters to stdout

tags: @spawn,@spawn

When

I run `cucumber -f progress -f pretty features/test.feature` 🍌 (607ms)

Then

it should fail with: 🍌 (000ms)

All but one formatter must use `--out`, only one can print to each stream (or STDOUT) (RuntimeError)

Scenario: Two formatters to stdout when using a profile

tags: @spawn,@spawn

Given

the following profiles are defined: 🍌 (000ms)

default: -q

When

I run `cucumber -f progress -f pretty features/test.feature` 🍌 (606ms)

Then

it should fail with: 🍌 (000ms)

All but one formatter must use `--out`, only one can print to each stream (or STDOUT) (RuntimeError)

Scenario outlines

Copying and pasting scenarios to use different values quickly becomes tedious and repetitive. Scenario outlines allow us to more concisely express these examples through the use of a template with placeholders, using Scenario Outline, Examples with tables and < > delimited parameters.

The Scenario Outline steps provide a template which is never directly run. A Scenario Outline is run once for each row in the Examples section beneath it (not counting the first row).

The way this works is via placeholders. Placeholders must be contained within < > in the Scenario Outline's steps - see the examples below.

IMPORTANT: Your step definitions will never have to match a placeholder. They will need to match the values that will replace the placeholder.

Background

tags: @spawn

Given

a file named "features/outline_sample.feature" with: 🍌 (000ms)

Feature: Outline Sample

Scenario: I have no steps

Scenario Outline: Test state

Given <state> without a table

Given <other_state> without a table

Examples: Rainbow colours

state	other_state	
missing	passing	
passing	passing	
failing	passing	

Examples:Only passing

state	other_state	
passing	passing	

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given(/passing without a table$/)/ { }  
Given(/failing without a table$/)/ { raise RuntimeError }
```

Scenario: Run scenario outline with filtering on outline name

tags: @spawn,@spawn

When

I run `cucumber -q features/outline_sample.feature` 🍌 (706ms)

Then

it should fail with: 🍌 (001ms)

Feature: Outline Sample

Scenario: I have no steps

Scenario Outline: Test state

Given <state> without a table

Given <other_state> without a table

Examples: Rainbow colours

state	other_state	
missing	passing	
passing	passing	
failing	passing	

RuntimeError (RuntimeError)

./features/step_definitions/steps.rb:2:in `/^failing without a table\$/'

features/outline_sample.feature:12:in `Given failing without a table'

features/outline_sample.feature:6:in `Given <state> without a table'

Examples: Only passing

state	other_state	
passing	passing	

Failing Scenarios:

cucumber features/outline_sample.feature:12

5 scenarios (1 failed, 1 undefined, 3 passed)

8 steps (1 failed, 2 skipped, 1 undefined, 4 passed)

Scenario: Run scenario outline steps only

tags: @spawn,@spawn

When

I run `cucumber -q features/outline_sample.feature:7` 🍌 (607ms)

Then

it should fail with: 🍌 (000ms)

Feature: Outline Sample

Scenario Outline: Test state

Given <state> without a table

Given <other_state> without a table

Examples: Rainbow colours

state	other_state	
missing	passing	
passing	passing	
failing	passing	

RuntimeError (RuntimeError)

./features/step_definitions/steps.rb:2:in `/^failing without a table\$/'

features/outline_sample.feature:12:in `Given failing without a table'

features/outline_sample.feature:6:in `Given <state> without a table'

Examples: Only passing

state	other_state	
passing	passing	

Failing Scenarios:

cucumber features/outline_sample.feature:12

4 scenarios (1 failed, 1 undefined, 2 passed)

8 steps (1 failed, 2 skipped, 1 undefined, 4 passed)

Scenario: Run single failing scenario outline table row

tags: @spawn,@spawn

When

I run `cucumber -q features/outline_sample.feature:12` 🍌 (504ms)

Then

it should fail with: 🍌 (001ms)

Feature: Outline Sample

Scenario Outline: Test state

Given <state> without a table

Given <other_state> without a table

Examples: Rainbow colours

state	other_state
-------	-------------

failing	passing	
---------	---------	--

RuntimeError (RuntimeError)

./features/step_definitions/steps.rb:2:in `/^failing without a table\$/'

features/outline_sample.feature:12:in `Given failing without a table'

features/outline_sample.feature:6:in `Given <state> without a table'

Failing Scenarios:

cucumber features/outline_sample.feature:12

1 scenario (1 failed)

2 steps (1 failed, 1 skipped)

Scenario: Run all with progress formatter

tags: @spawn,@spawn

When

I run `cucumber -q --format progress features/outline_sample.feature` 🍌 (606ms)

Then

it should fail with exactly: 🍌 (000ms)

```
U-..F-..
```

```
(::) failed steps (::)
```

```
RuntimeError (RuntimeError)
```

```
./features/step_definitions/steps.rb:2:in `/^failing without a table$/'
```

```
features/outline_sample.feature:12:in `Given failing without a table'
```

```
features/outline_sample.feature:6:in `Given <state> without a table'
```

```
Failing Scenarios:
```

```
cucumber features/outline_sample.feature:12
```

```
5 scenarios (1 failed, 1 undefined, 3 passed)
```

```
8 steps (1 failed, 2 skipped, 1 undefined, 4 passed)
```

Scenario outlines `--expand` option

In order to make it easier to write certain editor plugins and also for some people to understand scenarios, Cucumber will expand examples in outlines if you add the `--expand` option when running them.

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature:

Scenario Outline:

Given the secret code is <code>

When I guess <guess>

Then I am <verdict>

Examples:

code	guess	verdict
blue	blue	right
red	blue	wrong

When

I run `cucumber -i -q --expand` 🍌 (013ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (000ms)

Feature:

Scenario Outline:

Given the secret code is <code>

When I guess <guess>

Then I am <verdict>

Examples:

Scenario: | blue | blue | right |
Given the secret code is blue
When I guess blue
Then I am right

Scenario: | red | blue | wrong |
Given the secret code is red
When I guess blue
Then I am wrong

2 scenarios (2 undefined)

6 steps (6 undefined)

Set up a default load path

When you're developing a gem, it's convenient if your project's `lib` directory is already in the load path. Cucumber does this for you.

Scenario: `./lib` is included in the `$LOAD_PATH`

Given

a file named "features/support/env.rb" with: 🍌 (000ms)

```
require 'something'
```

And

a file named "lib/something.rb" with: 🍌 (000ms)

```
class Something
end
```

When

I run `cucumber` 🍌 (009ms)

Then

it should pass 🍌 (000ms)

Showing differences to expected output

Cucumber will helpfully show you the expectation error that your testing library gives you, in the context of the failing scenario. When using RSpec, for example, this will show the difference between the expected and the actual output.

Scenario: Run single failing scenario with default diff enabled

Given

a file named "features/failing_expectation.feature" with: 🍌 (000ms)

Feature: Failing expectation

Scenario: Failing expectation
Given failing expectation

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given /^failing expectation$/ do x=1
  expect('this').to eq 'that'
end
```

When

I run `cucumber -q features/failing_expectation.feature` 🍌 (022ms)

Then

it should fail with: 🍌 (000ms)

Feature: Failing expectation

Scenario: Failing expectation
Given failing expectation

expected: "that"
got: "this"

(compared using ==)

(RSpec::Expectations::ExpectationNotMetError)

./features/step_definitions/steps.rb:2:in `/^failing expectation\$/'
features/failing_expectation.feature:4:in `Given failing expectation'

Failing Scenarios:

cucumber features/failing_expectation.feature:3

1 scenario (1 failed)

1 step (1 failed)

Skip Scenario

Scenario: With a passing step

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature: test
  Scenario: test
    Given this step says to skip
    And this step passes
```

And

the standard step definitions 🍌 (000ms)

And

a file named "features/step_definitions/skippy.rb" with: 🍌 (000ms)

```
Given /skip/ do
  skip_this_scenario
end
```

When

I run `cucumber -q` 🍌 (011ms)

Then

it should pass with exactly: 🍌 (000ms)

```
Feature: test

  Scenario: test
    Given this step says to skip
    And this step passes

1 scenario (1 skipped)
2 steps (2 skipped)
```

Scenario: Use legacy API from a hook

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
Feature: test
  Scenario: test
    Given this step passes
    And this step passes
```

And

the standard step definitions 🍌 (000ms)

And

a file named "features/support/hook.rb" with: 🍌 (000ms)

```
Before do |scenario|
  scenario.skip_invoke!
end
```

When

I run `cucumber -q` 🍌 (011ms)

Then

it should pass with: 🍌 (000ms)

```
Feature: test

  Scenario: test
    Given this step passes
    And this step passes

1 scenario (1 skipped)
2 steps (2 skipped)
```

Snippets

Cucumber helpfully prints out any undefined step definitions as a code snippet suggestion, which you can then paste into a step definitions file of your choosing.

Scenario: Snippet for undefined step with a pystring

Given

a file named "features/undefined_steps.feature" with: 🍌 (000ms)

```
Feature:
Scenario: pystring
  Given a pystring
    """
    example with <html> entities
    """
  When a simple when step
  And another when step
  Then a simple then step
```

When

I run `cucumber features/undefined_steps.feature -s` 🍌 (009ms)

Then

the output should contain: 🍌 (000ms)

```
Given(/^\s+pystring$/) do |string|
  pending # Write code here that turns the phrase above into concrete actions
end

When(/^\s+simple when step$/) do
  pending # Write code here that turns the phrase above into concrete actions
end

When(/^\s+another when step$/) do
  pending # Write code here that turns the phrase above into concrete actions
end

Then(/^\s+simple then step$/) do
  pending # Write code here that turns the phrase above into concrete actions
end
```

Scenario: Snippet for undefined step with a step table

Given

a file named "features/undefined_steps.feature" with: 🍌 (000ms)

```
Feature:  
Scenario: table  
  Given a table  
    | table |  
    |example|
```

When

I run `cucumber features/undefined_steps.feature -s` 🍌 (007ms)

Then

the output should contain: 🍌 (000ms)

```
Given(/^a table$/) do |table|  
  # table is a Cucumber::Core::Ast::DataTable  
  pending # Write code here that turns the phrase above into concrete actions  
end
```

Snippets message

If a step doesn't match, Cucumber will ask the wire server to return a snippet of code for a step definition.

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

Feature: High strung

Scenario: Wired

Given we're all wired

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

host: localhost

port: 54321

Scenario: Wire server returns snippets for a step that didn't match

tags: @wire,@wire,@spawn

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f pretty` 🍌 (908ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (001ms)

Feature: High strung

Scenario: Wired # features/wired.feature:2

Given we're all wired # features/wired.feature:3

1 scenario (1 undefined)

1 step (1 undefined)

And

the output should contain: 🍌 (000ms)

You can implement step definitions for undefined steps with these snippets:

```
foo()  
  bar;  
baz
```

State

You can pass state between step by setting instance variables, but those instance variables will be gone when the next scenario runs.

Scenario: Set an ivar in one scenario, use it in the next step

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature:

Scenario:

Given I have set @flag = true

Then @flag should be true

Scenario:

Then @flag should be nil

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given /set @flag/ do
  @flag = true
end
Then /flag should be true/ do
  expect(@flag).to be_truthy
end
Then /flag should be nil/ do
  expect(@flag).to be_nil
end
```

When

I run **cucumber** 🍌 (014ms)

Then

it should pass 🍌 (000ms)

Step matches message

When the features have been parsed, Cucumber will send a `step_matches` message to ask the wire server if it can match a step name. This happens for each of the steps in each of the features.

The wire server replies with an array of StepMatch objects.

When each StepMatch is returned, it contains the following data:

- * `id` - identifier for the step definition to be used later when it needs to be invoked. The identifier can be any string value and is simply used for the wire server's own reference.
- * `args` - any argument values as captured by the wire end's own regular expression (or other argument matching) process.

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

```
Feature: High strung
  Scenario: Wired
    Given we're all wired
```

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

```
host: localhost
port: 54321
```

Scenario: Dry run finds no step match

tags: @wire,@wire

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber --dry-run --no-snippets -f progress` 🍌 (061ms)

And

it should pass with: 🍌 (000ms)

U

1 scenario (1 undefined)

1 step (1 undefined)

Scenario: Dry run finds a step match

tags: @wire,@wire

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber --dry-run -f progress` 🍌 (024ms)

And

it should pass with: 🍌 (000ms)

-

1 scenario (1 skipped)

1 step (1 skipped)

Scenario: Step matches returns details about the remote step definition

tags: @wire,@wire

Optionally, the StepMatch can also contain a source reference, and a native regexp string which will be used by some formatters.

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (001ms)

When

I run `cucumber -f stepdefs --dry-run` 🍌 (015ms)

Then

it should pass with: 🍌 (000ms)

```
-  
  
we.*    # MyApp.MyClass:123  
  
1 scenario (1 skipped)  
1 step (1 skipped)
```

And

the stderr should not contain anything 🍌 (000ms)

Strict mode

Using the `--strict` flag will cause cucumber to fail unless all the step definitions have been defined.

Background

Given

a file named "features/missing.feature" with: 🍌 (000ms)

```
Feature: Missing  
  Scenario: Missing  
    Given this step passes
```

And

a file named "features/pending.feature" with: 🍌 (000ms)

```
Feature: Pending  
  Scenario: Pending  
    Given this step is pending
```


Scenario: Fail with --strict due to undefined step

When

I run `cucumber -q features/missing.feature --strict` 🍌 (016ms)

Then

it should fail with: 🍌 (000ms)

Feature: Missing

Scenario: Missing

Given this step passes

Undefined step: "this step passes" (Cucumber::Undefined)
features/missing.feature:3:in `Given this step passes'

1 scenario (1 undefined)

1 step (1 undefined)

Scenario: Fail with --strict due to pending step

Given

the standard step definitions 🍌 (000ms)

When

I run `cucumber -q features/pending.feature --strict` 🍌 (015ms)

Then

it should fail with: 🍌 (000ms)

Feature: Pending

Scenario: Pending

Given this step is pending

TODO (Cucumber::Pending)
./features/step_definitions/steps.rb:3:in `/^this step is pending\$/'
features/pending.feature:3:in `Given this step is pending'

1 scenario (1 pending)

1 step (1 pending)

Scenario: Succeed with --strict

Given

the standard step definitions 🍌 (000ms)

When

I run `cucumber -q features/missing.feature --strict` 🍌 (010ms)

Then

it should pass with: 🍌 (000ms)

Feature: Missing

Scenario: Missing

Given this step passes

1 scenario (1 passed)

1 step (1 passed)

Table diffing

To allow you to more easily compare data in tables, you are able to easily diff a table with expected data and see the diff in your output.

Scenario: Extra row

Given

a file named "features/tables.feature" with: 🍌 (000ms)

Feature: Tables

Scenario: Extra row

Then the table should be:

	x		y	
	a		b	

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```

Then /the table should be:/ do |expected| x=1
  expected.diff!(table(%{
    | x | y |
    | a | c |
  }))
end

```

When

I run `cucumber features/tables.feature` 🍷 (015ms)

Then

it should fail with exactly: 🍷 (000ms)

Feature: Tables

```

Scenario: Extra row          # features/tables.feature:2
  Then the table should be: # features/step_definitions/steps.rb:1
    | x | y |
    | a | b |
    Tables were not identical:

      |      x |      y |
      | (-) a | (-) b |
      | (+) a | (+) c |
    (Cucumber::MultilineArgument::DataTable::Different)
    ./features/step_definitions/steps.rb:2:in `/the table should be:/'
    features/tables.feature:3:in `Then the table should be:'

```

Failing Scenarios:

cucumber features/tables.feature:2 # Scenario: Extra row

1 scenario (1 failed)

1 step (1 failed)

0m0.012s

Tag logic

In order to conveniently run subsets of features

As a Cuker

I want to select features using logical AND/OR of tags

Background

Given

a file named "features/test.feature" with: 🍌 (000ms)

```
@feature
Feature: Sample

  @one @three
  Scenario: Example
    Given passing

  @one
  Scenario: Another Example
    Given passing

  @three
  Scenario: Yet another Example
    Given passing

  @ignore
  Scenario: And yet another Example
```

Scenario: ANDing tags

When

I run `cucumber -q -t @one -t @three features/test.feature` 🍌 (008ms)

Then

it should pass with: 🍌 (000ms)

```
@feature
Feature: Sample

  @one @three
  Scenario: Example
    Given passing

1 scenario (1 undefined)
1 step (1 undefined)
```

Scenario: ORing tags

When

I run `cucumber -q -t @one,@three features/test.feature` 🍌 (010ms)

Then

it should pass with: 🍌 (000ms)

```
@feature
Feature: Sample

  @one @three
  Scenario: Example
    Given passing

  @one
  Scenario: Another Example
    Given passing

  @three
  Scenario: Yet another Example
    Given passing

3 scenarios (3 undefined)
3 steps (3 undefined)
```

Scenario: Negative tags

When

I run `cucumber -q -t ~@three features/test.feature` 🍌 (008ms)

Then

it should pass with: 🍌 (000ms)

```
@feature
Feature: Sample

  @one
  Scenario: Another Example
    Given passing

  @ignore
  Scenario: And yet another Example

2 scenarios (1 undefined, 1 passed)
1 step (1 undefined)
```

Scenario: Run with limited tag count, blowing it on scenario

When

I run `cucumber -q --no-source --tags @one:1 features/test.feature` 🍌 (005ms)

Then

it fails before running features with: 🍌 (000ms)

```
@one occurred 2 times, but the limit was set to 1
features/test.feature:5
features/test.feature:9
```

Scenario: Run with limited tag count, blowing it via feature inheritance

When

I run `cucumber -q --no-source --tags @feature:1 features/test.feature` 🍌 (005ms)

Then

it fails before running features with: 🍌 (000ms)

```
@feature occurred 4 times, but the limit was set to 1
features/test.feature:5
features/test.feature:9
features/test.feature:13
features/test.feature:17
```

Scenario: Run with limited tag count using negative tag, blowing it via a tag that is not run

When

I run `cucumber -q --no-source --tags ~@one:1 features/test.feature` 🍌 (004ms)

Then

it fails before running features with: 🍌 (000ms)

```
@one occurred 2 times, but the limit was set to 1
```

Scenario: Limiting with tags which do not exist in the features

Originally added to check [Lighthouse bug

#464](<https://rspec.lighthouseapp.com/projects/16211/tickets/464>).

When

I run `cucumber -q -t @i_dont_exist features/test.feature` 🍷 (004ms)

Then

it should pass 🍷 (000ms)

Tagged hooks

Background

Given

the standard step definitions 🍌 (000ms)

And

a file named "features/support/hooks.rb" with: 🍌 (000ms)

```
Before('~@no-boom') do
  raise 'boom'
end
```

And

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: With and without hooks
  Scenario: using hook
    Given this step passes

    @no-boom
    Scenario: omitting hook
      Given this step passes

  Scenario Outline: omitting hook on specified examples
    Given this step passes

    Examples:
    | Value      |
    | Irrelevant |

    @no-boom
    Examples:
    | Value      |
    | Also Irrelevant |
```

Scenario: omit tagged hook

When

I run `cucumber features/f.feature:2` 🍷 (016ms)

Then

it should fail with exactly: 🍷 (000ms)

Feature: With and without hooks

```
Scenario: using hook      # features/f.feature:2
boom (RuntimeError)
./features/support/hooks.rb:2:in `Before'
  Given this step passes # features/step_definitions/steps.rb:1
```

Failing Scenarios:

cucumber features/f.feature:2 # Scenario: using hook

1 scenario (1 failed)

1 step (1 skipped)

0m0.012s

Scenario: omit tagged hook

When

I run `cucumber features/f.feature:6` 🍷 (010ms)

Then

it should pass with exactly: 🍷 (000ms)

Feature: With and without hooks

```
@no-boom
Scenario: omitting hook  # features/f.feature:6
  Given this step passes # features/step_definitions/steps.rb:1
```

1 scenario (1 passed)

1 step (1 passed)

0m0.012s

Scenario: Omit example hook

When

I run `cucumber features/f.feature:12` 🍌 (013ms)

Then

it should fail with exactly: 🍌 (000ms)

Feature: With and without hooks

Scenario Outline: omitting hook on specified examples # features/f.feature:9
Given this step passes # features/f.feature:10

Examples:

Value
boom (RuntimeError)
./features/support/hooks.rb:2:in `Before'
Irrelevant

Failing Scenarios:

cucumber features/f.feature:14 # Scenario Outline: omitting hook on specified examples, Examples (#1)

1 scenario (1 failed)

1 step (1 skipped)

0m0.012s

Transforms

If you see certain phrases repeated over and over in your step definitions, you can use transforms to factor out that duplication, and make your step definitions simpler.

Background

Let's just create a simple feature for testing out Transforms. We also have a `Person` class that we need to be able to build.

Given

a file named "features/foo.feature" with: 🍌 (000ms)

Feature:

Scenario:

Given a Person aged 15 with blonde hair

And

a file named "features/support/person.rb" with: 🍌 (000ms)

```
class Person
  attr_accessor :age

  def to_s
    "I am #{age} years old"
  end
end
```

Scenario: Basic Transform

This is the most basic way to use a transform. Notice that the regular expression is pretty much duplicated.

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Transform(/a Person aged (\d+)/) do |age|
  person = Person.new
  person.age = age.to_i
  person
end

Given /^(a Person aged \d+) with blonde hair$/ do |person|
  expect(person.age).to eq 15
end
```

When

I run `cucumber features/foo.feature` 🍌 (009ms)

Then

it should pass 🍌 (000ms)

Scenario: Re-use Transform's Regular Expression

If you keep a reference to the transform, you can use it in your regular expressions to avoid repeating the regular expression.

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
A_PERSON = Transform(/a Person aged (\d+)/) do |age|
  person = Person.new
  person.age = age.to_i
  person
end

Given /^(#{A_PERSON}) with blonde hair$/ do |person|
  expect(person.age).to eq 15
end
```

When

I run `cucumber features/foo.feature` 🍌 (012ms)

Then

it should pass 🍌 (000ms)

Unicode in tables

You are free to use unicode in your tables: we've taken care to ensure that the tables are properly aligned so that your output is as readable as possible.

tags: @spawn,@spawn

Given

a file named "features/unicode.feature" with: 🍌 (000ms)

Feature: Featuring unicode

Scenario: table with unicode

Given passing

	Brüno		abc	
	Bruno		æøå	

When

I run `cucumber -q --dry-run features/unicode.feature` 🍌 (605ms)

Then

it should pass with: 🍌 (000ms)

Feature: Featuring unicode

Scenario: table with unicode

Given passing

	Brüno		abc	
	Bruno		æøå	

1 scenario (1 undefined)

1 step (1 undefined)

Usage formatter

In order to see where step definitions are used
Developers should be able to see a list of step definitions and their use

Background

Given

a file named "features/f.feature" with: 🍌 (000ms)

```
Feature: F
  Background: A
    Given A
  Scenario: B
    Given B
  Scenario Outline: CA
    Given <x>
    And B
    Examples:
      |x|
      |C|
      |A|
  Scenario: AC
    Given A
    Given C
```

And

a file named "features/step_definitions/steps.rb" with: 🍌 (000ms)

```
Given(/A/) { }
Given(/B/) { }
Given(/C/) { }
Given(/D/) { }
```

Scenario: Run with --format usage

When

I run `cucumber -f usage --dry-run` 🍌 (015ms)

Then

it should pass with exactly: 🍌 (000ms)

```
-----  
  
/A/      # features/step_definitions/steps.rb:1  
  Given A # features/f.feature:3  
  Given A # features/f.feature:12  
  Given A # features/f.feature:14  
/B/      # features/step_definitions/steps.rb:2  
  Given B # features/f.feature:5  
  And B   # features/f.feature:11  
  And B   # features/f.feature:12  
/C/      # features/step_definitions/steps.rb:3  
  Given C # features/f.feature:11  
  Given C # features/f.feature:15  
/D/      # features/step_definitions/steps.rb:4  
  NOT MATCHED BY ANY STEPS  
  
4 scenarios (4 skipped)  
11 steps (11 skipped)
```

Scenario: Run with `--expand --format usage`

When

I run `cucumber -x -f usage --dry-run` 🍌 (018ms)

Then

it should pass with exactly: 🍌 (000ms)

```
-----  
  
/A/      # features/step_definitions/steps.rb:1  
  Given A # features/f.feature:3  
  Given A # features/f.feature:12  
  Given A # features/f.feature:14  
/B/      # features/step_definitions/steps.rb:2  
  Given B # features/f.feature:5  
  And B   # features/f.feature:11  
  And B   # features/f.feature:12  
/C/      # features/step_definitions/steps.rb:3  
  Given C # features/f.feature:11  
  Given C # features/f.feature:15  
/D/      # features/step_definitions/steps.rb:4  
  NOT MATCHED BY ANY STEPS  
  
4 scenarios (4 skipped)  
11 steps (11 skipped)
```

Scenario: Run with `--format stepdefs`

When

I run `cucumber -f stepdefs --dry-run` 🍌 (024ms)

Then

it should pass with exactly: 🍌 (000ms)

```
-----  
  
/A/  # features/step_definitions/steps.rb:1  
/B/  # features/step_definitions/steps.rb:2  
/C/  # features/step_definitions/steps.rb:3  
/D/  # features/step_definitions/steps.rb:4  
  NOT MATCHED BY ANY STEPS  
  
4 scenarios (4 skipped)  
11 steps (11 skipped)
```


Using descriptions to give features context

When writing your feature files its very helpful to use description text at the beginning of the feature file, to write a preamble to the feature describing clearly exactly what the feature does.

You can also write descriptions attached to individual scenarios - see the examples below for how this can be used.

It's possible to have your descriptions run over more than one line, and you can have blank lines too. As long as you don't start a line with a Given, When, Then, Background:, Scenario: or similar, you're fine: otherwise Gherkin will start to pay attention.

Background

Given

the standard step definitions 🍌 (000ms)

Scenario: Everything with a description

Given

a file named "features/test.feature" with: 🍌 (000ms)

Feature: descriptions everywhere

We can put a useful description here of the feature, which can span multiple lines.

Background:

We can also put in descriptions showing what the background is doing.

Given this step passes

Scenario: I'm a scenario with a description

You can also put descriptions in front of individual scenarios.

Given this step passes

Scenario Outline: I'm a scenario outline with a description

Scenario outlines can have descriptions.

Given this step <state>

Examples: Examples

Specific examples for an outline are allowed to have descriptions, too.

	state	
	passes	

When

I run `cucumber -q` 🍌 (021ms)

Then

the stderr should not contain anything 🍌 (000ms)

Then

it should pass with exactly: 🍌 (000ms)

Feature: descriptions everywhere

We can put a useful description here of the feature, which can span multiple lines.

Background:

We can also put in descriptions showing what the background is doing.

Given this step passes

Scenario: I'm a scenario with a description

You can also put descriptions in front of individual scenarios.

Given this step passes

Scenario Outline: I'm a scenario outline with a description

Scenario outlines can have descriptions.

Given this step <state>

Examples: Examples

Specific examples for an outline are allowed to have descriptions, too.

state	
passes	

2 scenarios (2 passed)

4 steps (4 passed)

[[Using-star-notation-instead-of-Given/When/Then, Using star notation instead of Given/When/Then]] === **Using star notation instead of Given/When/Then**

Cucumber supports the star notation when writing features: instead of using Given/When/Then, you can simply use a star rather like you would use a bullet point.

When you run the feature for the first time, you still get a nice message showing you the code snippet you need to use to implement the step.

Scenario: Use some *

Given

a file named "features/f.feature" with: 🍌 (000ms)

Feature: Star-notation feature

Scenario: S

* I have some cukes

When

I run `cucumber features/f.feature` 🍌 (010ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (000ms)

Feature: Star-notation feature

Scenario: S # features/f.feature:2

* I have some cukes # features/f.feature:3

1 scenario (1 undefined)

1 step (1 undefined)

And

it should pass with: 🍌 (000ms)

You can implement step definitions for undefined steps with these snippets:

```
Given(/^I have some cukes$/) do
```

```
  pending # Write code here that turns the phrase above into concrete actions
end
```

Wire protocol table diffing

In order to use the amazing functionality in the Cucumber table object

As a wire server

I want to be able to ask for a table diff during a step definition invocation

Background

tags: @wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

Feature: Hello

Scenario: Wired

Given we're all wired

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

host: localhost

port: 54321

Scenario: Invoke a step definition tries to diff the table and fails

tags: @wire,@wire,@spawn

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (001ms)

When

I run `cucumber -f progress --backtrace` 🍌 (807ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should fail with: 🍌 (001ms)

F

(::) failed steps (::)

Not same (DifferentException from localhost:54321)

a.cs:12

b.cs:34

features/wired.feature:3:in 'Given we're all wired'

Failing Scenarios:

cucumber features/wired.feature:2 # Scenario: Wired

1 scenario (1 failed)

1 step (1 failed)

Scenario: Invoke a step definition tries to diff the table and passes

tags: @wire,@wire

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber -f progress` 🍌 (181ms)

Then

it should pass with: 🍌 (001ms)

.

1 scenario (1 passed)

1 step (1 passed)

Scenario: Invoke a step definition which successfully diffs a table but then fails

tags: @wire,@wire,@spawn

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌
(002ms)

When

I run `cucumber -f progress` 🍌 (908ms)

Then

it should fail with: 🍌 (001ms)

F

(::) failed steps (::)

I wanted things to be different for us (Cucumber::WireSupport::WireException)
features/wired.feature:3:in 'Given we're all wired'

Failing Scenarios:

cucumber features/wired.feature:2 # Scenario: Wired

1 scenario (1 failed)

1 step (1 failed)

Scenario: Invoke a step definition which asks for an immediate diff that fails

tags: @wire,@wire,@spawn

Given

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f progress` 🍌 (808ms)

And

it should fail with exactly: 🍌 (001ms)

F

(::) failed steps (::)

Tables were not identical:

```
| (-) a | (+) b |  
(Cucumber::MultilineArgument::DataTable::Different)  
features/wired.feature:3:in 'Given we're all wired'
```

Failing Scenarios:

```
cucumber features/wired.feature:2 # Scenario: Wired
```

1 scenario (1 failed)

1 step (1 failed)

0m0.012s

Wire protocol tags

In order to use Before and After hooks in a wire server, we send tags with the scenario in the `begin_scenario` and `end_scenario` messages

Background

tags: @wire

And

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

```
host: localhost
port: 54321
```

Scenario: Run a scenario

tags: @wire,@wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

```
@foo @bar
Feature: Wired

  @baz
  Scenario: Everybody's Wired
    Given we're all wired
```

And

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f pretty -q` 🍌 (145ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should pass with: 🍌 (000ms)

```
@foo @bar
Feature: Wired

  @baz
  Scenario: Everybody's Wired
    Given we're all wired

1 scenario (1 passed)
1 step (1 passed)
```

Scenario: Run a scenario outline example

tags: @wire,@wire

Given

a file named "features/wired.feature" with: 🍌 (000ms)

```
@foo @bar
Feature: Wired

@baz
Scenario Outline: Everybody's Wired
  Given we're all <something>

Examples:
  | something |
  | wired    |
```

And

there is a wire server running on port 54321 which understands the following protocol: 🍌 (002ms)

When

I run `cucumber -f pretty -q` 🍌 (147ms)

Then

the stderr should not contain anything 🍌 (001ms)

And

it should pass with: 🍌 (001ms)

```
@foo @bar
Feature: Wired

@baz
Scenario Outline: Everybody's Wired
  Given we're all <something>

Examples:
  | something |
  | wired    |

1 scenario (1 passed)
1 step (1 passed)
```

Wire protocol timeouts

We don't want Cucumber to hang forever on a wire server that's not even there, but equally we need to give the user the flexibility to allow step definitions to take a while to execute, if that's what they need.

Background

tags: @wire

And

a file named "features/wired.feature" with: 🍌 (000ms)

```
Feature: Telegraphy
  Scenario: Wired
    Given we're all wired
```

Scenario: Try to talk to a server that's not there

tags: @wire,@wire

Given

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (001ms)

```
host: localhost
port: 54321
```

When

I run `cucumber -f progress` 🍌 (012ms)

Then

the stderr should contain: 🍌 (000ms)

```
Unable to contact the wire server at localhost:54321
```

Scenario: Invoke a step definition that takes longer than its timeout

tags: @wire,@wire,@spawn

Given

a file named "features/step_definitions/some_remote_place.wire" with: 🍌 (000ms)

```
host: localhost
port: 54321
timeout:
  invoke: 0.1
```

And

there is a wire server on port 54321 which understands the following protocol: 🍌 (000ms)

And

the wire server takes 0.2 seconds to respond to the invoke message 🍌 (002ms)

When

I run `cucumber -f pretty` 🍌 (908ms)

Then

the stderr should not contain anything 🍌 (000ms)

And

it should fail with: 🍌 (001ms)

Feature: Telegraphy

```
Scenario: Wired          # features/wired.feature:2
  Given we're all wired # Unknown
    Timed out calling wire server with message 'invoke' (Timeout::Error)
    features/wired.feature:3:in 'Given we're all wired'
```

Failing Scenarios:

```
cucumber features/wired.feature:2 # Scenario: Wired
```

```
1 scenario (1 failed)
```

```
1 step (1 failed)
```