

Inbound rules

Info

Security group rule ID	Type	Protocol	Port range	Source	Description - optional
	Info	Info	Info	Info	Info
sgr-01b5ed431d6cab19e	SSH	TCP	22	Custom	
sgr-0ca2edd1eff92bd48	HTTP	TCP	80	Custom	
sgr-06652627bdaeacbf0	HTTPS	TCP	443	Custom	

Add rule

3. SSH into the machine

ssh -i <keyname>.pem ubuntu@<public_ip_address>

4. Install Docker

```
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo apt-key add -  
sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu  
$(lsb_release -cs) stable" sudo apt-get update  
sudo apt-get install -y docker-ce
```

```
Get:17 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 Packages [366 kB]  
Get:18 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe Translation-en [150 kB]  
Get:19 https://download.docker.com/linux/ubuntu noble/stable amd64 Packages [13.8 kB]  
Get:20 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 Components [45.0 kB]  
Get:21 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/universe amd64 c-n-f Metadata [14.3 kB]  
Get:22 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/restricted amd64 Packages [317 kB]  
Get:23 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/restricted Translation-en [61.5 kB]  
Get:24 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/restricted amd64 c-n-f Metadata [424 B]  
Get:25 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Packages [14.4 kB]  
Get:26 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse Translation-en [3608 B]  
Get:27 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Components [212 B]  
Get:28 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 c-n-f Metadata [532 B]  
Get:29 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/main amd64 Components [288 B]  
Get:30 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/main amd64 c-n-f Metadata [112 B]  
Get:31 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 Packages [10.6 kB]  
Get:32 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe Translation-en [10.8 kB]  
Get:33 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 Components [17.6 kB]  
Get:34 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/universe amd64 c-n-f Metadata [1104 B]  
Get:35 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/restricted amd64 Components [216 B]  
Get:36 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/restricted amd64 c-n-f Metadata [116 B]  
Get:37 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/multiverse amd64 Components [212 B]  
Get:38 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports/multiverse amd64 c-n-f Metadata [116 B]  
Get:39 http://security.ubuntu.com/ubuntu noble-security/main amd64 Packages [351 kB]  
Get:40 http://security.ubuntu.com/ubuntu noble-security/main Translation-en [77.3 kB]  
Get:41 http://security.ubuntu.com/ubuntu noble-security/main amd64 c-n-f Metadata [4416 B]  
Get:42 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Packages [267 kB]  
Get:43 http://security.ubuntu.com/ubuntu noble-security/universe Translation-en [111 kB]  
Get:44 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Components [8632 B]  
Get:45 http://security.ubuntu.com/ubuntu noble-security/universe amd64 c-n-f Metadata [10.1 kB]  
Get:46 http://security.ubuntu.com/ubuntu noble-security/restricted amd64 Packages [317 kB]  
Get:47 http://security.ubuntu.com/ubuntu noble-security/restricted Translation-en [61.5 kB]  
Get:48 http://security.ubuntu.com/ubuntu noble-security/restricted amd64 c-n-f Metadata [428 B]  
Get:49 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 Packages [10.9 kB]  
Get:50 http://security.ubuntu.com/ubuntu noble-security/multiverse Translation-en [2808 B]  
Get:51 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 Components [208 B]  
Get:52 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 c-n-f Metadata [344 B]  
Fetched 28.9 MB in 5s (5720 kB/s)  
Reading package lists... Done  
W: https://download.docker.com/linux/ubuntu/dists/noble/InRelease: Key is stored in legacy trusted.gpg keyring (/etc/apt/trusted.gpg), see the DEPRECATION s  
ection in apt-key(8) for details.  
ubuntu@ip-172-31-45-229:~$
```

Then, configure cgroup in a daemon.json file.

```
cd /etc/docker
cat <<EOF | sudo tee /etc/docker/daemon.json
{
  "exec-opts": ["native.cgroupdriver=systemd"]
}
EOF
sudo systemctl enable docker sudo
systemctl daemon-reload sudo systemctl
restart docker
```

5. Install Kubernetes

```
sudo apt-get update
# apt-transport-https may be a dummy package; if so, you can skip that package
sudo apt-get install -y apt-transport-https ca-certificates curl gpg
# If the directory `/etc/apt/keyrings` does not exist, it should be created before the curl command, read
the note below.
# sudo mkdir -p -m 755 /etc/apt/keyrings
curl -fsSL https://pkgs.k8s.io/core:/stable:/v1.31/deb/Release.key | sudo gpg
--dearmor -o /etc/apt/keyrings/kubernetes-apt-keyring.gpg # This
overwrites any existing configuration in
/etc/apt/sources.list.d/kubernetes.list
echo 'deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg]
https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /' | sudo tee
/etc/apt/sources.list.d/kubernetes.list sudo apt-get
update
sudo apt-get install -y kubelet kubeadm kubectl sudo apt-mark
hold kubelet kubeadm kubectl
sudo systemctl enable --now kubelet
```

```

ubuntu@ip-172-31-40-255:~$ # Add Kubernetes GPG key
curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | sudo apt-key add -

# Add Kubernetes repository
sudo tee /etc/apt/sources.list.d/kubernetes.list <<EOF
deb https://apt.kubernetes.io/ kubernetes-xenial main
EOF

# Update package list
sudo apt-get update

# Install kubelet, kubeadm, and kubectl
sudo apt-get install -y kubelet kubeadm kubectl

# Hold the versions of Kubernetes components
sudo apt-mark hold kubelet kubeadm kubectl
Warning: apt-key is deprecated. Manage keyring files in trusted.gpg.d instead (see apt-key(8)).
OK
deb https://apt.kubernetes.io/ kubernetes-xenial main
Hit:1 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://eu-north-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu noble InRelease
Hit:5 http://security.ubuntu.com/ubuntu noble-security InRelease
Ign:6 https://packages.cloud.google.com/apt kubernetes-xenial InRelease
Err:7 https://packages.cloud.google.com/apt kubernetes-xenial Release

```

After installing Kubernetes, we need to configure internet options to allow bridging.

```

sudo swapoff -a
echo "net.bridge.bridge-nf-call-iptables=1" | sudo tee -a
/etc/sysctl.conf sudo
sysctl -p

```

```

ubuntu@ip-172-31-45-229:~$ # Disable swap
sudo swapoff -a

# Allow bridging for iptables
echo "net.bridge.bridge-nf-call-iptables=1" | sudo tee -a /etc/sysctl.conf

# Apply sysctl changes
sudo sysctl -p
net.bridge.bridge-nf-call-iptables=1
net.bridge.bridge-nf-call-iptables = 1
ubuntu@ip-172-31-45-229:~$

```

6. Initialize the Kubecluster

```

sudo kubeadm init --pod-network-cidr=10.244.0.0/16

```

```
Your Kubernetes control-plane has initialized successfully!
```

To start using your cluster, you need to run the following as a regular user:

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Alternatively, if you are the root user, you can run:

```
export KUBECONFIG=/etc/kubernetes/admin.conf
```

You should now deploy a pod network to the cluster.

Run "kubectl apply -f [podnetwork].yaml" with one of the options listed at:
<https://kubernetes.io/docs/concepts/cluster-administration/addons/>

Then you can join any number of worker nodes by running the following on each as root:

```
kubeadm join 172.31.45.229:6443 --token s9zq75.bsi7js5f62ridulc \
--discovery-token-ca-cert-hash sha256:91eae090fdd49337bf70d5bf7478e60bc85820d0996651871129a082db6fa8f1
ubuntu@ip-172-31-45-229:~$
```

Copy the mkdir and chown commands from the top and execute them

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Then, add a common networking plugin called flannel as mentioned in the code.

```
kubectl apply -f https://raw.githubusercontent.com/coreos/flannel/master/Documentation/
kube-flannel.yml
```

```
ubuntu@ip-172-31-45-229:~$ kubectl apply -f https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml
namespace/kube-flannel created
clusterrole.rbac.authorization.k8s.io/flannel created
clusterrolebinding.rbac.authorization.k8s.io/flannel created
serviceaccount/flannel created
configmap/kube-flannel-cfg created
daemonset.apps/kube-flannel-ds created
```

7. Now that the cluster is up and running, we can deploy our nginx server on this cluster.

Apply this deployment file using this command to create a deployment

```
kubectl apply -f https://k8s.io/examples/application/deployment.yaml
```

```
ubuntu@ip-172-31-45-229:~$ kubectl apply -f https://k8s.io/examples/application/deployment.yaml
deployment.apps/nginx-deployment created
ubuntu@ip-172-31-45-229:~$
```

Use 'kubectl get pods' to verify if the deployment was properly created and the pod is working correctly.

```
ubuntu@ip-172-31-45-229:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-krhbw    0/1     Pending   0           2m29s
nginx-deployment-d556bf558-mhlm2    0/1     Pending   0           2m29s
ubuntu@ip-172-31-45-229:~$
```

Next up, create a name alias for this pod. `POD_NAME=$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}")`

8. Lastly, port forward the deployment to your localhost so that you can view it.

```
kubectl port-forward $POD_NAME 8080:80
```

9. Verify your deployment

Open up a new terminal and ssh to your EC2 instance.

Then, use this curl command to check if the Nginx server is running.

```
curl --head http://127.0.0.1:8080
```

```
ubuntu@ip-172-31-45-229:~$ curl --head http://127.0.0.1:8080
HTTP/1.1 200 OK
Server: nginx/1.18.0
Date: Sat, 14 Sep 2024 7:20:53 GMT
Content-Type: text/html
Content-Length: 612
Connection: keep-alive
ETag: "5c0692e1-265"
Accept-Ranges: bytes
```

If the response is 200 OK and you can see the Nginx server name, your deployment was successful.

We have successfully deployed our Nginx server on our EC2 instance.

Conclusion:

In this project, we effectively set up Kubernetes and Docker on an AWS EC2 Ubuntu instance, fine-tuned the necessary configurations, and initiated a Kubernetes cluster. We then deployed an Nginx server via a Kubernetes Deployment and utilized the Flannel networking plugin to enable pod communication. By checking the status of the pods and using port forwarding, we were able to access the Nginx server from our local environment. The successful `200 OK` response from the `curl` command verified the successful deployment. This exercise highlighted key Kubernetes functionalities, including cluster setup, application deployment, and operational validation, demonstrating Kubernetes' capability to manage and orchestrate containerized applications with efficiency.