Step 2: Running the buggy tennis_scoring.py

```
$ python processor.py  (valid input)
==== Running parse_score ====
Enter points won as A-B (e.g. 3-2): Points A and B: (3, 2)

==== Running game_lead ====
Enter a game score (e.g. 40-30): Lead in Points: 1

==== Running set_spread ====
Enter games won per set as CSV (e.g. 6,4,7): Spread: 3

$ python processor.py  (invalid input)
  File "/Users/adyanthmallur/SE-Lab-6/L6_L7_34_tennis_scoring/lab7/tennis_scoring.py", line 17, in main
    result = parse_score(user_input)
  File "/Users/adyanthmallur/SE-Lab-6/L6_L7_34_tennis_scoring/lab7/tennis_scoring.py", line 2, in parse_score
    a, b = text.split('-')
    ^^^^
ValueError: not enough values to unpack (expected 2, got 1)
```

Step 4: test_tennis_scoring.py failing on the buggy code

```
$ pytest test_tennis_scoring.py
========================================= test session starts ==========================================
platform darwin -- Python 3.14.6, pytest-9.2.0, pluggy-1.7.0
rootdir: /Users/adyanthmallur/SE-Lab-6/L6_L7_34_tennis_scoring/lab7
plugins: hypothesis-6.170.14
collected 6 items

test_tennis_scoring.py FFF...                                                                  [100%]

======================================== short test summary info =======================================
FAILED test_tennis_scoring.py::test_parse_score_no_crash - ExceptionGroup: Hypothesis found 3 distinct fail...
FAILED test_tennis_scoring.py::test_game_lead_no_crash - ExceptionGroup: Hypothesis found 3 distinct failur...
FAILED test_tennis_scoring.py::test_set_spread_no_crash - ExceptionGroup: Hypothesis found 2 distinct failu...
========================================= 3 failed, 3 passed in 0.93s ==========================================

$ failing inputs found by Hypothesis (from the full log)
AssertionError: parse_score crashed with: ValueError("invalid literal for int() with base 10: ''")
s='-',
AssertionError: parse_score crashed with: ValueError('not enough values to unpack (expected 2, got 1)')
s='',
AssertionError: parse_score crashed with: AttributeError("'NoneType' object has no attribute 'split'")
s=None,
AssertionError: game_lead crashed with: KeyError('')
s='-',
AssertionError: game_lead crashed with: ValueError('not enough values to unpack (expected 2, got 1)')
s='',
AssertionError: game_lead crashed with: AttributeError("'NoneType' object has no attribute 'split'")
s=None,
AssertionError: set_spread crashed with: ValueError("invalid literal for int() with base 10: ''")
s='',
AssertionError: set_spread crashed with: AttributeError("'NoneType' object has no attribute 'split'")
s=None,
```

Step 5: Running the fixed tennis_scoring.py

```
$ python processor.py  (valid input)
==== Running parse_score ====
Enter points won as A-B (e.g. 3-2): Points A and B: (3, 2)

==== Running game_lead ====
Enter a game score (e.g. 40-30): Lead in Points: 1

==== Running set_spread ====
Enter games won per set as CSV (e.g. 6,4,7): Spread: 3

$ python processor.py  (invalid input)
==== Running parse_score ====
Enter points won as A-B (e.g. 3-2): Invalid input: expected two integers like 3-2

==== Running game_lead ====
Enter a game score (e.g. 40-30): Invalid input: use 0, 15, 30 or 40 on each side, e.g. 40-30

==== Running set_spread ====
Enter games won per set as CSV (e.g. 6,4,7): Invalid input: expected comma-separated integers like 6,4,7
```

Step 6: test_tennis_scoring.py passing on the fixed code

```
$ pytest test_tennis_scoring.py
========================================= test session starts ==========================================
platform darwin -- Python 3.14.6, pytest-9.2.0, pluggy-1.7.0
rootdir: /Users/adyanthmallur/SE-Lab-6/L6_L7_34_tennis_scoring/lab7
plugins: hypothesis-6.170.14
collected 6 items

test_tennis_scoring.py ......                                                                  [100%]

========================================== 6 passed in 0.59s ===========================================
```