ETH zürich



# Introduction to Scientific Computation
# Lecture 5
# Fall 2026

## PDEs, Sparse Matrices, C/C++ in Python

Mikhail Usvyatsov, Yury Kartynnik October 21, 2026

# PDEs

See `lecture_code.ipynb`

# Dense matrices

Dense matrix:

- Mathematical object
- Good DS for storing 2D arrays

Properties:

- Memory allocated once for all items
- Fast access to entries


$$A_{dense} = \begin{bmatrix} A_{11} & A_{12} & A_{13} & A_{14} & A_{15} \\ A_{21} & A_{22} & A_{23} & A_{24} & A_{25} \\ A_{31} & A_{32} & A_{33} & A_{34} & A_{35} \\ A_{41} & A_{42} & A_{43} & A_{44} & A_{45} \\ A_{51} & A_{52} & A_{53} & A_{54} & A_{55} \end{bmatrix}$$

## Sparse Matrices

Often the data around is sparse

It means:

- Data is almost empty
- Storing all the zeros is wasteful
- Think **compression**



Cons:

- Usually slow individual elements access,

But depends on storage algorithm

## Storage schemes

- csc_matrix: Compressed Sparse Column format
- csr_matrix: Compressed Sparse Row format
- bsr_matrix: Block Sparse Row format
- lil_matrix: List of Lists format
- dok_matrix: Dictionary of Keys format
- coo_matrix: COOrdinate format (aka IJV, triplet format)
- dia_matrix: DIAgonal format

Each suitable for some tasks

```
import scipy.sparse as sps
```

**warning** for NumPy users:

- the multiplication with '*' is the *matrix multiplication* (dot product)
- not part of NumPy!
  - passing a sparse matrix object to NumPy functions expecting ndarray/matrix does not work

## Implementation details

Subclasses of **spmatrix**

- default implementation of arithmetic operations
  - always converts to CSR
  - subclasses override for efficiency

- shape, data type set/get
  - nonzero indices
  - format conversion, interaction with NumPy (*toarray()*, *todense()*)

- attributes:
  - *mtx.A* - same as mtx.toarray()
  - *mtx.T* - transpose (same as mtx.transpose())
  - *mtx.H* - Hermitian (conjugate) transpose
  - *mtx.real* - real part of complex matrix
  - *mtx.imag* - imaginary part of complex matrix
  - *mtx.size* - the number of nonzeros (same as self.getnnz())
  - *mtx.shape* - the number of rows and columns (tuple)
- data usually stored in NumPy arrays

## DIAgonal format

- Simple
- Diagonals in dense numpy format, shape (**n_diags, length**)
- Fixed length -> waste space a bit when far from main diagonal
- Offset for each diagonal
  - 0 is the main diagonal
  - negative offset = below
  - positive offset = above
- Fast matrix * vector (sparsetools)
- Fast and easy item-wise operations
- No slicing, no individual item access

```
offset: row

  2:  9
  1:  --10------
  0:  1  . 11  .
 -1:  5  2  . 12
 -2:  .  6  3  .
 -3:  .  .  7  4
      ---------8
```

## List of Lists format (LIL)

- Row-based linked list
- Each row is a Python list (sorted) of column indices of non-zero elements
- Rows stored in a NumPy array (*dtype=np.object*)
- Non-zero values data stored analogously
- Slow arithmetics, slow column slicing due to being row-based
- Used when sparsity pattern is not known apriori or changes

```
>>> print(mtx)
  (0, 1)  1.0
  (0, 2)  1.0
  (0, 3)  1.0
  (1, 1)  1.0
  (1, 3)  1.0
>>> mtx.todense()
matrix([[ 0.,  1.,  1.,  1.,  0.],
        [ 0.,  1.,  0.,  1.,  0.],
        [ 0.,  0.,  0.,  0.,  0.],
        [ 0.,  0.,  0.,  0.,  0.]])
```

## Dictionary of Keys format

- Subclass of Python dict
  - keys are *(row, column)* index tuples (no duplicate entries allowed)
  - values are corresponding non-zero values

- Efficient for constructing sparse matrices incrementally

- Efficient O(1) access to individual elements
- Flexible slicing, changing sparsity structure is efficient
- Can be efficiently converted to a coo_matrix once constructed
- Slow arithmetics (*for* loops with *dict.iteritems()*)
- Used when sparsity pattern is not known apriori or changes

## Coordinate format (COO)

- also known as the ‘ijv’ or ‘triplet’ format
  - three NumPy arrays: *row*, *col*, *data*
  - *data[i]* is value at *(row[i], col[i])* position
  - permits duplicate entries

- fast format for constructing sparse matrices

- very fast conversion to and from CSR/CSC formats
- fast matrix * vector (sparsetools)
- fast and easy item-wise operations
  - manipulate data array directly (fast NumPy machinery)

- no slicing, no arithmetics (directly)
- use:
  - facilitates fast conversion among sparse formats
  - when converting to other format (usually CSR or CSC), duplicate entries are summed together

## Coordinate format (COO)

```
>>> row = np.array([0, 3, 1, 0])
>>> col = np.array([0, 3, 1, 2])
>>> data = np.array([4, 5, 7, 9])
>>> mtx = sparse.coo_matrix((data, (row, col)), shape=(4, 4))
>>> mtx
<4x4 sparse matrix of type '<... 'numpy.int64'>'
        with 4 stored elements in COOrdinate format>
>>> mtx.todense()
matrix([[4, 0, 9, 0],
        [0, 7, 0, 0],
        [0, 0, 0, 0],
        [0, 0, 0, 5]])
```

## Compressed Sparse Row format (CSR)

- row oriented
  - three NumPy arrays: *indices*, *indptr*, *data*
    - *indices* is array of column indices
    - *data* is array of corresponding nonzero values
    - *indptr* points to row starts in *indices* and *data*
    - length is *n_row + 1*, last item = number of values = length of both *indices* and *data*
    - nonzero values of the *i*-th row are *data[indptr[i]:indptr[i+1]]* with column indices *indices[indptr[i]:indptr[i+1]]*
    - item *(i, j)* can be accessed as *data[indptr[i]+k]*, where *k* is position of *j* in *indices[indptr[i]:indptr[i+1]]*
- fast matrix vector products and other arithmetics (sparsetools)
- efficient row slicing, row-oriented operations
- slow column slicing, expensive changes to the sparsity structure
- use:
  - actual computations (most linear solvers support this format)

## Compressed Sparse Column format (CSC)


- row oriented
  - three NumPy arrays: *indices*, *indptr*, *data*
    - *indices* is array of row indices
    - *data* is array of corresponding nonzero values
    - *indptr* points to column starts in *indices* and *data*
    - length is *n_col + 1*, last item = number of values = length of both *indices* and *data*
    - nonzero values of the *i*-th column are *data[indptr[i]:indptr[i+1]]* with row indices *indices[indptr[i]:indptr[i+1]]*
    - item *(i, j)* can be accessed as *data[indptr[i]+k]*, where *k* is position of *j* in *indices[indptr[i]:indptr[i+1]]*
- fast matrix vector products and other arithmetics (sparsetools)
- efficient column slicing, column-oriented operations
- slow row slicing, expensive changes to the sparsity structure
- use:
  - actual computations (most linear solvers support this format)

## C/C++ bindings

- Cython
- SWIG
- Pybind11


## Cython

- A hybrid programming language/compiler
- Python statements are valid
- You have to provide argument types



## SWIG

- Simplified Wrapper and Interface Generator
- You have to define interface files, the rest SWIG will do for you



**pybind**

- Simplified Wrapper and Interface Generator
- You have to define interface files, the rest SWIG will do for you

