

# Final Year Thesis Topic: Development and implementation dynamic balance algorithms for bipedal robot locomotion.

Prof. Eugeni Magid  
Innopolis University  
e.magid@innopolis.ru

## 1 Context and Background

Human anatomy allows people to work in different workspaces. With the help of two legs human can swim, walk, and even climb the mountains. Such abilities are the reason of the progress in science and technology. However, there is huge amount of applications where the human have to sacrifice his life and limb. Such works as nuclear objects control, car tests, submarine services, car driving, e.t.c. can be done only with double legged robots. Robots now are very restricted. For each particular problem we have a particular robot. Vacuum-cleaner robot cannot delete dust from the cupboard. But double legged mechanisms will be able to work with devices designed for people with precision of robot.

## 2 Problem Statement

This project is concerned with analyzing the structure of bipedal robot, computer model design, developing the dynamic balance algorithm based on ZMP approach or any other for this robot and implementing it on the real mechanism.

## 3 Objectives and Possible Approaches

The goal of this exercise is to develop a software system that can output commands for robot's motors and it should make the robot to reach the target position in minimal time. Commands define the angles for motors that affect the robot. To compute these angles the surveillance application needs to be able to do the following.

1. Measure ZMP point with help of pressure sensors.
2. Solve inverse kinematics problem.
3. Solve the system of differential equations representing dynamics.

Computer model can be done in Simulink environment. It will allow to test the algorithm and improve it iteratively. Then it is necessary to check the model on the real robot and again iteratively improve the model. Finally, robot should be able to follow the strait line on the floor.

## 4 Tools and Resources

This project with use the matlab, simulink environment, YARP/ROS. The final thesis will be written using  $\text{\LaTeX}$ [1].

## 5 Plan

1. Compare different approaches to bipedal locomotion.

Bipedal locomotion consists of several phases. There are walking and staying parts. Each of this part requires different type of stability. If robot is statically stable, then it wouldn't require any energy while it stays. On the other hand, during walking bipedal robot should be stable, but previous characteristic doesn't provide this property. So we came up with the idea of dynamical stability, that will allow the robot to move. There are several ways to achieve it. E.g. neural networks, ZMP, passive walking, capture point, to name a only few.

2. Choose the most appropriate approach.

The process of bipedal walking consists of continuous falling of the robot but it have to prevent it on time and change the phase. From this point of view it doesn't seems that neural networks are the good idea because we can describe the model precisely. More over bipedal robot is interesting because of its anthropomorphism because of it robot can be placed in the same environment as a human. This requirements make us think about the approach that is energy and computationally efficient and also provide a good precision of walking in several degrees of uncertainty.

3. Make the computer model of the robot.

During the development we should compare several models the control, also mistakes are inevitable. Thus virtual simulation environment is necessary to prevent robot failure and reduce the time of problems identifying.

4. Implement algorithm on this model.

Algorithm should be implemented in simulator to prove that it allows control the entire model.

5. Iteratively improve the model and algorithm.

It is inevitable that some approaches would be better than others, therefore it is very important to improve the model iteratively, and so to achieve better solution of the problem.

6. Implement the algorithm on practice.

Theoretical solving of problem cannot guarantee that it really works. So real world test would be the best prove, the the work is done correctly.

7. Adapt the model.

After constructing the simple model, we want to make it more complicated to be able to work in different conditions and environments and solve real world problems.

## 6 Literature review

Nowadays, mankind has invented almost all the devices that are needed for the modern human and society in general. The science is now engaged in the improvement and optimization of existing solutions. These solutions can be traced with trends that are repeated and replicated. For example, the machine has 4 wheels, bike - two, and wheels are round, at room there are four walls, etc. This approach is quite good: gain experience, accumulate knowledge and apply them to the latest developments.

It was common to think before the advent of industrial robots that robots should look like humans. The first use of the word "robot" referred to the humanoid machines that were supposed to serve a human. However, from the very beginning almost every automatic device intended for production and other operations normally performed by the human was called robot. Intensive development of robots has begun after the Second World War, which was associated with the emergence of the nuclear industry.

Robots in today's presentation (autonomous device that performs some work in automatic mode) can be attributed with machine "Lunokhod-1", created in 1966. This is the first in the history machine that worked on the surface of Moon (1970). Recent tendency in robotics is replacing people not only in manufacturing but also in the military sphere. Constantly emerging information about the achievements of the leading countries in the development of military land, underwater robots and unmanned aerial vehicles is evidenced for this thesis. The era of development of bipedal humanoid walking robots develops nowadays.

The trend towards automation is a core part of progress. Automation reduces the cost of technical processes and the risk to humans. Therefore, the research and implementation of patterns in this task are on the cutting edge of science and technology and require special attention and investment in its development. Every year in the world there are more and more situations requiring people perform a wide variety of work in heavy, dangerous, and sometimes incompatible with the life conditions. In response, there are new tools of extreme robotics. However, for the most part they are very similar to each other. Usually, to perform the task on the ground is a autonomous wheeled or tracked vehicle with installed manipulator. Control is carried out remotely by radio or cable. These robots are produced for more than a dozen years. Engineers during that time has accumulated a lot of experience in their development and applications, in some cases, very effective. However, it is undeniable that this technique has (like any other) limited scope of application. And as before, the people at the risk of life and limb, work in the rubbles, on fire, in terms of chemical, biological and radioactive contamination, are fighting against criminals and terrorists. Moreover, most of all this actions are situated not in the area of open field but in the buildings and various facilities, cabins and rooms of various equipment, generally in conditions originally created for humans, given its two arms and two legs, the typical size, weight, and, if I may say so, the kinematics of the body. For this reason other areas of extreme robotics are developing now. One of this is a robotic system including a anthropomorphic bipedal walking robot. Kinematics, size and weight similar to human characteristics, is equipped with an energy source, communication channel with the control station, and powerful autonomous control system, allowing to perform some action in the supervisory or automatic mode (independent transportation from the place of work in the absence of communication). Such a robot can have significant advantages in a workspace adapted for humans.

Bipedal locomotion is a very complex task. It still doesn't have complete general solution however the research of this has a long history. The development of the models starts from the inverted pendulum model of human walking and goes to the complex approach of actuated passive walking with ZMP control.

In 1970 Miomir Vukobratovi has proposed Zero Moment Point, a theoretical model to explain biped locomotion. According to [2] we can divide all the existing humanoid bipedal walking

robots into two big groups: ZMP-controlled ones and passive - dynamic walkers.

Zero moment point is a concept related with dynamics and control of legged locomotion for humanoid robots. It specifies the point with respect to which dynamic reaction force at the contact of the foot with the ground does not produce any moment in the horizontal direction, i.e. the point where the total of horizontal inertia and gravity forces equals to zero. Miomir Vukobratovic in [3] defines ZMP (Zero Moment Point) as a point in which we can reduce all the forces with one single force. This ZMP should be on the foot. The problem is that we cannot manipulate the foot directly. According to [3] we can do it by ensuring the appropriate dynamics of the mechanism above the foot. If the resulting force in ZMP lies not in vertical direction than foot will slide. It means that dynamical stability was not achieved due to the fact, that there is a rotational moment that will affect the robot. On the other hand, if ZMP was achieved in the polygon of foot and moreover it coincides with the contact point, than robot is stable, due to the fact, that all the resulting forces lies in vertical direction. During the walk the position of ZMP should be computed simultaneously and the problem of control is to keep ZMP and contact point to be coincided inside the support polygon of contact foot with the ground.

In [2] it was mentioned that ZMP approach give us the solution that is based on the principle of dynamical stability, however it is not energy efficient. It requires simultaneous control over all the joints of the robot. The method that was described in [4] is called passive-walker dynamics and it uses gravity forces to reduce the amount of necessary energy to control the robot.

It was mentioned earlier that active control of the robot should be performed with applying dynamical stability principle, elsewhere the robot will loose the balance and fall. So, it makes sense to apply passive-walker dynamics with ZMP based control. According to [3] ZMP method is the most well known and so it is necessary to start with it. Than iteratively increasing the complexity of the problem and applying new technics and constraints we will reach the optimal solution.

According to [3] the most important task in the bipedal locomotion is to maintain dynamical stability. It can be accomplished if the foot have a full contact with the ground, it means, that the contact is not only in the edge or in the point. Moreover it shows that ZMP position depends on the robot dynamics: the resulting force in the contact polygon and total moment there. So, during the motion the position of ZMP changes and there are border situations when ZMP reaches the edge of support polygon. In these situations if additional moments appear, robot will rotate around foot edge and collapse. [3] suggests the way to measure the load on the sole via force sensors on it. The algorithm of ZMP control is quite obvious. Compute wanted ZMP coordinates, measure the error and apply correcting signal. Very important notion is about Center of Pressure (CoP). According to [3] the pressure between foot and the ground can be replaced with the force applied in CoP. With this we can define stability condition as ZMP and CoP coincident.

In [5] it was mentioned the new approach to solve ZMP control problem. Using neural network trained with back propagation method was used to control the position of the robot given the errors between ZMP position and CoP.

## References

- [1] Leslie Lamport and A LaTEX. *Document Preparation System*. Addison-Wesley Reading, MA, 1986.
- [2] Ian R Manchester, Uwe Mettin, Fumiya Iida, and Russ Tedrake. Stable dynamic walking over uneven terrain. *The International Journal of Robotics Research*, page 3, 2011.
- [3] Miomir Vukobratović and Branislav Borovac. Zero-moment point thirty five years of its life. *International Journal of Humanoid Robotics*, 1(01):157–173, 2004.
- [4] Steven H Collins, Martijn Wisse, and Andy Ruina. A three-dimensional passive-dynamic walking robot with two legs and knees. *The International Journal of Robotics Research*, 20(7):607–615, 2001.
- [5] Dong W Kim, Nak-Hyun Kim, and Gwi-Tae Park. Zmp based neural network inspired humanoid robot control. *Nonlinear Dynamics*, 67(1):793–806, 2012.