



PAREXLANKO

EXTERNAL INSULATION FACADE SYSTEM REPORTS

EI120421
rev001



TRADECRAFT
BUILDING PRODUCTS

Contents

Basecoat Report3

Boarding Report4

Preparation Report.....5

Complaints Report.....6

Complaints Procedure7

Product Information.....8

Finish Report.....9

Component List10

Project Completion Report.....12

Site Survey13

 Sketch of wall build up :.....13

 BUILDING TYPE 14

 ELECTRICAL DETAILS.....14

 PLUMBING DETAILS.....14

 GENERAL DETAILS.....15

 MATERIAL DETAILS16

 HEALTH AND SAFETY.....17

 BUILDING SKETCH.....18

 BUILDING SKETCH.....19

 BUILDING SKETCH.....20

 SILL MEASUREMENTS DETAILS.....21

Client Name :

Date : / /

Address :

Reference Number :

Supervisor :

Temperature :

Weather Conditions :

Impact Resistance Category :

Inspection :

EIFS System :

ONSITE CHECK LIST

- | | | |
|--|--|---|
| ☐ Scaffolding Secure | ☐ Health & Safety | ☐ Gutter Pipes Secure |
| ☐ All Vents Clear/ Sills Secure | ☐ Boards Dry/Clean | ☐ Double Mesh |
| ☐ Plinth Complete | ☐ Materials Protected/Checked | ☐ Stress Points Meshed |
| ☐ 5mm applied with mesh | ☐ Windows protected | |

Notes :

Checked By :

☐ Photo's

Client Name :

Date : / /

Address :

Reference Number :

Supervisor :

Temperature :

Weather Conditions :

Insulation Type :

Inspection :

EIFS System :

ONSITE CHECK LIST

- | | | |
|--|--|--|
| ☐ Scaffolding Secure | ☐ Drain covers clear | ☐ Substrate dry/clean |
| ☐ Materials Protected | ☐ All vents clear | ☐ Fire break required |
| ☐ Boards Staggered | ☐ Soffit insulation | ☐ Lead flashing installed |
| ☐ L detail complete | ☐ Below ground insulation | |
| ☐ 4-5 fixings installed per sheet | Fixing type <input type="text"/> | Length <input type="text"/> |
| ☐ Plinth insulation | ☐ Reveal insulation | ☐ Sill insulation |

Notes :

Checked By :

☐ Photo's

Client Name :

Date : / /

Address :

Reference Number :

Supervisor :

Temperature :

Inspection :

Sills/Reveals Removed :

EIFS System :

ONSITE CHECK LIST

- | | | |
|--|--|---|
| ☐ Scaffolding Secure | ☐ Health & Safety | ☐ Substrate dry/clean |
| ☐ Test Fixings in Substrate | ☐ Access Maintained | ☐ Electric's sleeved |
| ☐ All vents clear | ☐ Gas box to be moved | ☐ Gates to be moved |
| ☐ Plumbing Secure | ☐ Drains to be moved | ☐ Satellite dish moved |
| ☐ Cavity closed/pumped | ☐ Special features | ☐ Movement joints |

Notes :

Checked By :

☐ Photo's

Client Name

:

Date

:

/

/

Address

:

Reference Number

:

Years completed

:

.....

Nature of problem:

Caue of problem:

Prevention of problem :

Checked By :

Photo's

6

Client Name

:

Date

:

/

/

Address

:

Reference Number

:

Taken by

:

.....

Action:

Arrange site inspection by

:

Date of inspection

:

/

/

General details of complaint from client :

Reaction:

- Fill out complaints form
- Rectify problem
- File forms

Signed by :

7

Client Name	:	
Date	:	/ /
Address	:	
Reference Number	:	
Supervisor	:	
EIFS System	:	

.....

Insert batch numbers from products where applicable

Product:

Batch No:

Insulation	:		
Insulation	:		
Fixings	:		
Starter Track	:		
Basecoat	:		
Insulation	:		
Finish Coat	:		
Reinforcing Mesh	:		

Checked By :

Client Name :

Date : / /

Address :

Reference Number :

Supervisor :

Temperature :

Weather Conditions :

Inspection :

EIFS System :

ONSITE CHECK LIST

- | | |
|--|--|
| ☐ Scaffolding Secure | ☐ Health & Safety |
| ☐ Materials Protected/Checked | ☐ Basecoat Dry/Clean |
| ☐ Check colour | ☐ Mastic pipes/penetrations |
| ☐ Check beads/seals | ☐ Clean over spills |

Notes :

Checked By :

☐ Photo's

Date : / /

Approved Applicator :

Contractor :

Job Reference :

Details	Amount
Starter Track & Stop Bead (2.5m per length)	
Fixing Kit Required (8 per length)	
XPS Insulation (1200mm x 600mm)	
Rockwool Insulation (1200mm x 600mm)	
EPS (1200mm x 600mm)	
Insulation Fixings (200 per box) *50mm longer than insulation	
Maite Basecoat/Facite (3.6-4m ² per bag)	
Maite Dry Dash Receiver	
UNITE-Basecoat/Finish Coat (1m ² per bag)	
Caliso Adhesive (6m ² per bag)	
Mesh Type-AVU (1m x 50m) AVR (1m x 25m)	

Details	Amount
Acrylic Type- Siloxane TG 1.6mm (10m ² per 25kg bucket)	
Primer(Regulator) (50m ² per 20kg bucket)	
Finish Colour	
EHI Mineral Finish (1.4m ² per 25kg bag)	
Angle Bead	
Frame SealBead	
Stop Bead	
Silicone Sealer (310ml per tube)	
Movement Bead	

Client Name :

Date : / /

Address :

Reference Number :

Supervisor :

Temperature :

Weather Conditions :

Inspection :

EIFS System :

ONSITE CHECK LIST

- | | | |
|--|---|---|
| ☐ <i>Install Soffit Ventilation</i> | ☐ <i>Examine Seals</i> | ☐ <i>Check pipework/drains</i> |
| ☐ <i>Clean all areas</i> | ☐ <i>Check all electrics</i> | ☐ <i>Check finish quality</i> |
| ☐ <i>Issue manual/warranty</i> | ☐ <i>Issue Invoice</i> | |

Notes :

Checked By :

☐ Photo's

Name	:	
Date	:	/ /
Address	:	
Conatct Number	:	
Reference Number	:	
Inspected by	:	
Planning Issues	:	
Wall construction build up	:	

.....

Sketch of wall build up :

*Add size of layers

Boroscope Inspection : ☒ Yes

☐ No

BUILDING TYPE

☐ Detached

☐ Semi-Detached

☐ Terraced

☐ Bungalow

☐ Du-plex

☐ High Rise

Structure Condition :

Pull test required for fixings required:

☐ Yes

☐ No

ELECTRICAL DETAILS

☐ Phone lines

☐ Phone boxes

☐ ESB cables

☐ ESB cabinet

☐ Extractor fans

☐ Satellite

☐ Lights

☐ Alarm Box

☐ Sensors

☐ Door bell

☐ Camera

☐ Intercom

☐ ESB brackets

☐ Earth rod boxes

☐ Comms boxes

All cables must be protected with conduit and surface mounted!

PLUMBING DETAILS

☐ Gas metre box

☐ Gas pipes

☐ Rainwater pipes

☐ Boiler flue

☐ Overflow

☐ Soil pipe

☐ Sink pipe

☐ Shower pipe

☐ Manhole

☐ Drain outlets

☐ Garden tap

All gas pipes and boxes to be adjusted by RGI installers only!

GENERAL DETAILS

- | | | |
|---|---|---|
| ☐ Wall vents | ☐ Soffit Vents | ☐ Hanging basket |
| ☐ Garage | ☐ Extension | ☐ Conservatory |
| ☐ Quoin Stone | ☐ Plinth | ☐ Gates |
| ☐ Clothes line | ☐ Tree/plants | ☐ Flower beds |
| ☐ Coal Bunker | ☐ Boiler house | ☐ Garden wall |
| ☐ Oil/Gas tank | ☐ Letter Box | ☐ Boundary Walls |
| ☐ Abutting Garden Wall | ☐ Abutting Boundary Wall | |

.....

Impact Category : BBQ Area :

Internal Insulation Build up :

Signs of dampness/moisture :

Clean Substrate :

Movement Joints :

Decorative bonded slips of facing materials :

Surface/facade finish :

Photos of walls/general details taken: ☐ Yes ☐ No

Surface features :

Structural Fixings :

Chimney Details :

Insulating Soffit : ☐ Yes ☐ No Insulating below ground : ☐ Yes ☐ No

Hollow Block Cavity Sealed : ☐ Yes ☐ No

Abutting Roofs :

Surface/Structural Cracks :

Condition of window/door heads :

Window/Door reveals clearance : mm

Floor Type :

Floor Ventilation :

Roof Ventilation :

Will soffit ventilation be obstructed, if present : ☐ Yes ☐ No ☐ N/A

If attic ventilation is obstructed, please state remediation measures :

Flashings required :

Flashing sizes :

Cold Bridging Issues :

Closed Cavity : ☐ Yes ☐ No

Customer Issues :

MATERIAL DETAILS

Window Sill Number

Sill Type ☐ Concrete ☐ Powder coat metal

Insulation type ☐ Rockwool ☐ White HD Aged EPS ☐ Grey Aged EPS

Insulation Thickness mm

XPS Plinth Insulation ☐ Yes ☐ No

Fire Break ☐ Yes ☐ No

HEALTH AND SAFETY

Areas and reason an area cannot receive external insulation:

Option of internal insulation:

Scaffolding details:

Accessibility :

Neighbouring building concerns:

Planning Restrictions : ☐ Yes ☐ No

Note:

Building sketch requirements.
Please put in measurements of all elevations.
Every element and feature must be shown in the sketch.

BUILDING SKETCH

Reference:

Please note overhang depth:

Front Elevation

.....

Please note overhang depth:

Back Elevation

.....

BUILDING SKETCH

Reference:

Please note overhang depth:

Side Elevation

.....

Please note overhang depth:

Side Elevation

.....

BUILDING SKETCH

Reference:

Please note overhang depth:

Side Elevation

.....

Please note overhang depth:

Side Elevation

.....

DARK SILLS ARE NOT RECOMMENDED
SILL MEASUREMENTS DETAILS

Job Reference :

Colour Required :

