

# Quantum Computing Seminar 5

YongHyun “Aeren” An

Samsung Research

December 2, 2024

December 16, 2024

# Entanglement

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob , without seeing its color.

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob , without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob 's ball as well.

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob, without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob's ball as well.
- Are the colors of their balls entangled?

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob, without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob's ball as well.
- Are the colors of their balls entangled? No.

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob, without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob's ball as well.
- Are the colors of their balls entangled? No.
- The followings are typical explanations of entanglement.
  - Measuring one qubit instantaneously affects the state of the other.
  - The state of the two qubits together cannot be described separately.
  - The two qubits maintains maintain a memory of each other.



# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob, without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob's ball as well.
- Are the colors of their balls entangled? No.
- The followings are typical explanations of entanglement.
  - Measuring one qubit instantaneously affects the state of the other.
  - The state of the two qubits together cannot be described separately.
  - The two qubits maintains maintain a memory of each other.
- All of these are true but fails to distinguish the above non-entangled probabilistic state with an entanglement in a meaningful way.

# Entanglement

- Let's say there are two boxes  $R$  and  $B$ , each containing 2 red balls and 2 blue balls respectively.
- Alice randomly selects a box and distribute the balls inside it to her and Bob, without seeing its color.
- Once Alice sees the color of her ball, she knows the color of Bob's ball as well.
- Are the colors of their balls entangled? No.
- The followings are typical explanations of entanglement.
  - Measuring one qubit instantaneously affects the state of the other.
  - The state of the two qubits together cannot be described separately.
  - The two qubits maintains maintain a memory of each other.
- All of these are true but fails to distinguish the above non-entangled probabilistic state with an entanglement in a meaningful way.
- The power of entanglement lies in what we can do with it.

# Entanglement

- We'll take a look at **(A) teleportation protocol**, **(B) superdense coding protocol**, and **(C) CHSH game**, all of which are stones in the foundation of quantum information.

# Entanglement

- We'll take a look at **(A) teleportation protocol**, **(B) superdense coding protocol**, and **(C) CHSH game**, all of which are stones in the foundation of quantum information.
- They all consume a pair of entangled qubits  $|\phi^+\rangle = \frac{1}{\sqrt{2}}|00\rangle + \frac{1}{\sqrt{2}}|11\rangle$  as a resource, which we'll call an **e-bit**.

# Entanglement


- We'll take a look at **(A) teleportation protocol**, **(B) superdense coding protocol**, and **(C) CHSH game**, all of which are stones in the foundation of quantum information.
- They all consume a pair of entangled qubits  $|\phi^+\rangle = \frac{1}{\sqrt{2}}|00\rangle + \frac{1}{\sqrt{2}}|11\rangle$  as a resource, which we'll call an **e-bit**.
- All of these are either impossible if we have a pair of non-entangled probabilistic bits instead of an e-bit.

# Teleportation Protocol

# Teleportation Protocol


<b>Preparation</b>	Alice and Bob each have a qubit, together forming an e-bit
<b>Objective</b>	Alice sends Bob one qubit of quantum information
<b>Communication</b>	Alice sends Bob two bits of classical information

## Protocol Overview






# Teleportation Protocol




# Teleportation Protocol




$$\begin{aligned}
 |\pi_0\rangle &= |\phi^+\rangle \otimes (\alpha|0\rangle + \beta|1\rangle) = \frac{1}{\sqrt{2}} (\alpha|000\rangle + \alpha|110\rangle + \beta|001\rangle + \beta|111\rangle) \\
 &= \frac{1}{2} (\alpha|0\rangle \otimes (|\phi^+\rangle + |\phi^-\rangle) + \alpha|1\rangle \otimes (|\psi^+\rangle - |\psi^-\rangle) + \beta|0\rangle \otimes (|\psi^+\rangle + |\psi^-\rangle) + \beta|1\rangle \otimes (|\phi^+\rangle - |\phi^-\rangle)) \\
 &= \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |\phi^+\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |\phi^-\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |\psi^+\rangle - (\alpha|1\rangle - \beta|0\rangle) \otimes |\psi^-\rangle)
 \end{aligned}$$

# Teleportation Protocol



$$\begin{aligned}
 |\pi_2\rangle &= (I_2 \otimes I_2 \otimes H)(I_2 \otimes CX_{0,1})|\pi_0\rangle \\
 &= \frac{1}{2}((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)
 \end{aligned}$$

# Teleportation Protocol



$$\begin{aligned}
 |\pi_2\rangle &= (I_2 \otimes I_2 \otimes H)(I_2 \otimes CX_{0,1})|\pi_0\rangle \\
 &= \frac{1}{2}((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)
 \end{aligned}$$

There are 4 possible outcomes to **Alice** 's measurement.

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow$



# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle - \beta|1\rangle$



# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle - \beta|1\rangle$
- **Bob's Action**  $\rightarrow$

# Teleportation Protocol

## Outcome 00

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle + \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  do nothing

## Outcome 01

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|0\rangle - \beta|1\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $Z$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$



# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle - \beta|0\rangle$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle - \beta|0\rangle$
- **Bob's Action**  $\rightarrow$

# Teleportation Protocol

## Outcome 10

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle + \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$

## Outcome 11

$$|\pi_2\rangle = \frac{1}{2} ((\alpha|0\rangle + \beta|1\rangle) \otimes |00\rangle + (\alpha|0\rangle - \beta|1\rangle) \otimes |01\rangle + (\alpha|1\rangle + \beta|0\rangle) \otimes |10\rangle + (\alpha|1\rangle - \beta|0\rangle) \otimes |11\rangle)$$

- **Probability**  $\rightarrow 1/4$
- **State of B**  $\rightarrow \alpha|1\rangle - \beta|0\rangle$
- **Bob's Action**  $\rightarrow$  Apply  $X$ , then apply  $Z$



# Teleportation Protocol

- Q) What exactly is **Alice** doing?

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?
  - Nothing. The outcome of her measurement has probability distribution independent from the initial state of  $Q$ .

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?
  - Nothing. The outcome of her measurement has probability distribution independent from the initial state of  $Q$ .
  - This turns out to be essential for the protocol to work. Extracting any amount of information from a qubit necessarily disturbs it.

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?
  - Nothing. The outcome of her measurement has probability distribution independent from the initial state of  $Q$ .
  - This turns out to be essential for the protocol to work. Extracting any amount of information from a qubit necessarily disturbs it.
- Q) What if  $Q$  is entangled with some other qubits?

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?
  - Nothing. The outcome of her measurement has probability distribution independent from the initial state of  $Q$ .
  - This turns out to be essential for the protocol to work. Extracting any amount of information from a qubit necessarily disturbs it.
- Q) What if  $Q$  is entangled with some other qubits?
  - The state of **Bob** 's qubit at the end has the same entangled state as the initial state of  $Q$ .

# Teleportation Protocol

- Q) What exactly is **Alice** doing?
  - Bell basis measurement
- Q) What information does **Alice** gain about the initial state of  $Q$  from her measurement?
  - Nothing. The outcome of her measurement has probability distribution independent from the initial state of  $Q$ .
  - This turns out to be essential for the protocol to work. Extracting any amount of information from a qubit necessarily disturbs it.
- Q) What if  $Q$  is entangled with some other qubits?
  - The state of **Bob** 's qubit at the end has the same entangled state as the initial state of  $Q$ .
  - It's not hard to repeat the same analysis to show this (left as an exercise), but it turns out that showing it for an independent qubit  $Q$  is enough, which will be discussed later.



# Teleportation Protocol

```
from qiskit import QuantumCircuit, QuantumRegister, ClassicalRegister
from qiskit_aer import AerSimulator
from qiskit.visualization import plot_histogram
from qiskit.result import marginal_distribution
from qiskit.circuit.library import UGate
from numpy import pi, random
```

```
Q = QuantumRegister(1, "Q")
A = QuantumRegister(1, "A")
B = QuantumRegister(1, "B")
C = ClassicalRegister(2, "C")
```

```
protocol = QuantumCircuit(Q, A, B, C)
```

```
# Alice's operations
```

```
protocol.cx(Q, A)
```

```
protocol.h(Q)
```

```
protocol.barrier()
```

```
# Alice measures and sends classical bits to Bob
```

```
protocol.measure(A, C[0])
```

```
protocol.measure(Q, C[1])
```

```
protocol.barrier()
```

```
# Bob uses the classical bits to conditionally apply gates
```


```
with protocol.if_test((C[0], 1)):
```

```
    protocol.x(B)
```

```
with protocol.if_test((C[1], 1)):
```

```
    protocol.z(B)
```

```
protocol.draw(output = "mpl", cregbundle = False)
```



# Teleportation Protocol

```
runner = QuantumCircuit(Q, A, B, C)

# Make random gate
random_gate = UGate(
    theta=random.random() * 2 * pi,
    phi=random.random() * 2 * pi,
    lam=random.random() * 2 * pi,
)


# Randomly selected state on Q
runner.append(random_gate, Q)

# Entangle A and B
runner.h(A)
runner.cx(A, B)
runner.barrier(label = "Protocol Start")

# Run protocol
runner = runner.compose(protocol)
runner.barrier(label = "Protocol End")


# Check the result
runner.append(random_gate.inverse(), B)
result = ClassicalRegister(1, "Result")
runner.add_register(result)
runner.measure(B, result)

runner.draw(output = "mpl", cregbundle = False)
```



# Teleportation Protocol

```
result = AerSimulator().run(runner).result()
statistics = marginal_distribution(result.get_counts(), [2])
plot_histogram(statistics)
```




# Superdense Coding Protocol


# Superdense Coding Protocol

<b>Preparation</b>	Alice and Bob each have a qubit, together forming an e-bit
<b>Objective</b>	Alice sends Bob two bits of classical information
<b>Communication</b>	Alice sends Bob one qubit of quantum information

## Protocol Overview




# Superdense Coding Protocol



We only have 4 cases to analyze

# Superdense Coding Protocol



We only have 4 cases to analyze

Input	Initial state	State after <b>Alice</b> 's operation	<b>Bob</b> 's measurement
00	$ \phi^+\rangle$	$ \phi^+\rangle$	00
01	$ \phi^+\rangle$	$ \phi^-\rangle$	01
10	$ \phi^+\rangle$	$ \psi^+\rangle$	10
11	$ \phi^+\rangle$	$ \psi^-\rangle$	11



# Superdense Coding Protocol

## Security of Superdense Coding

# Superdense Coding Protocol

## Security of Superdense Coding

- Suppose that an evil eavesdropper **Eve** intercepted the qubit sent by **Alice**

# Superdense Coding Protocol

## Security of Superdense Coding

- Suppose that an evil eavesdropper **Eve** intercepted the qubit sent by **Alice**
- For the input  $c$  and  $d$ , **Alice** 's operation converts the state into

$$|u\rangle = \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |c\rangle + (-1)^d |1\rangle \otimes |1-c\rangle \right)$$

# Superdense Coding Protocol

## Security of Superdense Coding

- Suppose that an evil eavesdropper **Eve** intercepted the qubit sent by **Alice**
- For the input  $c$  and  $d$ , **Alice** 's operation converts the state into

$$|u\rangle = \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |c\rangle + (-1)^d |1\rangle \otimes |1-c\rangle \right)$$

- For an arbitrary projective measurement  $M = \{ |b_0\rangle \langle b_0|, |b_1\rangle \langle b_1| \}$  on the qubit,

# Superdense Coding Protocol

## Security of Superdense Coding

- Suppose that an evil eavesdropper Eve intercepted the qubit sent by Alice
- For the input  $c$  and  $d$ , Alice's operation converts the state into

$$|u\rangle = \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |c\rangle + (-1)^d |1\rangle \otimes |1-c\rangle \right)$$

- For an arbitrary projective measurement  $M = \{ |b_0\rangle\langle b_0|, |b_1\rangle\langle b_1| \}$  on the qubit,

$$\begin{aligned} \mathcal{P}_{M=k}(|u\rangle) &= \left| \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |b_k\rangle\langle b_k|c\rangle + (-1)^d |1\rangle \otimes |b_k\rangle\langle b_k|1-c\rangle \right) \right|^2 \\ &= \frac{1}{2} \left( |\langle b_k|c\rangle|^2 + |\langle b_k|1-c\rangle|^2 \right) = \frac{1}{2} \end{aligned}$$

# Superdense Coding Protocol

## Security of Superdense Coding

- Suppose that an evil eavesdropper **Eve** intercepted the qubit sent by **Alice**
- For the input  $c$  and  $d$ , **Alice** 's operation converts the state into

$$|u\rangle = \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |c\rangle + (-1)^d |1\rangle \otimes |1-c\rangle \right)$$

- For an arbitrary projective measurement  $M = \{ |b_0\rangle \langle b_0|, |b_1\rangle \langle b_1| \}$  on the qubit,

$$\begin{aligned} \mathcal{P}_{M=k}(|u\rangle) &= \left| \frac{1}{\sqrt{2}} \left( |0\rangle \otimes |b_k\rangle \langle b_k|c\rangle + (-1)^d |1\rangle \otimes |b_k\rangle \langle b_k|1-c\rangle \right) \right|^2 \\ &= \frac{1}{2} \left( |\langle b_k|c\rangle|^2 + |\langle b_k|1-c\rangle|^2 \right) = \frac{1}{2} \end{aligned}$$

- Therefore, **Eve** cannot gain any information.

# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .

# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .
- Teleportation protocol allows us to send 1 qubit by sending 2 classical bits, and the hypothetical protocol allows us to send 2 classical bits by sending 1 qubit, so by combining them, we can send  $2 + \epsilon$  classical bits by sending 2 classical bits.



# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .
- Teleportation protocol allows us to send 1 qubit by sending 2 classical bits, and the hypothetical protocol allows us to send 2 classical bits by sending 1 qubit, so by combining them, we can send  $2 + \epsilon$  classical bits by sending 2 classical bits.
- Composing them enough times allows us to send arbitrary long message by sending 2 classical bits. This sounds crazy enough, but there is more!

# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .
- Teleportation protocol allows us to send 1 qubit by sending 2 classical bits, and the hypothetical protocol allows us to send 2 classical bits by sending 1 qubit, so by combining them, we can send  $2 + \epsilon$  classical bits by sending 2 classical bits.
- Composing them enough times allows us to send arbitrary long message by sending 2 classical bits. This sounds crazy enough, but there is more!
- Now, instead of receiving 2 classical bits, Bob can guess one of the 4 result. With the help of checksum, Bob can tell whether the guess was correct. Note that nothing is physically being transferred.

# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .
- Teleportation protocol allows us to send 1 qubit by sending 2 classical bits, and the hypothetical protocol allows us to send 2 classical bits by sending 1 qubit, so by combining them, we can send  $2 + \epsilon$  classical bits by sending 2 classical bits.
- Composing them enough times allows us to send arbitrary long message by sending 2 classical bits. This sounds crazy enough, but there is more!
- Now, instead of receiving 2 classical bits, Bob can guess one of the 4 result. With the help of checksum, Bob can tell whether the guess was correct. Note that nothing is physically being transferred.
- The probability that Bob guesses correctly at least once out of  $N = 100$  attempt is  $1 - \left(\frac{3}{4}\right)^{100} \approx 1 - 3.2072022 \cdot 10^{-13}$ , and Bob almost surely can receive the message without physically receiving anything.

# Superdense Coding Protocol

## Ultradense Coding

- Suppose there exists a protocol which can send  $2 + \epsilon$  classical bits by sending 1 qubit for some positive real  $\epsilon$ .
- Teleportation protocol allows us to send 1 qubit by sending 2 classical bits, and the hypothetical protocol allows us to send 2 classical bits by sending 1 qubit, so by combining them, we can send  $2 + \epsilon$  classical bits by sending 2 classical bits.
- Composing them enough times allows us to send arbitrary long message by sending 2 classical bits. This sounds crazy enough, but there is more!
- Now, instead of receiving 2 classical bits, **Bob** can guess one of the 4 result. With the help of checksum, **Bob** can tell whether the guess was correct. Note that nothing is physically being transferred.
- The probability that **Bob** guesses correctly at least once out of  $N = 100$  attempt is  $1 - \left(\frac{3}{4}\right)^{100} \approx 1 - 3.2072022 \cdot 10^{-13}$ , and **Bob** almost surely can receive the message without physically receiving anything.
- **Alice** and **Bob** now have achieved a faster-than-light communication.

# Superdense Coding Protocol

```
from qiskit import QuantumCircuit, QuantumRegister, ClassicalRegister
from qiskit_aer.primitives import Sampler
from qiskit_aer import AerSimulator
from qiskit.visualization import plot_histogram
```

```
A = QuantumRegister(1, "A")
B = QuantumRegister(1, "B")
C_Alice = ClassicalRegister(2, "C_Alice")
C_Bob = ClassicalRegister(2, "C_Bob")


protocol = QuantumCircuit(A, B, C_Alice, C_Bob)

# Alice modifies her qubit then send it to Bob
with protocol.if_test((C_Alice[0], 1)):
    protocol.z(A)
with protocol.if_test((C_Alice[1], 1)):
    protocol.x(A)
protocol.barrier()

# Bob's operation
protocol.cx(A, B)
protocol.h(A)
protocol.barrier()

# Bob's measurement
protocol.measure(A, C_Bob[0])
protocol.measure(B, C_Bob[1])

protocol.draw(output = "mpl", cregbundle = False)
```



# Superdense Coding Protocol


```
R = QuantumRegister(1, "Randomizer")
runner = QuantumCircuit(A, B, R, C_Alice, C_Bob)

# Make random bits
runner.h(R)
runner.measure(R, C_Alice[0])
runner.h(R)
runner.measure(R, C_Alice[1])

# Entangle A and B
runner.h(A)
runner.cx(A, B)
runner.barrier(label = "Protocol Start")


# Run protocol
runner = runner.compose(protocol)
runner.barrier(label = "Protocol End")

# Check the result
runner.draw(output = "mpl", cregbundle = False)
```



# Superdense Coding Protocol


```
result = AerSimulator().run(runner).result()
statistics = result.get_counts()
display(plot_histogram(statistics))
```







## Game Description



$(x, y)$	win	lose
$(0, 0)$	$a = b$	$a \neq b$
$(0, 1)$	$a = b$	$a \neq b$
$(1, 0)$	$a = b$	$a \neq b$
$(1, 1)$	$a \neq b$	$a = b$

- It is a cooperative game where **Alice** and **Bob** work together to achieve a particular outcome.
- A referee uniformly and randomly choose a pair of integer  $x$  and  $y$ , each of which are either 0 or 1, and give  $x$  to **Alice** and  $y$  to **Bob**
- Alice** and **Bob** each replies with an integer  $a$  and  $b$ , each of which are again 0 or 1. They win according to the table on the left.
- Alice** and **Bob** can discuss their strategy beforehand, but they're not allowed to communicate after the game starts.

## Classical Strategy (Deterministic)

## Classical Strategy (Deterministic)

- Here, Alice and Bob 's responses are functions of  $x$  and  $y$ , i.e.  $a = f(x)$  and  $b = g(y)$  for some  $f$  and  $g$ .

## Classical Strategy (Deterministic)

- Here, Alice and Bob 's responses are functions of  $x$  and  $y$ , i.e.  $a = f(x)$  and  $b = g(y)$  for some  $f$  and  $g$ .
- Q) Can they win on all inputs?

## Classical Strategy (Deterministic)

- Here, **Alice** and **Bob** 's responses are functions of  $x$  and  $y$ , i.e.  $a = f(x)$  and  $b = g(y)$  for some  $f$  and  $g$ .
- Q) Can they win on all inputs? No.

## Classical Strategy (Deterministic)

- Here, Alice and Bob's responses are functions of  $x$  and  $y$ , i.e.  $a = f(x)$  and  $b = g(y)$  for some  $f$  and  $g$ .
- Q) Can they win on all inputs? No.
- However,  $f(x) = g(x) = 0$  allows them to win on 3 out of 4 possible inputs. Thus, the best deterministic strategy has the winning probability of 0.75.

## Classical Strategy (Probabilistic)

## Classical Strategy (Probabilistic)

- A probabilistic strategy can be regarded as choosing a deterministic strategy at random.



## Classical Strategy (Probabilistic)

- A probabilistic strategy can be regarded as choosing a deterministic strategy at random.
- Since the average is equal or less than the maximum, it cannot perform better than a deterministic one.

## Classical Strategy (Probabilistic)

- A probabilistic strategy can be regarded as choosing a deterministic strategy at random.
- Since the average is equal or less than the maximum, it cannot perform better than a deterministic one.
- Therefore, the best probabilistic strategy has the winning probability of 0.75.

## Quantum Strategy

- Can they achieve a better winning probability than 0.75 if they had prepared a shared e-bit?

## Quantum Strategy

- Can they achieve a better winning probability than 0.75 if they had prepared a shared e-bit?
- The answer is yes. We demonstrate one such strategy.

# CHSH Game

## Quantum Strategy

We define the following variables.

# CHSH Game

## Quantum Strategy

We define the following variables.

1.

$$|\psi_{\theta}\rangle = \cos(\theta) |0\rangle + \sin(\theta) |1\rangle$$

# CHSH Game

## Quantum Strategy

We define the following variables.

1.

$$|\psi_{\theta}\rangle = \cos(\theta) |0\rangle + \sin(\theta) |1\rangle$$

It represents the point at angle  $\theta$  on the unit circle.

# CHSH Game

## Quantum Strategy

We define the following variables.

1.

$$|\psi_\theta\rangle = \cos(\theta) |0\rangle + \sin(\theta) |1\rangle$$

It represents the point at angle  $\theta$  on the unit circle.

The following formulae can easily be verified.

- $\langle\psi_\alpha|\psi_\beta\rangle = \cos(\alpha - \beta)$
- $\langle\psi_\alpha \otimes \psi_\beta|\phi^+\rangle = \frac{1}{\sqrt{2}} \cos(\alpha - \beta) = \frac{1}{\sqrt{2}} \langle\psi_\alpha|\psi_\beta\rangle$



# CHSH Game

## Quantum Strategy

We define the following variables.

1.

$$|\psi_\theta\rangle = \cos(\theta) |0\rangle + \sin(\theta) |1\rangle$$

It represents the point at angle  $\theta$  on the unit circle.

The following formulae can easily be verified.

- $\langle\psi_\alpha|\psi_\beta\rangle = \cos(\alpha - \beta)$
- $\langle\psi_\alpha \otimes \psi_\beta|\phi^+\rangle = \frac{1}{\sqrt{2}} \cos(\alpha - \beta) = \frac{1}{\sqrt{2}} \langle\psi_\alpha|\psi_\beta\rangle$

2.

$$\begin{aligned} U_\theta &= |0\rangle \langle\psi_\theta| + |1\rangle \langle\psi_{\theta+\pi/2}| \\ &= \begin{bmatrix} \cos(\theta) & \sin(\theta) \\ -\sin(\theta) & \cos(\theta) \end{bmatrix} \end{aligned}$$

# CHSH Game

## Quantum Strategy

We define the following variables.

1.

$$|\psi_\theta\rangle = \cos(\theta) |0\rangle + \sin(\theta) |1\rangle$$

It represents the point at angle  $\theta$  on the unit circle.

The following formulae can easily be verified.


- $\langle\psi_\alpha|\psi_\beta\rangle = \cos(\alpha - \beta)$
- $\langle\psi_\alpha \otimes \psi_\beta|\phi^+\rangle = \frac{1}{\sqrt{2}} \cos(\alpha - \beta) = \frac{1}{\sqrt{2}} \langle\psi_\alpha|\psi_\beta\rangle$

2.

$$\begin{aligned} U_\theta &= |0\rangle \langle\psi_\theta| + |1\rangle \langle\psi_{\theta+\pi/2}| \\ &= \begin{bmatrix} \cos(\theta) & \sin(\theta) \\ -\sin(\theta) & \cos(\theta) \end{bmatrix} \end{aligned}$$

It represents the clockwise rotation by  $\theta$ .

# Strategy Overview



# CHSH Game

**Alice** and **Bob** are choosing angles  $\alpha$  (which is 0 if  $x = 0$  and  $\pi/4$  otherwise) and  $\beta$  (which is  $\pi/8$  if  $y = 0$  and  $-\pi/8$  otherwise) depending on  $x$  and  $y$ , applying  $U_\alpha$  and  $U_\beta$ , then measuring their qubit.

$$\begin{aligned} & (U_\alpha \otimes U_\beta) |\phi^+\rangle \\ &= |00\rangle \langle \psi_\alpha \otimes \psi_\beta | \phi^+ \rangle + |01\rangle \langle \psi_\alpha \otimes \psi_{\beta+\pi/2} | \phi^+ \rangle + |10\rangle \langle \psi_{\alpha+\pi/2} \otimes \psi_\beta | \phi^+ \rangle \\ &+ |11\rangle \langle \psi_{\alpha+\pi/2} \otimes \psi_{\beta+\pi/2} | \phi^+ \rangle \\ &= \frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle) \end{aligned}$$

# CHSH Game

$$\frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle)$$



The probabilities of each outcome can be thought of as the following.

# CHSH Game

$$\frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle)$$

The probabilities of each outcome can be thought of as the following.

**Alice** and **Bob** first pick the following orthonormal basis, where **blue** represents 0 and **red** represents 1.



The probability of each outcome is  $\frac{1}{2} \cos^2(\theta)$  where  $\theta$  is the angle between corresponding vectors of **Alice** and **Bob**

# CHSH Game

$$\frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle)$$

And finally,

$$\mathcal{P}(a = b) = \frac{1}{2} |\langle \psi_\alpha | \psi_\beta \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle|^2 = \cos^2(\alpha - \beta)$$

$$\mathcal{P}(a \neq b) = \frac{1}{2} |\langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle|^2 = \sin^2(\alpha - \beta)$$

# CHSH Game

$$\frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle)$$

And finally,

$$\mathcal{P}(a = b) = \frac{1}{2} |\langle \psi_\alpha | \psi_\beta \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle|^2 = \cos^2(\alpha - \beta)$$

$$\mathcal{P}(a \neq b) = \frac{1}{2} |\langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle|^2 = \sin^2(\alpha - \beta)$$

Can be interpreted as  $\cos^2(\lambda)$  and  $\sin^2(\lambda)$  where  $\lambda$  is the angle between vectors of the same color.



# CHSH Game

$$\frac{1}{\sqrt{2}} (\langle \psi_\alpha | \psi_\beta \rangle |00\rangle + \langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle |01\rangle + \langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle |10\rangle + \langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle |11\rangle)$$

And finally,

$$\mathcal{P}(a = b) = \frac{1}{2} |\langle \psi_\alpha | \psi_\beta \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_{\beta+\pi/2} \rangle|^2 = \cos^2(\alpha - \beta)$$


$$\mathcal{P}(a \neq b) = \frac{1}{2} |\langle \psi_\alpha | \psi_{\beta+\pi/2} \rangle|^2 + \frac{1}{2} |\langle \psi_{\alpha+\pi/2} | \psi_\beta \rangle|^2 = \sin^2(\alpha - \beta)$$

Can be interpreted as  $\cos^2(\lambda)$  and  $\sin^2(\lambda)$  where  $\lambda$  is the angle between vectors of the same color.

Note that you can pick any such pair of vectors and the result will be the same.


# CHSH Game

Case  $(x, y) = (0, 0)$



# CHSH Game


Case  $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) =$

# CHSH Game


Case  $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$

# CHSH Game


Case  $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) =$

# CHSH Game


Case  $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$

# CHSH Game


Case  $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =

# CHSH Game

Case  $(x, y) = (0, 0)$




- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$




# CHSH Game

## Case $(x, y) = (0, 0)$




- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

## Case $(x, y) = (0, 1)$




# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) =$


# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$


# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) =$


# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$


# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =


# CHSH Game

## Case $(x, y) = (0, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (0, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

# CHSH Game


Case  $(x, y) = (1, 0)$





# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) =$

# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$

# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) =$

# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$

# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =

# CHSH Game


Case  $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


# CHSH Game

## Case $(x, y) = (1, 0)$




- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

## Case $(x, y) = (1, 1)$




# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

## Case $(x, y) = (1, 1)$




- $\mathcal{P}(a = b) =$




# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (1, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{3\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$


# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (1, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{3\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) =$


# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (1, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{3\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{3\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$


# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$


## Case $(x, y) = (1, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{3\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{3\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- (Winning Probability) =


# CHSH Game

## Case $(x, y) = (1, 0)$



- $\mathcal{P}(a = b) = \cos\left(\frac{\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

## Case $(x, y) = (1, 1)$



- $\mathcal{P}(a = b) = \cos\left(\frac{3\pi}{8}\right)^2 = \frac{2-\sqrt{2}}{4}$
- $\mathcal{P}(a \neq b) = \sin\left(\frac{3\pi}{8}\right)^2 = \frac{2+\sqrt{2}}{4}$
- (Winning Probability) =  $\frac{2+\sqrt{2}}{4}$

- We conclude that this strategy has the winning probability of  $\frac{2+\sqrt{2}}{4} \approx 0.85355$ , which is exceeding the classical bound of 0.75.

# CHSH Game

- We conclude that this strategy has the winning probability of  $\frac{2+\sqrt{2}}{4} \approx 0.85355$ , which is exceeding the classical bound of 0.75.
- It turns out that  $\frac{2+\sqrt{2}}{4}$  is the upper bound of quantum strategy. See **Tsirelson's bound**.

- We conclude that this strategy has the winning probability of  $\frac{2+\sqrt{2}}{4} \approx 0.85355$ , which is exceeding the classical bound of 0.75.
- It turns out that  $\frac{2+\sqrt{2}}{4}$  is the upper bound of quantum strategy. See **Tsirelson's bound**.
- The basic idea of such experiments, where entanglement leads to statistical results that are inconsistent with any classical description is due to John Bell, and people often refer to this sort of experiments as Bell Tests for this reason.



- We conclude that this strategy has the winning probability of  $\frac{2+\sqrt{2}}{4} \approx 0.85355$ , which is exceeding the classical bound of 0.75.
- It turns out that  $\frac{2+\sqrt{2}}{4}$  is the upper bound of quantum strategy. See **Tsirelson's bound**.
- The basic idea of such experiments, where entanglement leads to statistical results that are inconsistent with any classical description is due to John Bell, and people often refer to this sort of experiments as Bell Tests for this reason.
- CHSH game acts as a straightforward proof that entanglement is real, by providing a way to “observe” the entanglement.

- We conclude that this strategy has the winning probability of  $\frac{2+\sqrt{2}}{4} \approx 0.85355$ , which is exceeding the classical bound of 0.75.
- It turns out that  $\frac{2+\sqrt{2}}{4}$  is the upper bound of quantum strategy. See **Tsirelson's bound**.
- The basic idea of such experiments, where entanglement leads to statistical results that are inconsistent with any classical description is due to John Bell, and people often refer to this sort of experiments as Bell Tests for this reason.
- CHSH game acts as a straightforward proof that entanglement is real, by providing a way to “observe” the entanglement.
- 2022 Nobel Prize in Physics was awarded to Alain Aspect, John Clauser, and Anton Zeilinger, for observing entanglement through Bell tests on entangled photons.

First, declare the CHSH game runner

```
from qiskit import QuantumCircuit
from qiskit_aer.primitives import SamplerV2
from numpy import pi
from numpy.random import randint

"""Plays the CHSH game
Args:
    strategy (callable): A function that takes two bits (as `int`s) and
        returns two bits (also as `int`s). The strategy must follow the
        rules of the CHSH game.
Returns:
    int: 1 for a win, 0 for a loss.
"""
def CHSH_game(strategy):
    # Referee chooses x and y uniformly at random
    x, y = randint(0, 2), randint(0, 2)

    # Alice and Bob chooses a and b according to their strategy
    a, b = strategy(x, y)

    return 1 if a ^ b == x & y else 0

def CHSH_game_runner(strategy, NUM_GAMES):
    WINS = 0
    for _ in range(NUM_GAMES):
        WINS += CHSH_game(strategy)
    print(f"Won {WINS} out of {NUM_GAMES} games, with winrate {WINS/NUM_GAMES}")
```

# CHSH Game

An optimal classical strategy has the winning probability of 0.75.

```
def classical_strategy(x, y):  
    """An optimal classical strategy for the CHSH game  
    Args:  
        x (int): Alice's bit (must be 0 or 1)  
        y (int): Bob's bit (must be 0 or 1)  
    Returns:  
        (int, int): Alice and Bob's answer bits (respectively)  
    """  
    # Alice's answer  
    if x == 0:  
        a = 0  
    elif x == 1:  
        a = 1  
  
    # Bob's answer  
    if y == 0:  
        b = 1  
    elif y == 1:  
        b = 0  
  
    return a, b  
  
CHSH_game_runner(strategy = classical_strategy, NUM_GAMES = 10000)
```

Won 7539 out of 10000 games, with winrate 0.7539

## Declare the CHSH circuit builder

```
def build_CHSH_circuit(x, y):
    """Creates a 'QuantumCircuit' that implements the best CHSH strategy.
    Args:
        x (int): Alice's bit (must be 0 or 1)
        y (int): Bob's bit (must be 0 or 1)
    Returns:
        QuantumCircuit: Circuit that, when run, returns Alice and Bob's
            answer bits.
    """
    qc = QuantumCircuit(2, 2)
    qc.h(0)
    qc.cx(0, 1)
    qc.barrier()

    # Alice
    if x == 0:
        qc.ry(0, 0)
    else:
        qc.ry(-pi / 2, 0)
    qc.measure(0, 0)


    # Bob
    if y == 0:
        qc.ry(-pi / 4, 1)
    else:
        qc.ry(pi / 4, 1)
    qc.measure(1, 1)

    return qc


for x in range(2):
    for y in range(2):
        print(f"Circuit for (x, y) = ({x}, {y})")
        display(build_CHSH_circuit(x, y).draw(output = "mpl", cregbundle = False))
```

# CHSH Game


Circuit for  $(x, y) = (0, 0)$




Circuit for  $(x, y) = (0, 1)$



Circuit for  $(x, y) = (1, 0)$



Circuit for  $(x, y) = (1, 1)$



# CHSH Game

An optimal quantum strategy has the winning probability of  $\frac{2+\sqrt{2}}{2} \approx 0.85355$ .

```
sampler = SamplerV2()

def quantum_strategy(x, y):
    """Carry out the best strategy for the CHSH game.
    Args:
        x (int): Alice's bit (must be 0 or 1)
        y (int): Bob's bit (must be 0 or 1)
    Returns:
        (int, int): Alice and Bob's answer bits (respectively)
    """
    # `shots=1` runs the circuit once
    result = sampler.run([build_CHSH_circuit(x, y)], shots=1).result()[0].data.c.get_counts()
    bits = list(result.keys())[0]
    a, b = int(bits[0]), int(bits[1])
    return a, b

CHSH_game_runner(strategy = quantum_strategy, NUM_GAMES = 10000)

Won 8601 out of 10000 games, with winrate 0.8601
```

The End