

Index

- 50% reaction, adiabatic efficiency and, 619–621
- Acceleration, equation of motion, 169–174
- Additive drag, 691
- Adiabatic efficiency
 - axial-flow turbine analysis, 612–614
 - blade spacing, 625
 - degree of reaction, 617
 - design metal angles, 622
 - exit swirl angle, 614
 - radial variations, 626–628
 - stage loading coefficient, 614–616
 - stage pressure ratio, 623–624
 - stage temperature ratio, 622–623
 - turbine airfoil nomenclature, 622
 - velocity ratio, 628
- Adiabatic flame temperature, chemical equilibrium and, 143–146
- Adiabatic flow, one-dimensional, 739–740
- Aeropropulsion system, xvii–xviii
 - turbojet engine, xviii
- Aerovehicle, evolution of, xv–xvii
- AFPROP computer program,
 - perfect gas and, 91–93
 - variable gas properties and, subroutine FAIR, SM Chap. 7, 38–45
- Afterburners
 - area variation, variable gas properties and, SM Chap. 8, 41–42
 - combustion systems and, 769–779
 - components, 771–777
 - afterburner liner, 777
 - atomization, 771–772
 - diffuser, 771
 - flame spread, 776–777
 - flame stabilization, 773–775
 - flame-holder-arrays, 776
 - fuel injection, 771–772
 - ignition, 772–773
 - vaporization, 771–772
 - cycle analysis, ideal turbojet and, 291–294
 - design parameters, 777–779
 - dual-spool, turbojet engine and, analysis of, SM Chap. 8, 49–61
 - equations, ideal turbojet and, 294–296
 - ideal mixed-flow turbofan and, SM Chap. 5, 1–27
 - ideal turbojet and, 291–302
 - liner, 777
 - optimum compressor pressure ratio, ideal turbojet and, 296–299
 - thrust augmentation and, 252
 - total pressure loss, 777
 - turbofan
 - mixed exhaust stream SM Chap. 7, 7–23, SM Chap. 8, 1–65
 - cycle analysis, SM Chap. 7, 13–15
 - engine mass flow, SM Chap. 8, 7–9
 - equations, SM Chap. 7, 16–23, SM Chap. 8, 9–20
 - high-pressure turbine, SM Chap. 8, 3–4
 - ideal mixer analytical model, SM Chap. 7, 8–12
 - iteration area, SM Chap. 8, 9
 - low-pressure turbine, SM Chap. 8, 3–4
 - mixer performance solution, SM Chap. 8, 4–7
 - nozzle area, SM Chap. 8, 7–9
 - separate exhaust streams, SM Chap. 7, 1–47
 - compressor type analysis, 487

Afterburners (*Continued*)turbofan (*Continued*)

- cycle analysis and, variable gas properties, SM Chap. 7, 39–40
- cycle analysis, SM Chap. 7, 1–3
- engine performance analysis and, 486–499
- equations and, 488–499
- variable gas properties, SM Chap. 7, 40–45
- equations, Afterburners

turbojet

- mass flow rate, 487–488
- modified combustion model, SM Chap. 7, 45–47, SM Chap. 8, 62–65
- real engine parametric cycle analysis and, 399–404
- equations, 402–404
- simple, 299–302

Air and $(\text{CH}_2)_n$ properties at low pressure, 803–819

Airbreathing

engines, 5–28

- aircraft engine performance parameters, 16–26
- fuel consumption, 27–28
- gas generator, 6
- jet, 5
- ramjet, 14–15
- specific thrust, 27–28
- turbofan, 9–12
- turbojet, 6–9
- turbojet/ramjet combined-cycle engine, 15–16
- turboprop, 12–14
- turboshaft, 12–14

jet propulsion, xxi

turbopropulsion systems

- evolution of, xlii–xlvii
- future potential of, xlvii–l
- high-bypass-ratio turbofans, development of, xlv–xlvii
- high-pressure-ratio turbojets, development of, xliii–xlv

Aircraft engine performance parameters,

airbreathing engines and, 16–26

flat rating, 18

Aircraft gas turbine engine, 233–258

Brayton power cycle, 252–257

components of, 244–252

combustor, 247–248

compressors, 245–247

exhaust nozzle, 250–251

inlets, 244–245

thrust augmentation, 251–252

turbines, 248–249

design procedures, 257–258

propulsive efficiency, 243

thrust equation, 233–258

uninstalled engine thrust, 233

Aircraft model

B58 Hustler, xvii

Bell Aircomet XP59A, xxvii

Boeing 747, xvii

Boeing F-22, 31–32

Douglas DC10, xx

Gloster Meteor, xxvi

Heinkel He-178, xx

HF-1 hypothetical fighter, 31–35

HP-1 hypothetical passenger aircraft, 31–32, 36–41

Junkers F13, xix

Lockheed L-1011, xx

Lockheed SR71 Blackbird, 15–16

XP59A, xxvii

Aircraft performance

design teams, importance of, 48–49

equations, 29–30

fuel consumption, 39–48

growth of, xviii–xx

landing speeds, 38–39

lift and drag, 30–38

propulsion and, 29–49

stall speeds, 38–39

takeoff speeds, 38–39

Airflow distribution, main burners

and, 761

Altitude tables

standard atmosphere, 789–790

temperature profiles, 790–791

units, 785–788

thrust and, 165

Angularity nozzle coefficient, 739

Annulus

area, flow path dimensions and, 573, 638

dimensions, axial-flow compressor

design and, 587–589

Area ratio, pressure ratio and, 201–202

Atomization, afterburner components

and, 771–772

Axial compressors, 246–247

Axial dimensions, flow path and,

638–642

- Axial leaving velocity, adiabatic efficiency, 619, 621–622
- Axial-flow compressor analysis
 - blade rows, 543–546
 - cascade field, 540
 - compressor performance, 596–600
 - design process
 - annulus dimensions, 587–589
 - number of compressor stages, 590–595
 - flow annulus area, 548–550
 - inlet guide vanes, 589
 - secondary flowfield, 540
 - stage parameters, 550–564
 - throughflow field, 540
 - turbomachinery and, 539–600
 - velocity diagrams, 546–547
- Axial-flow compressor stage analysis
 - design process, 585–596
 - rotational speed selection, 587–589
- Axial-flow compressor stage parameters
 - blade Mach number M_b , 560–564
 - cascade airfoil nonmenclature, 553–554
 - degree of reaction, 553
 - diffusion factor, 554–556
 - efficiencies, 550–553
 - flow path dimensions, 573–576
 - mean-line design, 564–572
 - radial variation, 577–585
 - repeating-row, 564–572
 - repeating-stage, 564–572
 - stage loading coefficient, 556–558
 - stage pressure ratio, 558–560
 - total pressure loss coefficient, 553–554
- Axial-flow turbine analysis
 - adiabatic efficiency, 612–614
 - axial-flow turbine stage, 628–638
 - cooling, 662–665
 - design process, 652–662
 - single-stage, 655
 - two-stage, 656–662
 - equations, 632–638
 - flow path dimensions, 638–644
 - performance, 665–668
 - sample calculations, 644–652
 - shaft speed, 652
 - stage parameters, 612–628
 - turbomachinery and, 607–673
- Axial-flow turbomachinery, 537
- Axisymmetric supersonic inlet, 710
- B58 Hustler, xvii
- BCM. *See* best cruise Mach
- Bell rocket nozzles, 191–192
- Best cruise Mach (BCM), 47
- Bipropellant chemical rockets, 213–217
- Blades,
 - Mach number M_b , axial-flow compressor stage parameters, 560–564
 - flow path dimensions and, 574–576, 642–644
 - number of flow path dimensions, 574, 638–642
 - rows
 - axial-flow compressor analysis and, 543–546
 - inlet guide vanes, 543
 - two-dimensional flow, 543–546
 - spacing, adiabatic efficiency and, 625
- Boeing 747, xvii, xx
- Boeing, F-22, 31–32
- Brayton power cycle, 252–257
- Breguet range equation, 41
- Burn rate
 - pressure exponent, 221
 - solid-propellant chemical rockets and, 221–223
- Burner efficiency, component performance and, 370–371
- Buzz, 717
- Bypass ratio analysis, separate exhaust turbofan engine and, 500–502
- Bypass ratio effects, ideal turbofans and, 336–339
- Calorically perfect gas, 84–85
- Cascade airfoil nonmenclature, axial-flow compressor stage parameters and, 553–554
- Cascade field, 540
- Centrifugal compressors, 246
- Centrifugal-flow compressor analysis, turbomachinery and, 600–607
- Centrifugal-flow turbine analysis, turbomachinery and, 668–673
- Chamber pressure and stability, solid-propellant chemical rockets and, 224–228
- Characteristic velocity, chemical rockets and, 197–198

Chemical

- component, enthalpy and, 143–146
- equilibrium, 140–142
 - adiabatic flame temperature, 143–146
 - enthalpy, 143–146
 - heat of reaction, 143–146
 - EQL software, 143
- reactions
 - equilibrium, 140–142
 - propulsion elements and, 139–146
- rockets
 - characteristic velocity, 197–198
 - ideal thrust coefficient, 203
 - ideal thrust equation, 196–197
 - liquid-propellant, 213–217
 - nozzle exit velocity, 198–201
 - nozzle mass flow, 194–196
 - optimum thrust coefficient, 203
 - parameters of, 194–228
 - pressure ratio, 201–202
 - solid-propellant type, 217–228
 - thrust coefficient, 202–203
 - vacuum thrust coefficients, 203–204
 - thermal propulsion system, 177–179
- Choked principle, nozzle design and, 126
- Closed cycle, liquid-propellant chemical rockets, 213
- Coefficient
 - core work, turboprop engine and, SM Chap. 8, 23
 - drag, xvi
 - exhaust nozzles and, 736–739
 - maximum lift, xvi
- Combustion
 - efficiency
 - main burner performance parameters and, 763, 766–767 *See* burner efficiency
 - systems, 744–779
 - afterburners, 769–779
 - diffusers, 754–756
 - fuels, 757
 - ignition, 748–749
 - length scaling, 750–752
 - main burners, 757–768
 - process of, 745–748
 - stability, 749–750
 - total pressure ratio, 752–753
- Combustor, aircraft gas turbine engine components and, 247–248

Component performance

- analytical tools, 355–378
- burner efficiency, 370–371
- compressor efficiencies, 360–370
- diffuser pressure recovery, 358–359
- exhaust nozzle loss, 371
- figures of merit, 357, 371–373
- gas properties variations, 355–357
- inlet pressure recovery, 358–359
- maps
 - compressors, 444–445
 - engine performance analysis and, 444
 - fans, 444–445
 - main burner, 445
 - turbines, 445–446
- power shaft mechanical efficiency, 371
- turbine efficiencies, 360–370
- variable C_p , 373–378
- COMPR computer, 575–576
- Compressible flow properties, 93–104
 - impulse function I , 106–107
 - isentropic area ratio, 105–106
 - Mach number functions, 101–103
 - mass flow parameter, 103–104
 - stagnation, 98–101
 - total enthalpy, 93–98
 - total pressure, 98–101
 - total temperature, 93–98
- Compressor
 - aircraft gas turbine engine components and, 245–247
 - axial, 246–247
 - centrifugal, 246
 - turboprop engine and, SM Chap. 8, 23
- Compressor analysis
 - afterburning turbojet and, 487
 - high-pressure, 487
 - low-pressure, 487
- Compressor efficiencies
 - component performance and, 360–370
 - compressor stage pressure ratio, 367
 - isentropic, 360–361
 - polytropic turbine, 363–364, 369–370
 - relationships between, 364–366
 - stage, 361–363
 - turbine
 - isentropic efficiency, 368
 - stage efficiency, 369

- Compressor map, 598
- Compressor materials, engine materials and, 832
- Compressor operating line, 449
 - gas generator and, 453–454
- Compressor performance
 - axial-flow compressor analysis, 596–600
 - corrected quantities, 596–597
 - maps, 444–445, 598
 - starting problems, 598–600
- Compressor pressure ratio
 - efficiencies and, 367
 - ideal turbojet, 288–291
 - afterburner, 296–299
- Compressor stage
 - axial-flow compressor design
 - process and, 590–595
 - low-pressure spool and, 519–521
- Concorde
 - exhaust nozzles and, 727
 - supersonic transport, 303
- Conical rocket nozzles, 189–191
- Conservation of mass
 - equation, 67–68
 - gas generator and, 447–449
- Constant area friction,
 - H-K* diagram, 118–119
 - one-dimensional gas dynamics and, 116–119
- Constant energy flows
 - isentropic, 109
 - one-dimensional gas dynamics and, 107–110
- Convergent exhaust nozzle, 250, 728
- Convergent-divergent exhaust nozzle, 250–251, 728
- Converging contour, nozzle design and, 124
- Cooling air, main burners and, 761
- Core work coefficient, turboprop engine and, SM Chap. 8, 23
- Corrected
 - component performance parameters, 441–444
 - engine speed, 443
 - fuel mass flow rate, 444
 - mass flow rate, 441
 - thrust, 443
 - thrust-specific fuel consumption, 443
 - engine
 - performance, single-spool turbojet and, 477–480
 - speed, 443
 - fuel mass flow rate, 444
 - mass flow rate, 441
 - quantities, compressor performance and, 596–597
 - thrust, 443
 - thrust-specific fuel consumption, 443
- Cruise climb, range and, 41
- Cycle analysis
 - afterburning
 - turbofan and mixed exhaust stream, Chap. 7, 13–15
 - turbofan and separate exhaust streams, SM Chap. 7, 1–3
 - variable gas properties and, SM Chap. 7, 39–40
 - engines and, 261–344
 - ideal
 - mixed-flow turbofan and, SM Chap. 5, 3–5
 - ramjet and, 268–271
 - turbofan and, 305–308
 - turbojet afterburner and, 291–294
 - turbojet and, 279–282
 - turboprop engines and, SM Chap. 5, 12–16
 - turboshaft engine w/ regenerator, SM Chap. 5, 24–25
 - parametric, 261–344
 - turboprop engine and, SM Chap. 7, 24–38
- Degree of reaction
 - 50% reaction, 619–621
 - adiabatic efficiency and, 617
 - axial leaving velocity, 619, 621–622
 - axial-flow compressor stage
 - parameters and, 553
 - zero, 619–620
- Design
 - inputs, parametric cycle analysis and, 264
 - metal angles, adiabatic efficiency and, 622
 - point analysis. *See* parametric cycle analysis

Design (*Continued*)

- procedures, aircraft gas turbine engine and, 257–258
- process
 - axial-flow compressor analysis, 585–596
 - annulus dimensions, 587–589
 - number of compressor stages, 590–595
 - rotational speed selection, 587–589
 - supersonic inlet and, 718–721
 - teams, importance of, 48–49
- Differential control volume analysis
 - one-dimensional gas dynamics and, 134–139
 - physical laws, 135–139
- Diffuser, 692–695
 - afterburner components and, 771
 - combustion systems and, 754–756
 - pressure recovery, component performances and, 358–359
- Diffusion faction, axial-flow compressor stage parameters and, 554–556
- Dimensionless component performance parameters, 441–444
- Discharge nozzle coefficient, 736–738
- Disk
 - thermal stress, turbomachinery stresses and, 830
 - torsional stress, turbomachinery stresses and, 829
 - uniform stress, turbomachinery stresses and, 827–829
- Diverging design, nozzle design and, 124
- Douglas DC10, xx
- Drag coefficient, xvi
- Dual-spool
 - afterburners
 - analysis and equations, SM Chap. 8, 49–61
 - turbojet, engine performance analysis and, 484–486
- Effective exhaust velocity C , thrust and, 165–166
- Efficiencies
 - axial-flow compressor stage parameters and, 550–553
 - polytropic, 551
 - stage, 550

- Electric propulsion systems
 - electromagnetic type, 181–185
 - rocket engines and, 181–186
 - space power plants, 185–186
- Electromagnetic propulsion systems, 181–182
 - magnetohydrodynamics (MHD), 181
- Electrostatic propulsion systems, 182–185
- Electrothermal propulsion system, 180–181
- Endurance, fuel consumption and, 40–41
- Energy equation of state, 66
- Engine
 - backpressure control, exhaust nozzle function and, 730–731
 - controls, gas generator and, 455–457
 - cycle analysis, 261–344
 - mass flow, afterburning turbofan and mixed exhaust stream, SM Chap. 8, 7–9
 - materials
 - compressor materials, 832
 - fan, 832
 - turbomachinery and, 831–833
 - performance analysis, 261, 437–523
 - afterburning turbojet, 486–499
 - assumptions, 439–440
 - sea-level static, 439–440
 - component performance maps, 444
 - corrected component performance parameters, 441–444
 - dimensionless component performance parameters, 441–444
 - dual-spool turbojet, 484–486
 - fixed-area turbine, 440
 - gas generator, 447–464
 - nomenclature, 439
 - reference values, 439–440
 - single-spool turbojet, 464–486
 - turbofan engine, separate exhausts, 499–519
 - rocket propulsion and, 176–188
 - speed
 - corrected, 443
 - gas generator, SM Chap. 8, 45
 - variation, 459–460
 - turboprop, SM Chap. 7, 24–38
- Enthalpy
 - chemical
 - component, 143–146
 - equilibrium and, 143–146
 - formation, 143–146

- EQL software, chemical reactions and, 143
- Equation of motion, rocket propulsion and, 169–174
- Equation of state, 66
 - one-dimensional flow, 67
 - steady flow, 67
- Equations
 - afterburning
 - turbofan, mixed exhaust stream, SM Chap. 7, 16–23, SM Chap. 8, 9–20
 - turbofan, separate exhaust streams, SM Chap. 7, 3–7
 - turbojet
 - real engine parametric cycle analysis and, 402–404
 - variable gas properties, SM Chap. 7, 40–45
 - axial-flow turbine stage and, 632–638
 - gas generator and, 461–464
 - ideal
 - mixed-flow turbofan, SM Chap. 5, 3–5
 - ramjet, 271–272
 - turbofan, 308–325
 - turbojet afterburner and, 294–296
 - turbojet and, 283–288
 - turboprop engines and, SM Chap. 5, 16–17
 - low-pressure spool and, 523
 - optimum
 - bypass ratio and, 329–332
 - fan pressure ratio and, 335–336
 - separate
 - exhaust stream turbofan engine cycle analysis and, 409–411
 - exhaust turbofan engine and, 504–519
 - single-spool turbojet and, 467–477
 - summary
 - ideal turboprop engines and, SM Chap. 5, 18–22
 - turboshaft engine w/regenerator, 25–27
 - turbojet
 - dual-spool afterburners, SM Chap. 8, 50–61
 - real engine parametric cycle analysis and, 385–399
 - w/afterburner, 488–499
 - turboprop engine and, SM Chap. 7, 29–32, SM Chap. 8, 25–32
- Equilibrium flow, liquid-propellant chemical rockets and, 216
- Euler's equations, 537–539
- Exhaust nozzles, 726–744
 - aircraft gas turbine engine components and, 250–251
 - coefficients, 736–739
 - Concorde, 727
 - convergent nozzle, 250, 728
 - convergent-divergent type, 250–251, 728
 - functions, 730–735
 - engine backpressure control, 730–731
 - infrared signature, 734–735
 - pressure ratio, 731–732
 - thrust reversing, 732–734
 - loss, component performance and, 371
 - performance, 739–744
 - turboprop engine and, SM Chap. 8, 24
 - two-stage, 728
- Exhaust stream, mixed, afterburning turbofan and, SM Chap. 7, 7–23
- Exhaust velocity, thrust and, 165–166
- Exit pressure conditions, separate exhaust stream turbofan engine cycle analysis and, 411–418
- Exit swirl angle, adiabatic efficiency and, 614
- Exit temperature profile, main burner performance parameters and, 765–766
- Exponential swirl distributions, 580
- External compression inlet, 707–709
- F-16, supersonic inlet design, 725
- FAIR subroutine program, SM Chap. 7, 38–45
- Fan
 - materials, engine materials and, 832
 - performance maps, 444–445
- Figures of merit, component performances and, 357, 371–373
- Finite control volume analysis, 107–121
- First-power swirl distributions, 581–582
- Fixed-area turbine, engine performance analysis and, 440
- Flame
 - spread, afterburner components and, 776–777
 - stabilization, afterburner components and, 773–775

- Flame-holder-arrays, afterburner components and, 776
- Flat rating, aircraft engine performance parameters and, 18
- Flow annulus area, axial-flow compressor analysis and, 548–550
- Flow nozzle coefficient, 736–738
- Flow path dimensions
 - annulus area, 573, 638
 - axial dimensions, 574, 638–642
 - axial-flow compressor stage parameters and, 573–576
 - axial-flow turbine analysis and, 638–644
 - blade profile, 574–576, 642–644
 - COMPR computer, 575–576
 - number of blades, 574
 - number of blades, 638–642
- Flux of energy, 70
- Forebody drag, 691
- Free space, rocket propulsion and, 174
- Free-expansion rocket nozzles, 192–194
- Free-vortex
 - flow, 578–579
 - swirl distributions, 580
- Frictional choking, one-dimensional gas dynamics and, 116–119
- Frozen flows, liquid-propellant chemical rockets and, 216
- Fuel
 - combustion systems and, 757
 - consumption
 - endurance, 40–41
 - range, 41–42
 - specific thrust and, 27–28
 - injection, afterburner components and, 771–772
 - mass flow rate, corrected, 444
- Gas generator, 278
 - airbreathing engines and, 6
 - compressor operating line, 449, 453–454
 - conservation of mass, 447–449
 - engine
 - controls, 455–457
 - performance analysis and, 447–464
 - speed, SM Chap. 8, 45
 - variation, 459–460
 - equations, 461–464
 - mass flow parameter, 447
 - pumping characteristics
 - high-pressure compressor, SM Chap. 8, 44–45
 - low-pressure compressor, SM Chap. 8, 44
 - main burner, SM Chap. 8, 45
 - solutions scheme, SM Chap. 8, 46–48
 - variable gas properties and, SM Chap. 8, 42–48
 - theta break, 457–459
 - turbine characteristics, 449–453
- Gas properties, variations, component performances and, 355–357
- Gas tables, perfect gas and, 89–90
- Gas turbine engine
 - aircraft, 233–258
 - data, 793–799
- Germany, turbojet development in, xxviii–xlii
- Gibbs' equation, 577–578
- Gloster meteor aircraft, xxvi
- Gross thrust nozzle coefficient, 736
- Guillaume, origins of jet propulsion, xxi
- Heat of reaction, chemical equilibrium and, 143–146
- Heinkel He-178, xx
- HF-1 hypothetical fighter, 31–35
- High-bypass-ratio turbofans, development of, xlv–xlvii
- High-pressure compressor analysis, 487
 - separate exhaust turbofan engine and, 501–502
- High-pressure compressor, gas generator and, SM Chap. 8, 44–45
- High-pressure turbine, afterburning turbofan and mixed exhaust stream and, SM Chap. 8, 3–4
- High-pressure-ratio turbojets, development of, xliii–xlv
- H-K* diagram, one-dimensional gas dynamics and, 118–119
- H-K* diagram, scramjet and, 120–121
- HP-1 hypothetical passenger aircraft, 31–32, 36–41
- Ideal cycle analysis, parametric cycle analysis and, 266
- Ideal mixed-flow turbofan
 - afterburning
 - cycle analysis, SM Chap. 5, 1–27
 - equations, SM Chap. 5, 3–5

- Ideal mixer analytical model, afterburning turbofan and mixed exhaust stream, SM Chap. 7, 8–12
- Ideal one-dimensional internal compression inlet, supersonic inlets and, 701–705
- Ideal pulse detonation engine, 341–344
- Ideal ramjet
 - cycle analysis, 268–271
 - equation summary, 271–272
 - mass flow rate, 276–277
 - optimum Mach number, 272–275
 - parametric cycle analysis, 266–277
- Ideal thrust coefficient
 - chemical rockets and, 203
 - determination via graphs, 204–207
- Ideal thrust equation, chemical rockets and, 196–197
- Ideal turbofan
 - bypass ratio effect results, 336–339
 - comparison of, 339–341
 - cycle analysis, 305–308
 - equations, 308–325
 - optimum bypass ratio, 325–332
 - equations, 329–332
 - optimum fan pressure ratio, 332–341
 - parametric cycle analysis and, 302–325
- Ideal turbojet,
 - afterburner, 291–302
 - cycle analysis, 291–294
 - equations, 294–296
 - optimum compressor pressure ratio, 296–299
 - cycle analysis, 279–282
 - equations summary, 283–288
 - gas generator, 278
 - optimum compressor pressure ratio, 288–291
 - optimum simple vs. afterburning turbojet, 299–302
 - parametric cycle analysis and, 278–291
- Ideal turboprop engines, SM Chap. 5, 11–22
 - cycle analysis, SM Chap. 5, 12–16
 - equations, SM Chap. 5, 16–22
 - optimal turbine temperature ratio, SM Chap. 5, 17–18
 - propulsive efficiency, SM Chap. 5, 11–12
 - very-high-bypass-ratio fans, SM Chap. 5, 11
- Ideal turboshaft engine, w/regenerator, SM Chap. 5, 22–27
 - cycle analysis, SM Chap. 5, 24–25
- Ignition
 - afterburner components and, 772–773
 - combustion systems and, 748–749
 - spontaneous ignition temperature, 748
- Impulse function
 - compressible flow properties and, 106–107
 - one-dimensional gas dynamics and, 110–111
- Impulse turbines, 249
- Infrared signature, exhaust nozzle functions and, 734–735
- Inlet, 685–725
 - aircraft gas turbine engine components and, 244–245
 - drag
 - additive, 691
 - forebody, 691
 - subsonic inlets and, 690–691
 - flow distortion, subsonic inlets and, 689–690
 - guide vanes, axial-flow compressor analysis and, 589
 - mass flow ratio, supersonic inlets and, 714
 - pressure recovery, component performances and, 358–359
 - sizing, subsonic inlets and, 688–689
 - subsonic, 244–245, 686–695
 - supersonic, 245, 695–726
 - total pressure ratio π_d , subsonic inlets and, 687–688
 - types
 - external compression inlet, 707–709
 - mixed compression, 709–710
 - supersonic and, 705–711
- Installed engine thrust, thrust equation and, 233
- Isentrope principle, nozzle design and, 125–126
- Isentropic
 - area ratio, compressible flow properties and, 105–106
 - constant energy flows and, 109
 - efficiency, compressors and, 360–361
 - flow, nozzle operating characteristics and, 126–129
 - process, perfect gas and, 85–86

Iteration

- area, afterburning turbofan and mixed exhaust stream, SM Chap. 8, 9
- scheme, turboprop engine and, SM Chap. 8, 24

J-79, supersonic inlet design, 725

Jet propulsion

- airbreathing jet propulsion, xxi
- Guillaume, xxi
- Lorin, xxi
- origins of, xxi
- ramjet, xxi

Junkers F13, xix

Landing speed/cruise speed ratio, xvi

Landing speeds, aircraft performance and, 38–39

Length scaling, combustion systems and, 750–752

Lift and drag

- aircraft performance and, 30–38
- HF-1 hypothetical fighter, 31–35
- HP-1 hypothetical passenger aircraft 31–32, 36–41

Lift/drag ratio L/D , xvi

Liquid-propellant chemical

- rockets, 213–217
- bipropellant, 213–217
- monopropellant, 213
- open cycle, 213
- performance calculations, 214–217
- equilibrium flow, 216
- frozen flows, 216
- performance results, 214–217
- propellant types, 213

Liquid-propellant rocket engines data, 801–802

Lockheed

- L-1011, xx
- SR71 Blackbird, 15–16

Lorin, origins of jet propulsion, xxi

Low-pressure analysis compressor analysis, 487

Low-pressure compressor, gas generator and, SM Chap. 8, 44

Low-pressure spool

- compressor stages on, 519–521
- equations, 523
- separate exhaust turbofan engine and, 519–521
- solution scheme, 521–522

Low-pressure turbine

- afterburning turbofan and mixed exhaust stream and, SM Chap. 8, 3–4
- analysis, separate exhaust turbofan engine and, 500
- turboprop engine and, SM Chap. 8, 23–24

Mach number

- functions, compressible flow properties and, 101–103
- ideal ramjet and, 272–275

Magnetohydrodynamics (MHD), 181

Main burner. *See also* combustor

- airflow distribution, 761
- combustion systems and, 757–758
- components, 759–761
- cooling air, 761
- design parameters, 768
- gas generator and, SM Chap. 8, 45
- performance maps, 445
- performance parameters, 763–767
- combustion efficiency, 763
- exit temperature profile, 765–766
- ignition, 766–767
- overall total pressure loss, 764–765
- types, 757

Mass flow

- characteristics
- inlet mass flow ratio, 714
- supersonic inlets and, 714–718
- parameter, 447
- compressible flow properties and, 103–104

rate

- afterburning turbojet and, 487–488
- corrected, 441
- ideal ramjet and, 276–277
- turboprop engine and, SM Chap. 8, 22–23

Maximum lift coefficient, xvi

Mean-line design, axial-flow

- compressor stage parameters and, 564–572

Measurements

- propulsion and, 2–3
- unit conversions, 3

MHD. *See* magnetohydrodynamics

Mixed compression inlets, 709–710

- Mixed exhaust stream
 - afterburning turbofan, SM Chap. 7, 7–23, SM Chap. 8, 1–65
 - cycle analysis, SM Chap. 7, 13–15
 - engine mass flow, SM Chap. 8, 7–9
 - equations, SM Chap. 7, 16–23, SM Chap. 8, 9–20
 - high-pressure turbine, SM Chap. 8, 3–4
 - ideal mixer analytical model, SM Chap. 7, 8–12
 - iteration area, SM Chap. 8, 9
 - low-pressure turbine, SM Chap. 8, 3–4
 - mixer performance solution, SM Chap. 8, 4–7
 - nozzle area, SM Chap. 8, 7–9
- Mixed-flow turbofan, afterburning, SM Chap. 5, 1–27
- Mixer performance solution, afterburning turbofan and mixed exhaust stream, SM Chap. 8, 4–7
- Mixtures of perfect gases, 87–89
- Modified combustion
 - model, afterburning turbojet and, SM Chap. 7, 45–47
 - type, afterburning turbojet and, SM Chap. 8, 62–65
- Mollier diagram, perfect gas and, 86–87
- Monopropellant liquid-propellant chemical rockets, 213
- Multiple-stage rocket vehicles, 174–176
- Nacelle drag, subsonic inlets and, 692
- Nomenclature, lvii–lx
- Non-airbreathing, propulsion, 1
- Normal shock wave
 - one-dimensional inlet flow and, 698–701
 - one-dimensional gas dynamics and, 112–113
- Notation
 - parametric cycle analysis and, 262–264
 - stagnation pressure, 262
 - stagnation temperature, 262
- Nozzle
 - area, afterburning turbofan and mixed exhaust stream, SM Chap. 8, 7–9
 - characteristics of, 133–134
 - coefficients
 - angularity, 739
 - discharge, 736–738
 - flow, 736–738
 - gross thrust, 736
 - one-dimensional adiabatic flow, 739–740
 - velocity, 738
 - design, 122–126
 - choked principle, 126
 - converging contour type, 124
 - diverging design type, 124
 - isentropic principle, 125–126
 - shock waves, 129–133
 - exhaust, 726–744
 - exit velocity, chemical rockets and, 198–201
 - flow, 129–133
 - mass flow, chemical rockets and, 194–196
 - operating characteristics, isentropic flow, 126–129
 - propulsion fundamentals and, 121–134
 - supersonic convergent-divergent type, 124
- Nuclear heat transfer thermal propulsion system, 179–180
- On-design analysis. *See* parametric cycle analysis
- One-dimensional adiabatic flow, nozzle coefficients and, 739–740
- One-dimensional flow, 65
 - equation of state, 67
- One-dimensional gas dynamics, 107–121
 - constant area friction, 116–119
 - constant area heating, 113–115
 - constant energy flows, 107–110
 - differential control volume analysis, 134–139
 - physical laws, 135–139
 - finite control volume analysis, 107–121
 - frictional choking, 116–119
 - H-K* diagram, 118–119
 - impulse function, 110–111
 - normal shock waves, 112–113
 - propulsion elements and, 134–139
 - scramjet, 120–121
 - stream thrust function, 110–111
 - thermal choking, 116
- One-dimensional inlet flow
 - normal shock wave, 698–701
 - sonic state points, 696–697
 - supersonic inlets and, 696–701

- Open cycle, liquid-propellant
 - chemical rockets and, 213
- Operational envelopes,
 - propulsions and, 4–5
- Optimal turbine
 - expansion ratio selection, turboprop engine and, SM Chap. 7, 29–32
 - temperature ratio, ideal turboprop engines and, SM Chap. 5, 17–18
- Optimum bypass ratio
 - equations, 329–332
 - ideal turbofan and, 325–332
 - α^* , separate exhaust stream
 - turbofan engine cycle analysis and, 418–427
- Optimum fan pressure ratio, 332–335
 - equations, 335–336
 - ideal turbofan and, 332–341
- Optimum thrust coefficient, chemical rockets and, 203
- Overall total pressure loss, main burner performance parameters and, 764–765
- Parametric cycle analysis, 261–344
 - design inputs, 264
 - ideal
 - cycle analysis, assumptions of, 266
 - pulse detonation engine, 341–344
 - ramjet, 266–277
 - turbofan, 302–325
 - turbojet, 278–291
 - afterburner, 291–302
 - notation, 262–264
 - stagnation pressure, 262
 - stagnation temperature, 262
 - real engines, 381–427
 - turbojets, 381–398
 - steps of, 264–266
 - turbofan separate exhaust streams and, 405–409
- Perfect gas, 65, 82–93
 - AFPROP computer program, 91–93
 - calorically perfect gas, 84–85
 - gas tables, 89–90
 - general characteristics, 82–84
 - isentropic process, 85–86
 - mixtures of, 87–89
 - Mollier diagram, 86–87
 - ref to appendix D, 90–91
- Performance equations, 29–30
- Physical laws, differential control volume analysis and, 135–139
- Plug rocket nozzle. *See* free-expansion rocket nozzles
- Polytropic
 - efficiencies, 551–553
 - compressors and, 363–364, 369–370
- Power plants, electric rocket propulsion systems and, 185–186
- Power shaft mechanical efficiency,
 - component performance and, 371
- Power turbine, turboprop engine and, SM Chap. 8, 23–24
- Pressure ratio
 - area ratio, 201–202
 - chemical rockets and, 201–202
 - velocity ratio, 201–202
- Propellant types
 - liquid-propellant chemical rockets and, 213
 - solid-propellant chemical rockets and, 218–221
- Propeller
 - engine, performance limit of, xix
 - performance, turboprop engine and, SM Chap. 8, 25
- Propulsion,
 - airbreathing engines, 1, 5–28
 - aircraft performance, 29–49
 - elements of, 1–64
 - chemical reactions, 139–146
 - one-dimensional gas dynamics, 134–139
 - fundamentals
 - compressible flow properties, 93–104
 - conservation of mass equation, 67–68
 - energy equation of state, 66
 - enthalpy, 66
 - equation of state, 66
 - nozzles, 121–134
 - one-dimensional flow, 65
 - gas dynamics, 107–121
 - perfect gas, 65, 82–93
 - review, 65–146
 - steady flow
 - energy equation, 68–75
 - entropy equation, 75–76
 - momentum equation, 76–82
 - thermal equation of state, 66
 - measurements used in, 2–3

- non-airbreathing, 1
- operational envelopes, 4–5
- rocket engines, 49, 161–228
- standard atmosphere, 4–5
- units and dimensions, 2–3
- Propulsive efficiency
 - aircraft gas turbine engine and, 243
 - ideal turboprop engines and, SM Chap. 5, 11–12
- Radial equilibrium equation, Gibbs' equation, 577–578
- Radial variation
 - adiabatic efficiency and, 626–628
 - axial-flow compressor stage parameters and, 577–585
 - comparison, 582–583
 - free-vortex flow, 578–579
 - radial equilibrium equation, 577–578
 - swirl distributions, 579–582
- Radial-flow type turbomachinery, 537
- Ramjet, 14–15
 - ideal, parametric cycle analysis and, 266–277
 - origins of jet propulsion, xxi
 - scramjet, 14
- Range
 - best cruise Mach (BCM), 47
 - Breguet range equation, 41
 - cruise climb, 41
 - fuel consumption and, 41–42
- Reaction turbines, 249
- Real engines
 - parametric cycle analysis, 381–427
 - afterburning turbojet, 399–404
 - turbofan, separate exhaust streams, 404–427
 - turbojet, 381–398
- Regenerator, ideal turboshaft engine and, SM Chap. 5, 22–27
- Repeating stage, axial-flow compressor stage parameters and, 564–572
- Repeating-row, axial-flow compressor stage parameters and, 564–572
- Rim web thickness, turbomachinery stresses, 824–827
- Rocket
 - engines, 49–55
 - data, liquid-propellant, 801–802
 - specific impulse, 52
 - thrust of, 50–52
 - vehicle acceleration, 52–55
 - nozzles
 - types, 189–194
 - bell, 191–192
 - conical, 189–191
 - free-expansion, 192–194
- propulsion, 161–228
 - acceleration, equation of motion, 169–174
 - chemical rocket parameters, 194–228
 - engines, 176–188
 - electric types, 181–186
 - thermal propulsion systems, 177–181
 - free space, 174
 - multiple-stage vehicles, 174–176
 - nozzle types, 189–194
 - requirements, 166–169
 - summary of types, 187–188
 - thrust, 161–166
- Rotational speed selection, axial-flow compressor design and, 587–589
- Rotor airfoil centrifugal type stresses, turbomachinery and, 823–824
- Scramjet, 14
 - H-K* diagram, 120–121
 - one-dimensional gas dynamics and, 120–121
- Sea-level static, engine performance analysis and, 439–440
- Secondary flowfield, 540
- Separate exhaust streams
 - afterburning turbofan
 - cycle analysis, SM Chap. 7, 1–3
 - equations, SM Chap. 7, 3–7
 - turbofans, 404–427
 - afterburners and, SM Chap. 7, 1–47
- turbofan engine
 - bypass ratio analysis, 500–502
 - equations, 504–519
 - high-pressure compressor analysis, 501–502
 - low-pressure
 - spool, 519–521
 - turbine analysis, 500
 - performance analysis and, 499–519
 - solution scheme, 502–504
- Shaft speed, 652
- Shock waves, nozzle design and, 129–133
- Simple turbojet vs. afterburning turbojet, 299–302

- Single-spool turbojet
 - corrected engine performance, 477–480
 - engine performance analysis and, 464–486
 - equations, 467–477
 - throttle ratio, 480–484
- Single-stage design, axial-flow turbine
 - analysis and, 655–656
- Sizing, supersonic inlet and, 718–721
- Software instructions, 835–840
- Solid-propellant chemical
 - rockets, 217–228
 - burning rate, 221–223
 - chamber pressure and stability, 224–228
 - propellant types, 218–221
- Solutions scheme
 - gas generator and, SM Chap. 8, 46–48
 - separate exhaust turbofan engine and, 502–504
- Sonic state points, one-dimensional inlet
 - flow and, 696–697
- Sound barrier, xvii
- Specific impulse, rocket engines and, 52
- Specific thrust, fuel consumption and, 27–28
- Spontaneous ignition temperature, 748
- Stage
 - efficiency, 550
 - compressors and, 361–363
 - loading coefficient
 - adiabatic efficiency and, 614–616
 - axial-flow compressor stage
 - parameters and, 556–558
 - parameters, axial-flow compressor
 - analysis and, 550–564
 - pressure ratio
 - adiabatic efficiency and, 623–624
 - axial-flow compressor stage
 - parameters and, 558–560
 - temperature ratio, adiabatic efficiency and, 622–623
- Stagnation
 - compressible flow properties and, 98–101
 - pressure, 262
 - temperature, 262
- Stall speeds, aircraft performance and, 38–39
- Standard atmosphere, 789–790
 - propulsion and, 4–5
- Starting problems, compressor
 - performance and, 598–600
- Steady flow, 67
 - energy equation, 68–75
 - flux of energy, 70
 - entropy equation, 75–76
 - momentum equation, 76–82
- Stream thrust function, one-dimensional
 - gas dynamics and, 110–111
- Subroutine FAIR, AFPROP and, SM Chap. 7, 38–45
- Subsonic inlets, 244–245, 686–695
 - diffuser, 692–695
 - drag, 690–691
 - flow distortion, 689–690
 - nacelle drag, 692
 - sizing, 688–689
 - total pressure ratio π_d , 687–688
- Supersonic
 - convergent-divergent nozzle,
 - design of, 124
 - inlets, 245, 696–726
 - axisymmetric, 710
 - buzz, 717
 - design, 718–721
 - existing, 724–726
 - ideal one-dimensional internal
 - compression inlet, 701–705
 - mass flow characteristics, 714–718
 - one-dimensional inlet flow, 696–701
 - sizing, 718–721
 - total pressure recovery, 711
 - two-dimensional, 710
 - types, 705–711
- Swept-back wing, xvii
- Swirl distributions, 579–582
 - exponential, 580
 - first-power, 581–582
 - free-vortex, 580
- Takeoff speeds, aircraft
 - performance and, 38–39
- Temperature profiles, 790–791
- Thermal
 - choking, one-dimensional
 - gas dynamics and, 116
 - equation of state, 66
 - propulsion systems
 - chemical type, 177–179
 - electrothermal type, 180–181
 - nuclear heat transfer type, 179–180
 - rocket engines, 177–181

- Theta break, gas generator and, 457–459
- Throttle ratio, single-spool turbojet and, 480–484
- Through flow field, 540
- Thrust
 - altitude, 165
 - augmentation
 - afterburning, 252
 - aircraft gas turbine engine components and, 251–252
 - water injection, 252
 - coefficient, chemical rockets and, 202–203
 - corrected, 443
 - effective exhaust velocity C , 165–166
 - equation
 - aircraft gas turbine engine and, 233–258
 - installed engine thrust, 233
 - uninstalled engine thrust, 233
 - ideal equation of, 161–163
 - optimum ideal, 163–164
 - reversing, exhaust nozzle functions and, 732–734
 - rocket
 - engines and, 50–52
 - propulsion and, 161–166
 - specific fuel consumption (TSFC), 11
 - vacuum ideal, 164
 - variation, 165
- Thrust-specific fuel consumption, corrected, 443
- Total enthalpy, compressible flow properties and, 93–98
- Total pressure
 - compressible flow properties and, 98–101
 - loss coefficient, axial-flow compressor stage parameters and, 553–554
 - loss, afterburners and, 777
 - ratio, combustion systems and, 752–753
 - recovery, supersonic inlets and, 711
- Total temperature, compressible flow properties and, 93–98
- Transonic drag rise
 - swept-back wing, xvii
 - Whitcomb rule and, xvi
- TSFC. *See* thrust specific fuel consumption
- Turbine
 - aircraft gas turbine engine components and, 248–249
 - airfoil nomenclature, adiabatic efficiency and, 622
 - characteristics
 - gas generator and, 449–453
 - variable gas properties and, SM Chap. 8, 38–48
 - cooling
 - axial-flow turbine analysis and, 662–665
 - methods, 664
 - efficiencies, component performance and, 360–370
 - gas generator, 447–464
 - high-pressure, SM Chap. 8, 3–4
 - impulse, 249
 - isentropic efficiency, compressor efficiencies and, 368
 - low-pressure, SM Chap. 8, 3–4
 - materials, 833
 - performance
 - axial-flow turbine analysis and, 665–668
 - maps, 445–446
 - reaction, 249
 - stage efficiency, compressor efficiencies and, 369
- Turbofan, 9–12
 - afterburning
 - mixed exhaust stream, SM Chap. 8, 1–65
 - separate exhaust streams, SM Chap. 7, 1–47
 - engine performance analysis and, separate exhausts, 499–519
 - separate exhaust streams
 - cycle analysis, 405–409
 - equations, 409–411
 - exit pressure conditions, 411–418
 - optimum bypass ratio α^* , 418–427
 - real engine parametric cycle analysis and, 404–427
 - thrust specific fuel consumption (TSFC), 11
- Turbojet, 6–9
- Turbojet
 - afterburner
 - engine performance analysis and, 486–499

Turbojet (*Continued*)

- afterburner (*Continued*)
 - modified combustion type, SM Chap. 8, 62–65
 - real engine parametric cycle analysis and, 399–404
 - development
 - Germany, xxviii–xliv
 - von Ohain, Hans, xxviii–xxxvi
 - engine
 - aeropropulsion system and, xviii
 - dual-spool afterburners, analysis of, SM Chap. 8, 49–61
 - equations, SM Chap. 8, 50–61
 - equations
 - w/afterburner, 488–499
 - w/o afterburner, 488–499
 - ideal, parametric cycle analysis and, 278–291
 - propulsion
 - origins of, xxiii–xxvi
 - Whittle, Frank, xxiii–xxvi
 - real engine parametric cycle analysis and, 381–398
 - equations, 385–399
 - simple vs. afterburning, 299–302
 - single-spool, engine performance analysis and, 464–486
- Turbojet/ramjet combined-cycle engine, 15–16
- Lockheed SR71 Blackbird, 15–16
- Turbomachinery, 537–674
- axial-flow
 - compressor analysis, 539–600
 - turbine analysis, 607–673
 - type, 537
 - centrifugal-flow
 - compressor analysis, 600–607
 - turbine analysis, 668–673
 - engine materials, 831–833
 - Euler's equations, 537–539
 - materials, 821–833
 - radial-flow type, 537
 - stresses, 821–833
 - disk of uniform stress, 827–829
 - disk thermal stress, 830
 - disk torsional stress, 829
 - rim web thickness, 824–827
 - rotor airfoil centrifugal type, 823–824
- Turboprop engine, 12–14, SM Chap. 7, 24–38, SM Chap. 8, 20–32
- compressor, SM Chap. 8, 23

- core work coefficient, SM Chap. 8, 23
 - cycle analysis, SM Chap. 7, 24–38
 - equations, SM Chap. 7, 29–32, SM Chap. 8, 25–32
 - exhaust nozzle, SM Chap. 8, 24
 - iteration scheme, SM Chap. 8, 24
 - low-pressure turbine, SM Chap. 8, 23–24
 - mass flow, SM Chap. 8, 22–23
 - optimal turbine expansion ratio selection, SM Chap. 7, 29–32
 - power turbine, SM Chap. 8, 23–24
 - propeller performance, SM Chap. 8, 25
- Turbopropulsion systems, airbreathing, evolution of, xlii–xlvii
- Turboshaft, 12–14
- engine, w/regenerator, equations summary, SM Chap. 5, 22–27
- Two dimensional
- flow, blade rows and, 543–546
 - supersonic inlet, 710
- Two-stage
- design, axial-flow turbine analysis and, 656–662
 - exhaust nozzle, 728
- Uniform stress, on disk, 827–829
- Uninstalled engine thrust, thrust equation and, 233
- Unit conversions, 3
- United States jet development
- early efforts, xxviii
 - Whittle, Frank and, impact on, xxvii–xxviii
- Vacuum ideal thrust, 164
- Vacuum thrust coefficients, chemical rockets and, 203–204
- Vaporization, afterburner components and, 771–772
- Variable C_p , component performances and, 373–378
- Variable gas properties, SM Chap. 7, 38–45, SM Chap. 8, 33–48
- AFPROP, subroutine FAIR, SM Chap. 7, 38–45
- afterburner area variation, SM Chap. 8, 41–42
 - cycle analysis, afterburning turbojet, SM Chap. 7, 39–40

- equations and, afterburning turbojet,
SM Chap. 7, 40–45
- gas generator pumping characteristics,
SM Chap. 8, 42–48
- turbine characteristics,
SM Chap. 8, 38–48
- Vehicle acceleration, rocket engines and,
52–55
- Velocity
 - diagrams, axial-flow compressor
analysis and, 546–547
 - nozzle coefficient, 738
 - ratio
 - adiabatic efficiency and, 628
 - pressure ratio and, 201–202
- Very-high-bypass-ratio fans, ideal
turbo-prop engines and,
SM Chap. 5, 11
- Von Ohain, Hans, turbojet development
and, xxviii–xxxvi
- Water injection, thrust augmentation
and, 252
- Whitcomb rule, transonic drag rise, xvi
- Whittle, Frank
 - impact on United States jet
development, xxvii–xxviii
 - origins of turbojet
propulsion, xxiii–xxvi
- Wright Brothers, xv
- XP59A Bell Aircomet, xxvii
- Zero reaction, adiabatic efficiency and,
619–620