

Annex III to ED Decision 2026/002/R**AMC and GM to Part-145 — Issue 2, Amendment 8**

The amendments are presented as follows:

- deleted text is ~~struck through~~;
- new text is highlighted;
- an ellipsis '[...]' indicates that the rest of the text is unchanged.

Note to the reader

In amended, and in particular in existing (that is, unchanged) text, 'Agency' is used interchangeably with 'EASA'. The interchangeable use of these two terms is more apparent in the consolidated versions. Therefore, please note that both terms refer to the 'European Union Aviation Safety Agency (EASA)'.

GM1 145.A.10 Scope

SMALL ORGANISATIONS

This Guidance Material (GM) provides guidance on how the following small organisations satisfy the intent of Part-145:

(a) Organisations that ~~only~~ employ **only** one person, who carries out the certification function and other functions, and that are approved under Part-145 may use the alternatives provided below limited to the ~~following~~ terms of approval **specified in point (m) of Appendix II of Part-145**:

~~Class A2 Base and line maintenance of aeroplanes of 5 700 kg maximum take-off mass (MTOM) or less (with piston engines only)~~

~~Class A3 Base and line maintenance of single-engined helicopters of 3 175 kg MTOM or less~~

~~Class A4 Aircraft other than A1, A2 and A3 aircraft~~

~~Class B2 Piston engines with maximum output of less than 450 HP~~

~~Class C Components~~

~~Class D1 Non-destructive testing~~

[...]

AMC1 145.A.20 Terms of approval and scope of work

The following table identifies the ATA Specification 2200 chapter for the category C component rating. If the maintenance manual (or equivalent document) does not follow the ATA ~~C~~ chapters, the corresponding subjects still apply to the applicable C rating.

CLASS	RATING	ATA CHAPTERS
COMPONENTS OTHER THAN COMPLETE ENGINES OR APUs	C1 Air Cond & Press	21
	C2 Auto Flight	22
	C3 Comms and Nav	23 – 34
	C4 Doors – Hatches	52
	C5 Electrical Power & Lights	24 – 33 – 85
	C6 Equipment	25 – 38 – 44 – 45 – 50
	C7 Engine – APU	49 – 71 – 72 – 73 – 74 – 75 – 76 – 77 – 78 – 79 – 80 – 81 – 82 – 83
	C8 Flight Controls	27 – 55 – 57.40 – 57.50 – 57.60 – 57.70
	C9 Fuel	28 – 47
	C10 Rotorcraft Helicopters – Rotors	62 – 64 – 66 – 67
	C11 Rotorcraft Helicopter – Trans	63 – 65
	C12 Hydraulic Power	29
	C13 Indicating/Recording Systems	31 – 42 – 46
	C14 Landing Gear	32
	C15 Oxygen	35

	C16 Propellers	61
	C17 Pneumatic & Vacuum	36 → 37
	C18 Protection ice/rain/fire	26 → 30
	C19 Windows	56
	C20 Structural	53 → 54 → 57.10 → 57.20 → 57.30
	C21 Water Ballast	41
	C22 Propulsion Augmentation	84
	C23 Others	

The rating for an organisation approved for the maintenance of an electric engine that powers a propeller/rotor to generate thrust and/or lift for the aircraft should be B4, rather than C5.

C23 should be used as component rating when C1 to C22 or the corresponding ATA chapters are not adequate for the component; for instance, in case of innovative aircraft architectures/systems.

[...]