



Technical Data Sheet

- Enclosed Gears & Centralized Systems
- Multi-purpose
- Lithium

Shell Gadus S2 V220 00(IN)

High Performance Multipurpose Extreme Pressure Semi-Fluid Grease

Shell Gadus S2 V220 00(IN) grease is high quality multipurpose greases based on a blend of select mineral oils and a lithium soap thickener and contain extreme-pressure and other proven additives to enhance their performance in a wide range of applications.

Shell Gadus S2 V220 00(IN) greases is designed for multipurpose grease lubrication of rolling element and plain bearings as well as hinges and sliding surfaces across most industrial and transport sectors.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Anti-wear and extreme pressure properties**
Efficient lubrication of high-speed components
- **Improved Mechanical Stability**
Works well in vibrating environments and does not soften causing leakages.
- **Good resistance to water wash out.**
Shell Gadus S2 V220 00(IN) greases have been formulated with water wash out resistance.
- **Oxidation stability**
Can withstand high operating temperatures without hardening or forming bearing deposits.

Main Applications



Shell Gadus S2 V220 00(IN) greases are specifically designed for:

- Steel mill lubrication where softer grease is necessary for specialised dispensing systems.
- Heavy duty Plain and rolling bearing operating under severe conditions including wet environments.
- Gearbox applications where semi-fluid grease are required.
- Centralized chassis lubrication systems on trucks and buses
- Granite cutting and polishing tool heads
- Special purpose sliding applications.

Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Gadus S2 V220 00(IN)
NLGI Consistency				00
Soap Type				Lithium
Base Oil				Mineral
Kinematic Viscosity	@40°C	cSt	IP 71 / ASTM D445	220
Cone Penetration, Worked	@25°C	0.1mm	IP 50 / ASTM D217	400-430
Four Ball Weld Load		Kg minimum	ASTM D2596	200

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Re-greasing Intervals and Dispensing**

Easily dispensed through standard lubrication equipment.

- **Operating Temperature:**

Can be used in Mobile equipment as an embedded grease and for some central lubrication systems. Operating temperatures for use in central lubrication systems are to be defined dependent on its characteristics.