



Technical Data Sheet

- Reliable Protection
- Multi-purpose Applications
- Lithium

Shell Gadus S2 V220 1(IN)

High Performance Multipurpose Extreme Pressure Grease

Shell Gadus S2 V220 1(IN) grease is high quality multipurpose greases based on a blend of select mineral oils and a lithium soap thickener and contain extreme-pressure and other proven additives to enhance their performance in a wide range of applications.

Shell Gadus S2 V220 1(IN) grease is designed for multipurpose grease lubrication of rolling element and plain bearings as well as hinges and sliding surfaces across most industrial and transport sectors.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Anti-wear and extreme pressure properties**
Efficient lubrication of high-speed components.
- **Improved Mechanical Stability**
Works well in vibrating environments and does not soften causing leakages.
- **Good resistance to water wash out.**
Shell Gadus S2 V220 1(IN) grease has been formulated with water wash out resistance.
- **Oxidation Stability**
Can withstand high operating temperatures without hardening or forming bearing deposits.
- **Anti Corrosion Protection**
Ability to protect bearing surfaces against corrosion even the grease is contaminated with water.

Main Applications



Shell Gadus S2 V220 1(IN) grease is specifically designed for:

- Heavy duty bearings Serviced by centralized greasing systems.
- Extreme pressure gear grease for applications at normal ambient temperature.
- Heavy duty Plain and rolling bearing operating under severe conditions including shock loading in wet environments.
- Injection Moulding machine Lubrication.

Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties	Method	Shell Gadus S2 V220 1(IN)
NLGI Consistency		1
Soap Type		Lithium
Base Oil		Mineral
Kinematic Viscosity @40°C cSt	IP 71 / ASTM D445	220
Cone Penetration, Worked @25°C 0.1mm	IP 50 / ASTM D217	310-340
Dropping Point °C	IP 396	180
Four Ball Weld Load Kg minimum	ASTM D2596	250

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Re-greasing Intervals**

For bearings operating near their maximum recommended temperatures, re-greasing intervals should be reviewed.

- **Operating temperature**

-20 degree C to +120 degree C in closed bearings

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative