


Object Oriented Programming

OOP




**Data Structures
and Other Objects
Using C++**

- Chapter 2 introduces Object Oriented Programming.
- OOP is a relatively new approach to programming which supports the creation of new data types and operations to manipulate those types.
- This presentation introduces OOP.


What is this Object ?

- There is no real answer to the question, but we'll call it a “thinking cap”.
- The plan is to describe a thinking cap by telling you what actions can be done to it.




Using the Object's Slots


- You may put a piece of paper in each of the two slots (green and red), with a sentence written on each.
- You may push the green button and the thinking cap will speak the sentence from the green slot's paper.
- And same for the red button.




Example




Example



Example




Thinking Cap Implementation



- We can implement the thinking cap using a data type called a class.

```
class thinking_cap
{
    ...
};
```


Thinking Cap Implementation



- The class will have two components called **green_string** and **red_string**. These components are strings which hold the information that is placed in the two slots.
- Using a class permits two new features . . .

```
class thinking_cap
{
    . . .
    char green_string[50];
    char red_string[50];
};
```



Thinking Cap Implementation



- The two components will be private member variables. This ensures that nobody can directly access this information. The only access is through functions that we provide for the class.

```
class thinking_cap
{
    ...
private:
    char green_string[50];
    char red_string[50];
};
```

Thinking Cap Implementation




- In a class, the functions which manipulate the class are also listed.

Prototypes for the thinking cap functions go here, after the word public:

```
class thinking_cap
{
public:
    ...
private:
    char green_string[50];
    char red_string[50];
};
```

Thinking Cap Implementation




- In a class, the functions which manipulate the class are also listed.

Prototypes for the
thinking cap
member functions
go here

```
class thinking_cap
{
public:
    ...
private:
    char green_string[50];
    char red_string[50];
};
```

Thinking Cap Implementation




Our thinking cap has at least three member functions:

```
class thinking_cap
{
public:
    void slots(char new_green[ ], char new_red[ ]);
    void push_green( ) const;
    void push_red( ) const;
private:
    char green_string[50];
    char red_string[50];
};
```

Function bodies
will be elsewhere.

Thinking Cap Implementation




The keyword **const** appears after two prototypes:

```
class thinking_cap
{
public:
    void slots(char new_green[ ], char new_red[ ] );
    void push_green( ) const;
    void push_red( ) const;
private:
    char green_string[50];
    char red_string[50];
};
```

This means that these functions will not change the data stored in a thinking_cap.

Files for the Thinking Cap




- The `thinking_cap` class definition, which we have just seen, is placed with documentation in a file called `thinker.h`, outlined here.
- The implementations of the three member functions will be placed in a separate file called `thinker.cxx`, which we will examine in a few minutes.

Documentation

Class definition:

- `thinking_cap` class definition which we have already seen

Using the Thinking Cap




- A program that wants to use the thinking cap must **include** the thinker header file (along with its other header inclusions).

```
#include <iostream.h>
#include <stdlib.h>
#include "thinker.h"

...
```

Using the Thinking Cap




- Just for fun, the example program will declare two `thinking_cap` variables named `student` and `fan`.

```
#include <iostream.h>
#include <stdlib.h>
#include "thinker.h"

int main( )
{
    thinking_cap student:
thinking_cap fan;
```


Using the Thinking Cap




- Just for fun, the example program will declare two thinking_cap objects named student and fan.

```
#include <iostream.h>
#include <stdlib.h>
#include "thinker.h"

int main( )
{
    thinking_cap student;
    thinking_cap fan;
```

Using the Thinking Cap




- The program starts by calling the slots member function for student.

```
#include <iostream.h>
#include <stdlib.h>
#include "thinker.h"

int main( )
{
    thinking_cap student;
    thinking_cap fan;
    student.slots( "Hello", "Goodbye");
}
```

Using the Thinking Cap




- The program starts by activating the slots member function for student.

```
#include <iostream.h>
#include <stdlib.h>
#include "thinker.h"

int main( )
{
    thinking_cap student:
    thinking_cap fan;

    student.slots( "Hello", "Goodbye");
```

Using the Thinking Cap




- The member function activation consists of four parts, starting with the object name.

```
int main()  
{  
    thinking_cap student;  
    thinking_cap fan;  
    student.slots( "Hello", "Goodbye");  
}
```


Name of the object

Using the Thinking Cap




- The instance name is followed by a period.

```
int main()  
{  
    thinking_cap student;  
    thinking_cap fan;  
  
    student.slots( "Hello", "Goodbye");
```



Using the Thinking Cap




- After the period is the name of the member function that you are activating.

```
int main() {  
    thinking_cap student;  
    thinking_cap fan;  
  
    student.slots( "Hello", "Goodbye");  
}
```

Name of the Function

Using the Thinking Cap



- Finally, the arguments for the member function. In this example the first argument (new_green) is "Hello" and the second argument (new_red) is "Goodbye".

```
#include "thinker.h"
```

```
int main() {
```


```
    thinking_cap student;
```

```
    thinking_cap fan;
```

```
    student.slots( "Hello", "Goodbye");
```

Arguments

A Quiz




***How would you
activate student's
push_green
member function ?***

***What would be the
output of student's
push_green
member function
at this point in the
program ?***

```
int main( )  
{  
    thinking_cap student;  
    thinking_cap fan;  
  
    student.slots( "Hello", "Goodbye");  
}
```


A Quiz




Notice that the **push_green** member function has no arguments.

At this point, activating **student.push_green** will print the string **Hello**.

```
int main() {  
    thinking_cap student;  
    thinking_cap fan;  
  
    student.slots( "Hello", "Goodbye");  
    student.push_green( );  
}
```


A Quiz



```
int main( )
{
    thinking_cap student;
    thinking_cap fan;
    student.slots( "Hello", "Goodbye");
    fan.slots( "Go Cougars!", "Boo!");
    student.push_green( );
    fan.push_green( );
    student.push_red( );
    ...
}
```

Trace through this program, and tell me the complete output.

A Quiz




```
int main( )
{
    thinking_cap student;
    thinking_cap fan;
    student.slots( "Hello", "Goodbye");
    fan.slots( "Go Cougars!", "Boo!");
    student.push_green( );
    fan.push_green( );
    student.push_red( );
    ...
}
```

Hello
Go Cougars!
Goodbye

What you know about Objects

- Class = Data + Member Functions.
- You know how to define a new class type, and place the definition in a header file.
- You know how to use the header file in a program which declares instances of the class type.
- You know how to activate member functions.
- But you still need to learn how to write the bodies of a class's member functions.

Thinking Cap Implementation




Remember that the member function's bodies generally appear in a separate .cxx file.

```
class thinking_cap
{
public:
    void slots(char new_green[ ], char new_red[ ]);
    void push_green( );
    void push_red( );
private:
    char green_string[50];
    char red_string[50];
};
```

Function bodies
will be in .cxx file.


Thinking Cap Implementation



We will look at the body of slots, which must copy its two arguments to the two private member variables.

```
class thinking_cap
{
public:
    void slots(char new_green[ ], char new_red[ ]);
    void push_green( );
    void push_red( );
private:
    char green_string[50];
    char red_string[50];
};
```

Thinking Cap Implementation




For the most part, the function's body is no different than any other function body.

```
void thinking_cap::slots(char new_green[ ], char new_red[ ])
{
    assert(strlen(new_green) < 50);
    assert(strlen(new_red) < 50);
    strcpy(green_string, new_green);
    strcpy(red_string, new_red);
}
```

But there are two special features about a member function's body . . .


Thinking Cap Implementation



- In the heading, the function's name is preceded by the class name and `::` - otherwise C++ won't realize this is a class's member function.

```
void thinking_cap::slots(char new_green[ ], char new_red[ ])
{
    assert(strlen(new_green) < 50);
    assert(strlen(new_red) < 50);
    strcpy(green_string, new_green);
    strcpy(red_string, new_red);
}
```



Thinking Cap Implementation



- Within the body of the function, the class's member variables and other member functions may all be accessed.

```
void thinking_cap::slots(char new_green[ ], char new_red[ ])
{
    assert(strlen(new_green) < 50);
    assert(strlen(new_red) < 50);
    strcpy(green_string, new_green);
    strcpy(red_string, new_red);
}
```

Thinking Cap Implementation




- Within the body of the function, the class's member variables and other member functions may all be accessed.

```
void thinking_cap::slots(char new_  
{  
    assert(strlen(new_green) < 50);  
    assert(strlen(new_red) < 50);  
    strcpy(green_string, new_green);  
    strcpy(red_string, new_red);  
}
```

But, whose member variables are these? Are they
student.green_string
student.red_string
fan.green_string
fan.red_string

Thinking Cap Implementation




- Within the body of the function, the class's member variables and other member functions may all be accessed.

```
void thinking_cap::slots(char new_green, char new_red)
{
    assert(strlen(new_green) < 50);
    assert(strlen(new_red) < 50);
    strcpy(green_string, new_green);
    strcpy(red_string, new_red);
}
```

If we activate student.slots:
student.green_string
student.red_string

Thinking Cap Implementation




- Within the body of the function, the class's member variables and other member functions may all be accessed.

```
void thinking_cap::slots(char new_  
{  
    assert(strlen(new_green) < 50)  
    assert(strlen(new_red) < 50);  
    strcpy(green_string, new_green);  
    strcpy(red_string, new_red);  
}
```

*If we activate
fan.slots:*

*fan.green_string
fan.red_string*


Thinking Cap Implementation



Here is the implementation of the `push_green` member function, which prints the green message:

```
void thinking_cap::push_green
{
    cout << green_string << endl;
}
```

Thinking Cap Implementation



Here is the implementation of the `push_green` member function, which prints the green message:

```
void thinking_cap::push_green
{
    cout << green_string << endl;
}
```

Notice how this member function implementation uses the `green_string` member variable of the object.

A Common Pattern

- Often, one or more member functions will place data in the member variables...

```
class thinking_cap {  
public:  
    void slots(char new_green[ ], char new_red[ ]);  
    void push_green( ) const;  
    void push_red( ) const;  
private:  
    char green_string[50];  
    char red_string[50];  
};
```



slots



push_green & push_red

- ...so that other member functions may use that data.




Summary

- Classes have member variables and member functions. An object is a variable where the data type is a class.
- You should know how to declare a new class type, how to implement its member functions, how to use the class type.
- Frequently, the member functions of an class type place information in the member variables, or use information that's already in the member variables.
- In the future we will see more features of OOP.

Presentation copyright 2010, Addison Wesley Longman
For use with *Data Structures and Other Objects Using C++*
by Michael Main and Walter Savitch.

Some artwork in the presentation is used with permission from Presentation Task Force (copyright New Vision Technologies Inc.) and Corel Gallery Clipart Catalog (copyright Corel Corporation, 3G Graphics Inc., Archive Arts, Cartesia Software, Image Club Graphics Inc., One Mile Up Inc., TechPool Studios, Totem Graphics Inc.).

Students and instructors who use *Data Structures and Other Objects Using C++* are welcome to use this presentation however they see fit, so long as this copyright notice remains intact.



THE END