Cheat Sheet: Introduction to React and Class Components

JSX syntax and Class Component	Description	Code Example
Vite tool	This tool is used to create React projects with the latest version	`npm create vite@latest`

JSX syntax with fragments	Jsx allows to include multiple tags within single parent tag only. For this you can include empty tags also known as fragments `<></>`	`<>`
		`<h1>This is a heading tag</h1>`
		`</>`

JSX syntax with parent tag	Jsx allows to include multiple tags within single parent tag only. For this you can include tags like div tag	`<div>`
		`<h1>This is a heading tag</h1>`
		`</div>`

Class component	A class component extends the `Component` class with a render method	`import React, { Component } from 'react'`
		`export default class Extra extends Component {`
		`  render() {`
		`  return (`
		`  <>`
		`  <p>This is class component</p>`
		`  </>`
		`  )`
		`  }`
		`}`

State management in class component	State can be managed using `this.state` within constructor of class component	`import React, { Component } from 'react'`
		`export default class Extra extends Component {`
		`  constructor(){`
		`  super();`
		`  this.state={`
		`  count:0`
		`  }`
		`  }`
		`  render() {`
		`  return (`
		`  <>`
		`<p>This is paragraph</p>`
		`  </>`
		`  )`
		`  }`
		`}`

Access data of state management within class component	Data can be accessed by including variable name declared within `{}` and include variable name within these curly braces	`import React, { Component } from 'react'`
		`export default class Extra extends Component {`
		`constructor(){`
		`super();`
		`this.state={`
		`count:0`
		`}`
		`}`
		`render() {`
		`return (`
		`<>`
		`<p>the count is {this.state.count}</p>`
		`</>`
		`)`
		`}`
		`}`

Props in class component	Props can be sent from parent component as attribute along with child component	`import React, { Component } from 'react'`
		`import ChildComponent from './ChildComponent'`
		`export default class App extends Component {`
		`constructor(){`
		`super()`
		`this.state={`
		`title:"Manager"`
		`}`
		`}`
		`render() {`
		`return (`
		`<>`
		`<Extra title={this.state.title}/>`
		`</>`
		`)`
		`}`
		`}`

Access props within child class component	Props can be accessed easily within the child class component using `this.props.variable_name`	`import React, { Component } from 'react'`
		`export default class Extra extends Component {`
		`constructor(props){`
		`super();`
		`this.state={`
		`count:0`
		`}`
		`}`
		`render() {`
		`return (`
		`<>`
		`<p>The count value is {this.props.title}</p>`
		`</>`
		`)`
		`}`
		`}`

Event handling in class component	Events such as click events are handled by defining a function before the `render` method	`import React, { Component } from 'react';`
		`class MyComponent extends Component {`
		`handleClick() {`
		`alert('Button clicked!');`
		`}`
		`render() {`
		`return (`

```
      <div>
        <h1>Event Handling in Class Component</h1>
        <button onClick={this.handleClick}>Click Me</button>
      </div>
    );
  }
}
export default MyComponent;
```

Skills Network